

FOUND 3/4" IRON PIN  
ON SECTION LINE



SET 1/2" IRON PIN

S 88° 52' 30" W

BARBED WIRE FENCE

1208.23

19'

SET 1/2" IRON PIN

849.82

17 16

20 21

S 0° 16' 00" E  
277.82  
FOUND PK NAIL

N 2° 34' 40" E  
685.00  
SET 1/2" IRON PIN

19 ACRES

S 88° 52' 30" W

1208.23

N 2° 34' 40" E  
685.00  
SET 1/2" IRON PIN

NOTES: BEARINGS ARE BASED ON SURVEY MADE BY S. WALLULIS  
DEC. 27, 1955 WHICH ESTABLISHED THE EAST LINE OF SEC. 20.  
ALL POINTS FOUND WERE SET BY D.L. STAEBLER.  
THE SECTION CORNER; COMMON TO SECTIONS 17, 16, 21 & 20;  
USED IN THIS SURVEY DOES NOT AGREE WITH PINS FOUND  
IN MGDEVITT ADDITION NO. 5; BUT IT DOES AGREE WITH  
SURVEYS DONE TO THE SOUTH, EAST & WEST.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR  
*David H. Kimber*  
DAVID H. KIMBER  
1933

SURVEY FOR HEMPHILL		WAYNE HARRIS CO. INC. I-197-A			
PARCEL IN NE 1/4 SEC. 20, T. 1S., R. 32 E. W.M.		ENGINEERS SURVEYORS		PENDLETON OREGON	
SCALE	1" = 20'	DRN. BY	<i>D.E.S.</i>	DRNG. NO.	
DATE	10-29-74	CKD. BY	<i>D.H.K.</i>	74-292A	

I-197-A