



To F. B. Hayes - Co. Surveyor.

W. E. O. CRIGER  
CONSULTING ENGINEER

Memorandum of field notes for survey  
17 - Sec. 12 - T. 5 S., R. 33 E. W. M.

From the N. E. Cor. of Sec. 12, T. 5 S., R. 33 E. W. M., which is a well marked corner with plainly marked Bearing trees, (this corner checked and marked by the U. S. F. S.; U. S. Land office and other Government agencies), I thence ran a traverse as follows S.  $53^{\circ}55'W$ . 320 ft., thence S.  $79^{\circ}25'W$ . 270 ft., thence S.  $52^{\circ}55'W$ . 180 ft., thence S.  $53^{\circ}25'W$ . 450 ft., thence S.  $30^{\circ}10'W$ . 470 ft., to the S. E. corner of the McKay tract. —

Also from the N/4 Cor. of said Sec. 12 - I ran South  $40^{\circ}30'E$ . 2000  $\frac{1}{2}$  ft., to a concrete monument with an iron pin imbedded in it, thence N  $19^{\circ}50'W$ . 457  $\frac{1}{2}$  ft., and set a hub; thence ran N.  $79^{\circ}40'E$ . 253  $\frac{1}{2}$  ft., to the S. E. corner of the McKay tract; I thence ran north 166  $\frac{1}{2}$  ft., and set an iron pin; thence due west 105  $\frac{1}{2}$  ft., and set an iron pin for the N. W. Cor.; thence due south 70  $\frac{1}{2}$  ft., and set an iron pin for the S. W. Cor.; thence N.  $87^{\circ}49'E$ . 105  $\frac{1}{2}$  ft., to the point of beginning of the tract, which is an iron pin and is the S. E. corner of the McKay tract.

W E O Criger. —