


LEGEND

- Monument Found
- Monument Set
- Fences
- () Record Measurement (BLM 1999)

SCALE: 1 INCH = 50 Feet



I CERTIFY THAT THIS SURVEY WAS PERFORMED AT THE REQUEST OF THE UMATILLA NATIONAL FOREST

David A. Schlaich 4/27/10
FOREST SUPERVISOR DATE

NARRATIVE:

PURPOSE:
The purpose of this survey was to identify and monument a portion of National Forest System Land to be sold in order to resolve an innocent encroachment by the adjacent landowner.

HISTORY:
1882, Herman D. Gradon, U.S. Deputy Surveyor, subdivided the township under General Land Office Contract No. 452 (survey approved March 31, 1883).

1997 - 1999, Richard S. Kaiser, Philip G. Griffin and Bryan S. Seibold, BLM Cadastral Surveyors, conducted a dependent resurvey of a portion of the subdivisional lines and subdivided section 5. This encroachment was discovered during the course of this survey (survey approved March 17, 2000).

2002, Michael P. LeJeune, Registered Land Surveyor No. 2535, surveyed and posted National Forest System Land boundaries in sections 4, 5, 6 and 9 (Umatilla County Survey No. 02-273-B).

PROCEDURES:
The direction of the lines are based on the true meridian as determined by Global Positioning System (GPS) measurements.

The survey was performed using a combination of GPS static measurements and terrestrial measurements. The GPS measurements utilized dual frequency carrier phase receivers and were executed in accordance with the "Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods", dated May of 2001, published by the U.S.D.A. Forest Service and U.S.D.I. Bureau of Land Management.

The static GPS vectors have been adjusted using computer software which incorporates a least squares adjustment routine. The maximum GPS cadastral measurement error ellipse at 95% confidence level is 0.10 feet based on local accuracy standards. Terrestrial measured distances and directions have been adjusted using computer software which incorporates a least squares adjustment routine. The maximum terrestrial error ellipse at 95% confidence level is 0.06 feet. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

New bearing trees are double blazed and have a 2 1/4 inch x 1/4 inch magnetic nail (Mag Nail), with a 1 1/2 inch diameter stainless steel washer stamped "OR LS-2308 WA LS-33150" driven at the base on right side center.

The 2010 estimated magnetic declination for this survey as determined by the N.O.A.A. National Geophysical Data Center is 15° 25' East.

The field notes for this survey are on file at the Supervisor's Office of the Umatilla National Forest located at Pendleton, Oregon.

I, David A. Schlaich, a Registered Land Surveyor in the state of Oregon, hereby certify that this plat and notes hereon are a true and correct representation of a survey I conducted in April of 2010, at the request of the Umatilla National Forest, in accordance with the statutes of the state of Oregon, and the Bureau of Land Management's, 2009 Manual of Surveying Instructions.

David A. Schlaich 04/27/2010
Signature Date

David A. Schlaich
Umatilla National Forest
2517 SW Halley Avenue
Pendleton, Or. 97801
Phone: (541) 278-3716




UNITED STATES DEPARTMENT OF AGRICULTURE
FOREST SERVICE
REGION 6 UMATILLA NATIONAL FOREST

Survey for
Umatilla National Forest
of
Small Tract No. 061412
Located in
Section 5, T. 1 N., R. 36 E., W.M.
Umatilla County, Oregon
April 2010

6-10
KK
10-13-B

Corner of sections 4, 5, 8 and 9

Found a stainless steel post, 2 1/2 ins. diam., projecting 6 ins. above ground, with BLM brass cap, 3 1/4 ins. diam., mkd.



from which

An uprooted ponderosa pine snag, 32 ins. diam., bears S. 71° W., 147.8 ft. dist., with a mound of dirt covering the blaze.

A ponderosa pine, 42 ins. diam., bears N. 70° W., 136.6 ft. dist. with healed blaze.

From this corner, the southeast corner of the house, bears N. 9°00' W., 92.4 ft. dist.

From this corner, the southwest corner of the shed, bears N. 8°08' E., 75.6 ft. dist.

From this corner, a steel U channel post bears S., 0.9 ft. dist., with attached F.S. Property Boundary and Land Survey Monument signs.

Set aluminum U channel post, 6 ft. long, 2.2 ft., W. of the corner, with attached F.S. Property Boundary sign.

WP

Found witness point, established by the BLM on the section line at the intersection with the westerly R-O-W boundary of the Union Pacific Railroad, monumented with a stainless steel post, 2 1/2 ins. diam., projecting 9 ins. above ground, with BLM brass cap, 3 1/4 ins. diam., mkd.



From this corner, a steel T bar fence post, bears W., 1.0 ft. dist.

AP-2

Set an aluminum post, 30 ins. long, 2 3/8 ins. diam., 16 ins. in the ground, with aluminum cap, 3 1/4 ins. diam., mkd.



No accessories within limits.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Set aluminum U channel post, 6 ft. long, with attached F.S. PROPERTY BOUNDARY and LAND SURVEY MONUMENT signs, 2.0 ft., N. of the corner.

Set aluminum U channel post, 6 ft. long, with attached F.S. PROPERTY BOUNDARY sign, 2.0 ft., W. of the corner.

AP-3

Set an iron rod, 36 ins. long, 5/8 ins. diam., top 1 inch below ground, with brass cap, 3 1/4 ins. diam., mkd.



from which

A ponderosa pine, 6 ins. diam., bears S. 8 1/4° W., 29.9 ft. dist., mkd. X BT.

A ponderosa pine, 8 ins. diam., bears N. 67 1/2° W., 49.9 ft. dist., mkd. APSS BT.

Set aluminum U channel post, 6 ft. long, with attached F.S. PROPERTY BOUNDARY and LAND SURVEY MONUMENT signs, 5.5 ft., S. 4°43' W. from the corner.

From this corner, the post, of a metal gate which extends N. 60° E. and of a fence which extends S. 6° W., bears S. 32 1/2° E., 11.4 ft. dist.

AP-4

Set an iron rod, 36 ins. long, 5/8 ins. diam., top 4 ins. below ground, with brass cap, 3 1/4 ins. diam., mkd.



from which

A ponderosa pine, 8 ins. diam., bears S. 62 1/4° W., 59.8 ft. dist., mkd. APSS BT.


A ponderosa pine, 16 ins. diam., bears N. 25 1/4° W., 86.3 ft. dist., mkd. APSS BT.

Set aluminum U channel post, 6 ft. long, with attached F.S. PROPERTY BOUNDARY sign and location poster, 7.4 ft., N. 4°43' E. from the corner.

From this corner, S. 89°14'17" E., 1.8 ft. dist., a steel gate, extends N. 10° E. and S. 10° W.

1/4 Section Corner of sections 5 and 8

Found a stainless steel post, 2 1/2 ins. diam., projecting 6 ins. above ground, with BLM brass cap, 3 1/4 ins. diam., mkd.



from which

A Douglas fir, 12 ins. diam., bears N. 42° E., 29.7 ft. dist., with scribing visible on partially healed blaze.

A ponderosa pine, 24 ins. diam., bears S. 9 3/4° W., 83.8 ft. dist., with scribing visible on partially healed blaze.

S1/16 Section Corner of sections 4 and 5

Found a stainless steel post, 2 1/2 ins. diam., projecting 8 ins. above ground, with BLM brass cap, 3 1/4 ins. diam., mkd.



from which

An iron rod, 5/8 ins. diam., bears E., 46.6 ft. dist., with aluminum cap, 1 1/2 ins. diam., mkd. WSI/RM 46.6 2535.

An iron rod, 5/8 ins. diam., bears S., 42.2 ft. dist., with aluminum cap, 2 ins. diam., mkd. WSI/RM 42.2 2535.

From this corner, a steel U channel post, bears S., 0.5 ft. dist.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David A. Schlaich
OREGON
JULY 16, 1987
DAVID A. SCHLAICH
2308

EXPIRATION DATE: 06/30/2010

UNITED STATES DEPARTMENT OF AGRICULTURE
FOREST SERVICE
REGION 6 UMATILLA NATIONAL FOREST

Survey for
Umatilla National Forest
of
Small Tract No. 061412
Located in
Section 5, T. 1 N., R. 36 E., W.M.
Umatilla County, Oregon
April 2010

Sheet 2 of 2

6-10
KK
10-23-B