

USDA-FOREST SERVICE

Index

File No. N-11

T 4S R. 33E

Merid. Willamette

CORNER RECORD (SEARCH)

(Ref. FSM 7151.4)

R.D. UKiah

N.F. Umatilla


Tract or Survey No. \_\_\_\_\_

County Umatilla

State Oregon

Cor. No. 1/4

CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND

Found a stone of approximately the right size set in the ground with faint scribing on North side from which:

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

N 46° E 20.0 feet is a 16" stump lying on the hill scribed "1/4 S", this stump had rolled down from higher on the hill. A stump hole bears N 49 1/2° W 9.0 feet. A 12" Pine with scribing "1/4 S" BT laying on hillside with roots still firm in ground

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

From Jct. of Rd. 54 and 5400-170 go southerly 1 mile, turn left past the gravel pit pond, go East .3 mi, where the road curves north, park and walk East 450' down hill to corner

PHOTO IDENTIFICATION DATA

Photo No. \_\_\_\_\_

Filed At. \_\_\_\_\_

Object Ident. \_\_\_\_\_

Ident. By \_\_\_\_\_

Signature

PLANE COORDINATE POSITION DATA

State \_\_\_\_\_ Zone \_\_\_\_\_

X \_\_\_\_\_

Y \_\_\_\_\_

Estab. By \_\_\_\_\_

Agency

Signature

*David H. Kilbride*

Title

PLS 933

Division

Headquarters

Date

8-84

7100-52-(3,68)

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

At the stone location set a 2 1/2" Brass Cap on a 2 1/2" x 30" galvanized pipe 6" in the ground with a 5 foot dia. stone mound to within 6" of the top stamped

T4S R33E  
1/4 S 16  
1/4 S 21  
1904  
PLS 933

ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

A 14" Fir bears N 40° W 30.7 feet scribed 1/4 S. 16 BT  
A 24" Ponderosa Pine bears S 74 1/2° W, 23.15 feet scribed  
1/4 S 21 BT

Work Done By D. Krumbain Title Surveyor Date 8/04 State Registration No. PLS 933  
or Agency

Certified Cor. Record Prepared?  Yes  No Filed At: Umatilla County Surveyor Date 8/04

REMARKS

Index File No. N-11 T. 4 S R. 33 E M. Willamette Tract or Surv. No.

Cor. 1/4

Index  
File No. N-11

**CORNER RECORD (SEARCH)**

(Ref. FSM 7151.4)

Tract or  
Survey No. \_\_\_\_\_  
Cor.  
No. \_\_\_\_\_


T 4S R. 33E

R.D. Ukiah County Umatilla

Merid. Willamette

N.F. Umatilla State Oregon

**CORNER DIAGRAM**



**DESCRIBE CORNER MONUMENT FOUND**

MATERIAL: Basalt Stone      SIZE: 20" X 12" X 5"  
HEIGHT ABOVE GROUND: 16"      CONDITION: Fair  
MARKINGS: 1/4 on n. face

**DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND**

Rotten 16" pine on ground-S56E approximately 30' distance  
(15 LKS in notes) blazed on NW face, scribed: 1/4S B.T. Rotten  
stump bears N42°E from stone. Scribing on North side. Stump  
has rolled downhill East from original location. There is a  
steel fence post with Forest Service attention poster on it beside  
the stone. Distance to SE bearing tree does not agree with  
G.L.O. notes. Bearing is O.K. but stone has probably (OVER)

**DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER**

**PHOTO IDENTIFICATION DATA**

Photo No. \_\_\_\_\_  
Filed At. \_\_\_\_\_  
Object Ident. \_\_\_\_\_  
Ident. By \_\_\_\_\_  
*Signature*

**PLANE COORDINATE POSITION DATA**

State \_\_\_\_\_ Zone \_\_\_\_\_  
X \_\_\_\_\_  
Y \_\_\_\_\_  
Estab. By \_\_\_\_\_  
*Agency*

Signature \_\_\_\_\_ Title \_\_\_\_\_ Division \_\_\_\_\_ Headquarters \_\_\_\_\_ Date \_\_\_\_\_

B. Moore      Engineering Technician

7100-52-(3/68)  
5-]]-76

## CORNER RECORD (PERPETUATION)

---

 MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT
 

---



---

 ACCESSORIES : DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE
 

---

I placed blank Forest Service bearing tree posters on the 2 B.T.s.

---

 Work Done By \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_ State Registration No. or Agency \_\_\_\_\_
 

---

 Certified Cor. Record Prepared ? Yes No Filed At: \_\_\_\_\_ Date \_\_\_\_\_
 

---

## REMARKS

3 CONTINUED- been moved uphill. Forest Service location poster on south side of 12" fir N50°W of stone 30' distance dated: 4/27/44 G.B.P.

---

 Index File No.

T.

R.

M.

Tract or Surv. No.

Cor.

12  
13