

Index  
File No. 2-9

T 5 S R. 3/4 E

Merid. Willamette

CORNER RECORD (SEARCH)

(Ref. FSM 7151.4)

R.D. LaGrande

County Union

N.F. WW-16

State Oregon


Tract or

Survey No. \_\_\_\_\_

Cor.

No. 1/4

CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND

16" x 12" x 8" basalt stone flush with surface with 1/4 mkd. on W face.

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

20" pine stump bears S 32 W, 21 lks. (old BT)  
Rotted fir on ground, base bears N 04 E, 33 lks.  
portions of scribing are visible. (old BT)

PHOTO IDENTIFICATION DATA

Photo No. \_\_\_\_\_

Filed At. \_\_\_\_\_

Object Ident. \_\_\_\_\_

Ident. By \_\_\_\_\_

*Signature*

PLANE COORDINATE POSITION DATA

State \_\_\_\_\_ Zone \_\_\_\_\_

X \_\_\_\_\_

Y \_\_\_\_\_

Estab. By \_\_\_\_\_

*Agency*

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

Approx. 450 ft. S of road s536D.

Signature  
**Hambleton**

Title

Division  
**ORLS**

Headquarters  
**645**

Date  
**8-78**

7100-52-(3/68)

## CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

Set a  $2\frac{1}{2}$ " x 30" iron pipe w/brass cap mkd.:  
Buried in a large mound of stone and dirt.

T 5 S  
1/4  
S 17 S 16  
R 34 E  
1978  
ORLS 645

9

ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

5" fir bears N 85 W, 47.0 feet scribed  $\frac{1}{4}$ S S 17 BT w/signs 54-3&4.  
9" tamarack bears S 25 E, 46.5 feet scribed  $\frac{1}{4}$ S S 16 BT w/signs 54-3&4.  
Painted blaze and band on BT's red & yellow.  
Set steel fence post by mound of stone w/signs 54-4&5.

10

Work Done By J. Hambleton Title Surveyor Date 8-78 State Registration No. ORLS 645  
or Agency  
Certified Cor. Record Prepared? Yes  No  Filed At: Union CS Date           

11

## REMARKS

Witnesses: L. Green  
L. Shirley

12


Index  
File No. 1-9

## CORNER RECORD (SEARCH)

(Ref. FSM 7151.4)

Tract or  
Survey No. \_\_\_\_\_Cor.  
No. 1/4T 5 S R. 34 ER.D. LaGrande County UnionMerid. WillametteN.F. WW-16 State Oregon

## CORNER DIAGRAM



## DESCRIBE CORNER MONUMENT FOUND

16" x 12" x 8" basalt stone flush with surface  
with  $\frac{1}{4}$  mkd. on W face.

## DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

20" pine stump bears S 32 W, 21 lks. (old BT)  
Rotted fir on ground, base bears N 04 E, 33 lks.  
portions of scribing are visible. (old BT)

## PHOTO IDENTIFICATION DATA

Photo No. \_\_\_\_\_

Filed At. \_\_\_\_\_

Object Ident. \_\_\_\_\_

Ident. By \_\_\_\_\_

*Signature*

## PLANE COORDINATE POSITION DATA

State \_\_\_\_\_ Zone \_\_\_\_\_

X \_\_\_\_\_

Y \_\_\_\_\_

Estab. By \_\_\_\_\_

*Agency*

## DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

Approx. 450 ft. S of road s536D.

Signature  
**Hambleton**

Title

Division  
**ORLS**Headquarters  
**645**Date  
**8-78**

7100-52-(3/68)

**CORNER RECORD (PERPETUATION)**

**MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT**

Set a 2 1/2" x 30" iron pipe w/brass cap mkd.:  
Buried in a large mound of stone and dirt,

T 5 S  
1/4  
S 17 | S 16  
R 34 E  
1978  
ORLS 645

9

**ACCESSORIES : DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE**

5" fir bears N 85 W, 47.0 feet scribed 1/4 S S 17 BT w/signs 54-3&4.  
9" tamarack bears S 25 E, 46.5 feet scribed 1/4 S S 16 BT w/signs 54-3&4.  
Painted blaze and band on BT's red & yellow.  
Set steel fence post by mound of stone w/signs 54-4&5.

10

Work Done By J. Hambleton Title Surveyor Date 8-78 State Registration No. ORLS 645  
or Agency  
Certified Cor. Record Prepared? Yes  No Filed At: Union CS Date \_\_\_\_\_

11

**REMARKS**

Witnesses: L. Green  
L. Shirley

12

Index File No. T. R. M. Tract or Surv. No. Cor. 13