


CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND

Found a 3 1/4" aluminum cap, set flush with the ground.

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

8" Lodgepole Pine Snag, N. 65 1/4 E., 14.2 feet, with scribing visible on double blaze.
6" Lodgepole Pine Snag, S. 44 E., 3.3 feet, with scribing visible on double blaze.

PHOTO IDENTIFICATION DATA

Photo No.
Filed At.
Object Ident.
Ident. By
Signature

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

The corner is located 200 feet southerly of Winom creek, approximately 2700 feet southwesterly down the creek from the bridge on road 5200-440.

PLANE COORDINATE-POSITION DATA

State: Zone:
X:
Y:
Datum:

Signature: **Schtaich** Title: **Land Surveyor** Division: Headquartes: **S.O.** Date: **10/22/1997** FS-7100-52 (3/97)

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

RM, 5/8" X 24" rebar with red plastic cap stamped "UMATILLA N.F." , set 23" in the ground, S. 73 1/4 W., 15.6 feet.
8" Lodgepole Pine, N. 22 1/2 E., 133.2 feet, scribed "WB/582" "BT" on double blaze.

Work Done By D. Schlaich Title Land Surveyor Date 10/22/1997 State Registration No. or Agency _____
Certified Corner Record Prepared? Yes No Filed At: _____ Date _____

REMARKS

Index File No.

T.

R.


M.

____ Tract or Survey No. **NFJD Unit**

Cor. **AP-582**

Index
 File No. T. 6 S. R. 34 E. Merid. WILLAMETTE
 CORNER RECORD (SEARCH)
 (Ref. FSM 7151.4)
 R.D. NFJD N.F. UMATILLA
 County UMATILLA State OREGON
 Tract or Survey No. NFJD Unit
 Cor. No. AP-582

CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND

NONE

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

NONE

PHOTO IDENTIFICATION DATA

Photo No.:
 Filed At:
 Object Ident.:
 Ident. By:

DESCRIBE CORNER RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

The corner is located 200 feet southerly of Winom creek, approx. 2700 feet southwesterly down the creek from the bridge on road 5200-440.

PLANE COORDINATE POSITION DATA

State: Oregon Zone: North
 X: 2,478,996.73'
 Y: 495,199.55'
 Datum: NAD1927

Signature
 D. Schlaich

Title
 Land Surveyor

Division

Headquarters
 S.O.

Date
 07-1993

FS-7100-52 (3/68)

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

5/8" by 36" rebar, with a 3 1/4" aluminum cap, flush with the ground, marked "NFJD WILDERNESS AP-582 RLS 2308 1993".

ACCESSORIES : DESCRIBE NEW BT's WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

8" Lodgepole Pine, N. 72° E., 14.2 ft., mkd. "WB/582""BT" on double blaze.

6" Lodgepole Pine, S. 34° E., 3.6 ft., mkd. "WB/582"BT" on double blaze.

Both BT's have a 3/4" brass washer stamped "RLS 2308" nailed next to "BT" scribing on lower blaze.

Work Done By **D. Schlaich**

Title Land Surveyor

Date **07-1993**

State Registration No.
or Agency

Certified Cor. Record Prepared ? **NO**

Filed At:

Date

REMARKS

Index File No.

T.

6 S.

R.

34 E.

M.

W.M.

Tract or Survey No.

NFJD Unit

Cor.

AP-582