

	Chain	Distance	∠	R
Thence	N 51° W	2.42	64 77	16°
"	N 61° W	175	66 52	10
"	N 55° W	320	69 72	6°
"	N 50° W	500	74 72	5°
"	N 70° W	240	77 12	20°
"	N 42° W	170	78 82	18°
"	N 62° W	118	8 000	20°
3 feet right marked 1. m.				
Thence	N 73° W	318		12°
"	N 64° W	425	7.43	9°
"	N 37° W	330	10 73	27°
"	N 57° W	160	12 33	20°
"	N 72° W	403	16 36	15°
"	N 43° W	645	22 81	29°
R.T. a Tamarack 20 inches diameter Marked P.T. 502 in S.E. 1/4 Sec 28 T 53 R 32 S.W.M				

I hereby certify that the foregoing are a true copy of field notes of Road Survey No 502, as surveyed by me on the 25th day of Nov. 1898

John W Kimbrell,
County Surveyor

Filed January 7th 1899

W.B. Burroughs, Clerk
By J. Lambirth Deputy

(Plat Record at Page 38 of Book
No 1 Road Plat Book)

ROAD No
503

In the matter of Viewing, Surveying and Laying out County Road No 503

To the Honorable County Court of the State of Oregon, for Umatilla County:
We, the undersigned, the Viewers heretofore appointed to view and locate Road No 503 submit the following report: Pursuant to an order of the Honorable Court we met John W Kimbrell, Surveyor, at R.M. Dorothy's house on the 7th day of December, 1898, and were by him, each, duly sworn to faithfully and impartially discharge the duties of our appointments.

We called to our aid J.B. Ross, Oliver Shick, Chairmen, Shel Hopkins, Marker, who were by the surveyor, each, duly sworn. We viewed, surveyed and located said road No. 503, as specified in our order, and find the Road practicable, and would most respectfully recommend the same be established and declared a public highway of Umatilla County, Oregon

J.B. Frazier }
Wm Talbot } Viewers, Road Survey No 503
Henry Wood }

Field notes of Road Survey No 503

I commenced at a point 40 rods north of the center of Sec 22 in T 5 N. R. 36 E. N. M.; Set stone 20x8x6 in mound of stone 18 inches high, 48 inch base, marked R. 503, from which a Hawthorn 5 inch dia. tree North 55 lbs, marked R. 503 135

Thence	Angle	Chains	Distance	L	R	Remarks
.	S 33° 30' E	5.15				
.	S 12° E	503	13 20	9'		
.	S 51° 5' E	655	19 75	39° 5'		
.	S 60° 49' E	765	27 40	9° 44'		
.	S 43° 50' E	715	34 55		16° 59'	
.	S 50° 45' E	808	42 63	6° 55'		
.	S 46° E	430	46 93		40° 45'	
.	S 67° 46' E	790	54 83	21° 46'		
.	S 40° 15' E	618	61 01		18° 31'	
.	S 30° 5' E	175	62 76		19° 10'	
.	S 51° E	625	69 01	20° 45'		
.	S 57° 50' E	197	70 93	6° 50'		
.	S 69° 10' E	416	75 09	11° 20'		
.	S 55° 30' E	491	80 00		40° 40'	1 Mile. A Stone in place 20 feet high
.	S 55° 30' E	335				48x36x20 inches marked "1. M"
.	S 54° 10' E	398	73 3		40° 20'	
.	S 41° 55' E	520	12 53		12° 15'	
.	S 59° 50' E	2030	32 83	17° 55'		
.	S 56° 37' E	845	41 25		38° 13'	
.	S 37° 55' E	778	51 74	13° 30'		
.	S 59° 48' E	655	58 79			
.	S 51° 37' E	870	66 99		9° 11'	
.	S 73° 10' E	549	72 48	21° 33'		
.	S 53° 33' E	245	74 93		19° 37'	
.	S 38° 35' E	345	75 38		14° 58'	
.	S 21° 50' E	162	80 00		16° 45'	2 Miles. Face of Stone bluff 10 feet high marked "2 M"
.	S 21° 50' E	350				
.	S 79° 50' E	300	65 0	8°		
.	S 70° 22' E	265	91 5	40° 32'		
.	S 82° 20' E	517	143 2	11° 55'		
.	S 83° 30' E	625	205 7	1° 10'		
.	S 58° E	600	26 57		25° 30'	
.	S 39° 30' E	420	30 77		15° 30'	
.	S 59° 30' E	296	33 73	20°		
.	S 59° 10' E	725	40 98		0.20'	
.	S 57° 10' E	737	48 35		2°	
.	S 55° 3' E	11.37	59 72		2° 7'	

inches diameter

20 inches di-

of field notes
a day of

year

is of Dept

by Road No 503

County:
had to view
Pursuant to
subrule, Sec
umber, 1895,
impartially

inmen, Shel
sworn, We
ad in our
perfectly acc
ighway of

Survey No 503

	Chains	Distance	R	R	
Thru	S 54° 33' E	496	6468		2° 30'
-	S 76° 37' E	193	6661	22° 4'	
-	S 58° 20' E	1339	5000		8° 17' 3 Miles. Set post 4x4x48 inches 20 feet left Marked 3 M. Just mound of stone 18 inches high, 48 inch base around post.
-	S 58° 20' E	292			
-	S 60° 7' E	537	829	1° 47'	
-	S 43° 10' E	371	1200		16° 57'
-	S 38° 20' E	89	1289		4° 40'
-	S 57° E	489	1775	19° 40'	
-	S 28° 45' E	174	1952		28° 15'
-	S 52° 50' E	815	2767	24° 5'	
-	S 57° 40' E	242	3009	4° 50'	
-	S 39° 5' E	90	3099		18° 35'
-	S 57° 12' E	100	3199	18° 7'	
-	S 42° 36' E	1100	4199		14° 46'
-	S 14° E	111	4310		28° 36'
-	S 61° 55' E	130	4440	47° 55'	
-	S 36° 20' E	755	5195		25° 35'
-	S 47° 15' E	762	5957	10° 45'	
-	S 83° 8' E	357	6314	35° 58'	
-	S 61° 31' E	947	7261		21° 38'
-	S 42° 45' E	290	7551		18° 45'
-	S 45° E	449	8000	2° 15'	4 Miles. A pin 5 inches diameter marked "4 M" in Md of stone 18x48 inches
-	S 45° E	866			
-	S 50° 50' E	1015	1881	5° 50'	
-	S 64° 12' E	580	2461	13° 32'	
-	S 63° 9' E	527	2958		1° 3'
-	S 80° E	215	3203	36° 51'	
-	S 59° 33' E	310	3513		20° 27'
-	S 51° 17' E	315	3828		8° 16'
-	S 66° 40' E	411	4239	15° 23'	
-	S 0 35' N	175	4414		67° 15'
-	S 40° 42' E	234	4648	41° 17'	
-	S 77° 15' E	232	4880	36° 33'	
-	S 55° 6' E	1425	6305		22° 9'
-	S 42° 10' E	225	6530		12° 56'
-	S 43° 10' E	685	7215	1°	
-	S 38° 30' E	630	7845		4° 40'
-	S 17° 53' E	155	8000		20° 37' 5 Miles. A pin 5 inches diameter 20 feet left marked 5 M. Md. of Stone.
-	S 17° 53' E	14			
-	S 38° 47' E	170	184	20° 52'	
-	S 42° 52' E	874	1058	4° 5'	
-	S 14° 28' E	125	1183		28° 24'

4 x 48 inches 20
built round of
8 inch base

the diameter
stone 18 x 48 inches

the diameter 20
No. of Stone.

	Lat	Chains	Distances	∠	∠
Stone	S 45° 50' E	515	1698	31° 22'	
.	S 25° 37' E	385	2083		20° 13'
.	S 24° 33' E	341	2424		10° 4'
.	S 60° 26' E	695	3119	35° 53'	
.	S 32° 15' E	208	3327		28° 11'
.	S 61° 20' E	450	3777	29° 5'	
.	S 31° 31' E	407	4184		29° 49'
.	S 47° 50' E	142	4326	16° 19'	
.	S 67° 28' E	485	4811	19° 38'	
.	S 74° 18' E	582	5393	6° 50'	
.	S 28° 45' E	440	5833		45° 33'
.	S 64° 13' E	250	6083	35° 28'	
.	N 71° 08' E	220	6303	44° 49'	
.	S 33° 45' E	235	6538		75° 7'
.	S 72° 20' E	100	6638	38° 35'	
.	N 86° 45' E	165	6803	20° 55'	
.	S 34° 10' E	275	7078		55° 50'
.	S 43° 35' E	215	7293	9° 25'	
.	N 89° 47' E	380	7673	46° 38'	
.	S 48° 45' E	327	8000		41° 28'
.	S 48° 45' E	532			6 miles. A Cherry tree 4 inches 20 feet left marked 6th. Md. of stone.
.	S 25° 35' E	175	707		23° 10'
.	S 42° 30' E	175	882	16° 55'	
.	S 38° 50' E	298	1180		3° 40'
.	S 63° 10' E	275	1455	24° 20'	
.	S 76° 15' E	478	1933	13° 5'	
.	S 70° 15' E	600	2533		6°
.	S 12° 10' E	190	2723		58° 5'
.	S 47° E	570	3293	34° 50'	
.	S 86° 40' E	295	3588	39° 40'	
.	N 64° 15' E	240	3828	29° 5'	
.	S 47° 55' E	916	4744		67° 50'
.	S 43° E	740	5484		40° 55'
.	S 1° N	320	5804		44°
.	S 57° E	312	6116	58°	
.	S 32° E	360	6476		25°
.	S 43° 45' E	265	6741	11° 45'	
.	S 77° E	320	7061	33° 15'	
.	S 35° 40' E	320	7381		41° 21'
.	S 25° E	100	7481		10° 40'
.	S 85° E	170	7651	60°	
.	S 75° E	150	7801		10°

6 miles. A Cherry tree 4 inches 20 feet
left marked 6th. Md. of stone.

{ P.D. An Elder 4 inches diameter marked
P.D. 503 in md of stone 18 inches
high and 4 ft wide at base

I hereby certify that the foregoing are a true copy of Field Notes of Road No 505 as surveyed by me on Dec 7th, 1895

John W Kimbrell
County Surveyor

Filed Dec. 28th 1898

W.S. Burroughs, Clerk. (That Recorded at Pages 81-85 & 84 Plat Book No 1)

ROAD No
505

In the matter of viewing, surveying and laying out County Road No 505

To the Honorable County Court of the State of Oregon, for Umatilla County:

We, the Undersigned, the viewers heretofore appointed to view and locate Road No 505 submit the following report: Pursuant to an order of the Honorable County Court we met J W Kimbrell, Surveyor, at Court House in Pendleton, on 23rd day of March, and were by him, each, duly sworn to faithfully and impartially discharge the duties of our appointments

We called to our aid Berkeley Bailey, H Fleming, Chairman, J W Kimbrell, Marker, who were by the Surveyor, each, duly sworn. We viewed, surveyed and located said Road No. 505 as specified in our order and the route practicable, and would most respectfully recommend the same be established and declared a public highway of Umatilla County Oregon

W D Hoarford }
Lot Livermore } Viewers Road Survey No 505
J S McLeod.

Field Notes of County Road No 505

Pendleton, Oregon, March 23rd, 1899

I commenced at a point 14.57 Chains south of the NN corner, Sec. 31, in T 3 N R 33 E N M, set post 4x4x48 inches 30 feet west of initial point, marked R 505, dug pits N. & S. and made mound around post

			Chains	Distance		
Thence	S	54°	E	7.03		
	S	35°	E	10.67	17.70	
	S	37°30'	E	6.43	24.13	
	S	29°	E	9.15	33.28	
	S	40°	E	8.05	41.33	
	S	57°	E	14.15	55.48	
	S	39°30'	E	2.95	58.43	Cross N + E R R
	S	60°	E	3.23	61.66	
	S	31°	N	5.30	66.96	
	S	28°	E	1.20	68.16	Cross Wild Horse Creek

ROAD No
505