```
ThenceS 89° E
                    530
   " N 81° E
                                 4680
                    1370
                                 6050
                                                A 6
     S 64° E
                    685
                                 6735
                                                A 7
     East
                    1265
                                 8000
                                                One Mile.
     East
                    1170
                                 Dist.
                                                AS
     N 73° E
                                                A 9
                                 1570
     S 51° E
                    870
                                2440
     N 53° E
                    340
                                2780
     N 21° E
                   190
                                2970
                                                a 12
     N 5° E
                   435
                                3405
    N 46° E
                                3605
  " N 75° E
                   573
                                4178
                                               a 15
     N 88° E
                   740
                                4918
                                               A 16
    N 66° E
                   400
                                5318
                                                A 17
     N 58° E
                   705
                                6023
                                                A 18
  " East
                                6698
                                               A 10
  " N 63° E
                                71 0
                   500
                                               A 20
  " N 45° E
                   193
                                7391
                                               R T at point in present County Road
S 45 ° E 7.40 chains dist. from the N W Corn of the N E 1/4 sec. 8, in T 2 N R 32
```

T here by certify that the foregoing are a correct copy of field notes of Road to be vacated as surveyed by me March 25th, 1904. Hille Manney 3 19 th Ment John W Kimbrell, County W. John W Kimbrell, County W. John W Kimbrell, County W. John W Kimbrell, County Fig. By Br. Nat. Styles of viewing, surveying and laying out County road No. 559 County Surveyor.

To the Honorable County Court, of the State of Oregon, for Umatilla County:
We, the undersigned, the viewers heretofore appointed to view and locate Road No. 559 submit the following report: Pursuant to an order of the Honorable Court we met John W Kimbrell Surveyor, at A W Danbners House of April the 1904, and were by him, each, duly sworn to faithfully and impartially discharge the duties of our appointments WE called to our aid Malcom Stevens )

A W Danbner ) chainmen. Chris A mosthrony Marker.

who were by the Surveyor, each, duly sworn, we viewed, surveyed and located said Road No. 559 as specified in our order; We find the road practicable the cost of building culverts, grading and making the road in good condition for travel would be about \$50 or \$60.00; the different tracts of land through which the proposed road is located would not be damaged in any amount but would be benefited as all parties need the road for an outlet to public highways at either terminus of said road and is it would be of public interest in general we would therefore recommend the same b. declared and established as a public highway of Umatilla County, Oregon. Filed may 4 19 04

John W KImbrell, County Surveyor E L Smith, OV D Chambrean E L Smith, By B & Wall Deputo William Mills,

) Viewers, Road Survey No 559

Field Notes of Road No. 559

Commencing at a point on County Road in Juniper Canyon in N W Cor. of S E 1/4 sec. 35 T 6 N R 31, E.W.M. set stone 14x10x8 inches 10 ins. in the ground marked R 559; dug pits E & W of stone and made mound of earth

```
chs
ThenceN 39° E
                                 dist.
      N 62° E
                    565
                                                A 1
      N 49° E
                    455
                                                A 2
      N 31° E
                                 3130
                                                A 3
      N 3° E
                   605
                                 3735
                                                A 4
      N 51° E
                   405
                                 4140
                                                A 5
      N 74° E
                   305
                                 4445
      N 36° E
                   650
                                 5095
                                                A 7
      N 15° E
                   294
                                 5389
                                                AB
      N 36° E
                   388
                                                A 9
      N 62° E
                   368
                                61 45
                                                A 10
      N 88° E
                                 7065
                                                A 11
      N 49° E
                   510
                                 7575
                                               A 12
      N 32° E
                   410
                                 7985
                                           A 13
      N 45° E
                    15
                                8000
                                                1 mile set atone 16x10x4 inches 20 feet
to right marked 1
ThenceN 45° E
                  M; dug
355
                     dug pits and raised mound of earth
                                Dist A 14
     N 31° E
                   398
                                7.53
                                                A 15
      N 29° E
                   810
                                15.63
                                                A 16
      N 46° E
                   620
                                2183
                                               A 17
      N 39° E
                   500
                                26.83
                                               A 18
      N 55° E
                   1200
                                3883
                                               A 10
      N 52° E
                   1280
                                5163
                                                A 20
      N 50° E
                   410
                                5573
                                                A 21
      N 10° E
                   335
                                5908
                                               A22
      N 39° E
                   1185
                                7093
                                               A 23
      N 48° E
                   367
                                 7460
                                                A 24
      N 22° E
                   335
                                               A 25
     N 61° E 205
                                8000
                                                A 26 2 miles set stone 16x10x6 inches
20 feet to left and marked a post 4 feet long 4 inches square I M dug pits and made
ThenceN 73° E
                                Dist
     N 24° E
                                1175
                                               A 28
     N 15° E
                                1795
                                                A 29
      N 25° E
                   660
                                               A 30
      N 20° E
                   420
                                2875
```

Thence 3080 N 35° E 1630 4760 A 33 N 40° E 332 5092 A34 N 45° E 840 5932 A 35 N 41° E 1065 6997 A 36 N 38° E 1003 8000 3 mile set post 4 feet long 4 ins. squa re 20 feet to right marked 3 M, dug pits and raised mound of earth N 38° E .95 Thence dist. A 37 N 55° E 9.50 N 33° E 2755 3705 A 39 N 16° E 9.90 4695 A 40 N 48° E 475 5170 A 41 N 53° E 700 5870 A 42 N 39° 1065 6935 A 43 to line bet. sec. 17 & 18 " N 3° W 815 77.50 R T a point on County foad about 8 North of S E Sec cor sec 18 T 6 R 32 E W M, set post 4 feet long 4 inches square 30 R T a point on County foad about 80 rds feet west of terminus marked R T No. 559

I hereby certify that the above are true copy of field notes of Road No. 559 as surveyed by me April 5th, & 6th, 1904.

In iled may 4, 1904 My B B Hall Deputy

Road

32

Road to

Road No.

pointments

aid Road

uilding

bout \$50

the road

ild be of

cated

and

/4 sec. 559;

we met

y him.

evor.

IN THE MATTER OF VIEWING, SURVEYING AND LAYING OUT COUNTY ROAD NO. 562. To the Honoralbe County Court of the State of Oregon, for Umatilla County: WE, the undersigned, the viewers heretofore appointed to view and locate Road No.562 submit the following report; Pursuant to an order of the Honorable Court we met John W Kimbrell, surveyor, at Weston, Oregon, on the 29th day of July, 1904, and were by him, each, duly sworn to faithfully and impartially discharge the duties of our appointments.

We called to our aid James Ritchey, C H Stanfield Chainmen, H Martin Marker; who were by the Surveyor, each, duly sworn. We viewed, surveyed and located said Road No. 562, as specified in our order; we find the route practicable; that the lands of Joseph Blumgreen will be damages in the sum of \$25.00; that the lands of J S Templeton will be damaged in the sum of \$133.00; that the lands of Sam Caplinger will be damaged in the sum of \$100.00; the cost of construction of said road will be about \$200.00; the proposed route will be a great improvement over the old route avoiding heavy grades in each direction, and is very much needed as there is are a great amount of heavy hauling over this road; we therefore most respectfully recommend it be established and declared a public highway of Umatilla County, Oregon, and that the old route be declared vacated and abandoned as per petition. Robt. Jamieson

F H Beathe ) Viewers, road Survey No. 562.
John W Kimbrell, Surveyor

John W Kimbrell,

County Surveyor.

Field Notes of Road No. 562.

Commencing at the 1/4 Sec. cor bet secs 24 and 25 in T 4 N R 35, E W M, marked stone 18x7x6 R No. 562, and built mound of stone over corner, thence S 50° E 16.67 chs. distance thence S 62° 22' E 3.09 chs 19.76; thence S 89° E 8.16 chs 27.92; thence N 86° 30' E 7.75 chs 35.67; thence S 80° 45' E 2.03 chs 37.70; thence S 54° E 3.50 chs. 41.20; thence S 18° 17' E 2.75 chs 43.95; thence S 15° 33' E 2.50 chs 46.45; thence S 28° 27' E 1.40 chs, 47.85; thence S 87° E 1.06 chs 48.91; thence N 77° 40' E 2.07 chs 50.98; thence S 85° 10' E .93 chs 51.91; thence S 37° 15' E 2.46 chs 54.37; thence N 84° E 2.10 chs 56.47; thence N 80° F 2.45 chs 58.92; thence S 66° E .89 chs 59.81; thence S 35° 30' 56.47; thence N 80° E 2.45 chs 58.92; thence S 66° E .89 chs 59.81; thence S 35° 30' E 4.55 chs 64.36; thence S 31° 30' E 3.83 chs 68.19; thence S 33° E 3.83 chs 72.02; thence S 24° 30' E 1.88 chs 73.90; thence S 16° E 2.75 chs 76.65; thence S 36° 30' E 655 to a M set post in md of stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L n 6. Thence S 36° 30' E 655 to a mainter of country and stone 20 feet to the West marked L point on County road and marked a pine 10 ins diam bears N 8° W 51 lks dist. marked R T No. 562, R T.

Road to be vacated in secs. 19 and 25, Tp. 4 N Range 35, & 36, E W M. Commencing at a point in sec. 19, T 4 N R 36, E W M, at terminus of road No. 562, thence N 61° W 3.60 chs dist; thence N 29° W 4.07 chs 7.67; thence N 13° 30' W 3.50 chs 11.17; thence N 33° 30' W 7.95 chs 19.12; thence N 40° W 4.50 chs 23.62; thence N 73° W 3.70 chs 27.72; thence N 61° W 3.72 chs 27.72 chs W 3.70 chs 27.32; thence N 81° W 2.80 chs 30.12; thence N 69° W 2.75 chs 32.87; thence N 74° W 3.00 chs 35.87; thence N 27° W 5.20 chs 41.07; thence N 59° W 4.55 chs 45.62; thence N 77° W 9.00 chs 54.62; thence N 70° W 6.90 chs 61.52 to angle No. 2 of road No.

Filed Sept. 9, 1904. Frank Saling, Clerk.

Read 1st time 9-1904.

inches made

es 20 feet