

who were by the surveyor each duly sworn. We viewed surveyed and located said road No 370 as specified in our order and would most respectfully recommend the petitioners prayer be granted and the road be vacated, except the last 15.80 chains, known angle No 7 and terminus of said road. The exception is for the reason the last 15.80 chains includes a portion of another county road that should not be vacated under any circumstances.

W D Hansford }  
J Barnhart } Viewers, Road Survey No 370  
J M Ferguson }

### Field Notes of Road No 370

I commenced at the SW corner of the NW 1/4, Sec 14 in Township No 1 North of Range No 32 East No. N., Set post 4x4 inches by 4 feet long, marked P of No 370, 30 feet East of initial point, dug pits and made mound around post.

Thence North 8000 set post 4x4x4 1/2 inch 30' East marked 1 M, dug pits and made mound around post

Thence	North	distance	
	28.25		
	N 26° W	10.25	38.50
	N 40° W	39.5	42.45
	N 23° W	19.36	61.81
	N 25° 50' W	13.45	75.26
	N 34° W	4.74	8000

Set post 30' feet left marked

2 M, dug pits and raised mound around post

Thence	N	distance	
	N 34° W	3.21	
	N 31° W	30.64	33.85
	North	15.80	49.65

To the NW corner of the NE 1/4 Sec

3 in Township 1 North Range 32 E N. N., marked telegraph pole more than 4x4x4 1/2 inches 30' right R D 370, dug pits and raised mound around it.

I hereby certify that the foregoing is a true transcript of the Field Notes of County Road No 370 as surveyed by me on the 26th day of October 1895,

John W Kimbrell  
Surveyor for Umatilla County, Oregon

Filed November 3, 1895

W D Burroughs, Clerk (Post recorded at Page 43, 2d Post Book No 1)

ROAD NO

500

In the Matter of Viewing, Surveying and Laying Out County Road No 500

To the Honorable County Court of the State of Oregon for Umatilla County:

We, the undersigned the viewers heretofore appointed to view and locate Road No 500, submit the following report: Pursuant to an order of the Honorable Court we met John W Kimbrell, Surveyor, at Post office at Pilot Rock on 27th day of Oct, 1895, and were by him, each duly sworn, to faithfully



and impartially discharge the duties of our appointments,

We called to our aid R Dick }  
6 Davis } Chainmen

G W Kimbrell, Marker

Who were by the Surveyor, each, duly sworn. We viewed, surveyed and located said Road N<sup>o</sup> 500, as specified in our order, and find the route practicable and would most respectfully recommend the same be established a public highway of Unadilla County, Oregon

Lewis J. Gault }  
Herbert Boylen } Viewers Road Survey N<sup>o</sup> 500  
J D Naugh }

Field Notes of Road N<sup>o</sup> 500

I commenced at a point on Range line between Ranges 32 and 33 East, Twp N<sup>o</sup> 2 South, Set Stone 24 x 9 x 8 inches 30' South of initial point marked R 500, built Stone mound around stone.

Angle	Chains	Distance		F.T.
Thence S 59° E	674		L R	1
• N 89° E	627	1301	32°	2
• S 71° E	1607	2908	20°	3
• S 81° E	485	3393	10°	4
• N 79° E	285	3678	20°	5
• S 74° E	607	4285	27°	6
• S 47° E	692	4977	27°	7
• S 68° 30' E	263	5240	21° 30'	8
• S 55° E	410	5650	13° 30'	9
• S 72° E	675	6325	17°	10
• S 56° E	350	6675	14°	11
• N 81° E	370	7045	13°	12
• S 76° E	185	7230	23°	13
• S 87° E	323	7553	11°	14
• S 67° E	447	8000	20°	15
Thence S 40° E	215		27°	16
• S 86° E	317	532	28°	17
• S 81° E	312	844	13°	18
• N 45° E	388	1732	56°	19
• S 80° E	495	1727	55°	20
• S 89° E	482	2209	9°	21
• S 75° E	795	3004	14°	22
• S 53° E	710	3714	22°	23
• S 86° 30' E	520	4234	33° 30'	24
• S 58° E	432	4666	28° 30'	25
• S 89° E	667	5333	31°	26

1 Mile. Marked a Cottonwood 18 inches 20' left Marked 1 M

rd. surveyed  
would most  
the road be  
terminus of  
ins includes  
nder any cir-  
Survey N<sup>o</sup> 370  
township N<sup>o</sup> 1  
g, Marked R  
around post.  
ked 1 M, dug  
It marked  
the N<sup>o</sup> 1/4 Sec  
raph pole mark  
round around it,  
the Field Notes  
October 1898,  
Oregon  
ook N<sup>o</sup> 1)  
N<sup>o</sup> 500  
County:  
nd locate Road  
of the Honor-  
at Plat Rock  
m do faithfully



Thence	N 81°	E	403	5736	10°		27		
	S 79°	E	625	6361		19°	28		
	N 88°	E	937	7295	13°		29		
	N 77°	E	702	8000	11°		30	2 Miles. Set stone 25x15x4 in mound of	
Thence	N 88°	E	750			11°	31	Stone marked 2 M.	
	N 76°	E	615	1365	12°		32		
	S 67°	E	545	1910		46°	33		
	N 49°	E	290	2200	63°		34		
	N 61° 10'	E	275	2475		12°	35		
	N 76° 30'	E	500	2975		15°	36		
	S 89°	E	181	3156		16° 30'	37		
	N 78° 30'	E	223	3379	14° 30'		38		
	N 89°	E	370	3749		10° 30'	39		
	S 67° 30'	E	385	4134		23° 30'	40		
	N 65° 30'	E	494	4628	47°		41		
	S 89°	E	520	5148		25° 30'	42		
	N 80°	E	362	5510	11°		43		
	S 72° 30'	E	1025	6535		27°	44		
	N 82° 30'	E	237	6772	25°		45		
	S 77°	E	973	7745		20° 30'	46		
	S 86°	E	255	8000	9°		47	3 Miles. A stone in place 3x4 feet 1 1/2	
Thence	S 67° 30'	E	420			19°	48	high, marked 3 M, 10 feet left.	
	S 71°	E	855	1275	4°		49		
	S 53°	E	350	1625		18°	50		
	S 73°	E	260	1885	20°		51		
	S 58°	E	188	2073		25°	52		
	S 80°	E	565	2638	22°		53		
	S 63°	E	200	2838		17°	54		
	S 48°	E	1480	4318		15°	55		
	S 40°	E	835	5153		8°	56		
	S 54° 30'	E	760	5913	14° 30'		57		
	S 77°	E	480	6393	23°		58		
	S 46°	E	455	6878		31°	59		
	S 67°	E	550	7428	21°		60		
	S 46° 30'	E	572	8000		9° 30'	61	4 Miles. A Cottonwood 20 inches dia. 20	
Thence	S 45°	E	290			1° 30'	62	left marked 4 M.	
	S 41°	E	468	758		4°	63		
	S 29°	E	268	1026		12°	64		
	S 35°	E	1000	2026	6°		65		
	S 30°	E	365	2381		5°	66		
	S 43°	E	495	2876	13°		67		
	S 46° 30'	E	675	3551	3° 30'		68		



4 in mound of  
M.

3x4 feet 1 ft  
0 feet left.

inches dia 20  
M.

					R	TE	
Thence	S 65° 30'	E	450	4001	19°		69
	S 55°	E	600	4601	19° 30'		70
	S 43° 30'	E	310	4911	41°		71
	S 64°	E	885	5796	20° 30'		72
	S 55°	E	1003	6799	9°		73
	S 66°	E	1201	8000	11°		74
Thence	S 55°	E	385		11°		75
	S 69°	E	280	665	14°		76
	S 59°	E	895	1560	10°		77
	S 53°	E	368	1928	5° 30'		78
	S 32°	E	250	2178	21° 30'		79
	S 45°	E	163	2341	13°		80
	S 60°	E	395	2736	15°		81
	S 46°	E	180	2916	26°		82
	S 77°	E	460	3376	31°		83
	S 62° 30'	E	570	4246	15° 30'		84
	S 70° 30'	E	925	5171	8°		85
	N 63° 30'	E	405	5576	46°		86
	N 60° 45'	E	440	6016	2° 15'		87
	N 74° 30'	E	235	6251	13° 15'		88
	N 61°	E	715	6969	13° 30'		89
	N 70°	E	635	7601	9°		90
	N 65° 30'	E	399	8000	4° 30'		91
Thence	N 65° 30'	E	504				91
	N 61°	E	540	1044	4° 30'		92
	N 72°	E	575	1919	11°		93
	N 45° 30'	E	645	2564	26° 30'		94
	S 77°	E	165	2729	57° 30'		95
	N 83°	E	420	3149	20°		96
	S 66°	E	325	3474	31°		97
	N 59°	E	753	4227	55°		98
	N 78° 30'	E	460	4687	19° 30'		99
	N 87° 30'	E	615	5302	9°		100
	S 64° 30'	E	410	5712	21° 30'		101
	S 72° 30'	E	330	6042	8°		102
	N 67°	E	255	6297	40° 30'		103
	S 75°	E	345	6642	38°		104
	S 67°	E	485	7127	8°		105
	S 47°	E	355	7482	20°		106
	N 84°	E	195	7677	49°		107
	S 65°	E	323	8000	31°		108
Thence	S 37°	E	205		28°		109

5 Miles. Set stone 20x8x7 20' left Marked  
5 M. Built mound of stone around it.

6 Miles. An Alder 6 inches dia. 20' left,  
Marked 6 M.

7 Miles. A Fir 9' diameter 20' right Marked  
7 M.



L R

fence	S 46° 30'	E	200	405	9° 30'	110
·	S 79°	E	355	760	17° 30'	111
·	S 40°	E	385	1145	11°	112
·	S 23° 30'	E	410	1555	26° 30'	113
·	S 35° 30'	E	325	1880	12°	114
·	S 21°	E	353	2263	14° 30'	115
·	S 1° 30'	E	365	2628	19° 30'	116
·	S 25°	E	200	2828	23° 30'	117
·	S 90°	E	260	3088	16°	118
·	S 1° 30'	E	228	3316	7° 30'	119
·	S 10°	N	185	3501	11° 30'	120
·	S 30°	E	271	3772	40°	121
·	S 12°	E	275	4047	18°	122
·	S 20°	N	260	4307	32°	123
·	S 5°	E	365	4672	28°	124
·	S 69°	E	245	4917	61°	125
·	S 3° 15'	E	255	5172	65° 45'	126
·	S 32° 15'	E	420	5597	29°	127
·	S 9°	E	145	5742	23° 15'	128
·	S 37°	E	320	6062	28°	129
·	S 53° 15'	E	360	6422	16°	130
·	S 55°	E	350	6772	2° 15'	131
·	S 75° 30'	E	200	6972	20° 30'	132
·	S 52° 30'	E	123	7095	23°	133
·	S 75° 45'	E	286	7381	23° 15'	134
·	S 67° 30'	E	380	7761	8° 15'	135
·	S 79°	E	185	7946	11°	136
·	S 50°	E	54	8000		
fence	S 50°	E	248			137
·	S 77°	E	290	538	27°	138
·	N 57°	E	365	903	16°	139
·	N 82°	E	845	1748	5°	140
·	N 54°	E	240	1988	25°	141
·	N 77° 45'	E	585	2573	23° 45'	142
·	S 80°	E	305	2878	22° 15'	143
·	N 56°	E	760	3638	44°	144
·	N 38° 45'	E	342	3980	17° 15'	145
·	N 76° 30'	E	395	4375	37° 45'	146
·	N 44°	E	350	4725	32° 30'	147
·	N 80°	E	585	5260	36°	148
·	N 72° 30'	E	505	5765	7° 30'	149
·	S 53° 30'	E	235	6000	54°	150

8 Miles. A pine 20 inches dia. 20' left marked 8 M

ROAD No  
502



				L	R	
Hence	S 82° 30' E	775	6775	29°		151
"	S 81° 30' E	408	7183	1°		152
"	N 83° 15' E	415	7598	15° 15'		153
"	S 85° E	402	8000	8° 30'		154

9 Nails, A pine 20 inches diameter 20'

Left, marked 9 M.

Hence S 51° 15' E 524 524 R.T. Marked Stone from which the SE corner of Sec 19  
T 2 S R 34 E N 11

Bears N 75° 15' E 11.36 chains distance  
a fir 15 inches dia N 26° E 41 lbs  
a pine 6 " " N 88° W 20 lbs

I hereby certify that the foregoing is a true transcript of the field notes of Road N° 500, as surveyed by me, commencing on the 27th day of Oct. 1898

John W Kimbrell  
Surveyor for Umatilla County, Oregon

Filed November 3<sup>d</sup> 1898

B. S. Durruths, Clerk (List recorded in P. D. Book N° 1 Pages 53 & 67)

ROAD N° 502

In the Matter of Viewing, Surveying and Laying Out County Road N° 502

To The Honorable County Court of the State of Oregon for Umatilla County:

We the undersigned, the Viewers heretofore appointed to view and locate Road N° 502, submit the following report: Pursuant to an order of the Honorable Court we met John W Kimbrell, Surveyor, at B. N. French's house on the 25th day of November, 1898, and were by him, each, duly sworn to faithfully and impartially discharge the duties of our appointments.

We called to our aid Elias Reeves, G. J. Calder, Chairman, N. B. Banks, marker, who were by the surveyor, each, duly sworn. We viewed surveyed and located said road N° 502, as specified in our order and find the route practicable and recommend the same be established as a public highway, as per petition.

E. Eads  
J. E. Clark  
N. B. Banks } Viewers Road Survey N° 502

Field Notes of Road Survey N° 502

I commenced at the S.E. corner, Sec 27 T 5 S R 32 E N 11; Set post 4x4x48 inches in mound of stone 18 inches high, 48 inches wide at Base in corner point marked "R. 502";

		Chains	Distance	L	R
Hence	West	58.25			
"	N 58° W	1.60	59.85		58°
"	N 35° W	2.50	62.35		23°

dia. 20  
8 M