

35 | 36
RLS 933 1980

1/4 COR. BETWEEN SECTIONS 35 & 36
FND. 2 1/2" BR. DISK, STAMPED AS SHOWN

CENTER 1/4 COR. SEC. 36
FND. 2 1/2" BR. DISK,
STAMPED AS SHOWN

COUNTY SURVEYOR
T6N
R35E
C1/4
S36
RLS 933 1980

LEGEND

- ⊙ MONUMENT FOUND AS NOTED, USED FOR CONTROL
- SET 1/2" x 30" STEEL REBAR WITH 1" PLASTIC CAP MKD. LS934, OR AS NOTED
- CALCULATED POINT, NOT FOUND OR SET
- CALCULATED 1/4 CORNER, NOT FOUND OR SET
- () BRACKETS INDICATE RECORD DISTANCES
- FOUND 1/2" STEEL ROD, DID NOT USE FOR CONTROL

DETAIL A

SCALE: 1" = 50'

REFERENCE DOCUMENTS:

- SURVEY BY PALMER FOR BRUMBACK
C.S. FILE # M-31-AX
- SURVEY BY NEWALL FOR CAMPBELL
DATED 4/1/87, IN CAMPBELL'S
POSSESSION.
- DEED RECORDS AS FOLLOWS:
BK. 206, Pg. 616
BK. 171, Pg. 636
R. 89, Pg. 722
BK. 191, Pg. 587
R. 27, Pg. 1540

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Victor M. McLind
OREGON
JULY 17, 1980
VICTOR M. McLIND
934

**SURVEY TO SET DEED CORNERS
IN S.W. 1/4 SEC. 36, T.6N., R.35E., W.M.
SURVEYED FOR HOWARD AND BARBARA CAMPBELL
SURVEYED BY VICTOR M. McLIND, L.S. 934, PH. 938-7519
MAY 6, 1986**

SCALE: 1" = 200'

BEARINGS ARE BASED ON ORE. STATE HWY. DEPT. GRID BEARINGS,
CORRECTED TO TRUE.

Umatilla County Surveyor
Date 5-7-86
Rec'd by *KA*
No. 84-38-B

