

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

P-13
400340

T. 1 N., R. 36 E.
1/4 Corner of sections 21 & 22

History of original corner establishment:

1882, Herman D. Graddon, U.S. Deputy Surveyor, while subdividing the township under GLO Contract No. 452 established the corner as follows:

Set a basalt stone 16 X 8 X 8 ins, 11 ins in the ground, from 1/4 sec cor., marked 1/4 on W. face, from which
A fir 20 ins diam, bears S. 65° E. 20 lks dist, marked 1/4 S.B.T.
A pine 28 ins diam, bears S. 30° W. 74 lks dist, marked 1/4 S.B.T.

1997-99, Kaiser, Griffin and Seibold, BLM Cadastral Surveyors, reestablish the corner as follows:

Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original cor.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap
from which

A Douglas fir, 18 ins. diam. bears S. 1° E., 94 1/2 lks. dist., mkd. 1/4 S22 BT.
A ponderosa pine, 14 ins. diam. bears N. 52 3/4° W., 36 lks. dist., mkd. 1/4 S21 BT.
Deposit a magnet in a white plastic case at the base of the stainless steel post.

2000, David L. Haddock, Registered Land Surveyor 852, while surveying in sections 21 and 22 for the Umatilla N.F., finds the original corner stone for the 1/4 corner of sections 21 & 22. This makes the BLM monument an erroneously established corner.

2001, Richard S. Kaiser, BLM Cadastral Surveyor, corrects the BLM's corner as follows:

The 1/4 sec. cor. of secs. 21 and 22, monumented with the original basalt stone, 13 X 7 X 7 ins., (Record 16 X 8 X 8 ins.), loosely set projecting 10 ins. above the ground, mkd. 1/4 on the S. face, from which the remains of the original bearing trees:

A badly decayed stump, species and size indeterminate, bears S. 63 1/4° E., 14.6 ft. dist., no marks visible. (Record: fir, S. 65° E., 13.2 ft.)

A badly decayed stump, species and size indeterminate, bears S. 25 1/2° W., 50.2 ft. dist., no marks visible. (Record: pine, S. 30° W., 48.8 ft.)

From this point, the 1/4 sec. cor. of secs. 21 and 22, erroneously established by Kaiser, Griffin, and Seibold in 1997-99, bears N. 39°27'37" W., 90.58 ft. dist.; monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. and witnessed as described in the official record. I obliterate all marks on both bearing trees.

Remove the stainless steel post and magnet and at the true corner point
Reset the stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top with brass cap
from which new bearing trees

A Douglas fir, 13 ins. diam. bears S. 41 1/2° E., 45.2 ft. dist., mkd. 1/4 S22 BT.

A Douglas fir, 11 ins. diam. bears S. 87° W., 15.2 ft. dist., mkd. 1/4 S21 BT.

These trees have a 2 1/2 in. by 1/4 in. magnetic nail (Mag Nail) driven at the base at the right side-center.

Deposit a magnet in a white plastic case at the base and bury the original stone alongside the stainless steel post.

Description of corner evidence found:

Found a 2 1/2" diameter stainless steel pipe, with 3 1/4" diameter brass cap, projecting 7" out of the ground, surrounded by a rock mound 2 feet in diameter by 5 inches high, marked as shown, from which:

Decayed remains of a stump bears S 61° E, 14.6 feet.

14" Douglas Fir bears S 41 1/2° E, 45.2 feet, with scribing visible on pitched over blaze.

Badly decayed stump bears S 25 3/4° W, 50.2 feet.

12" Douglas Fir bears S 86 3/4° W, 15.2 feet, with scribing visible on pitched over blaze.

Description of monument and accessories I established to perpetuate the original location of this corner:

New references:

17" Douglas Fir bears N 73 1/2° E, 28.1 feet, scribed "1/4 S22" "BT".

11" Ponderosa Pine bears S 10 3/4° W, 48.1 feet, scribed "1/4 S21" "BT".

The new bearing trees are double blazed and have a 3/4" diameter brass washer stamped "RLS 2308" nailed to the lower blaze between the scribed "B T".

DATUM: NAD83(1991) Oregon High Accuracy Reference Network
STATE PLANE COORDINATES: Oregon North Zone in International Feet
No. Latitude Longitude Northing(Y) Easting(X)
400340 45°33'04.22464" N. 118°18'28.03675" W. 694663.763 8763610.648'


Work Performed By: David A. Schlaich (RLS 2308)

Witnessed By: Matthew Duffy

Equipment: Topcon GPT-6005C Total Station

Magnetic Declination: 17 1/2° East

Date: August 22, 2002



**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

David A. Schlaich

OREGON
JULY 16, 1987
DAVID A. SCHLAICH
2308

RENEWAL DATE: 06/30/2004

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 20.....

..... by.....
(COUNTY OFFICIAL) (DEPUTY)