


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

R-15
440300
T. 1 N., R. 36 E.
1/4 Corner of sections 22 & 27

History of original corner establishment:

1882, Herman D. Graddon, U.S. Deputy Surveyor, while subdividing the township under GLO Contract No. 452 established the corner as follows:
Set a basalt stone 14 X 14 X 4 ins, 9 ins in the ground, for 1/4 sec cor., marked 1/4 on N. face, from which
A fir 28 ins diam, bears N. 10° E. 34 lks dist, marked 1/4 S.B.T.
A fir 26 ins diam, bears S. 58° W. 15 lks dist, marked 1/4 S.B.T.



1997-99, Kaiser, Griffin and Seibold, BLM Cadastral Surveyors, reestablish the corner as follows:
Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original cor.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to solid rock, and supported in a mound of stone, 3 ft. base, to top, with brass cap from which
A Douglas fir, 22 ins. diam. bears S. 75 3/4° E., 8 lks. dist., mkd. 1/4 S27 BT.
A Douglas fir, 16 ins. diam. bears N. 2 1/4° W., 50 lks. dist., mkd. 1/4 S22 BT.
Deposit a magnet in a white plastic case at the base of the stainless steel post.

2000, David L. Haddock, Registered Land Surveyor 852, while surveying in sections 21 and 22 for the Umatilla N.F., Found the standard BLM brass capped monument in good shape as described. Both bearing trees were found in good shape and marked new BT's to reference the BLM corner
16" Douglas Fir bears N. 85° W., 75.2 feet scribed 1/4 S27 BT.
11" Douglas Fir bears S. 36 3/4° W., 49.2 feet scribed 1/4 S22 BT.
After marking the new bearing trees Haddock finds the original corner stone and GLO BT's. Haddock reports this discovery to the Forest Service which instructs him that they will report the revisions to the county after the BLM corrects their survey.

2001, Richard S. Kaiser, BLM Cadastral Surveyor, corrects the BLM's corner as follows: The 1/4 sec. cor. of secs. 22 and 27, monumented with the original basalt stone, 15 X 12 X 5 ins., (Record 14 X 14 X 4 ins.), loosely set 6 ins. in the ground, mkd. 1/4 on the N. face, from which the remains of the original bearing trees:
A Douglas fir, 36 ins. diam. bears N. 20 1/2° E., 23.8 ft. dist., with a healed blaze (Record: N. 10° E., 22.4 ft.)
A fir snag, 26 ins. diam. bears S. 45 3/4° W., 9.6 ft. dist., with scribe marks 1/4 S BT and axe marks visible on partially opened blaze. (Record: S. 58° W., 9.9 ft.)
From this point, the 1/4 sec. cor. of secs. 22 and 27, erroneously reestablished by Kaiser, Griffin, and Seibold in 1997-99, bears S. 0°56'05" E., 45.51 ft. dist.; monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, and in a mound of stone, 3 ft. base, 1/2 ft. high, with brass cap mkd. and witnessed as described in the official record. I obliterate all marks on both bearing trees.
Remove the stainless steel post and magnet and at the true corner point
Reset the stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap from which the bearing trees mkd. by Dave Haddock, Registered Land Surveyor No. 852, in 2000 and not yet recorded
A fir, 11 ins. diam. bears S. 18 3/4° W., 89.3 ft. dist., with scribe marks 1/4 S27 BT visible on open blaze and an aluminum washer mkd. RLS 852 nailed onto face.
A fir, 16 ins. diam. bears S. 63° W., 84.6 ft. dist., with scribe marks 1/4 S21 BT visible on open blaze. (erroneously marked).
Deposit a magnet in a white plastic case at the base, and bury the original stone alongside the stainless steel post.

Description of corner evidence found:

Found a 2 1/2" diameter stainless steel pipe, with 3 1/4" diameter brass cap, projecting 5" out of the ground, surrounded by a ring of stones with the original corner stone lying on the south side of the pipe, marked as shown, from which:
36" Douglas Fir bears N 16 3/4° E, 22.8 feet, with healed blaze.
11" Douglas Fir bears S 18 3/4° W, 89.9 feet, with scribing visible on pitched over blaze and a 3/4" diameter aluminum washer stamped "RLS 852" nailed to the bottom of the blaze.
26" Douglas Fir snag bears S 46 1/2° W, 9.9 feet, with scribing 1/4 S BT visible on chopped open blaze.
16" Douglas Fir bears S 62 3/4° W, 84.6 feet, with scribing visible on pitched over blaze.

Description of monument and accessories I established to perpetuate the original location of this corner:

New reference:
16" Douglas Fir bears S 55° E, 20.7 feet, scribed "1/4 S27" "BT" on double blaze with a 3/4" diameter brass washer stamped "RLS 2308" nailed to the lower blaze between the scribed "B T".

DATUM: NAD83(1991) Oregon High Accuracy Reference Network
STATE PLANE COORDINATES: Oregon North Zone in International Feet
No. Latitude Longitude Northing(Y) Easting(X)
440300 45°32'38.86099" N. 118°17'51.63263" W. 692166.315' 8766270.168'

Work Performed By: David A. Schlaich (RLS 2308)
Witnessed By: Matthew Duffy
Equipment: Topcon GPT-6005C Total Station
Magnetic Declination: 17 1/2' East
Date: August 28, 2002



**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

David A. Schlaich

OREGON
JULY 16, 1987
DAVID A. SCHLAICH
2308

RENEWAL DATE: 06/30/2004

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 20.....
..... by.....
(COUNTY OFFICIAL) (DEPUTY)