

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment:

Corner established by George S. Pershin under G.L.O. contract number 304 dated Sept., 19, 1878.

Surveyor General's records state:

Set a fir post on nearly level for 1/4 sec cor from which:

- A fir 12" diam. bears N 38° W., 30 lks dist. marked 1/4 S BT
- A fir 14" diam. bears S 30° W., 54 lks dist. marked 1/4 S BT



2-19

Description of corner evidence found:

A fir stump 30" diam. with healed lower blaze and a downed and rotting tree alongside with visible scribing 1/4 S.

Description of monument and accessories established to perpetuate the original location of this corner

Set a 2 1/2" brass cap on a 2" iron pipe 31" long 6" above ground with a 6' steel fence post 3' west with a sign 54-4 attached.

new bearing trees:

- A fir 9" diam. bears N 56° E., 22.0 ft. dist. marked 1/4 S 35 BT
- A fir 10" diam. bears S 02° E., 20.0 ft. dist. marked 1/4 S 2 BT

Each BT has a sign 54-3 attached 6" below a band of red paint and has a brass washer marked RPE 2808 nailed flush with BT blaze.



Office of.....Surveyor..... County of.....Umatilla.....
 State of.....Oregon....., I hereby certify that the within instrument was filed in this office
 for record on the 26 day of August, 1976
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment:

Corner established by George S. Pershin under G.L.O. contract number 304 dated Sept., 19, 1878.

Surveyor General's records state:

Set a fir post on nearly level for 1/4 sec cor from which:

- A fir 12" diam. bears N 38° W., 30 lks dist. marked 1/4 S BT
- A fir 14" diam. bears S 30° W., 54 lks dist. marked 1/4 S BT



Description of corner evidence found:

A fir stump 30" diam. with healed lower blaze and a downed and rotting tree alongside with visible scribing 1/4 S.

Description of monument and accessories established to perpetuate the original location of this corner

Set a 2 1/2" brass cap on a 2" iron pipe 31" long 6" above ground with a 6' steel fence post 3' west with a sign 54-4 attached.

new bearing trees:

- A fir 9" diam. bears N 56° E., 22.0 ft. dist. marked 1/4 S 35 BT
- A fir 10" diam. bears S 02° E., 20.0 ft. dist. marked 1/4 S 2 BT

Each BT has a sign 54-3 attached 6" below a band of red paint and has a brass washer marked RPE 2808 nailed flush with BT blaze.



Office of.....Surveyor..... County of.....Umatilla.....
 State of.....Oregon....., I hereby certify that the within instrument was filed in this office
 for record on the 26 day of August, 1976
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)