

OREGON CORNER RESTORATION FORM

Section 10 Township 4N Range 28E

E-13

County UMATILLA Date 11/95

CORNER DESIGNATION

NW Cor.

- Condition Report Only
- Not Found
- Renewed
- Unrecorded
- Surveyed In
- Referenced Out


Previous Renewals/Surveys, etc. ORIG. SURVEYED IN 1860 BY HAFT
KRUMBEIN SET BC in Place of CONTRACT # 93
1" I.Pipe in 1980

Monument(s) & Accessories Found: (Condition and Source)

End 5/8" rebar I set in 1987 for West S 87° 14' 57" W 477.09 Feet from Cor.
End 5/8" rebar I set in 1984 for Flink S 9° 45' 06" W 202.28 Feet from Cor.

Monument Detail

Sketch



Monument Set (Procedures and Description)

From my top 5/8" rebar I set a 5/8" x 30" rebar with a
2" Alum. Cap stamped as above Flush with the pavement.

SEE MY SURVEY FOR COLUCCIO

New Accessories

- An Alum tag #951 in P. Pole lies N 75° 23' 12" E 133.63 Ft.
- An Alum Tag #951 in P. Pole lies N 36° 00' 54" W 42.92 Ft.
- An Alum Tag #951 in P. Pole lies S 81° 45' W 249.83 Ft.
- A 1" x 30" I. Pipe with 2 3/8" BC Bears S 39° 17' 41" E 63.29 FT.

Location & Comments

At the intersection Compass Declination
of ELM & 11TH Streets Firm/Agency EDWARDS
SURVEYING
Address P.O. Box 763
HERMISTON, OR 97038
Party Chief D. Edwards
Notes
Witness J. Coppock

Surveyor's Seal

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

G. Dennis Edwards

OREGON
 JULY 16, 1971
 G. DENNIS EDWARDS
 951

RENEWS 12/31/95

09-39-A