


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established.



K-24

Description of corner evidence found:

N/A

Description of monument and accessories established to perpetuate the original location of this corner:

Set 3"x30" iron pipe with 3" brass cap stamped as shown on the diagram, set 14 inches in the ground and raised a mound of stone around the pipe.

From which:

A juniper 10 in. dia. bears S64°W, 9.5 ft. scribed NE 1/16 S 13 BT. No other tree available.

Set steel posts with warning and boundary signs 5 ft. North and 5 ft. East from corner.

Nailed bearing tree signs and brass washers stamped PLS 848 to tree. Painted a red band around tree.

I hereby certify that the above corner monument was established as herein described on 8/5/81.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Douglas M. Ferguson
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Witnesses: D. Mitchell Ferguson

Mike Woodward

Office of... Co. Surveyor..... County of... Umatilla.....
State of... Oregon..... I hereby certify that the within instrument was filed in this office
for record on the... 2nd... day of... January....., 1982
... *David Krumm*... by *Betty Shurt*...
(COUNTY OFFICIAL) (DEPUTY)