


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. G-11

History of original corner establishment:

No corner was originally set.



Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

At surveyed point set 1"x30" Galvanized Pipe with brass cap stamped:

Set cap 24" in ground with mound of stone to cap.

Bearing Trees:

A White Fir 16" dia. bears S24°W 10.4 ft., scribed:  
C 1/4 S9 BT.

A White Fir 25" dia. bears S89°W 15.8 ft., scribed:  
C1/4 S9 BT.

Attached 54-3 and 54-4 signs to both BTs. Attached brass washers stamped LS 1294 to foot blaze of both BTs. Painted blazes and 6" band around both BTs red.



I hereby certify the above corner monument was established as herein described on September 26, 1980.

Witnesses: R. Orton  
G. Wagoner  
L. Huntsman  
A. Hanley

Office of..... County Surveyor..... County of..... Umatilla  
 State of..... Oregon....., I hereby certify that the within instrument was filed in this office  
 for record on the..... day of..... December..... 19..... 80  
*Dennis A. Hummer* by *Billy Skatto*  
 (COUNTY OFFICIAL) (DEPUTY)