


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

17-0

History of original corner establishment:

None



Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner

Set 32" X 2" flanged iron pipe with brass cap marked:

From Which

White Fir, 11" Dia., BRS. S20°E., 23.3 Ft. Dist.

Marked: W 1/16 S6 BT

White Fir, 14" Dia., BRS. S32½°W., 34.2 Ft. Dist.

Marked: W 1/16 S6 BT

6" Iron Fence Post with "Survey Monument" sign within 5' of Corner.


T6S R30E
W 1/16
S6
1979
PLS 346

All B.T. have BT tag and painted red stripe. New BTs have brass washer stamped: PLS 346; nailed to lower blaze.

Office of County Surveyor County of Umatilla  
 State of Oregon, I hereby certify that the within instrument was filed in this office  
 for record on the        day of         
 \_\_\_\_\_ by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

**RECEIVED BY**  
**Umatilla County Surveyor**  
 Date 10-17-79  
 Rec'd By WMS  
 No. 0-1171-B



A-2