

Index

File No. C-18

T. 7 S. R. 34 E.

Merid. WILLAMETTE

CORNER RECORD (SEARCH)

(Ref. FSM 7151.4)

R.D. NFJD

N.F. UMATILLA


County GRANT

State OREGON

Tract or
Survey No.

Cor.
No.

CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND

2 1/2" aluminum pipe with 2 1/2" aluminum cap, projecting 3" out of the ground, marked "W1/16 C----C S2 RPLS 1910 1986".

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

8" Lodgepole Pine, N. 47° E., 12.6 ft., mkd. "CW1/16 S2""BT" on double blaze.
 10" Lodgepole Pine, N. 22° E., 26.9 ft., mkd. "CW1/1 S2""BT" on double blaze.
 Both BT's have a 3/4" brass washer marked "RPLS 1910" nailed to the lower blaze by the "BT" scribing.

PHOTO IDENTIFICATION DATA

Photo No.:
 Filed At.:
 Object Ident.:
 Ident. By:

Signature

DESCRIBE CORNER RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

From the jct. of roads 52 and 5225 travel southeasterly on 5225 approx. 2.50 miles to the property line crossing. Then walk N. 0° 33' W., approx. 520 feet to the corner.

PLANE COORDINATE POSITION DATA

State: Zone:

Y:
 Datum:

Signature
D. Schlaich

Title
Land Surveyor

Division

Headquarters
S.O.

Date
10-1993

FS-7100-52 (3/68)

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

ACCESSORIES : DESCRIBE NEW BT's WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

Work Done By **D. Schlaich**

Title **Land Surveyor**

Date **10-1993**

State Registration No.
or Agency

Cellfied Cor. Record Prepared ? **YES**

Filed At: **Grant County Surveyor's Office**

Date

REMARKS

Index File No.
C-18

T.
7 S.

R.
34 E.

M.
W.M.

Tract or Survey No.

Cor.

Index

File No. C-18

CORNER RECORD (SEARCH)

(Ref. FSM 7151.4)

Tract or Survey No. _____ Cor. No. _____


T 7 S. 5 R. 34 E.

R.D. NORTH FORK JOHN DAY County GRANT

Merid. WILLAMETTE

N.F. UMATILLA State OREGON

CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND

NONE

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

NONE

PHOTO IDENTIFICATION DATA

Photo No. _____

Filed At. _____

Object Ident. _____

Ident. By _____

Signature

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

TAKE ROAD 5225 TO POSTED BOUNDARY, GO NORTH 525' TO CW 4/16.

PLANE COORDINATE POSITION DATA

State _____ Zone _____

X _____

Y _____

Estab. By _____

Agency

Clayton J. [Signature]

Signature

LAND SURVEYOR

Title

Division

Headquarters

Date

10/25/06

FS-7100-52 (3/68)

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

SET A 2 1/2" DIAM. ALUM. CAP ON A 2 1/2" X 30" ALUM. PIPE
W/FLARE AT BOTTOM. CAP MKD. PER SKETCH.

SET STEEL POSTS 4' ± E. & S. W/PROP. BANDY, ATTN. & MON.
SIGNS ATTACHED.

C $\frac{W'116}{S2}$ C
RPLS 1910
1986

ACCESSORIES : DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

① 10" D.B.H. LODGEPOLE PINE, N. 22° E, 26.9', SCRIBED CW'116 S2 BT.

② 7" D.B.H. LODGEPOLE PINE, N. 47° W, 12.6', SCRIBED CW'116 S2 BT.

EACH BT. HAS A BRASS WASHER MKD. RPLS 1910 SET BTWN. B&T, BT. TAG,
ATTN. SIGN, BAND AND FACE PAINTED RED.

Work Done By C.J. MARTIN Title LAND SURVEYOR Date 10/25/86 State Registration No. LS 1910
or Agency

Certified Cor. Record Prepared ? Yes (No) Filed At: _____ Date _____

REMARKS

Index File No. T. 7 S R. 34 E M. WILLAMETTE Tract or Surv. No.

C-18

Cor. CW'116