

# FIELD NOTES

47

Of the survey of the Subdivision of Allotments

Lines of Township 1 North

Range 33 East Willamette Meridian,

Oregon, as surveyed by James P. Carrin

U. S. Deputy Surveyor, under his Contract No. 537

dated March 5th 1889

Survey commenced, June 18th 1889

Survey completed, June 22nd 1889

## NAMES AND DUTIES OF ASSISTANTS,

James P. Carrin, Compassman.

J. R. Sarrance, Chainman.

G. L. Brown, Chainman.

/, Chainman.

/, Chainman.

C. M. Stone, Axeman.

R. E. Long, Axeman.

/, Flagman.

47A

# PRELIMINARY OATHS OF ASSISTANTS.

We, J. R. Saramore, J. L. Brown,  
C. M. Stone & R. E. Long,

do solemnly swear that we will faithfully execute the duties of Chain Carriers, that we will level the chain over even and uneven ground, and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we will assist in measuring, to the best of our skill and ability, and in accordance with the instructions given us in

the survey of the Subdivisional and  
Settlement lines of T. 1. N. R. 33.  
E. Willamette Meridian, Oregon.

J. R. Saramore, Chainman.  
J. L. Brown, Chainman.  
\_\_\_\_\_, Chainman.  
\_\_\_\_\_, Chainman.

Subscribed and sworn to before me, this 18th  
day of June 1889  
[SEAL.] Thos FitzGerald  
Notary Public

We, C. M. Stone and  
R. E. Long, do solemnly swear  
that we will well and truly perform the duties of Axemen in the establishment of corners  
and other duties, according to instructions given us, and to the best of our skill and abil-  
ity, in the survey of the \_\_\_\_\_

\_\_\_\_\_, Willamette Meridian, Oregon.  
C. M. Stone, Axeman.  
R. E. Long, Axeman.

Subscribed and sworn to before me, this 18th  
day of June 1889  
[SEAL.] Thos FitzGerald  
Notary Public



553  
105  
Allotment

Subdividing T. 1 North R. 33 East  
Willamette Meridian, Oregon.

See 18

From the <sup>closing</sup> corner to Ties  
7 and 18 on West boundary  
of Township which is a  
basalt stone 16 + 10 + 8 ins  
12 ins in the ground marked  
C.C. on E. face & 4  
notches on S and 2 notches  
on N. edges with pits 18  
x 18 x 12 ins N. E. & S of stone  
5 1/2 ft. dia & mound of  
earth 2 1/2 ft. high 4 1/2 ft  
base over it

I marked stone D.R.  
on the E face.

From

South on the W. bdy of  
Sect. 18.

Var 21° 30' E

2.15 To the old corner to Ties 12 & 13.  
T. 1 N R 32 E.

199 Subdivision of T. 1 North R. 33 East

Willamette Meridian, Oregon.

See 18

(8093-10 M.)

which is a Basalt stone  
 9 x 8 x 7 ins<sup>6 ins.</sup> in the ground  
 marked with 3 notches on  
 N. & S. edges pits in each  
 section 5 1/2 ft. dirt and  
 mound of earth alongside  
 I marked D R on E. face

22.75

Top of hill

27.75

Gulch corner N.

-50

40.00

Set a stone 9 x 8 x 7 ins  
 6 ins in the ground for  
 closing 1/4 Sec corner to S. 18

T. 1 N R 33 E. marked.

C.C. 1/4 on E. face; dug pits

18 x 18 x 12 ins N & S. of

stone 5 1/2 ft dirt and raised

a mound of earth 1 1/2  
 feet high 3 1/2 ft base on it.

41.95

Intersect the 1/4 Sec corner

on the E. side of <sup>Sec</sup> 13. S. 18

N R 32 E.

Allotment

5757

Subdivision of T. 1 North R. 33 East 107  
Willamette Meridian, Oregon.

Sec 18

which is a basalt stone  
18 x 19 x 8 in 7 in in the  
ground marked 1/4 on W face  
sets 18 x 18 x 12 in N + S of  
corner 5 1/2 ft dirt & mound  
of earth 1 1/2 ft high 3 1/2 ft base  
around.

I marked stone D R on  
East face

50.75	Top of hill	+ 100
55.50	Dry Gully corner N.	- 50
80.00	The closing corner to Secs. 18 + 19. T. 1 N R 33 E.	

Land rolling

Soil 3<sup>d</sup> rate

Very little grass.

Attachment

Subdiv of T. 1 North R. 33 E. 119

Willamette Meridian, Oregon.

See 19

From the corner to Sees 18 + 19 on N. ldy of Sp  
South Var 21° E.

1.72 Pass corner to Sees 13 + 24  
T. 1 N R 32 E. which is a  
basalt stone 9 + 8 + 7 ins l.  
ins in the ground marked with  
3 notches on N. & S edges; pits 18 +  
18 + 12 in each sec - mound  
of earth 2 ft high 4 1/2 ft base  
over it.  
I marked stone D. R. on E face

480 Trail corner N.W.

3080 Summit corner W.

3350 Gulch corner W

39.50 Set stone 9 + 8 + 7 ins  
6 ins in the ground for 1/4  
See corner marked 1/4 on N  
face and D R on E face  
dry pits 18 + 18 + 12 ins N & S  
of stone 5 1/2 ft deep & raised a  
mound of earth 2 1/2 ft high  
3 1/2 ft base over it.

68B

120

Allotment

Sub Area of T. 1 North R. 33 E.

Willamette Meridian, Oregon.

Sec 19

(8093-10 M.)

4134 Intersected the  $\frac{1}{4}$  Sec corner  
 on E. body of Sec 24 S. 1 N. R. 33 E.  
 which is a basal stone 14  
 12 x 8 ins <sup>10</sup> in the ground  
 marked  $\frac{1}{4}$  on N face pits 18  
 x 18 x 12 ins N. S. of corner 5  $\frac{1}{2}$   
 ft dirt mound of earth 1  $\frac{1}{2}$   
 ft high 3  $\frac{1}{2}$  ft base over it  
 I marked stone D. R. on E. face

5680 summit of hill

6180 Gulch corner W

7920 To the corner to Secs 19  
 & 30 S. 1 N. R. 33 E. which is  
 a basal stone 9 x 8 x 7 ins  
 6 ins in the ground marked  
 C. C. on E. faces with 2  
 notches on S. and 4 notches  
 on N edges with pits 18  
 x 18 x 12 ins N. E. & S. of stone  
 5  $\frac{1}{2}$  ft dirt mound of earth  
 2 ft high 4  $\frac{1}{2}$  ft base over it  
 I marked Stone D. R. on E. face  
 Land rolling Soil 3<sup>d</sup> out  
 bunch grass & sage brush,

Allotment

1725  
177

Subdivision of T. 1 North R. 33 East  
Willamette Meridian, Oregon.

See 30

78.14 Intersect West. boundary of  
Sp. at closing. corner to Secs  
30 & 31. T. 1 N R. 33 E.

which is a basalt stone  
9 + 8 + 7 ins 6 ins in the ground  
marked C.C. on E. face with  
1 notch on S. and 5 notches  
on N. faces. with pits 18 + 18 + 12  
ins N.E. & S. of stone 5 1/2 ft dia  
and mound of earth 2 ft. high  
4 1/2 ft. base over it. I marked  
stone D.R. on E. face

Land rolling  
Soil very ashy  
very little grass.

From the corner to Secs. 19 + 30  
on the West bdy of Sp.

I run  
South on true line on the  
West bdy of Sec 30.  
Var 20° E

Subdivisions of T. 1 North R. 33 East  
Willamette Meridian, Oregon.

See 30.

(8093-10 M.)

130

To the corner of Tces 24 + 25  
T. 1 N. R. 32 E. which is a  
basalt stone 14 + 10 + 8. ins  
10 ins in the ground marked  
2 notches on S. and 4 notches on  
N. edges pits 18 + 18 + 12 ins  
in each see 5 1/2 ft dist and  
mound of earth 2 ft high 4 1/2  
ft base along side I marked  
stone D. R. on E face

2000

Deposited charred stake 12 ins  
in the ground for 1/6 Sec cor  
day pits 18 + 18 + 12 ins N. S.  
of corner 5 1/2 ft dist and  
raised mound of earth 1 1/2  
ft high 3 1/2 ft base over it.  
In N. pit drove a stake  
2 ft long 2 ins square 12 ins  
in the ground marked 1/6 S.  
on N. face + D R on E face

Allotment

127

Subdivision of T. 1 North R. 33 East <sup>179</sup>  
Willamette Meridian, Oregon.

See 30

40.00 Set a basalt stone 10 x 8 x 6 ins  
6 ins in the ground for  $\frac{1}{4}$  Sec.  
corner marked  $\frac{1}{4}$  on N. and D.R.  
on the E. face dug pits 18 x 18  
x 12 ins N. & S. of stone 5  $\frac{1}{2}$  ft. dia  
and raised a mound of earth  
1  $\frac{1}{2}$  ft high 3  $\frac{1}{2}$  ft base over it.

41.15 To the  $\frac{1}{4}$  Sec corner on E ldy  
of Sec 25 T. 1 N R 33. E  
which is a basalt stone 12.  
x 10 x 10 ins 8 ins in the ground  
marked  $\frac{1}{4}$  on W. face pits 18 x 18.  
x 12 ins N. & S. of stone 5  $\frac{1}{2}$  ft dia  
and mound of earth alongside  
I marked Stone D.R. on E. face

60.00 Set basalt stone 10 x 8 x 7 ins  
6 ins in the ground for  $\frac{1}{6}$  Sec.  
corner marked  $\frac{1}{6}$  on N. and D.R.  
on E face dug pits 18 x 18 x 12  
ins N. & S. of stone 5  $\frac{1}{2}$  ft dia.

128

Attachment

Subdivided of T. 1. North R. 33 East

Willamette Meridian, Oregon.

Sec. 30

(8093-10 M.)

and raised a mound of earth 1 1/2 ft high 3 1/2 ft low over it.

8000

To the Closing corner to Sec. 30 & 31.

Land rolling

Soil ashy

Very little vegetation

From the 1/6 Sec corner 20 ch N. of corner to Secs. 29 & 30 - 31 & 32.

I run

West on random line through 1/4 of Sec. 30.

Var 20° East

Setting temporary corners at 20 - 40 - 60 ch and at

78.20 Intersect the West boundary of Township 6 th South of 1/6 Sec cor on W bdy. of Sec 30.

Subdivision of T. 1 North R. 33 East  
 Willamette Meridian, Oregon.

Sec 30.

(8093-10 M.)

- 58.25 Set a basalt stone  $9 \times 8 \times 7$   
 ins 6 ins in the ground for  
 $\frac{1}{16}$  Sec. corner marked  $\frac{1}{16}$  on  
 N face. dig pits  $18 \times 18 \times 12$   
 ins E. & W. of stone  $5\frac{1}{2}$  ft. dist.  
 and raised a mound of earth  
 $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft low over it.
- 66.75 Creek  $5\frac{1}{2}$  wide course S.  $\frac{1}{2}$  N.
- 78.25 To the  $\frac{1}{16}$  Sec corner between  
 Secs 29 & 30  
 Land mostly level  
 Soil 2<sup>nd</sup> rate  
 Needs.

From the closing corner of  
 Secs 30 & 31. on West ldy  
 of S.  $\frac{1}{2}$  N.

From  
South on true line on W. ldy  
 of Sec 30.

Var  $20^{\circ} 30'$  East

Attachment

187

138

Subdivision of T. 1 North R. 33 East

Willamette Meridian, Oregon.

See 30.

- 1.22 To the old corner to corner  
 Secs 25 & 36. T. 1 N R 32 E.  
 which is a basalt stone 16 x  
 12 x 8 ins 11 ins in the ground  
 marked 1. notch on S. & 5 notches  
 on N. edges pits in each sec.  
 18 x 18 x 12 ins. 5 1/2 ft dirt and  
 mound of earth 2 ft high 4 1/2  
 ft base alongside. In marked stone  
 D R. on E. face  
 900 Trail corner S.W.  
 2000 Set a basalt stone 10 x 8 x 7 ins  
 6 ins in the ground for 1/16 Sec.  
 corner marked 1/16 on W. face  
 & D.R. on E. face.  
 dug pits 18 x 18 x 12 ins N & S.  
 of stone 5 1/2 ft dirt and raised  
 a mound of earth 1 1/2 ft high  
 3 1/2 ft base over it.  
 3600 Gulch corner W. West  
 4000 Set basalt stone 9 x 8 x 7 ins

## Allotment

Subdivision of T. 1 North R. 33 East  
Willamette Meridian, Oregon.

See 31.

(8093-10 M.)

6 ins in the ground for  $\frac{1}{4}$   
See corner marked  $\frac{1}{4}$  on W.  
and D.R. on E. face  
dug pits 18 + 18 + 12 ins N + S  
of stone  $5\frac{1}{2}$  ft dirt and raised  
a mound of earth  $1\frac{1}{2}$  ft high  
 $3\frac{1}{2}$  ft base over it.

40.60 To the old  $\frac{1}{4}$  See corner on the  
East body of See 36. T. 1 N. R.  
33 E. which is a basalt stone  
10 + 8 + 6 ins 7 ins in the ground  
marked  $\frac{1}{4}$  on W. face pits  
18 + 18 + 12 ins N + S of stone  
 $5\frac{1}{2}$  ft dirt and mound  
of earth  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft  
base over it. I marked  
stone D.R. on E. face

60.00 Set a basalt stone 9 + 8 + 7 ins  
6 ins in the ground for  $\frac{1}{16}$   
See corner marked  $\frac{1}{16}$  on W.  
+ D.R. on E.  
face. dug pits 18 + 18 + 12.

Attachment

189

Subdivision of T. 1 North R. 33 East

Willamette Meridian, Oregon.

See 31.

ins N. S. of stone 5 1/2 ft dirt  
 and raised a mound of earth  
 1 1/2 ft high 3 1/2 ft base over it.  
 8000 To the corner to Township 1.  
 N. Range 32 & 33 E. in the  
 Base line which is a basal  
 stone 16 x 14 x 10 ins 11 ins in  
 the ground marked S. C. with  
 6 notches on N. E. & W edges  
 and mound of stone over it.  
 I marked stone D. R. on E.  
 face.

Land level

Soil 2d rate

Very little grass.

210  
FINAL OATHS FOR SURVEYS.

A list of the names of the individuals employed by James P. Currier, U. S. Deputy Surveyor, to assist in running, measuring and marking the lines and corners described in the foregoing field notes of the survey of the Subdivisional and Allotment lines of T. 1. N. R. 33 E. Willamette Meridian, Oregon, showing the respective capacities in which they acted :

- ....., Compassman.
- J. R. Laramore....., Chainman.
- T. L. Brown....., Chainman.
- W. B. H......, Chainman.
- ....., Chainman.
- C. M. Stone....., Axeman.
- R. E. Long....., Axeman.
- ....., Flagman.

FINAL OATHS OF ASSISTANTS.

We hereby certify that we assisted James P. Currier, U. S. Deputy Surveyor, in surveying all those parts or portions of the Subdivisional and Allotment lines of T. 1. N. R. 33. E. Willamette Meridian, Oregon, as are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the U. S. Surveyor General of Oregon.

- ....., Compassman.
- J. R. Laramore....., Chainman.
- T. L. Brown....., Chainman.
- ....., Chainman.
- ....., Chainman.
- C. M. Stone....., Axeman.
- R. E. Long....., Axeman.
- ....., Flagman.

Subscribed and sworn to before me, this 2nd day of July

1889  
[SEAL.] Thos Fitzherald  
Notary Public

## FINAL OATH OF DEPUTY SURVEYOR.

I, James P. Currin  
United States Deputy Surveyor, do solemnly swear that in pursuance of

instructions received from Douglas H. Taylor

U. S. Surveyor General for Oregon, bearing date of the 19th

day of March 1889, I have well, faithfully and truly, in my own proper person, and in strict conformity with the instructions furnished by the U. S. Surveyor General for Oregon, the Surveying Manual, and the laws of the United States, surveying all those

parts or portions of Subdivisional and Allot-

ment Lines of T. 1. N. R. 33. E.

Willamette Meridian, in the State of Oregon, as are represented in the foregoing field notes as having been surveyed by me and under my directions; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Surveying Manual, printed instructions, the special written instructions of the U. S. Surveyor General for Oregon, and in the specific manner described in the field notes, and that the foregoing are the *true* field notes of such survey, and should any fraud be detected I will suffer the penalty of perjury under the provisions of an Act of Congress approved August 8, 1846.

James P. Currin  
U. S. Deputy Surveyor.

Subscribed and sworn to before me, this 2nd

day of July 1889

Thos FitzGerald  
Notary Public

218

Office U. S. Surveyor General,

Portland, Oregon, August 31 - 1889

*Benegany*  
The following Field Notes of the Survey of the

*Subdivisional and Allotment*  
*Lines of Township 1 North*  
*Range 33 E. Will Mar Oregon*

executed by *James J. Currier* U. S. Deputy  
*Surveyor*  
under his Contract No. *537*, dated

*March 5<sup>th</sup>* 1889, having been critically examined, the  
necessary corrections and explanations made, the said Field Notes  
and the survey they describe, are hereby approved.

*Douglas W. Taylor*  
Surveyor General.