

FIELD NOTES

Of the survey of the

*Exteriors*Lines of *Tps. 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100**R's 31, 33, 34 & 35, E. Tps. 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35* Willamette Meridian, Oregon,as surveyed by *James P. Currier and James E. Poland*
their special

U. S. Deputy Surveyor, under his Contract No. _____

dated *May 4th*, 1887Survey commenced, *June 14th*, 1887Survey completed, *Aug 30th*, 1887

NAMES AND DUTIES OF ASSISTANTS.

L. J. Wooley , Compassman.
J. Medley , Chainman.
W. H. Medley , Chainman.
Guy Davis , Chainman.
Frank Selshard , Chainman.
J. P. Crowner , Axman.
J. A. Hadley , Axman.
..... , Flagman.

PRELIMINARY OATHS OF ASSISTANTS.

36 We, J. S. Medley, W. H. Medley, Frank Behshaw
and Guy Davis

do solemnly swear that we will faithfully execute the duties of Chain Carriers; that we will level the chain over even and uneven ground, and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we will assist in measuring, to the best of our skill and ability, and in accordance with the instructions given us in the survey

of the Exterior lines of Twp. 10, R. 32, 33 & 34 E. Twp. 21, R. 33 & 35 E. Twp. 1 lines of Twp. 32, 33, 34 & 35 E. Twp. 21, R. 32, 34 & 35 E. Willamette Meridian, Oregon.

J. S. Medley, Chainman.
W. H. Medley, Chainman.
Frank Behshaw, Chainman.
Guy Davis, Chainman.

Subscribed and sworn to before me this 14th day of June, 1887

[SEAL.] James P. Currier
U.S. Deputy Surveyor

We, B. B. Crowner and J. R. Haddley, do solemnly swear that we will well and truly perform the duties of Axmen in the establishment of corners and other duties, according to instructions given us, and to the best of our skill and ability, in the survey of the

Exterior lines Twp. 10, R. 32, 33 & 34 E. Twp. 21, R. 33 & 35 E. Twp. 1 R. 32, 33, 34 & 35 E. Twp. 21, R. 32, 34 & 35 E. Willamette Meridian, Oregon.

B. B. Crowner, Axman.
J. R. Haddley, Axman.

Subscribed and sworn to before me this 14th day of June, 1887

[SEAL.] James P. Currier
U.S. Deputy Surveyor

Extriors of T. 7 North R. 35 East -
 Willamette Meridian, Oregon.

Beginning on Base Line at The
 Cor. To Tps. 1 N. R. 34 & 35 East - I
 Run North on true line bet Tps
 34 & 35 East - & Secs. 31 & 36

Var. $23^{\circ} 30' E$

- 30.00 Leave Table land & rise and
 40.00 Set a basalt stone $20 \times 12 \times 12$ ins
 15 ins in the ground for $\frac{1}{4}$ Sec. Cor.
 mtd $\frac{1}{4}$ on W. face. From which
 a pine 20 ins in diam to $N 52\frac{1}{2}^{\circ} W$
 43 lks. dist - mtd. $\frac{1}{4}$ S. B. S. No other
 tree in limits. Raised a wd of
 stone along side P's impracticable
 52.75 N. Fork McKay creek 20 lks wide Cause N. - 1000
 62.50 Ramp of rock 20 ft high
 75.00 Table land + 1000 2
 80.00 Set a basalt stone $9 \times 8 \times 7$ ins 6 ins
 in the ground for Cor. To Secs.
 25, 30, 31 & 36 mtd. 1 notch on S &
 5 notches on N. edges. From which
 a pine 40 ins in diam to N

Extensions of T. 1 North R. 35 East
Willamette Meridian, Oregon.

(8093-10 M.)

30° E. 29 lks dist. - Mtcd T. 1 N. S. 30
B.T. a Pine 15 ins in diam ls.
S 82° E dist. 285 lks dist. - Mtcd. R.
35° E. S. 31 B.T. a Pine 12 ins in diam
ls. S 48° W 65 lks. dist. - mtcd S. 36
B.T. a Pine 12 ins in diam ls S 88° W
42 lks. dist. - Mtcd R. 34 E. S. 25 B.T.
Land Mainly 80. chs
Soil rocky 4th rate
Scattering Pine timber on N. Slopes
Good Bunch Grass

North Lot. Secs. 25 + 30

Var 19° 30' E

4000 Set a Gas all stone 9x8x7 ins 6
ins in the ground for 1/4 Sec. Cor.
Mtcd 1/4 on W. face. From which a
pine 24 ins ^{in diam.} ls. S 45° E 5 lks dist. - mtcd
1/4 S. B.T. a Pine 16 ins ^{in diam.} ls S 80° W dist.
10 lks. - Mtcd 1/4 S. B.T.

Extensiors of T. 1 North R. 35 East -
Willamette Meridian, Oregon.

80.00 Set a basalt-stone 18x10x8 ins 12 ins
 in the ground for Cor. To Secs. 19,
 24, 25 & 30. mtd 2 notches on S. & 4
 on N. Edges. From which a Pine
 16 ins in diam ls. N 52° E dist. 175
 lks. mtd T. 1 N. R. 35 E. S. 19 B.T. A
 fir 10 ins. in diam, ls. S 85° E dist. 62
 lks. mtd. S. 30 B.T. A fir 12 ins in
 diam ls S. 35° W, dist. 20 lks mtd
 S. 25 B.T. A pine 18 ins in diam ls.
 N. 50° W dist. 143 lks. mtd R. 34 E. S.
 24. B.T.

Land rolling soil rocky with rate
 Timber pine & fir 80. chs.
 Good bunch grass.

North bet. Secs. 19 & 24
 Var 20° 30' E

20.00 ^{Point of} Canon-heavy timber & under brush
 40.00 Set a basalt-stone 10x8x7 ins 6 ins

Extension of T. 7 North R. 35 East -
 Willamette Meridian, Oregon.

(8093-10 M.)

in the ground for $\frac{1}{4}$ Sec. Cor. Mtd
 $\frac{1}{4}$ on W face. From which a pine
 20 ins in diam. ls. N 88° E dist 10 lks.
 Mtd. $\frac{1}{4}$ S. B. D. A fir 10 ins in diam.
 ls. S 30° W. dist 28 lks mtd $\frac{1}{4}$ S. B. D.

47.75-

Brook 10 lks wide Course ^{leave timber} W - 500

80.00

Set a basalt-stone 10 x 10 x 8 ins $\frac{1}{2}$ ins in ⁵⁰⁰
 The ground for Cor. To Secs. 13, 18, 19
 + 24. Mtd. 3 notches on N. & S. edges.
 From which a pine 10 ins in diam ls.
 N 80° E dist 217 lks. mtd T. 1 N. R. 35 E. S.
 18. B. D. A pine 6 ins in diam ls. S 80° E.
 dist 300 lks. mtd S. 19. B. D. No other
 tree in limits. Raised mound of
 stone along side. ^{is impracticable}
 Land mountainous 80. chs
 Soil rocky 4th rate
 Timber Pine + fir 47.75 chs
 Poor bunch grass

Extremities of T. 1 North R. 35 East
Willamette Meridian, Oregon.

North lat. Secs. 13 + 18

Var 18° E

2140 A Forked Pine 2 ft in diam ascend

4000 Set a post 36x3x3 ins 2 ft in the ground for 1/4 Sec. Cor. Mtd 1/4 S. on W. face. From which a pine 28 ins in diam to S. 10° E dist. 62 lbs.

Mtd. 1/4 S. B. D. A pine 12 ins in diam to S 30° W dist. 30 lbs. Mtd. 1/4 S. B. D. - 200

7100 bluff - 200

8000 Set a basalt stone 20x10x8 ins 15 ins in the ground for Cor. 75 Secs.

7, 12, 13 + 18. Mtd 4 notches on S + 2 notches on N edges. Raised a md. of stone along side this impracticable Land maintenance 80, chs Soil rocky + the rate Scattering pine timber is common Poor bunch grass

Extriors of T. 1 North R. 35 East

Willamette Meridian, Oregon.

(8093-10 M.)

North 1/4 Secs. 7 + 12

Var. 17° E

- 5000 Branch of McKay creek 6 lks wide S.W. - 300
- 4000 Set a basalt-stone 9x8x7 ins 6
ins in the ground for 1/4 Sec. Cor. Wkd.
1/4 on W face. Raised md. of stone
along side. Ditto impracticable
- 4100 Summit of hill + 400
- 4750 Canon Course S.E. - 100
- 8000 Set a post-48x4x4 ins 24 ins in the
ground for Cor. To Secs. 1, 6, 7 + 12
Wkd T. 1 N. S. 1 on N.W. S. 6 on N.E.
R. 35 E S. 7 on S.E. R. 34 E. S. 12 on
S.W. faces. 7 5' notches on S. 7 + 1 on
N. Edges from which a pine 18 in
in diam to N 60° E dist 10 lks Wkd
T. 1 N. R. 35 E S. 6 B. T. a pine 10 ins
in diam to S 52° E dist 54 lks.
Wkd S. 7 B. T. a pine 20 ins in diam.
to S 80° W dist 7 lks. Wkd R. 34 E.
S. 12 B. T. a pine 18 ins in diam.

Extensions of T. 1 North R. 35 East

Willamette Meridian, Oregon.

ls. N 82 W dist: 38 lks. mtvd S. B. T.
 Land Mammotians 80. cho
 Soil rocky H Th soil
 Scattering pine timber
 Good bunch grass

North Sec. 1 & 6

Var 20 E

40.00 Set a Gas all stone 10x8x6 in
 7 in in the ground for 1/4 Sec cor.
 Mtvd. 1/4 on W face. From which a
 Pine 26 in in diam ls. N 87 E dist-
 83 lks. mtvd 1/4 S. B. T. A pine 20 in
 in diam ls. S 35 W dist 115 lks. Mtvd,
 1/4 S. B. T.

53.00 Pendleton & Lagrange wagon road E 1/2 1/2

70.00 Spring

80.00 A Pine tree 20 in in diam which
 I marked for Cor. To Tps. 1 & 2 N. R.
 34 & 35 East - T. 1 N. R. 35 E. S. 6 mi

Extensions of T. 1 North R. 35 East -
 Willamette Meridian, Oregon.

(8093-10 M.)

an S. E. T. 2 A. S 31 an N. E. T. 2
 N. R. 34 E. S 36 an N. W. T. 1 N. R. 34
 E. S. 1 an S. W. T. 6 notches an N. S.
 E. + W. Edges. From which a fir
 14 ins in diam. Ls. S. 10 E dist. 171
 Ecs. mtd. T. 1 N. R. 35 E. S. 6 B. T.
 A fir 14 ins in diam. Ls. S 70 N dist
 67 Ecs. mtd. R. 34 E. S. 1 B. T. a Pine
 24 ins in diam. Ls. N 60 W. dist 112
 Ecs. mtd. T. 2 N. R. 34 E S 36 B. T.
 No other trees in limits

Land rolling
 Soil 2nd rate
 Scattering Pine fir + Tama-
 arack timber in hollows
 Good Grass

June 14th 1887

Land in this Township is mounta-
 inous with good timber in some pla-
 ces. It is well watered + suitable
 chiefly for Grazing

FINAL OATHS FOR SURVEYS.

A list of the names of the individuals employed by James P. Currier
and James E. Holland, U. S. Deputy Surveyors, to assist in
 running, measuring, and marking the lines and corners described in the
 foregoing field notes of the survey of the Exterior lines of Tps. 1, 2,
Rs. 32, 33, 34 & Tps. 2, 1, R. lines of 33 & 35 E, Tps. 1 & 2, Rs. 32, 33, 34 & 35 E
Tps. 2 & 1, Rs. 32, 34 & 35 E Willamette Meridian, Oregon,
 showing the respective capacities in which they acted:

L. A. Wooley....., Compassman.
J. J. Medley....., Chainman.
W. H. Medley....., Chainman.
Frank Belshaw....., Chainman.
Guy Davis....., Chainman.
B. B. Crowner....., Axman.
J. R. Hadley....., Axman.
 , Flagman.

FINAL OATHS OF ASSISTANTS.

We hereby certify that we assisted James P. Currier and James
E. Holland, U. S. Deputy Surveyors, in surveying
 all those parts or portions of the Exterior lines of Tps. 1, 2, Rs. 32, 33, 34 & E
Tps. 2 & 1, Rs. 33 & 35 E, Tps. 1 & 2, Rs. 32, 33, of 34 & 35 E, Tps. 2 & 1, Rs.
3, 2, 34, & 35 E Willamette Meridian, Oregon,
 as represented in the foregoing field notes as having been surveyed by
 him and under his direction; and that said survey has been in all respects,
 to the best of our knowledge and belief, well and faithfully surveyed,
 and the corner monuments established, according to the instructions
 furnished by the U. S. Surveyor General of Oregon.

L. A. Wooley....., Compassman.
J. J. Medley....., Chainman.
W. H. Medley....., Chainman.
Frank Belshaw....., Chainman.
Guy Davis....., Chainman.
B. B. Crowner....., Axman.
J. R. Hadley....., Axman.
 , Flagman.

Subscribed and sworn to before me this 30th day of

September, 1887.

[SEAL.]

James P. Currier
 U. S. Deputy Surveyor.

FINAL OATH OF DEPUTY SURVEYOR.

We, James P. Currier and James E. Poland, United States
Deputy Surveyor, do solemnly swear that in pursuance of instructions
received from Douglas H. Taylor, U. S.

Surveyor General for Oregon, bearing date of the 13th

day of May, 1887, I have well, faithfully,
and truly, in my own proper person, and in strict conformity with the
instructions furnished by the U. S. Surveyor General for Oregon, the
Surveying Manual, and the laws of the United States, surveying all

those parts or portions of Exterior lines of Twp. 1 N., R. 32, 33 & 34 E., Twp. 1

2 N., R. 33 & 35 E., Twp. 1 N., R. 32, 33, 34 & 35 E., Twp. 2 N., R. 32, 34 & 35 E.

Willamette Meridian, in the State of Oregon, as are represented in the
foregoing field notes as having been surveyed by me and under my
directions; and I do further solemnly swear that all the corners of said
survey have been established and perpetuated in strict accordance with
the Surveying Manual, printed instructions, the special written instruc-
tions of the U. S. Surveyor General for Oregon, and in the specific man-
ner described in the field notes, and that the foregoing are the *true* field
notes of such survey, and should any fraud be detected I will suffer the
penalty of perjury under the provisions of an act of Congress approved
August 8, 1846.

James P. Currier James E. Poland
U. S. Deputy Surveyors

Subscribed and sworn to before me this

day of Fifteenth
February, 1888

W. Woodcock
Notary Public
for Oregon

Office of U. S. Surveyor General,

Portland, Oregon, June - 11th, 1888.

foregoing

The following Field Notes of the Survey of the

Eastern lines of T. 1 S. Rgs 32.

34. E. T. 2 S. Rgs 33 and 35

T. 1 N. Rgs 32-33-34 and 35 East

T. 2 N. Rgs 32-34 and 35 East

Will. Mel. Or.

executed by James J. Currier and James E. Noel

Special Joint U.S. Dept. Surveyors

under his Contract No. —, dated May

4th, 1887, having been critically examined,

the necessary corrections and explanations made, the

said Field Notes and the survey they describe, are

hereby approved.

Douglas W. Taylor

Surveyor General.