

FIELD NOTES

Of the survey of the Subdivisional Allotment

Lines of T. 1 N. R. 34 E.

----- Willamette Meridian,

Oregon, as surveyed by James Pleussin

U. S. Deputy Surveyor, under his Contract No. 537

dated March 5th 1889

Survey commenced, June 29th, 1889

Survey completed, June 29th, 1889

NAMES AND DUTIES OF ASSISTANTS,

- , Compassman.
- , Chainman.
- , Chainman.
- J. R. Laramore, Chainman.
- J. L. Brown, Chainman.
- C. M. Stone, Axeman.
- R. E. Long, Axeman.
- , Flagman.



PRELIMINARY OATHS OF ASSISTANTS.

We, J. R. Saramore &  
J. L. Brown

do solemnly swear that we will faithfully execute the duties of Chain Carriers, that we will level the chain over even and uneven ground, and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we will assist in measuring, to the best of our skill and ability, and in accordance with the instructions given us in

the survey of the Subdivisional and  
Allotment lines of T. 1 N. R.  
34. E. Willamette Meridian, Oregon.

J. R. Saramore, Chainman.  
J. L. Brown, Chainman.  
\_\_\_\_\_, Chainman.  
\_\_\_\_\_, Chainman.

Subscribed and sworn to before me, this 29th

day of June 1889  
[SEAL.] Thos FitzGerald  
Notary Public

We, C. M. Stone and  
R. E. Long

do solemnly swear that we will well and truly perform the duties of Axemen in the establishment of corners and other duties, according to instructions given us, and to the best of our skill and ability,

in the survey of the Subdivisional & Allotment  
line of T. 1 N. R. 34 E. Willamette Meridian, Oregon.

C. M. Stone, Axeman.  
R. E. Long, Axeman.

Subscribed and sworn to before me, this 29th

day of June 1889  
[SEAL.] Thos FitzGerald  
Notary Public



# INDEX

Referring the Lines to the Pages of the Field Notes.

T. 1 North R. 34 East Will. Mer.

6 13-17	5 1-12	4	3	2	1
7	8 18-30	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Meanders of \_\_\_\_\_ Pages \_\_\_\_\_ to \_\_\_\_\_

Meanders of \_\_\_\_\_ Pages \_\_\_\_\_ to \_\_\_\_\_



Allotment

Subdivision of T. 1. North R. 34 East

Willamette Meridian, Oregon.

See 5.

From the corner to See's  
4-5-8 and 9 which is  
a basalt stone  $10 \times 8 \times 8$  ins  
7 ins in the ground marked  
with 5 notches on S. and 4  
notches on E. edges & mound  
of stone over it.  
I run

North on true line between  
See's. 4 and 5

Var  $21^{\circ}$  East

2000 Set basalt stone  $10 \times 8 \times 7$  ins  
7 ins in the ground for 1/6.  
See corner marked 1/6 on W.  
face, & raised mound of  
stone over it.

Pits impracticable

4000 Intersect the 1/4 See corner  
which is a post 3 ins square  
firmly set in ground.  
marked 1/4 S. on W. face



2

302

Allotment

Subdivision of T. 1 North R. 34 East

Willamette Meridian, Oregon.

See 5.

(8093-10 M.)

from which

a fir 24 ins diam hrs S 15°  
O. dist 80 lbs marked  
1/4 S. B. I.

a fir 5 ins diam hrs N 20° W  
29 lbs dist. marked 1/4 S. B. I.

Land summit & rolling

Soil 1.5<sup>rate</sup> & rocky

Good grass.

X



Allotment

303

Subdivision of T. 1 North R. 34 East

Willamette Meridian, Oregon.

See 5

From the corner to Sees 5+6.  
7+8. which is a Basalt  
stone 18 x 14 x 14 ins 14 ins in  
the ground marked with  
5 notches on S. and 5 notches  
on E. edges and mound of  
stone over it.

Iron  
No. 54° E. on true line  
between Sees. 5 x 6.

Var 20° 45' E.

20.00 Set basalt stone 12 x 8 x 6 ins  
8 ins in the ground for 1/4  
See corner marked 1/4 on  
N. face, and raised mound  
of stone over it

40.00 <sup>Fits impracticable</sup> Inter at the 1/4 See corner bet Sees  
5+6. which is a basalt stone 16 x 12  
+ 12 ins 12 ins in the ground marked  
1/4 on N. face with pits 18 x 18 x 12 ins  
N+ S of stone 5 1/2 ft dia & mound of  
earth 1 1/2 ft high + 3 1/2 ft low over it



4

Allotment

Subdivision of T. 1 North R. 34 East

Willamette Meridian, Oregon.

Sec 5.

(8093-10 M.)

Land rolling & mountainous  
Soil not rich with patches  
of rock.  
Good grass.



Allotments

5

Subdivision of T. 1 North R. 34 East 305

Willamette Meridian, Oregon.

Sec 5

From the corner to Secs.  
5-6-7 and 8.

I run

N 89° 47' E on random  
line between Secs. 5 + 8.

Var 20° 45' East

Setting temporary corners at  
20-40 and 60 chains and at

80.20 Intersect the N. + S. line at  
corner to Secs. 4-5-8 + 9

Then I run

S 89° 47' W on true line  
between Secs 5 + 8.

Var 20° E.

20.05 Set staves 14 x 9 x 7 ins 10 ins  
in the ground for  $\frac{1}{16}$  Sec corner  
marked  $\frac{1}{16}$  on N. face;  
raised a mound of stumps  
over it.

Pits unpracticable



Allotment

Subdivision of T. 1 North R. 34 East  
Willamette Meridian, Oregon.

Sec 5

(8093-10 M.)

- 23.00 Gulch corner N.W.
- 35.00 Road corner N
- 40.10 Intersect the  $\frac{1}{4}$  Sec corner  
which is a basalt stone  
18 x 16 x 14 ins 14 ins in  
the ground marked  $\frac{1}{4}$  on  
N. face & mound of stone  
over it
- 60.15 Set basalt stone 14 x 12 x 10  
ins 10 ins in the ground  
for  $\frac{1}{16}$  Sec corner; marked  
 $\frac{1}{16}$  on N. face. dug pits  
18 x 18 x 12 ins E. & W. of stone  
5  $\frac{1}{2}$  ft. dirt and raised mound  
of earth 1  $\frac{1}{2}$  ft. high 3  $\frac{1}{2}$  ft  
bar over it.
- 80.20 The corner to Secs. 5-6-7 and  
8.  
Land rolling & covered with  
brush grass. Soil 2d rate



Subdivision of T. 1 North R. 34 E.

Willamette Meridian, Oregon.

See 5

From the  $\frac{1}{16}$  Sec corner  
20 chs. North of corner to  
Secs 5-6-7 and 8

I run

N 89° 47' E on random  
line through the  $\frac{1}{4}$  of Sec 5  
Var. 20° E.

Setting temporary corner at every

20 - 40 and 60 chains & at

80.00 Intersect the N. S. line

at  $\frac{1}{16}$  Sec corner 20 chs

N of corner to Secs 4-5-8 & 9

Then from S 89° 47'

West on true line through

the  $\frac{1}{4}$  of Sec 5.

Var 20° E.

1.50 Summed N. E.

20.00 Set brass stake 10 x 10 x 8 ins

6 ins in the ground for  $\frac{1}{16}$

Sec corner marked



## Allotment

308  
 Subdivision of T. 1 North R. 34 East

Willamette Meridian, Oregon.

See 5

(8093-10 M.)

- $\frac{1}{16}$  on N face dug pits 18  
 18 x 12 ins E. & W. of stone  $5\frac{1}{4}$   
 ft dist and raised mound  
 of earth  $1\frac{1}{4}$  ft high  $3\frac{1}{4}$  ft  
 base over it
- 4000 Set basalt stone 19 x 8 x 7  
 7 ins in the ground for  $\frac{1}{16}$   
 Set corner, marked  $\frac{1}{16}$  on N.  
 face. dug pits 18 x 18 x 12  
 ins E. & W. of stone  $5\frac{1}{4}$  ft  
 dist. and raised mound of  
 earth  $1\frac{1}{4}$  ft. high  $3\frac{1}{4}$  ft  
 base over it.
- 4150 Gulch corner N. - 75
- 5500 Road from La Grande to Pendleton  
 corner N.
- 6000 Set basalt stone 14 x 8 x 6  
 ins 10 ins in the ground  
 for  $\frac{1}{16}$  Set corner marked  
 $\frac{1}{16}$  on N. face. and



Allotment

9

300

Subdivision of T. 1 North R. 34 East  
Willamette Meridian, Oregon.

Sec 5

raised mound of Stone  
along side

Pits impracticable

6500 Gulch course N. 80° W

7500 " " N.

8000 " " "

To the 1/6 Sec corner 20 ch  
N of corner to Secs 5-6.  
7 & 8.

Land rolling mountainous

Soil 1st rate

Covered with good grass &

sunflowers



18

31

Attachment

Subdiv. of T. 1 North R. 34 E.  
Willamette Meridian, Oregon.

Sec 5

(8093-10 M.)

From the  $\frac{1}{16}$  Sec corner 20  
chains N. & 20 chs E of cor  
to Secs 5-6-7 & 8.

From  
North on a true line in  
Sec 5.

Var 21° East

800 Pencil lines and La Grande  
Wagon Road corner T.C.

2009 Set basalt studs 10 x 9 x 8 ins  
6 ins in the ground for  $\frac{1}{16}$   
Sec corner marked  $\frac{1}{16}$  on N.  
face and raised a mound  
of stone over it  
Pits unfracturable

Land rolling summit  
Soil 1st rate and rocky.  
Good grass.



11  
311  
Allotment

Subdivision of T. 1 North R. 34 E.  
Willamette Meridian, Oregon.

Sec 5

From the  $\frac{1}{16}$  Sec corner 20  
chains E. of  $\frac{1}{4}$  Sec corner  
between Secs 5 + 6.

I run

East on random line

through the Centre of  
Sec 5. Var.  $19^{\circ}$  E

Setting temporary corner at  
20 + 40 chains and at

60.00 Intersect the N + S line  
at  $\frac{1}{4}$  Sec corner between  
Secs 4 + 5.

Thence I run

West on a true line  
through the Centre of Sec 5  
Var.  $20^{\circ}$  E

1500 Summit

2003 Set basalt stone 10 x 8 x 7 ins  
6 ins in the ground for  $\frac{1}{16}$   
Sec corner marked  $\frac{1}{16}$  in N face



12

312

Allotment

Subdivision of T. 1 North R. 34 East

Willamette Meridian, Oregon.

Sec 5

(8093-10 M.)

raised mound of stone  
over it

Pits impracticable

20.70 Gulch course N.W. - 50

35.00 Summit course N. + 100

40.07 Set basal stone 12 x 10 x 7  
ins 8 ins in the ground for  
1/4 Sec course marked 1/4 on  
N. face, and raised mound  
of stone over it

Pits impracticable

53.50 Gulch course N

Stream in center - 100

60.00 To the 1/6 Sec course 20 chains  
E of the 1/4 Sec course bet Secs  
5 & 6.

Land rolling summits  
Soil 100 rods and rocky  
Good grass



Allotment

13

313

Subdivision of T. 1 North R. 34 E.

Willamette Meridian, Oregon.

Sec 6.

From the  $\frac{1}{4}$  Sec corner between  
Secs. 5 & 6. which is a  
Basalt stone  $16 \times 12 \times 12$  ins  
 $12$  ins in the ground marked  
 $\frac{1}{4}$  on W. face pits  $18 \times 18 \times 12$   
ins N. & S. of stone  $5\frac{1}{2}$  ft dia  
& mound of earth  $1\frac{1}{2}$  ft high  
 $3\frac{1}{2}$  ft base along side

I run

N $0^{\circ}54'$ E on true line between  
Secs. 5 & 6.

Var  $20^{\circ}$  E.

8.00 Pendleton & La Grande Wagon  
Road course N.W.

10.00 Set basalt stone  $11 \times 10 \times 7$  ins  
 $7$  ins in the ground for  $\frac{1}{32}$  Sec  
corner marked  $\frac{1}{32}$  on W. face  
dug pits  $18 \times 18 \times 12$  ins N. & S.  
of stone  $5\frac{1}{2}$  ft dia and raised  
mound of earth  $1\frac{1}{2}$  ft high  
 $3\frac{1}{2}$  ft base over it.



Allotment

314  
Subdiversy of T. 1 North R. 34 E

Willamette Meridian, Oregon.

Sec 6.

(8093-10 M.)

Var 18° 30' E.

3000

Set basalt stand 9 x 8 x 7 in  
6 in in the ground for 1/6  
See corner marked 1/6 on W.  
face, and raised mound of  
stone over it

Pits impracticable  
This corner stands on N.E.  
slope

Land rolling and inclined  
to the North

Soil not rich & rocky

Good grass.



15  
315  
Allotment

Subdivision of T. 1 North R. 34 E.  
Willamette Meridian, Oregon.

Sec 6.

From the  $\frac{1}{16}$  Sec corner 10 chs  
North of  $\frac{1}{4}$  Sec corner between  
Secs 5 & 6.

Iron

West on true line in Sec 6.

Var  $18\frac{1}{2}$  East

3.50 Pendleton & La Grande Wagon  
road course N.W.

20.00 Set basalts stones 10 + 8 + 7 in  
6 in in the ground for  $\frac{1}{16}$  Sec  
corner marked  $\frac{1}{16}$  on N face  
and raised a mound of stone  
over it

Pits impracticable

Land rolling and inclined  
to North.

Soil not rate & rocky  
Good grass



16

# Allotment

Subdivision of T. 1 North R. 34 East

Willamette Meridian, Oregon.

## Sec 6.

(8093-10 M.)

From the  $\frac{1}{16}$  Sec corner 10  
chains N. & 20 chains W of  
 $\frac{1}{4}$  Sec corner bet Secs 5 & 6.

I run

No. 54 - Run a true line in  
Sec 6.

Var  $21^{\circ} 30'$  East

2000

Set basalt stake  $12 \times 8 \times 8$  ins  
8 ins in the ground for  $\frac{1}{16}$  Sec  
corner marked  $\frac{1}{16}$  on W face  
and raised mound of stone  
over it.

Pits impracticable

Land rolling and inclined  
to North

Soil red rube & rocky  
Good grass



Allotment

17

Subdividing T. 1 North R. 34 E 317

Willamette Meridian, Oregon.

Sec 6.

From the  $\frac{1}{16}$  Sec corner 30 ch  
N. and 20 chains W. of  $\frac{1}{4}$  S.  
corner between Secs 5 & 6.

I run

East on true line in Sec  
6.

Var  $20^{\circ} 30'$  East

350 Suddleton and Lagrande Wagner  
Road corner N.W.

1500 Gulch corner N.E.

2900 To the  $\frac{1}{16}$  Sec corner 30 chains  
N. of the  $\frac{1}{4}$  Sec corner between  
Secs 5 & 6.

Land rolling & inclined to  
North

Soil sub rate and rocky  
Good grass



Allotment

Subdivision of T. 1 North R. 34 East  
Willamette Meridian, Oregon.

Sec 8.

(8093-10 M.)

From the  $\frac{1}{16}$  Sec corner 20 ch  
East from corner to Secs 5-6  
7 & 8.

Iron.

South on true line in Secs  
8. Var  $21^{\circ}$  E

800

Rocky flat 100 ch wide  
course E & W

1050

Road course W.

2000

Set Stone  $10 \times 8 \times 6$  ins 6 ins  
in the ground for  $\frac{1}{16}$  Sec corner  
marked  $\frac{1}{16}$  on W. face in  
flat Gulch course W.

raised a stone mound over  
it. - Land rolling with some  
rocky flats on summit of Mt.  
Soil generally to rate good grass  
& sunflowers.

From the  $\frac{1}{16}$  Sec corner 20 ch

West of corner to Secs 4 & 5. 8 & 9

Iron



Allotment

19  
319

Subdivision of T. 1 North R. 34 E

Willamette Meridian, Oregon.

Sec 8

South on true line in Section  
8. Var 21° E

1600 Road course W

2000 Set stews 14 + 9 + 7 ins 10 ins  
in the ground per  $\frac{1}{16}$  Sec corner  
marked  $\frac{1}{16}$  in W. face. and  
raised a mound of stews around  
Pits impracticable

Land rolling with some rocky  
flats on Summit of Mt.

Soil generally 1st rate

Good grass and sunflowers

From the  $\frac{1}{16}$  Sec corner 20 chs  
S. and 20. chain E of corner to  
Secs 5-6-7 and 8.

From

East on random line in  
Sec. 8. Var 21° E

Setting temporary corner at  
20. chs and at.



20

320

# Allotment

Subdivision of T. 1 North R. 34 E

Willamette Meridian, Oregon.

## Sec 8

(8093-10 M.)

39.90 Intersect  $\frac{1}{16}$  Sec corner 20  
chains E. + 20 ch S. of corner  
to Secs. 4-5-8+9.

Thence I run

West on true line in Sec. 8

Var  $20^{\circ}30'$  E

19.95 Set stakes 12 x 9 + 8 ins 8 ins  
in the ground for  $\frac{1}{16}$  Sec corner  
marked  $\frac{1}{16}$  on N. face and  
raised a mound of stone  
over it.

30.00 Road corner S + W.

39.90 To  $\frac{1}{16}$  Section corner in  
Section 8. 20 ch S. + 20 ch  
E. of corner to Secs 5+6-7+8.

Land gently rolling

Soil 1<sup>st</sup> rate + rocky

Good grass



Attachment

21  
321

Subdivision of T. 1 North R. 34 East  
Willamette Meridian, Oregon.

Sec 8

From the Corner to Secs 7-8  
17 + 18 which is a basalt  
stone 12 + 10 + 8 ins 8 ins in the  
ground marked with 4 notches  
on S. and 5 notches on E.  
edges + mound of stone over it.  
E. side

East on a true line between  
Secs. 8 and 7.

Var 18° 45' E.

- 350 Gulch corner N. - 100
- 1902 Set a post 3 ft. long 3 ins square  
24 ins in the ground for  $\frac{1}{32}$  Sec  
Corner marked  $\frac{1}{32}$  S on N face  
from which  
a pine 8 ins diam br S 45° W 163  
the dist marked  $\frac{1}{32}$  S. B. S.
- a pine 12 ins diam br S 25° W.  
145 the dist marked  $\frac{1}{32}$  S. B. S.
- 2004 Set basalt stone 10 + 9 + 8 ins  
6 ins in the ground for  $\frac{1}{32}$  Sec



22

322

Allotment

Subdivision of T. 1 North R. 34 East  
Willamette Meridian, Oregon.

Sec 8.

(8093-10 M.)

marked  $\frac{1}{32}$  on W. &  $\frac{1}{16}$  on E.  
& D. R. on N. edge, raised  
a mound of stone over it  
Pits unfracturable

4008

To the  $\frac{1}{4}$  Sec corner which is  
basalt stone  $20 \times 12 \times 3$  ins 15 ins  
in the ground marked  $\frac{1}{4}$  on N. face  
from which  
a pine 16 ins dia bears N.  $83^\circ$  E. 65  
lb dist. marked  $\frac{1}{4}$  T. B. T.

5000

a pine 12 ins diam bears S  $50^\circ$  E 84  
lb dist marked  $\frac{1}{4}$  T. B. T.  
Set basalt stone  $11 \times 7 \times 6$  ins  
6 ins in the ground marked  
 $\frac{1}{32}$  <sup>+ D. R.</sup> on N. face; from which  
a pine 30 ins diam bears S  $10^\circ$  W.  
10 lb dist marked  $\frac{1}{32}$  T. B. T.  
a pine 20 ins diam bears N  $75^\circ$  E.  
20 lb dist marked  $\frac{1}{32}$  T. B. T.

Land gently rolling  
Soil <sup>not</sup> salt  
Darker pine



Allotment

323

Subdivision of T. 1 North R. 34 East  
Willamette Meridian, Oregon.

Sec 8.

From the  $\frac{1}{4}$  Sec corner betw  
Secs 8 and 17

Draw

North on true line in the  
Center of Sec 8  
Var  $21^{\circ}$  E.

20.00 Set a basalt stone  $10 \times 8 \times 7$  in  
6 ins in the ground for  $\frac{1}{16}$   
Sec corner marked  $\frac{1}{16}$  on N. face  
rased around of stone  
cover it

Pits impracticable

22.25 Road course  $N10^{\circ}$  E

28.50 Head of Draw course W.

30.00 Set a basalt stone  $10 \times 7 \times 6$  ins  
6 ins in the ground for  $\frac{1}{32}$  Sec  
corner marked  $\frac{1}{32}$  on N. face  
dug pits  $18 \times 18 \times 12$  ins N. & S.  
of stone  $5\frac{1}{2}$  ft dirt and raised  
a mound of earth  $1\frac{1}{2}$  ft high  
 $3\frac{1}{2}$  ft low over it



24

# Allotment

Subdividing of T. 1 North R. 34 East  
Willamette Meridian, Oregon.

## See 8.

(8093-10 M.)

3500

Summit curve I.W. + 30

4000

Set basal stone 12 x 10 x 8 in

8 in in the ground for  $\frac{1}{4}$

See corner accounted  $\frac{1}{4}$  cu

W. face dug pits 18 x 18 x 12

in N. & S. of stone 5  $\frac{1}{2}$  ft dist

and raised a mound of  
earth 1  $\frac{1}{2}$  ft high 3  $\frac{1}{2}$  ft  
base over it.

Land rolling

Soil to rate

Grass and scattering pine  
timber



Subdividing of T. 1. North R. 34<sup>0</sup>.

Willamette Meridian, Oregon.

Sec 8.

From  $\frac{1}{4}$  Sec corner in the  
Centre of Sec. 8.

From

East on a true line to  
Sec 8

Var  $19^{\circ}$  E

7.00

Road course N & S.

1002

Set small stone  $14 \times 10 \times 8$  ins

10 ins in the ground for  $\frac{1}{32}$

Sec corner marked  $\frac{1}{32}$  on N.

face. dug pits  $18 \times 18 \times 12$  ins

E & W. of stone  $5\frac{1}{2}$  ft dirt

and raised a mound of earth

$1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft low around.

Land rolling

Set out rods

Scattering seed timothy

Good grass.



266

Allotment

Subdivision of T. 1 North R. 34 E.  
Willamette Meridian, Oregon.

Sec 8.

(8093-10 M.)

From the  $\frac{1}{16}$  Sec corner 20  
chains N of  $\frac{1}{4}$  Sec corner  
of Sec 8 & 17  
Iron

Cast on true line in  
Sec. 8. Var  $19^{\circ}$  E

850

Gulch corner S.E.

1003

Set basalt stone  $9 \times 8 \times 7$  in

6 in in the ground for  $\frac{1}{32}$   
Sec corner marked  $\frac{1}{32}$  on  
N. face, dug pits  $18 \times 18$   
 $+ 12$  in E & W of stone  $5\frac{1}{2}$   
ft. dirt and raised a  
mound of earth  $1\frac{1}{2}$  ft  
high  $3\frac{1}{2}$  ft base over it.

Land rolling  
Scattering pine timber  
Set  $\frac{1}{16}$  rule



Allotment

27

327

Subdivision of T. 1 North R. 34 E.  
Willamette Meridian, Oregon.

Sec 8

From the  $\frac{1}{32}$  Sec corner 10 ch  
East from the corner to Secs  
7-8-17 & 18

I run

North on a true line in  
Sec 8.

Var. 19" East

2000

Set basalt stone 14 x 10 x 8 ins  
10 ins in the ground for  $\frac{1}{32}$   
Sec corner marked  $\frac{1}{32}$  in N face  
and raised as mound of  
stone over it

Pits impracticable

from which

a pine - was drawn by N 30° E

165 lb did marked  $\frac{1}{32}$  T.B.S.

Land rolling

Soil test vats

Scattering pine timber  
& grass.



329  
 Subdivision of T. 1 North R. 34 E.

Willamette Meridian, Oregon.

Sec 8

(8093-10 M.)

From  $\frac{1}{32}$  Sec corner 10 ch  
 E. and 20 ch N from the  
 corner to Secs 7-8-17 and 18  
 I run

East on random line in  
 Sec 8.

Var  $19^{\circ}$  E.

Setting temporary corner at  
 10 chains & at

30.00 Intersect line at  $\frac{1}{16}$  Sec.

corner 20 ch N. of  $\frac{1}{4}$  Sec  
 cor between Secs 8 & 17

Thence I run

West on true line in Sec 8

Var  $19^{\circ}$  E

20.00 Set basal stone  $12^{\circ} 9' 7''$   
 8 ins in the ground for  $\frac{1}{16}$   
 and  $\frac{1}{32}$  Sec corner marked  
 $\frac{1}{16}$  on S.  $\frac{1}{32}$  on the N. face  
 and raised a stone around  
 over it.



allotment

29

Subdivisions of T. 1 North R. 34 E 329

Willamette Meridian, Oregon.

Sec 8.

Pits unpracticable

21.00 Gulch course N.W.

30.00 To the 1/32 Sec corner 10 ch  
E + 29 ch N. of corner to Secs  
7-8-17 + 18.

Land rolling

Soil not out

Scattering pine timber +  
Grass



Attachment

Subdivision of T. 1 North R. 34 E.

Willamette Meridian, Oregon.

Sec 8

(8093-10 M.)

From the  $\frac{1}{16}$  &  $\frac{1}{32}$  Sec corner  
20 chs E. & 20 chs N. of  
the corner to Secs 7-8-17 & 18  
I run

North on a true line in  
Sec 8.

Var.  $21^{\circ}$  E

850

Gulch course N. ~ 75

1000

Stone in place  $12 \times 12 \times 8$   
in above ground for  $\frac{1}{32}$   
Sec corner marked  $\frac{1}{32}$  on  
and (+) cross at exact corner  
N. face, and raised a  
mound of stone over it  
Its impracticable

Land rolling

Soil not rut

Scattering pine timber +

Grass

June 29<sup>th</sup> 1889



Allotment

331

Subdiv. of T. 1 North R. 34 E.

Willamette Meridian, Oregon.

General Description

The lands allotted in this Township are situated on and near summit of Blue Mts and are rolling and broken, soil mostly 1st rate producing grass sunflowers and some fine timber



34 332  
Allotment

Subdiv. of T. 1 North R. 34 E.

Willamette Meridian, Oregon.

(8093-10 M.)

In accordance with the requirements of the manual of surveys I have carefully tested the adjustment of my instrument by taking the latitude daily weather permitting during the progress of the surveys represented by the foregoing field notes and in all cases the instruments was found in correct adjustment.

James P. Currier  
U. S. Dept. Surveyor

---



331

### FINAL OATHS FOR SURVEYS.

A list of the names of the individuals employed by James P. Currier, U. S. Deputy Surveyor, to assist in running, measuring and marking the lines and corners, described in the foregoing field notes of the survey of the Subdivisional & Allotment lines of T. L. A. R. R. 34 E. Willamette Meridian, Oregon, showing the respective capacities in which they acted:

- , Compassman.
- , Chainman.
- , Chainman.
- J. R. Saramore, Chainman.
- J. L. Brown, Chainman.
- C. M. Stone, Axeman.
- R. E. Long, Axeman.
- , Flagman.

### FINAL OATHS OF ASSISTANTS.

We hereby certify that we assisted James P. Currier U. S. Deputy Surveyor, in surveying all those parts or portions of the Subdivisional & Allotment lines of T. L. A. R. R. 34 E. Willamette Meridian, Oregon, as are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the U. S. Surveyor General of Oregon.

- , Compassman.
- J. R. Saramore, Chainman.
- J. L. Brown, Chainman.
- , Chainman.
- , Chainman.
- C. M. Stone, Axeman.
- R. E. Long, Axeman.
- , Flagman.

Subscribed and sworn to before me, this 2nd day of

July 1889  
 [SEAL.] Thos Fitz Gerald  
Notary Public



## FINAL OATH OF DEPUTY SURVEYOR.

I, James P. Currier  
 United States Deputy Surveyor, do solemnly swear that in pursuance of  
 instructions received from Douglas M. Taylor  
 U. S. Surveyor General for Oregon, bearing date of the 19th  
 day of March 1889, I have well, faith-  
 fully and truly, in my own proper person, and in strict conformity with  
 the instructions furnished by the U. S. Surveyor General for Oregon, the  
 Surveying Manual, and the laws of the United States, surveying all those  
 parts or portions of allotment & subdivision  
al lines of T. 1. N. R. 34 E.

Willamette Meridian, in the State of Oregon, as are represented in the  
 foregoing field notes as having been surveyed by me and under my direc-  
 tions; and I do further solemnly swear that all the corners of said survey  
 have been established and perpetuated in strict accordance with the Sur-  
 veying Manual, printed instructions, the special written instructions of  
 the U. S. Surveyor General for Oregon, and in the specific manner de-  
 scribed in the field notes, and that the foregoing are the *true* field notes of  
 such survey, and should any fraud be detected I will suffer the penalty of  
 perjury under the provisions of an Act of Congress approved August 8,  
 1846.

James P. Currier  
 U. S. Deputy Surveyor.

Subscribed and sworn to before me, this 2nd  
 day of July 1889

Thos Fitzgerald  
 Notary Public



Office U. S. Surveyor General,

Portland, Oregon, August 31 - 1889

The <sup>following</sup> ~~following~~ Field Notes of the Survey of the

Subdivisional and Allotment

Lines of Township 1 North

Range 34 East Will. Mer. Or

executed by James P. Curran U.S.  
Dept Surveyor

under his Contract No. 537, dated

March 5 1889, having been critically examined, the

necessary corrections and explanations made, the said Field Notes

and the survey they describe, are hereby approved.

Douglas W. Taylor  
Surveyor General.