

FIELD NOTES

Examination of corners.
Of the survey of the *Subdivision*,

Lines of T. 2 N. R. 32 E. T. 1. 2 & 3 N. R. 33 E.

T. 3 & 4 N. R. 34 E. T. 3 & 4 N. R. 35 E. Willamette Meridian,

Oregon, as surveyed by *James Pleuriss & James E. Roland*
Special

U. S. Deputy Surveyor, under his Contract No.

dated May 4 1887.

Survey commenced, April 20th 1890.

Survey completed, Aug 1st 1890.

NAMES AND DUTIES OF ASSISTANTS.

-, Compassman.
- James J. Beck*....., Chainman.
- William Ararberger*....., Chainman.
-, Chainman.
-, Chainman.
-, Axeman.
-, Axeman.
-, Flagman.

PRELIMINARY OATHS OF ASSISTANTS.

We, James T. Beck, & William Marburger

do solemnly swear that we will faithfully execute the duties of Chain Carriers; that we will level the chain over even and uneven ground, and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we will assist in measuring, to the best of our skill and ability, and in accordance with the instructions given us in

the survey of the Examination of corners on
Subdivisional lines of R. 2 N. R. 32 E. T. 1, 2 & 3 N.

R. 33 E. T. 3 & 4 N. R. 34 E. & T. 3 & 4 N. R. 35 E. Willamette Meridian, Oregon.

James T. Beck, Chainman.

William Marburger, Chainman.

....., Chainman.

....., Chainman.

Subscribed and sworn to before me, this 23d

day of May April 1890.

[SEAL.]

Harro
Notary Public for O.

We, and

....., do solemnly swear that we will well and truly perform the duties of Axemen in the establishment of corners and other duties, according to instructions given us, and to the best of our

skill and ability, in the survey of the

..... Willamette Meridian, Oregon.

....., Axeman.

....., Axeman.

Subscribed and sworn to before me, this

day of 18.....

[SEAL.]

Subdivisions of T. 2 North R. 33 East

Willamette Meridian, Oregon.

295

West between secs. 10 & 15; I
 pass to $\frac{1}{4}$ sec. cor. well pre-
 served to cor. secs. 9-10-15 & 16
 a Post 26 x 4 x 4 ins above ground
 marked S. 10. T. 2 N. on N.E. S. 15. R. 33 E.
 on S.E. S. 16 on S. N. & S. 9 on N. N.
 faces. No notches. I cut
 3 on E & 4 on S. edges. Pits
 filled with sand &
 mound about gone.

West bet secs. 9 & 16.
 Passed to $\frac{1}{4}$ & $\frac{1}{16}$ corners. all right
 except pits filled with
 sand at two of them.
 found cor. sec. 8. 9. 16 & 17 Post
 broken off & split. ^{fragment} 24 x 4 x 4 ins. marked
 S. 9 on N. T. 2 N. on N.E. S. 16 R. 33
 E on S.E. S. 17 on S. N. & S. 8 on N.
 N. faces. with 4 notches on E & S. edges.
 mound & pits partly destroyed. Reset post.

Subdivisions of T. 2 North R. 33 East
Willamette Meridian, Oregon.

296

(8093-10 M.) Examination of corners.

Found corner secs. 20, 21, 28 & 29
a post 4 ft long by 4 ins square
marked S. 21, R. 33 E. on N. E. S.
28 on S. E. S. 29 on S. N. & S.
20 J. I. N. on N. N. ^{faces} Cut 4 notches
on E & 2 on S. edges. Cut off the J & R.
marks & put J. 2 N on N. E. & R. 33 E on S. E. faces.
Pits & mound very well preserved.

Along East bet. secs. 22 & 27. O
passed $\frac{1}{16}$ - $\frac{1}{4}$ to cons. all well
preserved & found cor. secs 22, 23,
26, & 27. a post 48 x 4 x 4 ins. 24 ins
in ground. Marked S. 23: J. I. N.
on N. E. S. 26 R. 33 E on S. E. S. 27
on S. N. & S. 22 on N. N. faces.
Cut 2 notches on S. & 2 on E.
edges. Pits & earth mound partly
destroyed.

For cor. 21-22-27 & 28 see page 22.

April 30th 1890

Subdivisions of T. 2 North R. 33 East
Willamette Meridian, Oregon.

297

Examination of corners.

Found cor. of 23-24-25 & 26
Mound with ^{pits} 5 ft dist
in each sec. Marked stake
gone. Pits & mound in good repair.
Going south between secs.
23 & 24. found cor. to secs 13, 14.
23 & 24. a post 4 ft long x 4 in
square marked S. 13. T. 2 N. on
N.E. S. 24 R. 33 E. on S.E. S
23 on S. N. S. 14. on N. N.
faces. but 1 notch on E & 3 on
S. edges. earth mound & pits partly
destroyed.

Cor. 27-28-33 & 34 a Post 4 ft long by
^{is firmly set in ground}
4 in square marked S. 27. T. 2 N. on N.E. S 34
R. 33 E on S.E. S. 33 on S. N. S 28
on N. N. ^{faces} no notches I cut
3 on E & one on S. edges. Pits
and earth mound partially destroyed.

Subdivisions of T. 2 North R. 33 East
Willamette Meridian, Oregon.

302

(8093-10-M.) Examination of corners.

Corners. 21-22-27 & 28
I found to be a a Post
4 in square by 2 ft above
ground. marked S. 22 on N.E.
S. 27. R. 33 E on S.E. S. 28. on S.W.
& S. 21 ~~and~~ 2 N. on N.W. faces. I
cut off the 2 N. & put it on
the N.E. face. also the post
had 3 notches on E & 2 on S
edges. The pits are $5\frac{1}{2}$ ft
dist in each sec. in
good state of preservation
E. mound ~~is~~ mostly gone.

May 1st 1890.

of T. R.

Willamette Meridian, Oregon.

I wish to say in connection with the examination of corners that we have carefully ^{gone} over the work as set forth in these Field Notes and find that it has been faithfully done.

The pits were all of regulation size & depth, but are partially filled now, and are the most important factors in perpetuating the position of corners.

The mounds of earth are generally very nearly beveled down or blown away by the wind, and where they were raised over the stone corners, such corners generally project through the flattened mound and are more firmly fixed in the ground than those that had the mound

(8093-10 M.)

of earth alongside.
The post and stakes being made of Balm Timber which is the best in this vicinity, are rapidly decaying, and many were pulled out or broken off at surface when the ground was frozen. The stone cons. were all ^{marked} properly.
The only irregularities that we found were in marks on Posts, set by two men.

In many cases notches were not found on them, so we visited at the ^{all} Post corners, set by those men & supplied notches, whenever found necessary. Also on some of said posts in interior of Townships only, the marks for Township & Range were not on N. E. & S. E. faces, but sec. mark

of T. R.

Willamette Meridian, Oregon.

were always correctly put on.
As the notches are duplicate
marks, and the failure to get
the T. & R. on A.E. & D.E. faces is
not misleading, but indicate
the Township & Range just
as correctly; these cannot
be regarded as anything more
than technical errors, and
do not in any way detract
from the value of the
survey, which is first-
class in every other respect.

James P. Currier
U. S. Deputy Surveyor

FINAL OATHS FOR SURVEYS.

A list of the names of the individuals employed by James P. Currier & James E. Roland, U. S. Deputy Surveyors to assist in running, measuring and marking the lines and corners described in the foregoing field notes of the survey of the Examination of corners of Subdivisional lines of T. 2. N. R. 32. E. J. 1. 2 + 3. N. R. 33 E. J. 3 + 4 N. R. 34 E. J. 3 + 4 N. R. 35 E. Williamette Meridian, Oregon, showing the respective capacities in which they acted:

- James J. Beck, Compassman.
James J. Beck, Chainman.
William Marburger, Chainman.
Chainman.
Chainman.
Axeman.
Axeman.
Flagman.

FINAL OATHS OF ASSISTANTS.

We hereby certify that we assisted James P. Currier and James E. Roland, U. S. Deputy Surveyors in examining all those parts or portions of the Examination of corners of Subdivisional lines of T. 2. N. R. 32. E. J. 1. 2 + 3. N. R. 33 E. J. 3 + 4 N. R. 34 E. J. 3 + 4 N. R. 35 E. Williamette Meridian, Oregon. as are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the U. S. Surveyor General of Oregon.

- James J. Beck, Compassman.
James J. Beck, Chainman.
William Marburger, Chainman.
Chainman.
Chainman.
Axeman.
Axeman.
Flagman.

Subscribed and sworn to before me, this 1st day of May 1890

[SEAL.]

Harrold
Notary Public
for Oregon

FINAL OATH OF DEPUTY SURVEYOR.

We James J. Currier and James E. Noland
United States Deputy Surveyors do solemnly swear that in pursuance of

instructions received from *Douglas W. Taylor*

U. S. Surveyor General for Oregon, bearing date of *15th*

day of *April*, 18*90*, ^{we} I have well, faith-
fully and truly, in ^{our} own proper persons and in strict conformity with
the instructions furnished by the U. S. Surveyor General for Oregon, the
Surveying Manual, and the laws of the United States, ^{examined} surveying all those

parts or portions of *T. 2 N. R. 32 E. T. 1-2 & 3 N. R. 33 E. T. 3 & 4 N.*

R. 34 E. T. 3 & 4 N. R. 35 E.

Willamette Meridian, in the State of Oregon, as are represented in the
foregoing field notes as having been ^{examined} surveyed by ^{us} me and under ^{my} my direc-
tions; and ^{we} I do further solemnly swear that all the corners of said survey
have been established and perpetuated in strict accordance with the Sur-
veying Manual, printed instructions, the special written instructions of
the U. S. Surveyor General for Oregon, and in the specific manner de-
scribed in the field notes, and that the foregoing are the *true* field notes of
such ^{examination} survey, and should any fraud be detected ^{we} I will suffer the penalty of
perjury under the provisions of an Act of Congress approved August 8,
1846.

James J. Currier
James E. Noland

U. S. Deputy Surveyor. S

Subscribed and sworn to before me, this *6th*

day of *May*, 18*90*

Wenman Baumhauer
Notary Public
for Oregon

Office U. S. Surveyor General,

Portland, Oregon, June 4 - 1899

The foregoing Field Notes of the Survey of the Examination of corners in Subdivisional Lines of T. 2 N R 32 E - T. 1. 2 + 3 N R 33 E. T 3 and 4 N R 34 E + T. 3 + 4 N R 35 E. Will. Mer Oregon executed by James P. Currier and Jas O'Noland Special U.S. Dept Surveyors under his contract No. _____, dated May

4th 1887, having been critically examined, the necessary corrections and explanations made, the said Field Notes and the ^{Examinations} ~~survey~~ they describe, are hereby approved.

Douglas W. Taylor -
Surveyor General.

