

## FIELD NOTES

Of the survey of the *Subdivisional*  
 Lines of *Township 2 South Range*  
*34 East* *Willamette Meridian, Oregon,*  
 as surveyed by *Jas. P. Currier & Jas. E. Roland*  
 U. S. Deputy Surveyor, under his Contract No. \_\_\_\_\_  
 dated *May 4<sup>th</sup>*, 1887.

Survey commenced, *July 16<sup>th</sup>*, 1887  
 Survey completed, *July 21<sup>st</sup>*, 1887

## NAMES AND DUTIES OF ASSISTANTS.

*L. F. Hooley*, Compassman.  
*J. S. Medley*, Chainman.  
*W. H. Medley*, Chainman.  
*Frank Belshaw*, Chainman.  
*Guy Davis*, Chainman.  
*B. B. Browner*, Axman.  
*A. V. Veatch*, Axman.  
 \_\_\_\_\_, Flagman.

4 PRELIMINARY OATHS OF ASSISTANTS.

We, J. S. Medley, W. H. Medley, Frank Belshaw, Guy Davis

do solemnly swear that we will faithfully execute the duties of Chain Carriers; that we will level the chain over even and uneven ground, and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we will assist in measuring, to the best of our skill and ability, and in accordance with the instructions given us in the survey

of the Subdivisional lines of T 2 S, Range 34 E Willamette Meridian, Oregon.

J. S. Medley, Chainman.
W. H. Medley, Chainman.
Frank Belshaw, Chainman.
Guy Davis, Chainman.

Subscribed and sworn to before me this 16th day of July, 1887

[SEAL.] James P. Plurrien, U.S. Deputy Surveyor

We, B. B. Crown and H. Beach, do solemnly

swear that we will well and truly perform the duties of Axmen in the establishment of corners and other duties, according to instructions given us, and to the best of our skill and ability, in the survey of the

Subdivisional lines of T 2 S, R 34 E, Willamette Meridian, Oregon.

B. B. Crown, Axman.
H. Beach, Axman.

Subscribed and sworn to before me this 16th day of July, 1887

[SEAL.] James P. Plurrien, U.S. Deputy Surveyor

# INDEX

411

Referring the Lines to the Pages of the Field Notes.

T. 2 South R. 34 East Will. Mer.

6	65	5	43	4	28	3	2	1
64	<del>65</del>	62		41				
7	61	8	40	9	27	10	11	12
60		58		39	<del>38</del>			
18	57	17	38	16	25	15	14	13
55		54	<del>37</del>	37		24		
19	53	20	35	21	22	22	74	23
51	<del>52</del>	50		34		21	<del>12</del>	13
30	49	29	32	28	19	27	77	26
47	<del>48</del>	44		29	<del>20</del>	16		8
31	46	32	31	33	18	34	10	35
								36

Meanders of \_\_\_\_\_, Pages \_\_\_\_\_ to \_\_\_\_\_

Meanders of \_\_\_\_\_, Pages \_\_\_\_\_ to \_\_\_\_\_

28

448

Subdivisions of T. 2 South R. 34 East  
 Willamette Meridian, Oregon.

(8093-10 M.)

- North on true line bet. Secs 3 & 4  
 Va.  $17^{\circ} 30'$  East.
- 1950 Dry bed of creek at N. E. - 200  
 Ascend
- 2835 Gulch S. E. - 100
- 40.00 Set Basalt Stone  $7 \times 8 \times 12$  ins.  
 8 ins. in the ground for  $\frac{1}{4}$  Sec.  
 Cor. marked  $\frac{1}{4}$  on N. face  
 Over which I raised a  
 mound of stone 18 ins. high  
 with  $3\frac{1}{2}$  ft. base. On side of  
 mountain
- 63.00 Summit of mountain N. E. 800 +  
 Descend
- 78.50 Intersect Township line 3.79 chs.  
 N. of Cor. to 33 & 34 T. 1 S. R. 34 E.  
 And set a Basalt Stone  $10 \times 12 \times 16$  ins.  
 12 ins. in the ground for  
 closing cor. to Secs. 3 & 4 marked  
 C. C. with 3 notches on E & N. edges  
 from which a line 30 ins.

Subdivisions of T. 2 South R. 34 East.

Willamette Meridian, Oregon.

	North on true line bet. Secs. 4 & 5 Wa 20° East.		
15.00	Creek 10 kcs. wide N.E.	-	1000
	Ascend		
25.00	Bluff of Rock	+	100
40.00	Set Stone 12 X 12 X 8 ins. 8 ins. in the ground for $\frac{3}{4}$ Sec. Cor. marked $\frac{3}{4}$ on N. face. Over which I raised a mound of stone 18 ins. high with 3 $\frac{1}{2}$ ft. base On East side of hill	+	900
55.00	Top of mountain Descend	+	1000
70.00	Canyon East	-	600
78.00	Intersect Township line 3.95 chs. N. of Cor. to Secs. 32 & 33 T. 1 S. R. 34 E. Set a post 4 ft. long $\frac{3}{4}$ in. square 24 ins in the ground for closing Cor. to Secs 4 & 5 marked T. 2 S. R. 34 E on S.		

44464

Subdivision of T. 2 South R. 34 East

Willamette Meridian, Oregon.

(8093-10 M.)

S. H. on E and

S. 5 on N. faces with  
H notches on E. and 2 on W.

Edges from which

A fir 10 ins diam. bears. S. 5° E

S 2 lks. dist marked S. 2. S. R. 34.

E. S. H. C. C. B. D.

A Tamarack 12 ins diam bears

S. 35° N. 80 lks. dist. marked

S. 2. S. R. 34. E. C. C. S. 5. B. D.

Land very rough <sup>78.00 ch</sup> and mountainous

Pine fir and Tamarack timber

Soil 3rd rate

Post on true line bet. Secs 29 + 32

Na. 18° 45' E.

40.00

Set post 3 ft. long + 4 ins. square

4 ins in the ground for 1/4 sec.

Cor. marked 1/4 S. on N. face

from which.

A Tamarack 10 ins diam. bears.

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

For clearing loc. to Secs. 6 & 7  
marked C. C. U. R. on E. face  
with 5 notches on S. and 1 on  
N. edges. Over which  
I raised a mound  
of stone 2 ft. high with  
4½ ft. base

Land mounting 39.00 lbs  
Timber in beams.

Some good bunch  
grass.  
Soil 4th rate and rocky.

North Bet. Secs. 5 and 6  
Pa. 19° 30' East.

8.10	Trail on Summit N.E. +	80
15.00	Descend	
28.00	Head of Gulch N. -	20
40.00	Set a Basalt Stone 4x12x14 ins.	

66

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

(8093-10 M.)

8 ins in the ground  
for <sup>1</sup>/<sub>4</sub> Sec. <sup>1</sup>/<sub>4</sub> marked  
<sup>1</sup>/<sub>4</sub> D. on W. face - 400  
Over which I raised  
a mound of Stone  
18 ins. high with 3 1/2 ft.  
base

73.00  
76.93

Rock Joint W. + 20  
Intersect Township  
line 355 chs. W. of cor.  
to Secs. 31 + 32 D. 1. S. R. 34. E.  
and set a Basalt Stone  
8 x 10 x 16 ins. <sup>10 ins</sup> in the ground  
for closing cor. to Secs.  
5 + 6 marked C. C. on S.  
face with 5 notches on  
E. and 1 on W. edges - 400  
from which I raised  
A line 12 ins diam. by  
S. 23° W. 25 chs. dist. marked  
D. 2. S. R. 34 E. C. C. S. C. B. D.



# FINAL OATHS FOR SURVEYS.

A list of the names of the individuals employed by Jas. P. Currier  
and Jas. E. Noland, U. S. Deputy Surveyor, to assist in  
running, measuring, and marking the lines and corners described in the  
foregoing field notes of the survey of the Subdivisional  
lines of Township 2 South  
R. 34. East Willamette Meridian, Oregon,  
showing the respective capacities in which they acted:

L. J. Wooley, Compassman.  
J. S. Medley, Chainman.  
W. H. Medley, Chainman.  
Frank Belshaw, Chainman.  
Guy Davis, Chainman.  
B. B. Brewer, Axman.  
H. Beach, Axman.  
\_\_\_\_\_, Flagman.

## FINAL OATHS OF ASSISTANTS.

We hereby certify that we assisted Jas. P. Currier and  
Jas. E. Noland, U. S. Deputy Surveyor, in surveying  
all those parts or portions of the Subdivisional  
Lines of Township 2  
South Range 34 East Willamette Meridian, Oregon,  
as represented in the foregoing field notes as having been surveyed by  
him and under his direction; and that said survey has been in all respects,  
to the best of our knowledge and belief, well and faithfully surveyed,  
and the corner monuments established, according to the instructions  
furnished by the U. S. Surveyor General of Oregon.

L. J. Wooley, Compassman.  
J. S. Medley, Chainman.  
W. H. Medley, Chainman.  
Frank Belshaw, Chainman.  
Guy Davis, Chainman.  
B. B. Brewer, Axman.  
H. Beach, Axman.  
\_\_\_\_\_, Flagman.

Subscribed and sworn to before me this 21st day of  
July, 1887.

[SEAL.]

James P. Currier  
U. S. Deputy Surveyor.

FINAL OATH OF DEPUTY SURVEYOR.

I, Mr. Jas. P. Currier & Jas. E. Toland, United States  
Deputy Surveyor, do solemnly swear that in pursuance of instructions  
received from Douglas W. Taylor, U. S.

Surveyor General for Oregon, bearing date of the 13<sup>th</sup>

day of May, 1887, I have well, faithfully,

and truly, in my own proper person, and in strict conformity with the  
instructions furnished by the U. S. Surveyor General for Oregon, the  
Surveying Manual, and the laws of the United States, surveying all

those parts or portions of Townships 2 S

Range 34 East

Willamette Meridian, in the State of Oregon, as are represented in the  
foregoing field notes as having been surveyed by me and under my  
directions; and I do further solemnly swear that all the corners of said  
survey have been established and perpetuated in strict accordance with  
the Surveying Manual, printed instructions, the special written instruc-  
tions of the U. S. Surveyor General for Oregon, and in the specific man-  
ner described in the field notes, and that the foregoing are the *true* field  
notes of such survey, and should any fraud be detected I will suffer the  
penalty of perjury under the provisions of an act of Congress approved  
August 8, 1846.

James P. Currier & James E. Toland  
U. S. Deputy Surveyors.

Subscribed and sworn to before me this Fifteenth

day of February, 1888

A. L. Woodcock  
Notary Public  
for Oregon

500

Office of U. S. Surveyor General,

Portland, Oregon, June 28<sup>th</sup>, 1888

The <sup>foregoing</sup> following Field Notes of the Survey of the

Subdivisional lines of Township  
2 South Range 34 East  
Willamette Meridian Oregon

executed by Jas. P. Carrin and Jas. E. Noland  
Special Joint U. S. Deputy Surveyors.  
under his Contract No. \_\_\_\_\_, dated May

4<sup>th</sup>, 1887, having been critically examined,  
the necessary corrections and explanations made, the  
said Field Notes and the survey they describe, are  
hereby approved.

Douglas W. Taylor -  
Surveyor General.