

FIELD NOTES

99

Of the survey of the Exterior

Lines of T. 3. S. R. 35. E., T. 2. S. R. 35. E., T. 1. S. R. 35. E.

T. 1. S. R. 34. E., T. 1. S. R. 37. E., T. 1. S. R. 38. E., Willamette Meridian,

Oregon, as surveyed by Jacob C

Cooper, U. S. Deputy Surveyor,

under his Contract No. 397, dated

July 1, 1881

Survey commenced, Aug 22 1881

Survey completed, Sept 27 1881

NAMES AND DUTIES OF ASSISTANTS.

....., Compassman.

W J Slater....., Chainman.

Jeff D Henton....., Chainman.

R. D. Cooper....., Chainman.

Chas W Ladd....., Chainman.

C D Goodrough....., Axeman.

R. M. Morgan....., Axeman.

....., Flagman.

100

PRELIMINARY OATHS OF ASSISTANTS:

We, Riley D. Cooper and
Charles W. Ladd

do solemnly swear that we will faithfully execute the duties of Chain Carriers, that we will level the chain over even and uneven ground, and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we will assist in measuring, to the best of our skill and ability, and in accordance with the instructions given us in

the survey of the Exterior
lines of T. 1. S. R. 37. E. and
T. 1. N. R. 37. T. 38. E. Willamette Meridian, Oregon.

R. D. Cooper, Chainman.
Charles W. Ladd, Chainman.
_____, Chainman.
_____, Chainman.

Subscribed and sworn to before me, this seventh
day of September 1881.

[SEAL.] Jacob C. Cooper
U.S. Dep Surveyor

We, Chas D. Goodnough and
Rufus M. Morgan

do solemnly swear that we will well and truly perform the duties of Axemen in the establishment of corners and other duties, according to instructions given us, and to the best of our

skill and ability, in the survey of the Exterior lines of T. 1. S. R. 37. E.
and T. 1. N. R. 37. T. 38. E. Willamette Meridian Oregon.

Chas D Goodnough, Axeman.
Rufus Morgan, Axeman.

Subscribed and sworn to before me, this seventh
day of September 1881.

[SEAL.] Jacob C. Cooper
U.S. Deputy Surveyor

STATE OF OREGON,

County of Union.

ss.

101

We Jeff D Fenton & W. P. Slater
R. M. Morgan, & C. D. Goodnough
Solemnly swear that we will well and faithfully
execute the duties of chain carriers that we
will level the chain upon even and uneven
ground and plumb the tally pins either by
sticking or dropping the same that we
will report the true distance to all notable
objects and the true length of all lines that
we assist in measuring to the best of our
skill and ability and in accordance with
the instructions given us in the Survey of Exterior
lines of Townships 1, 2 ^{and} 3 South Range 35 East
of Townships 1 South Ranges 36 ^{and} 37 East
of Townships 1 North Ranges 37 ^{and} 38 East
Willamette Meridian Oregon

Jeff D Fenton

Chairman

W. P. Slater

Chairman

R. M. Morgan

Chairman

C. D. Goodnough

Chairman

102

Subscribed and sworn to before me
this 16th day of July 1881

Geo. W. King
Notary Public
for Oregon

We R. M. Morgan & C. D. Goodnough

do solemnly swear that - we will well and truly perform the duties of assessors in the establishment of corners and other duties according to instructions given us and to the best of our skill and ability in the survey of Exterior lines of Townships East 3 South Range 35 East, of Townships & South Ranges 36th & 37 East of Township & North Ranges 36th & 37 East Willamette Meridian Oregon

R M Morgan Assessor
C D Goodnough Assessor

Subscribed and sworn to before me
this 16 day of July 1881

Geo. M. King

Notary Public for Oregon.

36

26

Exteriors

of T. 3 S

R. 35 E

Willamette Meridian, Oregon.

Chains

1/4 S on E & W faces

A pine 14 in diam bears

N 63° W 49 lbs dist marked

1/4 S B T no other trees in limits raised around
of stone along side.

N 21° E

Descend

72.00

Ascend in open pine timber

80.00

Set post 5 ft long 4 1/2 in square

2 1/2 ins in the ground for cor

to Tps 2 & 3 S R 34 & 35 E

(Summit of ridge in open pine

timber at head of ravine

course east) marked

T 2 S S 31 on NE

R 35 E S 6 on SE

T 3 S S 1 on SW and

R 34 E S 36 on NW faces

with 6 notches on each edge

raised a mound of stone about

post 3 ft at base 1 1/2 ins high, from

A pine 12 ins diam bears

27

0137

Exteriors of T. 3 S R. 35 E

Willamette Meridian, Oregon.

Chains S 12° W 57 lks dist marked
 T 3 S R 34 E S 1 B T
 A leaning pine 12 ins diam bears
 S 42° E 51 lks dist marked
 T 3 S R 35 E S 6 B T
 A fir 14 ins diam bears
 N 72° E 71 lks dist marked
 T 2 S R 35 E S 31 B T
 Land high rolling and
 mountainous, Soil gravelly
 and rocky 3rd rate
 Timber pine and fir
 Aug 23 1881

This township is rolling and
 hilly in the southern part,
 Soil medium. The valleys
 along some of the small streams
 that empty into the Grand
 Ronde river, are very fertile and
 are occupied by settlers who

FINAL OATHS FOR SURVEYS.

288

A list of the names of the individuals employed by.....

Jacob C. Cooper, U. S. Deputy Surveyor, to assist in running, measuring and marking the lines and corners described in the foregoing field notes of the survey of the *Exterior*

lines of *Townships 1, 2 & 3 S. Range 35 E of T1 S, R, 36 E* Willamette Meridian, Oregon, showing the respective capacities in which they acted :

-, Compassman.
- W. T. Slater*....., Chainman.
- J. D. Fenton*....., Chainman.
-, Chainman.
-, Chainman.
- R. Morgan*....., Axeman.
- C. D. Goodnough*....., Axeman.
-, Flagman.

FINAL OATHS OF ASSISTANTS.

We hereby certify that we assisted.....

Jacob C. Cooper, U. S. Deputy Surveyor, in surveying all those parts or portions of the *Exterior lines of Townships 1, 2 and 3 South Range 35 E. of Town 1 S R 36 E* Willamette Meridian, Oregon, as are represented in the foregoing field notes as having been surveyed by him and under his direction ; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the U. S. Surveyor General of Oregon.

-, Compassman.
- W. T. Slater*....., Chainman.
- J. D. Fenton*....., Chainman.
-, Chainman.
-, Chainman.
- R. M. Morgan*....., Axeman.
- C. D. Goodnough*....., Axeman.
-, Flagman.

Subscribed and sworn to before me, this *second* day of

September 188*1*

[SEAL.]

Robert J. Leach
Notary Public

FINAL OATHS FOR SURVEYS.

290 A list of the names of the individuals employed by.....

Jacob C Cooper....., U. S. Deputy Surveyor, to assist in running, measuring and marking the lines and corners described in the foregoing

field notes of the survey of the *Exterior lines*.....

lines of *T1SR 37 E and*.....

T1NRs 37 & 38 E..... Willamette Meridian, Oregon, showing the respective capacities in which they acted :

-, Compassman.
- R. D. Cooper*....., Chainman.
- Chas W Ladd*....., Chainman.
- C. D. Goodnough*....., Chainman.
-, Chainman.
- C. D. Goodnough*....., Axeman.
- R. M. Morgan*....., Axeman.
-, Flagman.

FINAL OATHS OF ASSISTANTS.

We hereby certify that we assisted *Jacob C Cooper*....., U. S. Deputy Surveyor, in surveying all those parts or portions of the *Exterior lines*.....

of *T1SR 37 E and*.....
T1NRs 37 & 38 East..... Willamette Meridian, Oregon, as are represented in the foregoing field notes as having been surveyed by him and under his direction ; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the U. S. Surveyor General of Oregon.

-, Compassman.
- C. D. Goodnough*....., Chainman.
- R. D. Cooper*....., Chainman.
- Charles Gadot*....., Chainman.
-, Chainman.
- C. D. Goodnough*....., Axeman.
- R. M. Morgan*....., Axeman.
- Charles Gadot*....., Flagman.

Subscribed and sworn to before me, this *13th*..... day of *October*..... 188*1*.....

[SEAL.]

Robert J. Staler
 Notary Public
 for Oregon

FINAL OATH OF DEPUTY SURVEYOR.

I, Jacob C Cooper

United States Deputy Surveyor, do solemnly swear that in pursuance of instructions

received from

James C Tolman

U. S. Surveyor General for Oregon, bearing date of the

first

day of

July, 188-1,

I have well, faithfully, and truly, in my own proper person, and in strict conformity with the instructions furnished by the U. S. Surveyor General for Oregon, the Surveying Manual, and the laws of

the United States, surveyed all those parts or portions of the Exterior lines ofTps 1, 2, 3, 3. S R 35-E, T1S R 36 & 37-E, T1N R 37 & 38-E

Willamette Meridian, in the State of Oregon, as are represented in the foregoing Field Notes as having been surveyed by me and under my directions; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Surveying Manual, printed instructions, the special written instructions of the U. S. Surveyor General for Oregon, and in the specific manner described in the field notes, and that the foregoing are the true field notes of such survey, and should any fraud be detected I will suffer the penalty of perjury under the provisions of an Act of Congress approved August 8, 1846.

Jacob C. Cooper

U. S. Deputy Surveyor.

Subscribed and sworn to before me, this

seventh

day of

January188-2.Henry Warner
Notary Public

292

Office U. S. Surveyor General,

Portland, Oregon, *April 5,* 188*2*

The following Field Notes of the Survey of

The E. 1/4 of Tps. 1-2-3 SR 35 E.
T 1 SR 36 and 37 E. and T 1-
N R 37 and 38 E.

executed by *Jacob C. Cooper*
under *his* contract No. *397*

dated *July 1,* 188*1*, having been
critically examined, the necessary corrections and ex-
planations made, the said field notes and the survey
they describe, are hereby approved.

James C. Tolman
Surveyor General.