

## FIELD NOTES

Of the survey of the Subdivisional  
 Lines of Township 2 South Range  
34 East Willamette Meridian, Oregon,  
 as surveyed by Jas. P. Currier & Jas. E. Roland  
 U. S. Deputy Surveyor, under his Contract No. \_\_\_\_\_  
 dated May 4<sup>th</sup>, 1887.

Survey commenced, July 16<sup>th</sup>, 1887  
 Survey completed, July 21<sup>st</sup>, 1887

## NAMES AND DUTIES OF ASSISTANTS.

L. F. Hooley, Compassman.  
J. S. Medley, Chainman.  
W. H. Medley, Chainman.  
Frank Belshaw, Chainman.  
Guy Davis, Chainman.  
B. B. Browner, Axman.  
A. V. Veatch, Axman.  
 \_\_\_\_\_, Flagman.

4 PRELIMINARY OATHS OF ASSISTANTS.

We, *J. S. Medley, W. H. Medley, Frank Belshaw, Guy Davis*

do solemnly swear that we will faithfully execute the duties of Chain Carriers; that we will level the chain over even and uneven ground, and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we will assist in measuring, to the best of our skill and ability, and in accordance with the instructions given us in the survey

of the *Subdivisional*

lines of *T 2 S,*

*Range 34 E* Willamette Meridian, Oregon.

*J. S. Medley*, Chainman.

*W. H. Medley*, Chainman.

*Frank Belshaw*, Chainman.

*Guy Davis*, Chainman.

Subscribed and sworn to before me this *16th*

day of *July*, 188*7*

*James P. Plurrien*  
[SEAL.] *W. S. Deputy Surveyor*

We, *B. B. Crown* and *H. Beach*

do solemnly swear that we will well and truly perform the duties of Axmen in the establishment of corners and other duties, according to instructions given us, and to the best of our skill and ability, in the survey of the

*Subdivisional lines of*  
*T 2 S, R 34 E* Willamette Meridian, Oregon.

*B. B. Crown*, Axman.

*H. Beach*, Axman.

Subscribed and sworn to before me this *16th*

day of *July*, 188*7*

*James P. Plurrien*  
[SEAL.] *W. S. Deputy Surveyor*

# INDEX

411

Referring the Lines to the Pages of the Field Notes.

T. 2 South R. 34 East Will. Mer.

6	65	5	43	4	28	3		2		1
64	<del>65</del>	62		41						
7	61	8	40	9	27	10		11		12
60		58		39	<del>40</del>					
18	57	17	38	16	25	15		14		13
55		54	<del>38</del>	37		24				
19	53	20	35	21	22	22	74	23		24
51	<del>52</del>	50	<del>35</del>	34		21	<del>74</del>	13		6
30	49	29	32	28	19	27	77	26	4	25
47	<del>48</del>	44		29	<del>30</del>	16		8		3
31	46	32	31	33	18	34	10	35		36

Meanders of \_\_\_\_\_, Pages \_\_\_\_\_ to \_\_\_\_\_

Meanders of \_\_\_\_\_, Pages \_\_\_\_\_ to \_\_\_\_\_

Subdivision of T. 2 South R. 34 East  
 Willamette Meridian, Oregon.

Survey commenced July 16<sup>th</sup> 1887.  
 with a Burts improved solar compass.

Beginning at cor. to Secs. 35 + 36  
 on South bdy. Township 2 South  
 R. 34 E. which is a stone 16x10x6  
 from which a pine 16 in in diam. bears  
 S 77° W. 27 lks dist. marked J. 38. R. 34 E. S. 2 B. J.  
 a pine 24 in in diam. bears S 73° E. 37 lks dist.  
 marked S 1. B. J. a pine 24 in in diam.  
 bears N 32° E. 39 lks dist. marked J 28.  
 R. 34 E. S. 36. B. J. a pine 36 in in diam.  
 bears N 82° W. 190 lks dist. marked  
 J. 28. R. 34 E. S. 35. B. J.

On 21° East

Thence North on true line, Cor. Secs 35 + 36.

18.00 Enter timber

36.45 Intersect U. R. bdy. at a point  
 S. 20° W. of 1/2 mile cor. in 63<sup>rd</sup>  
 mile 85 lks dist. And set  
 a post 4 ft. long + 4 ins.

square 24 ins. in the ground  
 for closing Cor. to Secs. 35 + 36  
 marked U. R. C. C. J. 2. S. R. 34 E.

Subdivisions of T. 2 South R. 34 East  
 Willamette Meridian, Oregon.

(8093-10 M.)

on south face, Sec. 36 N. E.

and Sec. 35 on W. face

from which a fir 16 ins.  
 diam. bears S. 70° E. 9 lks.

dist. marked @. 2. S. U. R. & C.

B. @. a fir 20 ins. diam. bears

South 60° W. 34 lks. dist. marked

R. 34. E. U. R. C. C. B. @.

4000 Set a post 3 ft. long 3 ins.

square 24 ins. in the ground

for  $\frac{1}{4}$  Sec. Gov. marked  $\frac{1}{4}$  S.

on W. face from which

a fir 16 ins. diam. bears S.

70° E. 25 lks. dist. marked

$\frac{1}{4}$  S. B. @. a fir 18 ins. diam.

bears N. 25° W. 40 lks. dist.

marked  $\frac{1}{4}$  S. B. @.

46.75 Daly wagon Road N. W.

79.50 Gulch course N. E.

8000 Set Basalt Stone 10 x 10 x 12 ins.

8 ins. in the ground for Gov.

600

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

to Secs. 25-26-35+36 marked  
with 7 notch on S. + E. edges.  
And raised a mound of  
stone alongside. Pits imp-  
racticable

Land mountainous and brushy  
Some Pine and fir timber  
good grass  
Soil 3rd Rate

43.55  
~~20.00~~

East on true line bet. Secs.  
25 + 36. Va. 19° East.

- 1.00 Gulch or canon N.E. — 50
- 6.00 Top of ridge N. + 1.00
- 13.00 Branch 5 lks. wide N.W. — 1.00

Ascend

15.85 Intersect U. R. by 5.60  
lbs. at 20° E of Gov. to 62nd  
mile and set post 4 ft.  
long 4 ins. square 24 ins.

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

(8093-10 M.)

in the ground for closing  
Cor. to Secs. 25 + 36 marked  
@. 2. S. R. 34. E. U. R. C. C. on N. Sec 25  
on N. T. Sec. 36 on S. face  
from which a pine 8 ins  
diam. bears N. 40° E. 27 lks.  
dist. marked @. 2. S. U. R. C. C.  
S. 25 B. D. A pine 16 ins.  
diam. bears S. 25° W. 3 lks  
dist. marked R. 34. E. U. R.  
C. C. S. 36 B. D.

Land rough and moun-  
-tainous <sup>15.85 chs</sup> Heavy pine and  
fir timber. <sup>15.85 chs</sup> Good bunch  
grass. Soil rocky 2" rate

North bet Secs. 25 + 26  
Va 19° East.

1800 Branch 10 lks. wide N.W.  
2000 " " " " N.E.

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

- 25.00 Branch 10 lks wide course N.W.
- 40.00 Set a post 3 ft. long 3 ins. square 24 ins. in the ground for  $\frac{1}{4}$  Sec. Cor. Marked  $\frac{1}{4}$  S. on N. face And raised a mound of stone  $1\frac{1}{2}$  ft. high by  $3\frac{1}{2}$  ft. base around it.  
Pits impracticable
- 65.00 Summit of sharp ridge + 800 ft
- 72.50 Spring branch 5 lks. wide N.W. - 400  
Ascend
- 80.00 Set a post 4 ft. long 4 ins. square 24 ins. in the ground for Cor. to Secs. 23-24-25+26+ 600  
Marked D. 2. S. S. 24 on N.E.  
R. 34. E. S. 25 on S.E.  
S. 26 on S.W. and S. 23 on N.W. faces. with 2 notches on  
on South and 1 on E edges  
from which a fir 24 ins. diam. bears N.  $10^{\circ}$  E. 200 lks.



## Subdivisions of T. 2 South R. 34 East

Willamette Meridian, Oregon.

(8093-10 M.)

R 34 E

dist marked S. 2 S. S. 24. B. D.  
 A fir 6 ins. diam. bears South  
 $30^{\circ}$  W. 136 lbs dist marked  
 S. 25 R 34 E.  
 S. 26. B. D. A fir 18 ins. diam.  
 bears N.  $20^{\circ}$  W. 117 lbs. dist.  
 marked S. 23. B. D. No other  
 tree within limits

Land extremely rough  
 and mountainous. 8000  
 ft. Scattering timber some good bunch  
 grass Soil rocky 2d rate

On account of the extremely rough & moun-  
 tainous character of the land. it being  
 utterly impossible to make any survey within  
 limits & the land being comparative worthless.  
 I discontinued the survey further

North and ran

East on true line bet. Secs  
 24 + 25.

Pa.  $19^{\circ} 30'$  East.

Ascend steep mountain  
 side

14 50	Summit sharp ridge N.W. +	1000
20 00	Gulch or cañon " "	1000

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

- 31.25 Top of ridge Course Ct. W. + 100
- 40.00 Top of Rimrock 10 ft. high  
which I marked  $\frac{1}{4}$  S. on  
N. face with ~~across~~ <sup>across</sup> ~~the~~ <sup>at</sup> ~~corner~~ <sup>point</sup>  
for  
 $\frac{1}{4}$  sec. Cor. over which I  
raised a mound of stone  
18 ins high and  $3\frac{1}{2}$  ft. base
- 41.00 Cross head of Sharp dip  
Cairn Course Ct. W.
- 45.50 I intersect U. R. bay. at a point  
at  $20^{\circ}$  E. of  $67^{\text{th}}$  mile Cor 10.75  
Chs. dist. And set a post  
4 ft. long 4 ins. square 24  
ins. in the ground for  
U. R. closing Cor. to Secs. 24 & 25  
marked T. 2 S. R. 34. E. U. R.  
C. C. on W. face. S. 25 on  
N. and S. 24 on S faces  
from which a pine 12 ins.  
diam. bears S.  $30^{\circ}$  E. 26 lks.  
dist marked U. R. C. C. S. 24

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

(8093-10 M.)

B. D. A Pine 24 ins. diam.  
bears. N. 30° W. 26 lks. dist.

marked M.R. C.C. S. 25. B. D.

Land Rough and mountain  
Pine <sup>45.50 chs.</sup> and fir timber. Good grass  
Soil 2<sup>nd</sup> rate

West on true line bet. Secs. 26 + 35  
Wa. 19° East.

1280 Top of mountain + 600

4 3300 Begin to descend

4000 Set Basalt Stone 12x12x24 ins.

18 ins. in the ground marked  
1/4 S. on N. face for 1/4 Sec. cor.

from which a Pine 16 ins.  
diam. bears. N. 75° E. 34 lks. dist.

marked 1/4 S. B. D. A pine 12 ins.

diam. bears. S. 65° E. 34 lks. dist.

marked 1/4 S. B. D.

60.60 Daly wagon Road N. W.

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

7650 Ravine N.W. — 20

8000 Set post 4 ft. long & 4 ins. square  
24 ins. in the ground for Cor. to  
Secs. 26-27-34 & 35 marked

T. 2, S. 26. on N.E. R. 34. E.

S. 35 on S.E. S. 34. on S.W. and

S. 27 on N.W. faces, from which

A pine 16 ins diam. bears N.

62° E. 76 lks dist. marked

T. 2, S. <sup>R34E</sup> 26. B. T. A pine

8 ins. diam. bears S. 25° E.

46 lks. dist. marked <sup>T. 29.</sup> R. 34. E.

S. 35. B. T. A pine 6 ins.

diam. bears S. 25° N. 70 lks.

dist. marked <sup>T. 29 R 34 E.</sup> S. 34 B. T.

A pine 10 ins. diam. bears N.

48° N. 59 lks. dist. marked <sup>T. 29 R 34 E.</sup>

S. 27. B. T.

Land rolling. Scattering  
pine fir and Lamanack  
timber. Soil 2<sup>nd</sup> rate & rocky

10 430

Subdivisions of T. 2 South R. 34 East

Willamette Meridian, Oregon.

(8093-10 M.)

South on true line bet Secs.  
34 & 35

Ca.  $19^{\circ}$  East

1700 Summit of ridge & Bluff of Rock  
10 feet high

4000 Set a post 3 ft. long & 3 ins.  
square 24 ins. in the ground  
for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  S. on  
N. face from which  
a pine 24 ins. diam. bears  $N 20^{\circ}$   
E 104 lks. dist. marked  $\frac{1}{4}$  S. B. D.  
a pine 24 ins. diam. bears  
S.  $70^{\circ}$  E 73 lks. dist. marked  
 $\frac{1}{4}$  S. B. D.

5000 Intersect U.R. bdy. 5.25 chs.  
N. of  $\frac{1}{2}$  mile cor. in 64<sup>th</sup> mile  
and set a post 4 ft. long  
4 ins. square 24 ins. in the  
ground for U.R. Closing  
Cor. to Secs. 34 & 35 marked  
D. 2. S. R. 34. E. U.R. C. C. on

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

at S. 35. on E. and S. 34  
on W. face. from which  
A Black Pine 10 ins. diam.  
bears at  $85^{\circ}$  E. 62 lks. dist.

marked U.R. C. C. S. 35. B. 2.

A fir 6 ins. diam. bears S.  $75^{\circ}$

W. 25 lks. dist marked U.R.

C. C. S. 34. B. 3.

Land mostly level scattering  
fine timber. Soil 2<sup>nd</sup> rate.

North on true line bet. Secs.  
26 & 27.

Pa.  $19^{\circ}$  East.

12.00	Ravine	at W.	—	20
19.50	Daly Wagon Road	" "	" "	
20.00	Enter timber	E + W		
28.00	Ravine	at W.	—	20
40.00	A Black Pine 4 ins. diam. which I marked $\frac{1}{4}$ S. on W. face			

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

(8093-10 M.)

For 1/4 Sec. Cor. from which  
A Black Pine 6 ins. diam.  
bears N. 88° East 11 lks. dist.  
marked 1/4 S. B. D. A Pine  
4 ins. diam. bears S. 86° W.

6 lks. dist. marked 1/4 S. B. D.

46.00 Ravine N. —

80.00 Set post 4 ft. long 4 ins.  
square 24 ins. in the ground  
for Cor. to Secs 22-23-26+27  
marked D. 2 S. S. 23 on  
N. E. R. 34 E. S. 26 on S. E.

S. 27 on S. W. and S. 22 on  
N. W. faces from which

A pine 28 ins. diam. bears  
N. 80° E. 80 lks. dist. marked  
D. 2 <sup>R34E</sup> S. S. 23. B. D.

A pine 12 ins. diam. bears  
S. 62° E. 71 lks. dist. marked

T. 2 S R. 34 E. S. 26. B. D.

A pine 6 ins. diam. bears S 25° W.

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

T. 2 S. R. 34 E.

74 lks. dist. marked S. 27. B. D.  
No other trees within limits.  
Raised a mound of stones 24 ins.  
high & 4 1/2 ft. base alongside  
Land rolling. Timber pine fir  
and tamarack. Soil 2nd rate Rocky

East On Random bet. Secs.

23 + 26

Va. 22° East.

4000 Set temp. 1/4 Sec cor.

8040 Intersect N-S line. 33 lks. North  
of Fox to Secs. 23-24-25 + 26.

Thence N. 89° 46' W. on true line

Va. 19° 30' East.

9.50 Branch 10 lks. wide in canon. N. 1800

10.00 Sharp ridge or divide + 100

12.00 Brook 5 lks. wide - 100

Ascend bluff facing East + 100

Ascend



14 434

Subdivisions of T. 2 South R. 34 East

Willamette Meridian, Oregon.

(8093-10 M.)

40.00

Set post 3 ft. long 3 ins. square  
24 ins. in the ground for  $\frac{1}{4}$  Sec.  
Cor. marked  $\frac{1}{4}$  S. on N. face  
from which a pine 5 ins.  
diam. bears N. 80° E. 14 lks. dist.  
marked  $\frac{1}{4}$  S. B. D.

A Tamarack 6 ins. diam. bears  
S. 75° E. 12 lks. dist. marked  
 $\frac{1}{4}$  S. B. D.

62.00

Top of mountain N. + 1800

80.40

Do low to Secs. 22-23-26+27

Land extremely rough and  
mountainous, 80.40 chs

Pine, Fir and Tamarack timber and  
brush. Soil 2<sup>d</sup> rate rocky

North on true line bet. Secs. 22+23

Wa. 22 East

10.00

Gulch

N.

40.00

Set a Basalt Stone 10x12x18 ins.

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

10 ins. in the ground for  
1/4 Sec. For marked 1/4 S. on N.  
face from which

A pine 12 ins. diam. bears S 22°  
E. 72 lks. dist. marked 1/4 S. B. 2.

A pine 8 ins. diam. bears N. 13°  
W. 36 lks. dist. marked 1/4 S. B. 2.

44.50	Top of ridge <sup>up</sup> bluff N. E.	+	100
49.50	Gulch or Canon E.	-	100
67.00	" " " "	-	50
70.00	Ridge E. end Descend	+	100

8000 Set post 4 ft. long 4 ins.  
square 24 ins. in the ground  
for Cor. to Secs. 14-15-22 & 23

marked @. 2. S. S. 14 on N. E.  
R. 34 E. S. 23 on S. E. S. 22, on  
S. W. and S. 15 on N. W. faces  
from which a pine 6 ins.  
diam. bears N. 15° E. 116 lks. dist.  
marked @. 2. S. S. 14. B. 2.

A pine 5 ins. diam. bears S. 30° E

Subdivisions of T. 2 South R. 34 East.  
Willamette Meridian, Oregon.

(8093-10 M.)

J 29

15 lks. dist. marked R. 34 Sec. 23

B. D. A pine 6 ins. diam. bears

S. 35° W. 25 lks. dist. marked

J 29 A 34 E

S. 22. B. D. And a pine 4 ins.

diam. bears N. 35° W. 82 lks.

J 29 A 34 E

dist. marked S. 15. B. D.

Land rough <sup>2nd</sup> mountain 80. ch  
Pine fir and tamarack timber  
Soil 2<sup>nd</sup> Rate.

The land is too rough N. & E.  
to continue the survey, being  
a perfect nest of canons and  
raggy bluffs.

July 16 1887

West. On pine line bet. Secs. 27 &amp; 34

Va. 19° East.

2250 Old wagon road bears N. E. &amp; S.

4000 Set Basalt Stone 10 X 10 X 12 ins.

8 ins. in the ground for 3/4 Sec.

For marked 1/4 S. on N. face

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

(SEE 01-500)

And raised a mound of stone  
18 ins. high with 3 1/2 ft. base  
over it as per instructions

7050

Enter prairie N. + S.

7800

Leave prairie

8000

Set post 4 ft. long 4 ins. square  
24 ins. in the ground for cor.  
to Sec. 27-28-33 + 34 marked  
D. 2 S. S. 27 on N. E.

R. 34 S. 34 on S. E.

S. 33 on S. W. and

S. 28 on N. W. faces, with  
3 notches on E. and 1 on S. edges  
from which a pine 30 ins.

diam. bears N. 85° E 142 chs  
R. 34 E.

dist. marked D. 2 S. S. 27. B. D.

A pine 24 ins diam. bears S. 76°  
E. 30 lks. dist. marked, R. 34 E.

S. 34. B. D. And a pine 42 ins.

diam. bears S. 60° W. 200 chs.

dist. marked, S. 33. B. D. No other  
T. 2 S. R. 34 E.

Subdivision of T. 2 South R. 34 East

Willamette Meridian, Oregon.

(8093-10 M.)

trees within limits raised mound  
of stone along side  
and rolling Pine & Fir timber  
Dense underbrush 70 chs  
Soil 2<sup>nd</sup> rate.

South on true line bet. Secs. 33 & 34

On. 18° 30' East.

3600 Leave timber E & W.

4000 Set Basalt Stone 4x10x14 ins.  
10 ins. in the ground for 3/4  
Sec. Cor. marked "4" on N.  
face, over which I raised  
a mound of stone 1 1/2 ft high  
with 3 1/2 ft. base as per instructions.

5025 Intersect U. R. bdy. 5.42 chs.  
N. of 1/2 mile from in 65<sup>th</sup> mile  
And Set a Basalt Stone 4x8x12  
ins. 8 ins. in the ground for  
U. R. Closing Cor. marked  
U. R. C. C. on N face and  
raised a mound of stone

Subdivisions of T. 2 South R. 34 East 439

Willamette Meridian, Oregon.

(25 of 200)

2 ft. high with 4 ft. base  
over it as per instructions  
Land rolling. Good fine  
and fir timber. Soil 4<sup>th</sup> rate  
and rocky.

North on true line bet. Secs. 27 & 28  
Va. 18° 30' East.

- 32.00 Leave timber <sup>and</sup> brush
- 35.75 Gulch N. & ascend
- 40.00 Set Basalt Stone 7x8x12 ins.  
8 ins. in the ground for 1/4 Sec.  
For marked 1/4 on N. face  
over which I passed a mound  
of stone 18 inches high with 3 1/2  
ft. base.
- 42.25 Enter brush E & W.
- 62.50 Ravine <sup>and</sup> leave Brush — 50
- 74.50 Daly Wagon Road
- 80.00 Set post 4 ft. long by 4 ins.  
square 24 ins. in the ground

20  
440

Subdivisions of T. 2 South R. 34 East.

Willamette Meridian, Oregon.

(8093-10 M.)

for Gov. to Secs. 21-22-27 & 28  
marked D. 2. S. S. 22 on N.E.

R. 34. E. S. 27 on S.E.

S. 28 on S.W. and

S. 21 on N.W. faces with  
3 notches on E and 2 on S. edges

from which a pine 10 ins.  
diam. bears N. 50° E. 81 lks.

dist. marked D. 2. S. <sup>R. 34 E.</sup> S. 22. B. D.

A pine 6 ins. diam. bears S. 58° E  
<sup>S. 23</sup>

187 lks. dist. marked R. 34. E. S. 27. B. D.

A pine 12 ins. diam. bears S. 15° W.  
<sup>S. 25 R. 34 E.</sup>

135 lks. dist. marked S. 28. B. D.

(No other trees within limits.) and

raised a mound of stone 2 ft.

high with 4 ft. base alongside

Land Rolling.

Some Fir, Pine, and Tamarack

timber, heavy underbrush <sup>70 lbs</sup>

Soil 2nd rate.

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

(16 of 5000)

East On Random bet Sec.  
22 & 27

Var. 21° East.

4000 Set temp. 1/4 Sec. Cor.

8000 Intersect N-S line 25 lks. N. of  
Cor. to Sec. 22-23-26 & 27.

Thence at 89° 49' W. on true line  
Var 22° East

1250 Gulch S.W. 23-

3100 Enter timber at + S.

3900 Leave timber " "

4000 Set Basalt Stone 12x12x12 ins.

8 ins. in the ground for 1/4  
Sec. Cor. marked 1/4 on N. face  
from which a Pine 16 ins.

diam. bears N. 50° W. 86 lks. dist.

marked 1/4 S. B. D. No other trees  
within limits. Raised a mound

of Stone 18 ins. high with 3 1/2 ft.  
base over Cor. as per instructions

4800 Gulch S.W.

6500 Enter pine thicket



Subdivisions of T. 2 South R. 34 East  
 Willamette Meridian, Oregon.

(8093-10 M.)

7600 Leaves thicket

8000 To cor. to Secs. 21-22-27+28

Land mostly level.

Some fine Red fir timber

Heavy mudbricks <sup>40 lbs</sup> Soil 2<sup>nd</sup> rate.

North on true line bet. Secs. 21+22

Va. 21° East

300 Entire fine thicket

4000 Set post 3 ft. long 3 ins. square

24 ins. in the ground for 1/4 Sec.

Cor. marked 1/4 on N. face

from which a pine 12 ins.

diam. bears N. 65° W. 5 lks

dist. marked 1/4 S. B. 3. and

a Red fir 10 ins. diam. bears

S. 20° E 10 lks. dist. marked

1/4 S. B. 3.

6325 Ravine bears N. W. — 50

8000 Set a post 4 ft. long 4 ins. square

Subdivisions of T. 2 South R. 34 E 4th  
Willamette Meridian, Oregon.

24 ins. in the ground for 90.  
to Secs. 15-16-21+22 marked  
D. 2. S. S. 15. on N. E.

R. 34 E. S. 22 on S. E.

S. 21 on S. W. and

S. 16 on N. W. faces, with  
3 notches on the S. and E. edges  
from which a Pine 10 ins.  
diam. bears N. 30° E. 37 lks.  
R 34 E.

dist. marked D. 2. S. S. 15. B. D.

A Pine 24 ins. diam. bears  
S. 45° E. 42 lks. dist. marked J 29.

R. 34 E. S. 22. B. D.

A Pine 4 ins. diam. bears

S. 50° W. 80 lks. dist. marked  
J 29 R 34 E.

S. 21. B. D. and

A Pine 16 ins. diam. bears

N. 55° W. 14 lks. dist. marked  
J 29 R 34 E.

S. 16. B. D. Land level. Pine

fir and tamarack timber. Heavy under-  
brushy Soil 3rd Rate.  
77 lbs

24

444

## Subdivisions of T. 2 South R. 34 East

Willamette Meridian, Oregon.

(8093-10 M.)

East on Random bet Secs.

15 + 22

Va.  $20^{\circ} 15'$  East.4000 Set temp  $\frac{1}{4}$  Sec. Cor. at

8020 Intersect N. S. line 12 lks.

North of Cor. to Secs. 14-15-22+23

Thence  $N 89^{\circ} 55' W.$  on true lineVa.  $24^{\circ}$  East800 Top of hill + enter timber & brush <sup>1400</sup>

4010 Set post 3 ft long and

3 ins. square 24 ins. in the

ground for  $\frac{1}{4}$  Sec Cor.Marked  $\frac{1}{4}$  S. on N. face

from which a fir 16 ins.

diam. bears  $N. 30^{\circ} E.$  11 lks. distmarked  $\frac{1}{4}$  S. B.D. And a

Pine 6 ins. diam. bears S.

 $10^{\circ} E.$  16 lks. dist marked  $\frac{1}{4}$  S. B.D.

7600 Leave timber &amp; enter small prairie

Subdivisions of T. 2 South R. 34 East

Willamette Meridian, Oregon.

(M 01-3008)

8020 To Cor. to Secs 15-16-21 & 22  
 Land mostly level. Pine fir  
 Spruce and Samanack timber  
 Very heavy underbrush. 68. chz  
 Soil 1st Rate

North all pine line bet. Secs. 15 & 16  
 Pa. 20° 15' East.

Ascend

4000 Set Basalt Stone 6x8x12 ins.  
 8 ins. in the ground for 1/4  
 Sec. lev. marked 1/4 on N. face  
 over which I raised a mound  
 of stone 18 ins. high with 3 1/2 ft.  
 base. Pits impracticable

5000 Top of Mountain + 700

7950 Canon N. E. - 400

8000 Set A post 4 ft long 4 ins.  
 square. 24 ins. in the ground  
 for Cor. to Secs. 9-10-15 & 16  
 marked D. 2. S. 10. on N. E.

Subdivisions of T. 2 South R. 34 East

Willamette Meridian, Oregon.

(8093-10 M.)

R. 34. E. S. 15 on S. E.  
 S. 16 on S. W. and  
 S. 9 on N. W. faces with  
 3 notches on E. and 4 on S. edges  
 from which a pine 8 ins.  
 diam. bears N. 85° E. 30 lbs.  
 dist marked <sup>R. 34 E</sup> D. 2 S. 10. B. D.  
 A fir 6 ins. diam. bears S. 65°  
 E. 13 lbs. dist marked <sup>S. 29</sup> R. 34. E.  
 S. 15. B. D.

A fir 6 ins. diam. bears  
 S. 15° N. 32 lbs. dist marked  
<sup>S. 29 R. 34 E.</sup>  
 S. 16. B. D. And  
 A fir 10 ins. diam. bears N.  
 70° W. 29 lbs. dist marked  
<sup>S. 29 R. 34 E.</sup>  
 S. 9. B. D.  
 Land very mountainous & brushy. 80. 43  
 Pine fir Spruce and tamarack  
 timber Soil 3rd rate

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

North on true line bet. Secs. 9 & 10  
Cra. 18° East.

36.50 Cañon et. N. - 600  
Ascend

40.00 Set Basalt Stone 16x18x28 ins. 12 ins.  
in the ground for 1/4 Sec. Cor. marked  
1/4 S. on N. face, over which I  
raised a mound of stone  
18 ins. high with 3 1/2 ft. base

*Its impracticable*  
On side of long ridge + 150

65.00 Summit of ridge & descend. 850

80.00 Set Basalt Stone 8x10x12 ins. 8 ins.  
in the ground for Cor. to Secs.  
3-4-9 & 10 marked with 3 notches  
on the E. and 5 on the S. edges  
Over which I raised a mound  
of stone 2 ft. high with  
4 ft. base. Land rough and  
mountainous <sup>80.00 of ds</sup> and fir  
timber in cañons. Soil 4 <sup>th</sup> rate

28

448

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

(8093-10 M.)

- North on true line bet. Secs 3 & 4  
Cra.  $17^{\circ} 30'$  East.
- 1950 Dry bed of creek at N. E. - 200  
Ascend
- 2835 Gulch S. E. - 100
- 40.00 Set Basalt Stone  $7 \times 8 \times 12$  ins.  
8 ins. in the ground for  $\frac{1}{4}$  Sec.  
Cor. marked  $\frac{1}{4}$  on N. face  
Over which I raised a  
mound of stone 18 ins. high  
with  $3\frac{1}{2}$  ft. base. On side of  
mountain
- 63.00 Summit of mountain N. E. 800 +  
Descend
- 78.50 Intersect Township line 3.79 chs.  
N. of Cor. to 33 & 34 T. 1 S. R. 34 E.  
And set a Basalt Stone  $10 \times 12 \times 16$  ins.  
12 ins. in the ground for  
closing cor. to Secs. 3 & 4 marked  
C.C. with 3 notches on E & N. edges  
from which a line 30 ins.

Subdivisions of T. 2 South R. 34 East.  
Willamette Meridian, Oregon.

(M 01-500)

diam. bears S. 65° E. 42 kcs.

dist. marked T. 2 S. R. 34 E.

S. 3. Q. C. B. D.

A pine 28 ins. diam. bears N. 50°

W. 51 kcs. dist. marked T. 2 S. R. 34 E. C. C.

B. D. (No other trees within limits)

And raised a mound of stone  
alongside 2 ft. high with  
4 1/2 ft. base.

Land rough and mountainous 78.50 ch  
Soil Rocky and 4th rate.

West on true line bet. Secs.

28 & 33

Pa. 18° 30' East.

500 Enter pine thicket

4000 Set post 3 ft. long and 3 ins.

square 24 ins. in the ground  
for 1/4 Sec. cor. marked 1/4 S. on  
N. face from which



3450

Subdivisions of T. 2 South R. 34 East

Willamette Meridian, Oregon.

(8093-10 M.)

A Pine 16 ins. diam. bears S. 50° East 113 lks. dist marked 4. S. B. D.

A Pine 8 ins. diam. bears N. 35° W. 22 lks. dist marked 1/4 S. B. D.

64.00

Jennings Creek South — 80

80.00

Set post 4 ft long & 4 ins. square 24 ins. in the ground for Cor. to Secs. 28-29-32 & 33 marked D. 2. S. S. 28 on N.E.

R. 34. E. S. 34. on S. E.

S. 33. on S. W. and

S. 29 on N. W. faces with 4 notches on E & 1 on S. Edges

from which A Pine 4 ins. diam. bears N. 30° E. 10 lks. dist marked D. 2. S. S. 28. B. D.

A Pine 5 ins. diam. bears S. 30° E. 45 lks. dist marked R. 34. E. S. 33. B. D.

A Damarack 5 ins. diam. bears S. 85° W. 30 lks. dist marked S. 32. B. D. and

Damarack 6 ins. diam. bears N. 45° W.

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

(M 01-100)

- D. 2 S. R. 34 E.
- 11 lks. dist marked, S. 29. B. D.  
Good timber for fine  
Land mostly level Soil 2<sup>nd</sup> & 3<sup>rd</sup>  
rate
- South on true line bet. Secs. 32 & 33  
Va.  $18^{\circ}45'$  East
- 26.00 South fork of Jennings Creek 10 lks.  
wide course S. E.
- 40.00 Set post 3 ft. long 3 ins. square  
24 ins. in the ground for  $\frac{1}{4}$  Sec.  
Cor. marked  $\frac{1}{4}$  S. on N. face from which  
A pine 5 ins. diam. bears N.  $42^{\circ}$  East  
9 lks. dist. marked  $\frac{1}{4}$  S. B. D.
- A Tamarack 5 ins. diam. bears S.  $38^{\circ}$  W.  
7 lks. dist marked  $\frac{1}{4}$  S. B. D.
- 51.10 Intersect U.R. body 5.58 chs. west  
of  $\frac{1}{2}$  mile cor. in 66" mile and  
Set a post 4 ft. long & 4 ins. square  
24 ins. in the ground for U.R. Closing  
Cor. marked D. 2. S. R. 34. E. U.R. & C

32

452

## Subdivisions of T. 2 South R. 34 East

Willamette Meridian, Oregon.

(8093-10 M.)

On North face. S. 33 on E. & S. 32 on W.  
faces from which.

A pine 4 ins. diam. bears N. 5° E.  
10 kcs. dist marked <sup>R 34 E</sup> D. 2, S. 33. C. C.  
B. D.

A pine 4 ins. diam. bears S 70° E. 12 kcs.  
dist marked <sup>S 23</sup> R. 34 E. C. C. B. D.

No other trees within limits

Land mostly level. Pine and  
fir timber. Soil 2<sup>nd</sup> rate.

July 18<sup>th</sup> 1887.

North on True Line Bet. Secs. 28 & 29

(Va. 18° 45' East.

Top of ridge covered with pine fir  
and tamarack timber

4000 Set Basalt Stone 8x10x12 ins. 8 ins.

in the ground, for 4 sec. cor.

marked  $\frac{1}{4}$  ft. on N. face <sup>plunged in</sup>

which I raised a mound of stone  
18 ins. high with 3½ ft. base, for impracticable

Subdivisions of T. 2 South R. 34 East  
 Willamette Meridian, Oregon.

(M 01-500)

8000 Set post 4 ft long and 4 ins. square  
 24 ins. in the ground for for. to Secs.  
 20-21-28+29 marked  
 D. 2. S. S. 21. on N. E  
 R. 34. E. S. 28. on S. E.  
 S. 29. on S. W. and  
 S. 20. on N. W. faces with  
 4 notches on East and 2 on South  
 Edges from which  
 A pine 8 ins. diam. bears N. 70°  
 E. 35 lks. dist marked D. 2. S. S. 21. B. D. <sup>R. 34 E.</sup>  
 A pine 8 ins. diam. bears S. 60° E. 60  
 lks. dist marked <sup>S. 28.</sup> R. 34. E. S. 28. B. D.  
 A pine 3 ins. diam. bears S. 70° W.  
 10 lks. dist, marked <sup>S. 29. B. D.</sup> S. 29. B. D. and  
 A pine 5 ins. diam. bears N. 15° W.  
 25 lks. dist marked <sup>S. 20. B. D.</sup> S. 20. B. D.  
 Land Level & covered with  
 heavy underbrush & scattering  
 pine & fir timber. Soil 1<sup>st</sup> rate.

34

454

## Subdivisions of T. 2 South R. 34 East

Willamette Meridian, Oregon.

(8093-10 M.)

	East On Random Bet Secs. 21 & 28
	Wa. $19^{\circ} 30'$ East
40.00	Set temp. $\frac{1}{4}$ Sec. Cor.
80.10	Intersect N. & S. line at cor. to Secs. 21-22-27 & 28
	Thence West on true line
	Wa. $21^{\circ}$ East.
4.00	Waly Wagon Road N.W.
10.00	Enter timber S.E.
15.00	Jennings Creek S.E.
40.05	Set Basalt Stone $6 \times 10 \times 14$ ins. 8 ins. in the ground for $\frac{1}{4}$ Sec. Cor. marked $\frac{1}{4}$ on N face. from which A pine 6 ins. diam. bears $N 45^{\circ} E$ 8 lbs. dist marked $\frac{1}{4}$ S B.D. A pine 5 ins diam. bears $S. 20^{\circ} W$ 46 lbs. dist marked $\frac{1}{4}$ S B.D.
80.10	To Cor. to Secs. 20-21-28 & 29
	Land mostly level with pine fir and Tamarack timber Soil 2 <sup>nd</sup> Rate

Subdivision of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

North on True Line Bet. Secs. 20 & 21

N. 19° 30' East.

- 4.00 Dry bed of Jennings Creek  
4.50 Daly Wagon Road N. W.  
21.25 Dry bed of Creek  
Ascend.
- 40.00 Set post 3 ft. long & 3 ins. square  
24 ins. in the ground for  $\frac{1}{4}$  Sec. Cor.  
marked  $\frac{1}{4}$  S. on N. face from which  
A pine 20 ins. diam. bears N. 50°  
E. 40 lks. dist. marked  $\frac{1}{4}$  S. B. D.  
A pine 12 ins. diam. bears N. 40°  
W. 56 lks. dist. marked  $\frac{1}{4}$  S. B. D.
- 60.00 Summit of hill or table land  
Enter prairie
- 80.00 Set post 4 ft. long & 4 ins. square  
24 ins. in the ground for cor.  
to Secs. 16-17-20 + 21 marked  
D. 2. S. S. 16 on N. E.  
R. 34. E. S. 21 on S. E.  
S. 20. on S. W. & S. 17. on N. W. bases

Subdivision of T. 2 South R. 34 East

Willamette Meridian, Oregon.

(8093-10 M.)

With 3 notches on S. Ed 4 on E.

Edges. From which

A Pine 24 ins. diam. bears N.

70° E. 66 lbs dist marked

T. 2. S. <sup>R 34 E.</sup> 16. B. D.

A Pine 20 ins. diam. bears S 70°

E 63 lbs. dist marked T. 2. S.

R. 34. E. S. 21. B. D.

A Pine 36 ins. diam. bears

N. 10° W. 112 lbs. dist marked

T. 2. S. R. 34 E. S. 17. B. D.

No other trees within limits

Raised a mound of stone

alongside 18 ins. high with

4 1/2 ft. base

Land gently rolling or

sloping toward South

Scattered pine & fir timber

Soil drift rate

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

East On Random Bear Secs. 16 + 21

Va.  $18^{\circ} 30'$  East

40.00 Set pump  $\frac{1}{4}$  Sec. Cor.

80.20 Intersect ~~line~~ <sup>North line</sup> 30 lks. N. of cor

to Secs. 15-16-21+22

Thence N.  $89^{\circ} 47'$  W. On true line

Va.  $20^{\circ} 15'$  East

40.10 A fir 4 ins. diam. which I  
marked for  $\frac{1}{4}$  Sec. Cor. marked

$\frac{1}{4}$  S. on N. face. from which

A fir 12 ins. diam. bears N.  $65^{\circ}$  E.

33 lks. dist. marked  $\frac{1}{4}$  S. B. D.

A fir 6 ins. diam. bears S.  $50^{\circ}$  E. 17

lks. dist marked  $\frac{1}{4}$  S. B. D.

80.20 Do Cor. to Secs. 16-17-20+21.

Land mostly level.

Timber - Pine & Fir

Soil 7<sup>th</sup> Rate.



## Subdivisions of T. 2 South R. 34 East.

Willamette Meridian, Oregon.

(8093-10 M.)

- North on true line bet. Secs. 16 + 17  
 Va 18° 30' East.
- 2.00 Descend <sup>and</sup> Enter timber
- 15.00 Leave timber
- 40.00 Set Basalt Stone 7x9x12 ins.  
 8 ins. in the ground for  $\frac{1}{4}$  Sec.  
 Cor. marked  $\frac{1}{4}$  S. on N. face  
 Over which I raised a mound  
 of stone 18 ins. high with  
 3 $\frac{1}{2}$  ft. base Pts impracticable
- 80.00 Set Basalt Stone 10x10x12 ins.  
 8 ins. in the ground for cor. to  
 Secs. 8-9-16+17 marked with  
 4 notches on S. + E. Edges  
 Over which I raised a mound  
 of stone 2 ft. high with 4 $\frac{1}{2}$  ft.  
 base. Pts impracticable
- Land mostly level. Open  
 pine timber. Bunch grass good  
 Soil Rocky <sup>and</sup> 4" rate.

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

East On Random bet Secs. 9+16

Wa.  $20^{\circ}$  East.

40.00 Set temp  $\frac{1}{4}$  Sec. Cor.

80.00 Intersect N. & S. line at Cor. to Secs.

9-10-15+16.

Thence West on true line

Wa.  $18^{\circ}$  East.

Ascend

10.00 Top of ridge N. + 600

40.00 Set post 3 ft. long & 3 ins. square  
24 ins. in the ground for  $\frac{1}{4}$  Sec. Cor.  
marked  $\frac{1}{4}$  S. on N. face from which

A fir 12 ins. diam. bears N.  $20^{\circ}$  E. 16

lks. dist. Marked  $\frac{1}{4}$  S. B. D. and

A fir 14 ins. diam. bears S.  $89^{\circ}$  W. 25 lks.

dist. Marked  $\frac{1}{4}$  S. B. D.

47.25 Rattle Snake Canon - 400

80.00 To Cor. to Secs. 8-9-16+17

Land rough <sup>and mountainous rocks</sup> bushy. Pine and

Fir timber, some red brush

Soil Rocky <sup>2<sup>nd</sup> rate</sup>

Subdivisions of T. 2 South R. 34 East.

Willamette Meridian, Oregon.

(8093-10 M.)

- North on true line bet. Secs. 8 + 9  
 Va. 20° East.
- 30.00 Gulch N. E. - 100  
 Ascend
- 40.00 Set Basalt stone 8x10x12 ins. 8 ins.  
 in the ground for  $\frac{1}{4}$  Sec. cor.  
 marked  $\frac{1}{4}$  S. on N. face  
 over which I raised a mound of  
 stone 18 ins. high with 3 $\frac{1}{2}$  ft. base
- 56.00 Summit of ridge + Begin to descend
- 67.50 Gulch N. W. - 120
- 75.00 Top of ridge + 100
- 80.00 Set post 4 ft. long & 4 ins.  
 square 24 ins. in the ground  
 for cor to Secs. 4-5-8+9 marked  
 T. 2 S. S. H. on N. E.  
 R. 34 E. S. 9. on S. E.  
 S. 8. on S. W. and  
 S. 5. on N. W. faces  
 with 5 notches on S. and 4 on  
 East. Edges from which

Subdivision of T. 2 South R. 34 East

Willamette Meridian, Oregon.

A fir 16 ins. diam. bears N. 55° E.

15 lks. dist. marked

Q. 2. S. <sup>R. 34 E.</sup> S. 4. B. D.

A fir 10 ins. diam. bears S. 55° E.

65 lks. dist. marked

S. 2 S. R. 34. E. S. 9. B. D.

A fir 10 ins. diam. bears

S. 89° W. 5 lks. dist. marked

S. 2 S. R. 34 E. S. 8 B. D. and

A pine 10 ins. diam. bears

N. 68° W. 18 lks. dist. marked

S. 2 S. R. 34 E. S. 5 B. D.

Land mountainous & brushy in

last 40 chs. Soil 3<sup>rd</sup> rate

Bunch grass good

East On Random bet. Secs. 4 & 9

va. 20° East.

40.00 Set temp. <sup>1/4</sup> Sec. Cor.

79.90 Intersect <sup>N. S.</sup> line 12 lks. N. of Cor.

to Secs. 3-4-9 & 10 thence N.

Subdivisions of T. 2 South R. 34 East  
 Willamette Meridian, Oregon.

(8093-10 M.)

	89° 55' W. On true line Va. 17° 30' East.	
	Descend	
1500	Canon <sup>W</sup> of dry bed of creek - 1000	
	Ascend	
3500	Top of ridge N. E.	
39.95	Det. Stone 7x8x9 ins. 8 ins. in the ground for $\frac{1}{4}$ Sec. corner marked $\frac{1}{4}$ on N. face, over which I raised a mound of Stone 18 ins. high with $3\frac{1}{2}$ ft. base	
4500	Canon N. E. - 100	
4800	Top of ridge + 100	
68.00	Canon N. W. - 600	
	Ascend	
79.90	Go cor. to Secs. 4-5-849	
	Land extremely mountainous 79.90 ds Some brush and scattering fine timber. Soil 2 <sup>nd</sup> rate July 19 <sup>th</sup> 1887.	

## Subdivisions of T. 2 South R. 34 East.

Willamette Meridian, Oregon.

	North on true line bet. Secs. 4 & 5		
	Wa 20° East.		
15.00	Creek 10 kcs. wide N.E.	-	1000
	Ascend		
25.00	Bluff of Rock	+	100
40.00	Set Stone 12 X 12 X 8 ins. 8 ins. in		
	the ground for $\frac{1}{4}$ Sec. Co. marked		
	$\frac{1}{4}$ on N. face. Over which		
	I raised a mound of stone		
	18 ins. high with $3\frac{1}{2}$ ft. base		
	On East side of hill	+	900
55.00	Top of mountain	+	1000
	Descend		
70.00	Canyon East	-	600
78.00	Intersect Township line 3.95 chs.		
	N. of Cor. to Secs. 32 & 33 T. 1 S.		
	R. 34 E.		
	Set a post 4 ft. long $\frac{1}{4}$ in.		
	square 24 ins in the ground		
	for closing Cor. to Secs 4 & 5 marked		
	T. 2 S. R. 34 E on S.		

44464

Subdivision of T. 2 South R. 34 East

Willamette Meridian, Oregon.

(8093-10 M.)

S. H. on E and

S. 5 on N. faces with  
H notches on E. and 2 on W.

Edges from which

A fir 10 ins diam. bears S. 5° E

8 2 lks. dist marked S. 2. S. R. 34.

E. S. H. C. C. B. D.

A Tamarack 12 ins diam bears

S. 35° W. 80 lks. dist. marked

S. 2. S. R. 34. E. C. C. S. 5. B. D.

Land very rough <sup>78.0000</sup> and mountainous

Pine fir and Tamarack timber

Soil 3rd rate

Post on true line bet. Secs 29 + 32

Na. 18° 45' E.

40.00

Set post 3 ft. long + 4 ins. square

4 ins in the ground for 1/4 sec.

Cor. marked 1/4 S. on N. face

from which.

A Tamarack 10 ins diam. bears

Subdivisions of T. 2 South R. 34 East  
 Willamette Meridian, Oregon.

N. 37 lks. dist. marked  $\frac{1}{4}$  S. B.  $\text{\textcircled{D}}$ .  
 A Tamarack 10 ins. diam. bears  
 S.  $48^{\circ}$  E. 10 lks. dist. marked  $\frac{1}{4}$  S. B.  $\text{\textcircled{D}}$ .  
 66.00 Jennings Creek N. E. - 100  
 69.00 Wood Road N. E.  
 74.50 Prairie + 50  
 80.00 Det. Frost 4 ft long 4 ins square 2 1/2 ins.  
 in the ground for. bor. to  
 Secs. 29-30-31 & 32 marked  
 $\text{\textcircled{D}}$ . 2 S. S. 29 on N E  
 R. 34. E. S. 32 on S. E.  
 S. 31. on S. W. and  
 S. 30. on N. W. faces with  
 5 notches on E and 1 on S. Edges  
 Around which I raised a  
 mound of stone 2 ft high  
 with 4 1/2 ft. base  
 Land rolling covered with  
 fine fir Tamarack and Spruce  
 timber and brush.  
 Soil 3<sup>d</sup> rate rocky



Subdivisions of T. 2 South R. 34 East.

Willamette Meridian, Oregon.

(8093-10 M.)

South on true line bet Secs. 31 + 32

On.  $19^{\circ}15'$  East

5.00 Enter timber & Road N.W.

25.35 Jennings Creek N.E.

40.00 Set post. 3 ft. long & 3 ins.

square 24 ins. in. the ground

for  $\frac{1}{4}$  sec. Cor. marked  $\frac{1}{4}$  S. on

N. face from which

A pine 20 ins. diam. bears N.  $55^{\circ}$

N. 46 lks. dist. marked  $\frac{1}{4}$  S. B. D.

A pine 24 ins. diam. bears S.  $67^{\circ}$  E.

24 lks. dist. marked  $\frac{1}{4}$  S. B. D.

50.27 Intersect U.R. bdy. 5.80 chs. West

of  $\frac{1}{2}$  mile cor. in  $67^{\frac{1}{2}}$  mile

Set post 4 ft. long & 4 ins. square

24 ins. in the ground for closing

cor. to Secs. 31 + 32 marked

D. 2 S. R. 34. E on N

S. 32 on E and

S. 31 on N. faces, from which

A pine 36 ins. diam. bears S.  $67^{\circ}$  E.

Subdivisions of T. 2 South R. 34 East.  
Willamette Meridian, Oregon.

N. 45° E. 121 kcs. dist. marked

D. 2. S. R. 34. E. S. 3. 2. C. C. B. D.

A pine 8 ins. diam. bears. N 57° W.

77 kcs dist. marked

D. 2. S. R. 34. E. S. 3. 1. C. C. B. D.

Land rolling Good timber. Pine  
Samarack and fir.

Soil 3rd rate + Rocky.

West on true line bet. Secs. 30 + 31

va. 19° 15' East.

508 Wagon Road N.E.

40.00 Det. post 3 ft long + 3 ins square

24 ins in the ground for 1/4 sec.

Cor. marked 1/4 S. on N. face

from which A pine 6 ins.

diam. bears. N 43° W. 22 kcs.

dist. marked 1/4 S. B. D. and

A pine 8 ins. diam. bears. S.

13 kcs. dist. marked 1/4 S. B. D.

Subdivision of T. 2 South R. 34 East.  
Willamette Meridian, Oregon.

(8093-10 M.)

42.20

Wagon Road N.W.

45.00

Creek 10 lks. wide N.E.

66.50

" " " " S.E.

75.00

Wagon Road N.E. + S.W.

79.20

Intersect West bdy. 294 chs.

N. of cor. to Secs. 25 + 36 @ 2 S.

R. 33. E. and

Set a post 4 ft. long + 4 ins.

square 24 ins. in. The ground

for closing cor. to Secs. 30 + 31

marked C.C. @ 2 S. R. 34 E

on N.

S. 30. on N and

S. 31 on S. faces with

5 notches on N. and 1 on S. edges

from which a fir 20 ins.

diam. bears N. 30° W. 21 lks. dist.

marked C.C. B.D. and

A fir 36 ins. diam. bears S. 57° E.

42 lks. dist marked C.C. @ 2 S.

R. 34. E. S. 31. B.D.

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

Land rolling. Pine and fir  
timber Some grass. Soil 3<sup>rd</sup> rate

North bet. Secs. 29 + 30  
Wa.  $19^{\circ} 15'$  East.

- 20.22 Wagon Road N. E.  
34.00 Enter timber E + W.  
40.00 Set a post 3 ft. long + 3 ins.  
square 24 ins. in the ground for  
 $\frac{1}{4}$  Sec. cor. marked  $\frac{1}{4}$  S. on N. face  
from which a line 8 ins.  
diam. bears N.  $79^{\circ}$  W. 19 lks dist.  
marked  $\frac{1}{4}$  S. B. D. and  
a line 8 ins. diam. bears S.  $30^{\circ}$  E.  
11 lks. dist. marked  $\frac{1}{4}$  S. B. D.  
40.75 Spring flows. W.  
45.50 Wagon Road E + W.  
47.00 Spring Branch 5 lks. wide E,  
53.65 Road N. E.  
65.25 Wagon Road E + W.

50

470

Subdivisions of T. 2 South R. 34 East.  
Willamette Meridian, Oregon.

(8093-10 M.)

- 73.50 Birch Creek Road E + W.
- 74.15 Daly Wagon " on ridge E + W.
- 80.00 Set Stone 6 X 10 X 12 ins. 8 ins. in  
the ground for cor. to secs.  
19-20-29 + 30 marked with  
5 notches on E. and 2 on S. edges  
over which I raised a mound  
of stone 2 ft. high with  
4½ ft. base.  
Land rolling Pine fir and  
Tamarack timber and under-  
brush with small openings  
Soil 3rd Rate
- East On Random Bet. secs. 20 + 29  
Pa. 19° 30' East.
- 40.00 Set temp. ¼ Sec. cor.
- 79.35 Intersect N. + S line at cor. to secs.  
20-21-28 + 29.  
Thence N. on true line
- 2.80 Jennings Creek N. E.

Subdivisions of T. 2 South R. 34 East.  
Willamette Meridian, Oregon.

7.50	Wagon Road N.E.		
39.67	Set Basalt Stone 6x12x18 ins. 12 ins. in the ground for $\frac{1}{4}$ Sec. Cor. marked $\frac{1}{4}$ on N. face Over which I raised a mound of Stone 18 ins. high with $3\frac{1}{2}$ ft. base.		
68.50	Ravine	S.	20
72.50	"	"	30
79.35	To Cor. to Secs. 19-20-29 & 30 Land rolling. Scattering pine timber. Soil Rocky & 3rd rate		
	West on line bet. Secs. 19 & 30 Pa. 20° East		
35.70	Wagon Road to Pilot Rock N.W.		
36.00	Gulch	S. W.	
38.00	"	"	
40.00	Set Basalt Stone 7x8x10 ins.		

52472

Subdivisions of T. 2 South R. 34 East.

Willamette Meridian, Oregon.

(8093-10 M.)

6 ins in the ground for  $\frac{1}{4}$  Sec.  
Cor. marked  $\frac{1}{4}$  on N. face  
Over which I raised a mound  
of Stone 1.8 ins. high with  $3\frac{1}{2}$  ft.  
base.

44.75 Pilot Rock Wagon Road S. W.  
Ascend hill

79.25 Intersect Township Line and  
M. R. by 3.65 chs. N. of cor.  
to Secs. 24 + 25 T. 2 S. R. 33 E.  
Set a Stone 7x9x12 ins. 8 ins. in  
the ground for closing cor. to  
Secs. 19 + 30 marked M. R. C. C.  
on E. face with 4 notches on the  
N. and 2 on S. edges. Around  
which I erected a mound of  
Stone 2 ft. high with  $4\frac{1}{2}$  ft. base.  
Land rolling & broken  
Pine & fir timber first  $\frac{1}{2}$  mile  
Soil Rocky and 3<sup>rd</sup> rate.

Subdivisions of T. 2 South R. 34 East.  
Willamette Meridian, Oregon.

North on @rue Line Bet. Secs. 19 + 20

Na. 19° 30' East.

13.00 Gulch E — 100

40.00 Set Stone 6x10x12 ins. 8 ins. in  
the ground for  $\frac{1}{4}$  Sec. cor. marked  
 $\frac{1}{4}$  on N. face. Around  
which I raised a mound of  
Stone 18 ins. high with 3 $\frac{1}{2}$  ft.  
base.

51.60 Wagon Road E + W.

55.20 Gulch E — 30.

71.50 Road E + W.

80.00 Set. Post 4 ft. long 4 ins.  
square 24 ins. in the ground for  
cor. to Secs. 17-18-19 + 20 marked  
D. 2. S. S. 17 on N.E.

R. 34. E. S. 20 on S.E.

S. 19. on S. W. and

S. 18. on N. W. faces with  
5 notches on E and 3 on S. edges.  
From which a line 10 ins.



54 474

Subdivisions of T. 2 South R. 34 East.

Willamette Meridian, Oregon.

(8093-10 M.)

diam. bears N. 45° E. 107 lks.

R 34 E.

dist. marked. T. 2 S. 17. B. D.

A pine 24 ins. diam. bears S. 67° E.

64 lks. dist. marked T. 2 S.

R. 34. E. S. 20. B. D.

A pine 20 ins diam. bears S. 40° W.

T. 2 S R 34 E.

62 lks. dist marked S. 19. B. D.

A pine 20 ins. diam. bears N. 45° W.

T. 2 S R 34 E.

110 lks. dist. marked S. 18.

B. D.

Land mostly open prairie.

Scattering pine timber.

Bunch grass. Soil 4<sup>th</sup> rate rocky

East on Random bet. Secs. 17 & 20

Pa. 20° East.

4000 Set temp. 1/4 Sec. lev.

79.25 Intersect N. S. line at lev. to sec.

16-17-20 & 21. Thence West on

true line. Pa. 18° 30' East.

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

14.50 Head of canon N. E.  
 29.50 " " " "  
 39.62 Set post 3 ft. long & 3 ins. square  
 24 ins. in. the ground for  $\frac{1}{4}$  Sec. cor.  
 marked  $\frac{1}{4}$  S. on N face from which  
 A fir 5 ins. diam bears N. 15 lks  
 dist. marked  $\frac{1}{4}$  S. B. D. and  
 A fir 8 ins. diam. bears S. 40° W.  
 19 lks. dist. marked  $\frac{1}{4}$  S. B. D.

67.50 Enter timber N. E.

79.25 Do cor. to Secs. 17-18-19 & 20  
 Land rolling. Soil 3<sup>rd</sup> rate  
 Pine and fir timber in canon.

July 20, 1887

West on true line bet. Secs. 18 & 19  
 Va. 20° East.

40.00 Set Stone 6x8x14 ins. 8 ins. in  
 the ground for  $\frac{1}{4}$  Sec. cor. marked  
 $\frac{1}{4}$  on N. face around  
 which I erected a mound of stone 18 ins.

## Subdivisions of T. 2 South R. 34 East

Willamette Meridian, Oregon.

(8093-10 M.)

- high with  $3\frac{1}{2}$  ft. base along side  
 51.60 gulch 2.00 chs. South of Spring <sup>George J.</sup>  
 65.10 Wagon Road N.W.  
 79.20 Intersect- Township line and  
 M.R. Bdy. 3.83 chs. N. of cor. to  
 Secs. 13 + 24 T. 2 S. R. 33 E. and  
 set a stone 12 x 14 x 16 ins. 10 ins. in  
 the ground for closing cor.  
 to Secs. 18 + 19. marked C.O.M.R.  
 on N face with 3 notches on  
 N. and S. edges. Around which  
 I raised a mound of stone  
 2 ft. high with  $4\frac{1}{2}$  ft. base  
 Land rolling and mostly  
 prairie.  
 Some bunch grass.  
 Soil 3<sup>rd</sup> Rate

Subdivisions of T. 2 South R. 34 East <sup>477</sup>  
 Willamette Meridian, Oregon.

	North on true line bet. Secs. 17+18 Pa. 20° East.	
15.00	Leave timber and Enter Prairie E. End N.	
25.00	Enter timber	
31.10	Canyon N.E.	
40.00	Set Post 3 ft. long and 3 ins. square 24 ins. in the ground for $\frac{1}{4}$ Sec. Cor. marked $\frac{1}{4}$ S. on N. face from which A pine 8 ins. diam. bears. N 40° W. 10 lks. dist. marked $\frac{1}{4}$ S. B.D. A fir 12 ins. diam. bears. S. 75° E. 21 lks. dist. marked $\frac{1}{4}$ S. B.D.	
45.00	Canyon N.E.	50
60.00	Summit of ridge N.E.	
73.00	Begin to descend.	

## Subdivisions of T. 2 South R. 34 East.

Willamette Meridian, Oregon.

(8093-10 M.)

80.00

Set Stone  $18 \times 18 \times 18$  ins. 12 ins.  
in the ground for cor. to  
Secs. 7-8-17+18 marked with  
5 notches on E. <sup>4<sup>ow</sup></sup> Ed. & S. Edges.  
from which a fir 20 ins.  
diam. bears S.  $45^\circ$  W. 5 lks. dist.  
marked T. 2. S. R. 34. E. S. 18. B. D.

No other trees within limits

Raised a mound of Stone  
2 ft. high with  $4\frac{1}{2}$  ft. base  
around cor.

Land Broken Soil 4<sup>th</sup> rate  
Pine and fir timber on  
first  $\frac{1}{2}$  mile. Some bunch grass.

East on Random bet.

Secs. 8+17.

Wa.  $20^\circ$  East.

40.00

Set temp.  $\frac{1}{4}$  Sec. cor.

79.60

Intersect N. & S. by line at cor.

Subdivisions of T. 2 South R. 34 East.  
Willamette Meridian, Oregon.

to Secs. 8-9-16+17.

Thence West on true line  
Wa. 20° East

700	barrow	at	-	300
39.80	Set Stone 8x10x10 ins. 6 ins.			
	in the ground for $\frac{1}{4}$ Sec. Cor.			
	marked $\frac{1}{4}$ on N. face			
	over which I raised			
	a mound of Stone			
	18 ins. high with 3 $\frac{1}{2}$ ft. base	alongside		
65.00	barrow	at	-	6.00
76.00	Top of ridge	at	+	2.00
79.60	Do bar to Secs. 7-8-17+18			

Land Mountainous 7960 chs  
some bunch grass.

Soil 4<sup>th</sup> Rate and Rocky

Subdivisions of T. 2 South R. 34 East.  
Willamette Meridian, Oregon.

(8093-10 M.)

- West on true line bet. 7+18  
Pa. 20° East.
- 400 Point of High rock N. + 80
- 18.65 Bed of creek water in holes - 700
- 40.00 Set Basalt Stone 12x12x16  
ins. 10 ins. in the ground  
for "4 Sec. cor. marked 4.  
on N. face. Over which  
I erected a mound of  
Stone 18 ins. high with  
3½ ft. base + 800
- 56.25 Gulch D. - 200
- 79.00 Intersect Township line  
4.00 chs. N. of Cor. to Sec. 12+13  
D. 2. S. R. 33. E. and  
Set Stone 12x18x18 ins. 12 ins.  
in the ground for closing  
cor. to Sec. 7+18 marked U.R.  
C.C. on E. face with 4 notches  
on S. and 2 on N. edges.  
Over which I raised a.

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

Mound of Stone 2 ft. high  
with 4½ ft. base  
Sand <sup>79. chs</sup>mountainous, Soil 3<sup>rd</sup> rate  
Timber in canon  
Accessable only at head  
of canon. Some bunch grass.

North on true line bet.  
Secs. 7 & 8.

Ca. 20° East.

27.00	Canon	N.E.	-	500
40.00	Set Stone 10 x 12 x 20 ins. 1/4 ins. in the ground for 1/4 Sec. cor. marked 1/4 on N. face around which I raised a mound of Stone 18 ins. high with 3½ ft. base +			300
44.55	Gulch	E	-	200
63.15	"	"	-	75
68.00	Summit of ridge or point	E	+	400



62482

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

(8093-10 M.)

- 72.40 Canon E - 200
- 80.00 Set Stone 16x18x18 ins.  
12 ins. in the ground for  
cor. to Secs. 5-6-7+8 marked  
with 5 notches on S. & E.  
edges over which I  
raised a mound of  
stone 2 ft. high with  
4 1/2 ft. base  
Land broken and mountainous  
So. chs Soil 4th Rate.  
Some bunch grass.
- East on Random bet 5+8  
Va. 18° 30' East.
- 40.00 Set temp. 1/4 Sec. cor.
- 79.30 Intersect N. S. line at cor.  
to Secs. 4-5-8+9  
Thence N. on true line  
Va. 20° East
- 21.00 Gulch N. - 100

Subdivisions of T. 2 South R. 34 East.  
Willamette Meridian, Oregon.

36.00 Canion N.E. — 400

39.65 Set a Stone 12x14x18 ins. 12 ins  
in the ground for  $\frac{1}{4}$  Sec.  
Cor. marked  $\frac{1}{4}$  on N. face  
over which I raised  
a mound of Stone  
18 ins. high with  $3\frac{1}{2}$  ft.  
base diameter

56.00 Gulch S. — 20

79.30 Do Cor. to Secs. 5-6-7+8

Land mountainous  
and rough 79.30 chs

Some bunch grass

Soil poor. 4<sup>th</sup> rate

64484

Subdivision of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

(8093-10 M.)

Set on true line bet. Secs. 6 & 7  
Cva.  $18^{\circ} 30'$  East.

40.00 Set Stone  $10 \times 12 \times 14$  ins.  
10 ins. in the ground  
for  $\frac{1}{4}$  Sec. cor. marked  
 $\frac{1}{4}$  on N. face from which  
a line 36 ins. diam. bears  
N.  $75^{\circ}$  E. 61 lks. dist. marked  
 $\frac{1}{4}$  S. B. D.

A line 6 ins. diam. bears  
S.  $50^{\circ}$  N. 75 lks. dist. marked  
 $\frac{1}{4}$  S. B. D. And raised a  
mound of Stone 18 ins.

high with  $3\frac{1}{2}$  ft. base along it

50.00 Summit N. + 100

61.50 Canon N. - 300

7900 Intersect Township line and

~~the~~ 4.00 qrs. N. of cor.

to Secs. 1 & 2 S. R. 33 E.

And set a Stone  $7 \times 8 \times 9$  ins  
6 ins. in the ground

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

For clearing loc. to Secs. 6 & 7  
marked C. C. U. R. on E. face  
with 5 notches on S. and 1 on  
N. edges. Over which  
I raised a mound  
of stone 2 ft. high with  
4½ ft. base

Land mountingy 39.00 lbs  
Timber in beams.

Some good bunch  
grass.  
Soil 4th rate and rocky.

North Bet. Secs. 5 and 6  
Pa. 19° 30' East.

8.10	Trail on Summit N.E. +	80
15.00	Descend	
28.00	Head of Gulch N. -	20
40.00	Set a Basalt Stone 4x12x14 ins.	

66

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

(8093-10 M.)

8 ins in the ground  
for <sup>1</sup>/<sub>4</sub> Sec. <sup>1</sup>/<sub>4</sub> marked  
<sup>1</sup>/<sub>4</sub> D. on W. face - 400  
Over which I raised  
a mound of Stone  
18 ins. high with 3 1/2 ft.  
base

73.00  
76.93

Rock Joint W. + 20  
Intersect Township  
line 355 chs. W. of cor.  
to Secs. 31 & 32 T. 1. S. R. 34. E.  
and set a Basalt Stone  
8 x 10 x 16 ins. <sup>10 ins</sup> in the ground  
for closing cor. to Secs.  
5 & 6 marked C. C. on S.  
face with 5 notches on  
E. and 1 on W. edges - 400  
from which I raised  
A line 12 ins diam. by  
S. 23° W. 25 chs. dist. marked  
T. 2. S. R. 34 E. C. C. S. C. B. D.

487

Subdivisions of T. 2 South R. 34 East  
Willamette Meridian, Oregon.

No other trees within limits

Raised a mound of stone 2 ft.  
high with 4 1/2 ft. base  
around cor. along

Land <sup>mountainous</sup> mountainous 40.00 chs.

Good bunch grass

No timber Soil 3rd rate  
July 20th 1887.

General Description

This township is rolling  
in the south portion very  
rough + mountainous in the  
north - Good Pine + Tamarack  
timber also good bunch grass  
Soil 1st + 4th rate.

That portion of the Township not  
subdivided is a nest of impassable  
canyons, making it impossible to survey  
the same within limits allowed, and  
the lands are comparatively worthless  
The timber in this sec. is poor and scat-  
tering and of no value on account  
of its inaccessability

In accordance  
with the requirements of  
the manual of surveys  
we have carefully tested  
the adjustment of our  
instruments by taking  
the latitude daily wea-  
ther permitting during  
the progress of the  
surveys represented  
by the foregoing field  
notes and in all cases  
the instruments were found  
to be in correct adjust-  
ment. James P. Currier  
James E. Toland  
U. S. Rept. Surveyors

# FINAL OATHS FOR SURVEYS.

A list of the names of the individuals employed by Jas. P. Currier  
and Jas. E. Noland, U. S. Deputy Surveyor, to assist in  
running, measuring, and marking the lines and corners described in the  
foregoing field notes of the survey of the Subdivisional  
lines of Township 2 South  
R. 34. East Willamette Meridian, Oregon,  
showing the respective capacities in which they acted:

L. J. Wooley, Compassman.  
J. S. Medley, Chainman.  
W. H. Medley, Chainman.  
Frank Belshaw, Chainman.  
Guy Davis, Chainman.  
B. B. Brewer, Axman.  
H. Beach, Axman.  
\_\_\_\_\_, Flagman.

## FINAL OATHS OF ASSISTANTS.

We hereby certify that we assisted Jas. P. Currier and  
Jas. E. Noland, U. S. Deputy Surveyor, in surveying  
all those parts or portions of the Subdivisional  
Lines of Township 2  
South Range 34 East Willamette Meridian, Oregon,  
as represented in the foregoing field notes as having been surveyed by  
him and under his direction; and that said survey has been in all respects,  
to the best of our knowledge and belief, well and faithfully surveyed,  
and the corner monuments established, according to the instructions  
furnished by the U. S. Surveyor General of Oregon.

L. J. Wooley, Compassman.  
J. S. Medley, Chainman.  
W. H. Medley, Chainman.  
Frank Belshaw, Chainman.  
Guy Davis, Chainman.  
B. B. Brewer, Axman.  
H. Beach, Axman.  
\_\_\_\_\_, Flagman.

Subscribed and sworn to before me this 21st day of  
July, 1887.

[SEAL.]

James P. Currier  
U. S. Deputy Surveyor.



FINAL OATH OF DEPUTY SURVEYOR.

I, James P. Currier & James E. Toland, United States

Deputy Surveyor, do solemnly swear that in pursuance of instructions received from Douglas W. Taylor, U. S.

Surveyor General for Oregon, bearing date of the 13<sup>th</sup>

day of May, 1887, I have well, faithfully,

and truly, in my own proper person, and in strict conformity with the instructions furnished by the U. S. Surveyor General for Oregon, the Surveying Manual, and the laws of the United States, surveying all

those parts or portions of Townships 2 S

Range 34 East

Willamette Meridian, in the State of Oregon, as are represented in the foregoing field notes as having been surveyed by me and under my directions; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Surveying Manual, printed instructions, the special written instructions of the U. S. Surveyor General for Oregon, and in the specific manner described in the field notes, and that the foregoing are the true field notes of such survey, and should any fraud be detected I will suffer the penalty of perjury under the provisions of an act of Congress approved August 8, 1846.

James P. Currier & James E. Toland  
U. S. Deputy Surveyors

Subscribed and sworn to before me this Fifteenth

day of February, 1888

A. L. Woodcock  
Notary Public  
for Oregon

500

Office of U. S. Surveyor General,

Portland, Oregon, June 28<sup>th</sup>, 1888

The <sup>foregoing</sup> following Field Notes of the Survey of the

Subdivisional lines of Township  
2 South Range 34 East

Willamette Meridian Oregon

executed by Jas. P. Carrin and Jas. E. Noland  
Special Joint U. S. Deputy Surveyors.  
under his Contract No. \_\_\_\_\_, dated May

4<sup>th</sup>, 1887, having been critically examined,  
the necessary corrections and explanations made, the  
said Field Notes and the survey they describe, are  
hereby approved.

Douglas W. Taylor -  
Surveyor General.