

## FIELD NOTES

*Be*  
Of the survey of the Subdivision

Lines of T. 2 + 3 North Range

32 - 33 & 34, East Willamette Meridian,

Oregon, as surveyed by Jas. P. Lurkin & Jas. E. Roland

U. S. Deputy Surveyor, under his Contract No.

dated May 4 - 1887.

Survey commenced, April 26th 1889.

Survey completed, May 1st 1890.

### NAMES AND DUTIES OF ASSISTANTS.

, Compassman.

J. J. Beck, , Chainman.

Wm. Marberger, , Chainman.

, Chainman.

, Chainman.

, Axeman.

, Axeman.

, Flagman.

## PRELIMINARY OATHS OF ASSISTANTS.

We, *James T. Beeck and  
William Marburger*,

do solemnly swear that we will faithfully execute the duties of Chain Carriers; that we will level the chain over even and uneven ground, and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we will assist in measuring, to the best of our skill and ability, and in accordance with the instructions given us in

the survey of the *Subdivisional*  
*lines of T. 24 S. R.*

*Rps 32-33 & 34 E* Willamette Meridian, Oregon

*James T. Beeck*, Chainman.  
*William Marburger*, Chainman.

, Chainman.

, Chainman.

Subscribed and sworn to before me, this

day of *18 April 1890*

[SEAL.]

*Harrison  
Notary Public pro. Dr.*

We, ----- and -----

do solemnly swear that we will well and truly perform the duties of Axemen in the establishment of corners and other duties, according to instructions given us, and to the best of our

skill and ability, in the survey of the -----

Willamette Meridian, Oregon.

, Axeman.

, Axeman.

Subscribed and sworn to before me, this

day of ----- 18 -----

[SEAL.]

# INDEX

Referring the Lines to the Pages of the Field Notes.

T.	R.	Will. Mer.
----	----	------------

6	5	4	3	2	1	
7	8	9	10	11	12	
18	17	16	15	14	13	
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

*Meanders of..... Pages..... to.....*

*Meanders of..... Pages..... to.....*

Before beginning the resurvey  
as set forth in these <sup>filled</sup> notes. I  
tested my compass, which  
is a Burt Solar compass,  
on a meridian previously  
established by an observation  
on the star Polaris and find  
it to be correct and during  
the progress of the work  
took latitudes at noon  
the weather permitting.

April 26th 1890.

Resurvey 357 13

Subdivision of T. 3 North R. 34 East.

Willamette Meridian, Oregon.

From Cor. secs. 10-11-14 & 15, which  
is a charred stake with pit  
in each sec  $5\frac{1}{2}$  ft dist. almost  
fall but conspicuous. Stake  
rotted off but marked S. 11 J

T. 3 N. on R. E. S. 14, R. 34 E. on S. E. S. 15 -  
~~(with 4 notches on S and 2 on E edges - Reset stake in S. E. pit  
on S. W. & S. 19 on N. W. faces)~~

mostly gone. Thence  
East between secs. 11 & 14,

Mar. 21<sup>st</sup> East.

Passing through plowed field  
I find that  $\frac{1}{16} - \frac{1}{4} + \frac{1}{16}$  corners  
are gone and at

S. 80.18 intersect E. bdy at cor to secs

11-12-13 & 14. Earth md. scattered  
with pits in each sec  $5\frac{1}{2}$  ft dist  
fall. Post broken off. & lying  
nearby. Marked S. 12. J. 3 N on  
N.E. S. 13, R. 34, E on S.E. S. 14 on S.W.  
S. 11. on N.W. faces no notches I cut 1  
notch on E & 4 on S. edges.

14

358

## Resurvey

Subdivisions of T. 3 North R. 34 East.

Willamette Meridian, Oregon.

(8003-10 M.)

and reset post in center of mound  
 Land rolling & all in  
 cultivation.  
 Soil 1st rate.

Iron cor. sees 3-4-9 & 10  
 which is a post, <sup>1/4 ft long 4 ins square</sup> marked  
 S. S. J. 3. N. on S. E. S. 10. R. 34. E. on  
 S.E. S. 9. on S. W. S. 4 on N. W.  
 faces. I cut <sup>3</sup> notches 8 on E & 5  
 on S. edges. The post being  
 pulled out of mud. I  
 reset it. fits in each  
 see partly filled.  
 I ran thence  
 N 89° 54' W. between sees 4 & 9,  
 Var. 20° East

6.00	Pend. & Athena Road course N. E. <sup>SW.</sup>
9.50	P & W. R. R. " " "
18.25	To Melander Cor. <sup>stone 14x10x8</sup> marked H. R. m. 6 on E face.

Resurvey

359<sup>15</sup>

Subdivisions of T. 3 North R. 34 East.

Willamette Meridian, Oregon.

with Pit & Mrs. E. and partly  
washed away. Stands set  
firmly in ground.

1875 Wild Horse creek new channel, <sup>copse</sup> S.W.

1870 " " " Old " "

40.10 To Old to sec cor.

Land E of creek level &  
soil retentive.

W of creek rolling &  
inolative.

May 1st 1890.

## FINAL OATHS FOR SURVEYS.

A list of the names of the individuals employed by *James P. Lennin*  
*and Jas. E. Holand*, U. S. Deputy Surveyor, to assist in  
running, measuring and marking the lines and corners described in the foregoing  
field notes of the survey of the *Subdivisional*  
lines of *Rs 2 & 3 N.*  
*Rs 32-33 & 34 E.* Williamette Meridian, Oregon,  
showing the respective capacities in which they acted:

<i>J. J. Beck</i>	, Compassman.
<i>John Marburger</i>	, Chainman.
	, Axeman.
	, Axeman.
	, Flagman.

## FINAL OATHS OF ASSISTANTS.

We hereby certify that we assisted *James P. Lennin*  
*James E. Holand*, U. S. Deputy Surveyors in surveying all  
those parts or portions of the *Subdivisional*  
lines of *Rs 2 & 3 North*  
*Rs 32-33 & 34 East*. Williamette Meridian, Oregon.  
This *as are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the U. S. Surveyor General of Oregon.*

<i>James J. Beck</i>	, Compassman.
<i>John Marburger</i>	, Chainman.
	, Chainman.
	, Chainman.
	, Axeman.
	, Axeman.
	, Flagman.

Subscribed and sworn to before me, this *First* day of

*May*

*1890*

[SEAL.]

*Eliza F. Barry Notary Public  
for Oregon.*

## FINAL OATH OF DEPUTY SURVEYOR.

*We James P. Currier and James E. Noland*  
 United States Deputy Surveyors do solemnly swear that in pursuance of  
 instructions received from *Douglas W. Taylor*

U. S. Surveyor General for Oregon, bearing date of *15<sup>th</sup>*

day of *April* <sup>1890</sup>, we have well, faithfully and truly, in my <sup>own</sup> proper persons and in strict conformity with the instructions furnished by the U. S. Surveyor General for Oregon, the Surveying Manual, and the laws of the United States, surveying all those parts or portions of *Subdivisional lines*

*of T 2 + 3 N. R 32 - 33 & 34 E.*

Willamette Meridian, in the State of Oregon, as are represented in the foregoing field notes as having been surveyed by <sup>us</sup> me and under <sup>our</sup> my directions; and we do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Surveying Manual, printed instructions, the special written instructions of the U. S. Surveyor General for Oregon, and in the specific manner described in the field notes, and that the foregoing are the *true* field notes of such survey, and should any fraud be detected we will suffer the penalty of perjury under the provisions of an Act of Congress approved August 8, 1846.

*James P. Currier.  
James E. Noland*

U. S. Deputy Surveyors

Subscribed and sworn to before me, this *6<sup>th</sup>*  
 day of *May* <sup>1890</sup>

*Herman Baumerhoer*  
*Notary Public*  
*for Oregon*

## Office U. S. Surveyor General,

Portland, Oregon.

June 4<sup>th</sup> 1890

Re-  
The foregoing Field Notes of the Survey of the part of the  
Subdivisional lines of Sec 2 & 3 N.  
Ranges 32-33 and 34 East  
Willamette Meridian Oregon

executed by James J. Curran & James C. Noland  
Special U. S. Dept Surveyors  
under his contract No. dated May

4<sup>th</sup> 1887 having been critically examined, the  
necessary corrections and explanations made, the said Field  
Notes and the survey they describe, are hereby approved.

Douglas W. Taylor  
Surveyor General.