

FIELD NOTES

583

Of the survey of the Subdivisional & Allotment

Lines of T. 3. N. R. 36 E

Willamette Meridian,

Oregon, as surveyed by James P. Currier

U. S. Deputy Surveyor, under his Contract No. 537

dated March 5th 1889

Survey commenced, June 7th 1889

Survey completed, June 8th 1889

NAMES AND DUTIES OF ASSISTANTS.

....., Compassman.

....., Chainman.

....., Chainman.

J. B. Laramore, Chainman.

J. L. Brown, Chainman.

Wm. Stone, Axeman.

R. E. Long, Axeman.

....., Flagman.

PRELIMINARY OATHS OF ASSISTANTS.

We, J. R. Saramore
 & J. L. Brown
 do solemnly swear that we will faithfully execute the duties of Chain Carriers, that we will level the chain over even and uneven ground, and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we will assist in measuring, to the best of our skill and ability, and in accordance with the instructions given us in

the survey of the Subdivisional and
Allotment lines of T. 3 N. R.
36 E. Willamette Meridian, Oregon.

J. R. Saramore, Chainman.
J. L. Brown, Chainman.
 _____, Chainman.
 _____, Chainman.

Subscribed and sworn to before me, this 7th
 day of June, 1889

[SEAL.] Thos Fitz Gerald
Notary Public

We, Esmer Stone and
R. E. Long, do solemnly swear
 that we will well and truly perform the duties of Axemen in the establishment of corners
 and other duties, according to instructions given us, and to the best of our skill and abil-

ity, in the survey of the Subdivisional and
Allotment lines T. 3 N. R. 36 E.
 Willamette Meridian, Oregon.

E. M. Stone, Axeman.
R. E. Long, Axeman.

Subscribed and sworn to before me, this 7th
 day of June, 1889

[SEAL.] Thos Fitz Gerald
Notary Public

INDEX

Referring the Lines to the Pages of the Field Notes.

T. *3 North* R. *36 East* Will. Mer.

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
18	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Handwritten notes in red ink:
 4
 5
 4
 1
 22
 21
 18
 19
 16
 14

Meanders of _____ Pages _____ to _____

Meanders of _____ Pages _____ to _____

Allotment

591

Subdivision of T. 3 North R. 36 East

Willamette Meridian, Oregon.

Sec 18.

From the corner to Secs.
13-18-19 and 24 on W.
bdy of Township which
is a post 4 ins square firmly
set in the ground marked
T. 3 N. T. 13 on N.W.

R. 36. E. T. 18 on N.E.

T. 19 on S.E.

R. 35 E. T. 24 on S.W. ^{faces} with 3
notches on N & S edges

from which

A pin 18 ins dia bor N 8° E

59 lbs marked T. 3 N. R.

36. E. T. 18 B. T.

A pin 36 ins dia bears

S. 65° W. 122 lbs marked R. 35

E. T. 24 B. T. with pits 18 x 18

12 ins in Secs 13 & 19. 5 1/2 ft

dist & mound of earth

along side

2

592

Allotment

Subdivision of T. 3 North R. 36 East

Willamette Meridian, Oregon.

Sec 18

(8093-10 M.)

I run

S 89° 28' E on random
line between Secs. 18 + 19

Var 18° 45' E

Setting temporary corner

at 20.00 chains and at

39.62 Intersect the line at $\frac{1}{4}$
Sec corner between Secs.

18 + 19. which is a basalt
stone 12 + 10 + 8 ins firmly
set in the ground marked
 $\frac{1}{4}$ on N face. and mound
of stone over it.

Then I run

N. 89° 28' W. on true line
between Secs. 18 + 19

same Var

20.00. Set basalt stone 12 + 10 + 7 ins
9 ins in the ground for $\frac{1}{16}$.
Sec corner marked $\frac{1}{16}$ on N.
face

523

Subdivision of T. 3 North R. 36 East

Willamette Meridian, Oregon.

See 18.

from which

A pine 36. ins diam bore S 40° E. 43 lbs
dial marked 1/16 I.B.I.

A pine 40 ins diam bore S 89° E.
63 lbs dial marked 1/16 I.B.I.

31.25 Gulch course I.

39.62 To corner to Secs. 13-18-19.
24.

Land mostly level along
flat Gulch.

Soil 1st rate.

Good grass.

Allotment

594
Subdivision of T. 3 North R. 36 East

Willamette Meridian, Oregon.

Sec 18

(8093-10 M.)

From the $\frac{1}{4}$ Sec corner betw.
Secs 13 & 18 on W. ldy of Sp.
which is a basalt stone
9 x 8 x 7 ins 6. ins in the
ground marked $\frac{1}{4}$ on W.
face from which

A pine 24 ins diam br N 50° E.
22 lbs dist marked $\frac{1}{4}$ S.B.S.

A pine 16. ins diam br S 83° W.
30 lbs marked $\frac{1}{4}$ S.B.S.

I run

South on true line between
Secs. 13 and 18

Var 21° E.

950 Road corner E. & W.
1000 Set basalt stone 9 x 8 x 7 ins
6 ins in the ground for $\frac{1}{32}$ Sec
corner marked $\frac{1}{32}$ on W. face
dug pits 18 x 18 x 12 ins N & S
of stone 5 1/2 ft dist and
raised a mound of

Subdivision of T. 3 North R. 36 East
 Willamette Meridian, Oregon.

See 18

earth $1\frac{1}{2}$ ft high $3\frac{1}{2}$ ft
 base alongside

2000 Set stake 9 + 8 + 7 in 6 in in
 the ground for $\frac{1}{16}$ See corner, marked
 $\frac{1}{32}$ in N.E. &
 $\frac{1}{16}$ in S.E. face; dug pits 18 + 18 + 12
 in N. & S of stake $3\frac{1}{2}$ ft dirt
 raised mound of earth $1\frac{1}{2}$ ft high
 $3\frac{1}{2}$ ft base over it.

Land on Summit of Mt.
 Soil 1st rate, good grain

From the $\frac{1}{32}$ See corner 10 ch
 S. of $\frac{1}{4}$ See corner between
 Secs. 13 + 18.

From
 S 89° 28' E. in tree
 line in See 18.
 Var 21° E.

1500 Enter brush and descend

1925 A pine, 36 in diam which
 I marked
 $\frac{1}{32}$ S. on N. face for $\frac{1}{32}$ See
 corner

Subdivision T. 3 North R. 36 East

Willamette Meridian, Oregon.

Sec 18.

(8093-10 M.)

from which
 a pine 36. ins diam bore N. 45° E.
 63 lbs dist marked $\frac{1}{32}$ I. B. I.
 a fir 25 ins diam bore S 30° W
 54 lbs dist marked $\frac{1}{32}$ I. B. I.
 Thence along steep bank of
 Wild Horse creek. Heavy
 timber & brush

36.09 Canyon corner N.W. - 75
 39.25 Set basalt stone 16 x 12 x 6 ins
 12 ins in the ground for $\frac{1}{32}$
 The corner marked $\frac{1}{32}$ on N.

from which
 a pine 20 ins diam bore North
 44 lbs dist marked $\frac{1}{32}$ I. B. I.
 a pine 40 ins diam bore N 4° W
 44 lbs dist marked $\frac{1}{32}$ I. B. I.
 Land rolling & hilly
 C. 25 chs Heavy timber

Attachment

7.

Subdivision of T. 3 North R. 36 East

Willamette Meridian, Oregon.

See 18

From the $\frac{1}{32}$ Sec corner ^{$\frac{1}{16}$} 20 chs
N. of the corner to Secs 13-18
19 & 24 on W. bdy of Sp.
Down

S 89° 28' E on true line
in Sec 18.

Var 19° 30' East

Along summit through

Sunflowers

19.25 Set basalt stone 18 x 8 x 6 ins
12 ins in the ground for $\frac{1}{16}$
+ $\frac{1}{32}$ Sec corner marked $\frac{1}{16}$ ^{on S.} $\frac{1}{32}$
on N. face dug pits 18 x 18
+ 12 ins E & W of stone 5 $\frac{1}{2}$ ft
dirt and raised a mound of
earth 1 $\frac{1}{2}$ ft high 3 $\frac{1}{2}$ ft low
over it.

Along summit ^{of mountains} through
scattering Pine & Fir.

8 598

Allotment

Subdivision of T. 3 North R. 36 East

Willamette Meridian, Oregon.

See 18.

(8093-10 M.)

3925 Set basalt stone 18 x 8 x 4 in
 14 ins in ground for $\frac{1}{16}$ & $\frac{1}{32}$
 See corner marked $\frac{1}{16}$ ^{on S.} & $\frac{1}{32}$
 on N. face dug pits 18 x 18.
 12 ins E. & W. of stone $5\frac{1}{2}$ ft
 dist and raised a mound
 of earth $1\frac{1}{2}$ ft high $3\frac{1}{2}$ ft
 base over it.

4925 Set basalt stone 14 x 10 x 7
 ins 9 ins in the ground
 for $\frac{1}{32}$ See corner marked $\frac{1}{32}$
 on N. face dug pits 18 x 18 x 12
 ins E. & W. of stone $5\frac{1}{2}$ ft dist.
 & raised a mound of earth $1\frac{1}{2}$ ft
 high $3\frac{1}{2}$ ft base over it.

from which

A pine 36. ins diam low West.

10 lb dist marked $\frac{1}{32}$ S. B. S.

Land rolling somewhat.

Scattered pine timber

Soil ~~is~~ rate. Good grass

Subdivision of T. 3 North R. 36 East
 Willamette Meridian, Oregon.

See 18

From the $\frac{1}{4}$ Sec corner between
 Secs 18 & 19

I run

S 89° 28' E on true line
 between Secs 18 & 19.

Var. 20° 30' E

10.00 Set basalt stone 19 x 8 x 7
 in 6 ins in the ground for
 $\frac{1}{32}$ Sec corner marked $\frac{1}{32}$ on
 N. face dug pits 18 x 18 x 12
 in E & W of stone 5 $\frac{1}{2}$ ft. dist
 and raised a mound of earth
 1 $\frac{1}{2}$ ft high 3 $\frac{1}{2}$ ft base
 over it.

Land rolling across with
 scattering pine timber
 Soil red into
 good grass

Subdivision of T. 3 North R. 36 E.

Willamette Meridian, Oregon.

Sec 18

(8093-10 M.)

From the $\frac{1}{32}$ Sec corner 10 ch
E. of $\frac{1}{4}$ Sec corner between Secs
18 & 19.

I run

North on random line in Sec.
18.

20.00

Intersect the E & W. line at
 $\frac{1}{32}$ Sec. corner 10 ch E & 30 ch
N. of $\frac{1}{4}$ Sec corner between Secs
18 & 19.

Thence I run

South on true line in Sec 18
Var 19° E.

20.00

The $\frac{1}{32}$ Sec corner 40 ch E. of
 $\frac{1}{4}$ Sec corner between Secs 18 & 19

Land rolling
Scattered timber
Good grass

June 7th 1889.

Allotment

11
001

Subdivision of T. 3 North R. 36 East
Willamette Meridian, Oregon.

Sec 19

From the corner to Secs. 13-18
19 and 24. on the West edge
of Township
I run

South on true line between
Secs 19 + 24.

Var $18^{\circ} 45' E$.

1000 Set post 3 ft long 3 ins square
with charred stake 12 ins
in the ground, for $\frac{1}{32}$ Sec
corner marked $\frac{1}{32}$ S on W face
dug pits 18 x 18 x 12 ins N & S
of post 5 $\frac{1}{2}$ ft dia and raised
a mound of earth 1 $\frac{1}{2}$ ft
high 3 $\frac{1}{2}$ ft base around post

2000 Set post 3 ft long 3 ins square
with marked stem 12 ins
in the ground for $\frac{1}{16}$ $\frac{1}{32}$ Sec corner
marked $\frac{1}{32}$ S. on W. face
+ $\frac{1}{16}$ on S. face — — —
dug pits 18 x 18 x 12 ins

602

Subdivision of T. 3 North R. 36. East
Willamette Meridian, Oregon.

See 19

(8093-10 M.)

N. & S. of post 5 1/2 ft dirt
and raised mound of earth
1 1/2 ft high 3 1/2 ft base
around post

3000 Set basalt stone 12 x 10 x 4
ins 8 ins in the ground
for 1/32 See corner marked
1/32 on W face dug pits
18 x 18 x 12 ins N. & S. of stone
5 1/2 ft dirt and raised
mound of earth 1 1/2 ft high
3 1/2 ft base over it.

4000 I line through timber
Intersect the 1/4 See corner
which is a basalt stone
12 x 10 x 8 ins 8 ins in the
ground marked 1/4 on W. face
pits 18 x 18 x 12 ins N. & S. of
stone 5 1/2 ft dirt and mound
of earth 1 1/2 ft high 3 1/2 ft
base alongside

Allotment

Subdivision of T. 3 North R. 36 East
 Willamette Meridian, Oregon.

See 19.

- over rounded summit N. 9.
- 50.00 Set basalt stone $9 \times 8 \times 7$ ins
 6 ins in the ground for $\frac{1}{32}$
 See corner marked $\frac{1}{32}$ on W.
 face, dug pits $18 \times 18 \times 12$ ins
 N. 9 of stone $5\frac{1}{4}$ ft dirt
 and raised mound of earth
 $1\frac{1}{2}$ ft high $3\frac{1}{4}$ ft base over it.
- 52.50 Gulch corner W. - 50
- 60.00 Set basalt stone $12 \times 12 \times 6$ ins
 8 ins in the ground for $\frac{1}{16}$ See
 corner marked $\frac{1}{16}$ on W. face
 dug pits $18 \times 18 \times 12$ ins N. 9.
 of stone $5\frac{1}{4}$ ft dirt, raised
 a mound of earth $1\frac{1}{2}$ ft
 high $3\frac{1}{4}$ ft base over it.
- 80.00 The corner to Secs. 19-24
 25×30 which is a basalt
 stone $12 \times 10 \times 8$ ins 8 ins in
 the ground marked 4 notches

Allotment

Subdivision of T. 3 North R. 36 East
Willamette Meridian, Oregon.

Sec 19

(8093-10 M.)

on N. & 2 notches on the
South edges & pits 18 x 18 x 12
ins in each sec 5 1/2 ft dist
& mound of earth 2 ft high
4 1/2 ft bar along side

Land rolling

Soil 1st rate but rocky in places

Timber in Gulches

Good grass and sunflowers

From the corner to Sec.

19-24-25+30 on the W

edge of Tp.

From

East on random line

between Secs 19 & 30

Var 19th E.

Setting temporary 1/6 Sec on

at 19.20 chains about at

39.80 I intersect the 1/4 Sec corner
between Secs 19 & 30

Altitude

005 15

Subdivision of T. 3 North R. 36. East

Willamette Meridian, Oregon.

Sec 19

which is a basalt stud 12
+ 10 + 8 ins 8 ins in the ground
marked 1/4 on N. face & mound
of stud over it.

Thence I run
West on true line between
Sections 19 + 30

Var. 19° E.

5.70 Canyon corner S. - 150

2000 Set basalt stud 12 + 9 + 8
ins 8 ins in the ground for
1/16 Sec corner marked 1/16 on N.
face, and raised mound of
stud over it.

Pits impracticable

39.80 To the corner of Secs. 19 - 24
25 + 30

Land rolling & breaks off
to the Umatilla River South
Soil rocky except near the
Sec corner some grass.

Allotments

Subdivision of T. 3 North R. 36 East
Willamette Meridian, Oregon.

Sec 19

(8093-10 M.)

From the $\frac{1}{16}$ Sec corner 20 ch
N. of the corner to Secs. 19-
24 - 25 - 30. on W. ldy of Sp.
I run

East on true line in Sec 19
Var 19° E

10.00 Gulch corner N.W.
19.30 Set stone 10 + 8 + 7 ins 6.
ins in the ground for $\frac{1}{16}$
Sec corner marked $\frac{1}{16}$ on N.
face, dug pits 18 + 18 + 12 ins
E + W. of stone $2\frac{1}{2}$ ft dist
and raised a mound of
earth $1\frac{1}{2}$ ft high $3\frac{1}{2}$ ft base
over it.

38.30 Gulch corner South

39.30 Set basalt stone 11 + 8 + 6 ins
7 ins in the ground for $\frac{1}{16}$
Sec corner marked $\frac{1}{16}$ on N.
face; dug pits 18 + 18 + 12 ins

Allotment

1887 '17

Allotment of T. 3 North R. 36 East

Willamette Meridian, Oregon.

Sec 19

E. & W. of stone 5 1/2 ft dirt, raised
a mound of earth 1 1/2 ft high
3 1/2 ft base over it.

55.30 Begin to descend hill

59.30 Set base of stone 12 x 9 x 8
ins 8 ins in the ground for 1/6
See corner, marked 1/6 on N face
dug pits 18 x 18 x 12 ins E. & W.
of stone 5 1/2 ft dirt raised
a mound of earth 1 1/2 ft high
3 1/2 ft base over it.

This corner stands on steep

South slope

Land rolling

Soil not rate

Grass and sunflowers

June 7th 1889

Allotment

Subdivision of T. 3 North R. 36 East
Willamette Meridian, Oregon.

Sec 19.

(8093-10 M.)

From the $\frac{1}{4}$ Sec corner bet.
Secs 19 + 24 on West. bdy. of $\frac{1}{4}$
I run
East on rased on line through
Sec. 19.

Var 19° E

79.30 Setting temporary corner at
20 - 40 and 60 chaining + at
Intersect the N + S line
40 lks S. of $\frac{1}{4}$ Sec corner bet.
Secs. 19 + 20. which is a
basalt stone 18 + 10 + 8 ins 12
ins in the ground marked $\frac{1}{4}$
on W. face + mound of stone
over it.

Thence from
S $89^{\circ} 43'$ W on true line
through the center of Sec 19.

Var 19° E.

20.00 Set post 3 ft long 3 ins square

Allotment

19
609

Subdiv of T. 3 North R. 36 East
Willamette Meridian, Oregon.

See 19.

with a charred knot 12 ins
in the ground for $\frac{1}{16}$ Sec corner
marked $\frac{1}{16}$ S. on N. face,
dry pits 18 x 18 x 12 ins E & W
of post 5 $\frac{1}{2}$ ft dirt & raised
mound of earth 1 $\frac{1}{2}$ ft high
3 $\frac{1}{2}$ ft base around post

21.50 Cut pine Timber and as used

40.00 Set basal stone 10 x 9 x 4 ins
6 ins in the ground for $\frac{1}{4}$ Sec.
corner marked $\frac{1}{4}$ on N. face
& raised a mound of stone
over it.

Pits impracticable

45.00 Dry Gulch corner South

60.00 Set basal stone 12 x 9 x 8 ins
8 ins in the ground for $\frac{1}{16}$ Sec
corner marked $\frac{1}{16}$ on N. face
dry pits 18 x 18 x 12 ins E & W of
stone 5 $\frac{1}{2}$ ft dirt. raised a

610

Allotment

Subdivision of T. 3 North R. 36 East
Willamette Meridian, Oregon.

See 19

(8093-10 M.)

mound of earth 1 1/2 ft high
3 1/2 ft base over it

60.75 Gulch course S.W.

79.30 To the 1/4 Sec corner between
Secs. 19 + 24 on W bdy of
Tp.

Land rolling

Soil not ^{except} very rocky

washed out in places

Good grass and sunflowers

July 1901

Allotment

6171

Subdivision of T. 3 North R. 36. East
Willamette Meridian, Oregon.

Sec 19

From the $\frac{1}{16}$ Sec corner 20 ch
N of $\frac{1}{4}$ Sec corner between Secs
19 + 24 on W. ldy of Sp.
I run $S 89^{\circ} 28'$
East on true line in Sec
19.

Var 20° E.

Over rolling ground

1930 Set a basalt stone $10 \times 8 \times 7$ ins
6 ins in the ground for $\frac{1}{16}$ + $\frac{1}{32}$
Sec corner marked $\frac{1}{16}$ ^{on S.} $\frac{1}{32}$
on N. face. dug pits $18 \times 18 \times$
 12 ins E. + W. of stone $5 \frac{1}{2}$ ft dirt
raised a mound of earth $1 \frac{1}{2}$ ft.
high $3 \frac{1}{2}$ ft. low over it.

3930 Set post 3 ft long 3 ins square
with charred stake 12 ins in
the ground for $\frac{1}{16}$ + $\frac{1}{32}$ Sec
corner marked $\frac{1}{16}$ ^{on S.} $\frac{1}{32}$ S.
on N. face. from which

Subdiv of T. 3 North R. 36 East

Willamette Meridian, Oregon.

Sec 19

(8093-10 M.)

A pine 30 ins diam brs N 30° E.

86 lbs dist marked $\frac{1}{6}$ - $\frac{1}{32}$ T. B. J.

A pine 30 ins diam brs N 3° E. 124

lbs. dist marked $\frac{1}{6}$ - $\frac{1}{32}$ T. B. J.

Land level, last 15 chains in timber

Soil very rich

Grass and sunflower.

From the $\frac{1}{32}$ Sec corner 10 ch

S. of corner to Secs. 18-19

13 & 24. on W. bdy of T. N.

I run

T 89° 28' E. on a true line
in Sec 19.

1930

Set box with stone 12 + 10 + 9 ins

9 ins in the ground for $\frac{1}{32}$ Sec

corner marked $\frac{1}{32}$ on N. face

and raised mound of stone

over it on edge of flat Gulch

Pits impracticable

Allotment

23

Subdivision of T. 3 North R. 36 East

Willamette Meridian, Oregon.

Sec 19

- 19.50 Gulch course N.W.
39.30 Set small stake $12 + 9 + 8$ ins
9 ins in the ground for $\frac{1}{32}$
See corner marked $\frac{1}{32}$ on N face
dry pits $18 + 18 \times 12$ ins E. W.
of stake $5\frac{1}{2}$ ft dirt and raised
around of earth $8\frac{1}{2}$ ft high
 $3\frac{1}{2}$ ft base over it

Land level

Timber on whole line

Soil red into

Pine and bunch grass

June 8th 1889

Subdividing of T. 3 North R. 36 E.
Willamette Meridian, Oregon.

General Description

These lands are in Sections
18 & 19 on the high summit
North of Umatilla River
They are rolling & often
run over brinks and canyons
Good bunch grass &
considerable pine timber

616
Allotment

Subdivision of T. 3 North R. 36 East

Willamette Meridian, Oregon.

(8093-10 M.)

In accordance with
the requirements of the
Manual of Survey I
have carefully tested the adjust-
ment of my instrument
by taking the Latitude
daily weather permitting
and in all cases the instru-
ment was found to be in
correct adjustment

James P. Currier
U. S. Dept. Surveyor

FINAL OATHS FOR SURVEYS.

A list of the names of the individuals employed by James P. Currier, U. S. Deputy Surveyor, to assist in running, measuring and marking the lines and corners described in the foregoing field notes of the survey of the Subdivisional & Allotment lines of T. 3 N. R. 36 E. Willamette Meridian, Oregon, showing the respective capacities in which they acted:

- , **Compassman.**
- J. P. Saramore, **Chainman.**
- J. L. Brown, **Chainman.**
- , **Chainman.**
- , **Chainman.**
- C. M. Stone, **Axeman.**
- R. E. Long, **Axeman.**
- , **Flagman.**

FINAL OATHS OF ASSISTANTS.

We hereby certify that we assisted James Pleurvie U. S. Deputy Surveyor, in surveying all those parts or portions of the Subdivisional and Allotment lines of T. 3 N. R. 36 E. Willamette Meridian, Oregon, as are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the U. S. Surveyor General of Oregon.

- , **Compassman.**
- J. P. Saramore, **Chainman.**
- J. L. Brown, **Chainman.**
- , **Chainman.**
- , **Chainman.**
- C. M. Stone, **Axeman.**
- R. E. Long, **Axeman.**
- , **Flagman.**

Subscribed and sworn to before me, this 2nd day of

[SEAL.] July 9 1889
Thos. H. Eberald
 Notary Public

FINAL OATH OF DEPUTY SURVEYOR.

I, James P. Currier
United States Deputy Surveyor, do solemnly swear that in pursuance of
instructions received from Douglas W. Taylor
U. S. Surveyor General for Oregon, bearing date of the 19th

day of March 1889, I have well, faith-
fully and truly, in my own proper person, and in strict conformity with
the instructions furnished by the U. S. Surveyor General for Oregon, the
Surveying Manual, and the laws of the United States, surveying all those

parts or portions of subdivisional and
lot lines of T. 3 N. R. 36 E

Willamette Meridian, in the State of Oregon, as are represented in the
foregoing field notes as having been surveyed by me and under my direc-
tions; and I do further solemnly swear that all the corners of said survey
have been established and perpetuated in strict accordance with the Sur-
veying Manual, printed instructions, the special written instructions of
the U. S. Surveyor General for Oregon, and in the specific manner de-
scribed in the field notes, and that the foregoing are the *true* field notes of
such survey, and should any fraud be detected I will suffer the penalty of
perjury under the provisions of an Act of Congress approved August 8,
1846.

James P. Currier
U. S. Deputy Surveyor.

Subscribed and sworn to before me, this 2nd
day of July 1889

Thos FitzGerald
Notary Public

Office U. S. Surveyor General,

Portland, Oregon, *Sept 14th* 188*9*

foregoing
The following Field Notes of the Survey of the

Subdivision and Allotment

Lines of Township 3 North
Range 36 East Will Mer Oregon

executed by

James J. Curran
U.S. Dept Survey

under his Contract No. *537*, dated

March 5 188*9* having been critically examined, the

necessary corrections and explanations made, the said Field Notes

and the survey they describe, are hereby approved.

Douglas W. Taylor
Surveyor General.