

FIELD NOTES

OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 3 SOUTH, RANGE 31 EAST,

Of the WILLAMETTE Meridian,

In the State of OREGON

EXECUTED BY

Craig L. Wanless, Cadastral Surveyor

Under special instructions dated May 3, 19 57, approved May 6, 1957,

_____, which provided for the surveys included under U.S. Survey/Group

Number 350, and assignment instructions dated March 27, 19 78.

Survey commenced May 10, 19 78

Survey completed May 18, 19 78

INDEX DIAGRAM

Township 3 South, Range 31 East,

| | | | | | | |
|----------|----------|---------------------|--------------------|-------------|-------------|----------|
| 6 | 5 | 4 | 3 | 2 | 1 | |
| 7 | 8 | 9 | 10 | 11 | 12 | |
| 18 | 17 | 16 | 15 | 14 | 13 | |
| 19 | 20 | 21 | 22 | 23 | 24 | <u>6</u> |
| 30 | 29 | 28 | 27 | 26 | 25 | <u>6</u> |
| | | <u>11</u> <u>12</u> | <u>9</u> <u>10</u> | <u>8</u> | <u>7</u> | <u>5</u> |
| 31 | 32 | <u>11</u> 33 | 34 | <u>8</u> 35 | <u>7</u> 36 | <u>5</u> |
| <u>4</u> | <u>4</u> | <u>3</u> | <u>3</u> | <u>2</u> | <u>2</u> | <u>1</u> |

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 31 E., Willamette Meridian, Oregon

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented with the original basalt stone, 12 x 10 x 8 ins., firmly set 6 ins. in the ground, and in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on W. face, from which the remains of an original bearing tree:

A sawed pine stump, 22 ins. diam., bears N. 53° W., 23 lks. dist., with scribe marks S BT visible on open blaze. (Record, N. 65° W.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 3 S R 31 E
 $\frac{1}{4}$
 S 35 | S 36
 1978

from which new bearing trees

A larch, 13 ins. diam., bears S. 80° E., $23\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S36 BT.

A fir, 10 ins. diam., bears S. $52\frac{1}{2}^\circ$ W., 51 lks. dist., mkd. $\frac{1}{4}$ S35 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 25, 26, 35, and 36, determined at record bearing and distance from the remains of the original bearing trees:

A sawed and decayed pine stump, size indeterminate, bears N. 63° E., 250 lks. dist., no marks visible.

A pine, 40 ins. diam., bears S. 62° E., 95 lks. dist., with scribe marks R31E S36 visible on open blaze.

A sawed pine stump, 28 ins. diam., bears S. 10° W., 127 lks. dist., with scribe marks S35 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 3 S R 31 E
 S 26 | S 25
 S 35 | S 36
 1978

from which new bearing trees

A ponderosa pine, 15 ins. diam., bears N. 43° E., 104 lks. dist., mkd. T3S R31E S25 BT.

A fir, 13 ins. diam., bears S. 19° W., 97 lks. dist., mkd. T3S R31E S35 BT.

A ponderosa pine, 18 ins. diam., bears N. $41\frac{1}{2}^\circ$ W., 105 lks. dist., mkd. T3S R31E S26 BT.

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 31 E., Willamette Meridian, Oregon

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, determined at record bearing and distance from the remains of the original bearing trees:

A pine, 34 ins. diam., bears S. 40° E., 18 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on open blaze.

A root hole, bears West, 167 lks. dist., with a down and decayed pine alongside, size indeterminate, no marks visible.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 3 S R 31 E
 $\frac{1}{4}$
S 34 | S 35
 1978

from which a new bearing tree

A ponderosa pine, 27 ins. diam., bears N. 87° W., 289 lks. dist., mkd. $\frac{1}{4}$ S34 BT.

The cor. of secs. 26, 27, 34, and 35, monumented with the original basalt stone, 18 x 12 x 5 ins., firmly set 8 ins. in the ground, mkd. with 3 notches on E. and 2 notches on S. edges, from which the remains of the original bearing trees:

A pine, 24 ins. diam., bears S. 21° W., 32 lks. dist., with healed blaze.

A pine stump, 34 ins. diam., bears N. 34° W., 48 lks. dist., with a down pine alongside, 34 ins. diam., with scribe marks T3S R31E S27 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 3 S R 31 E
S 27 | S 26
S 34 | S 35
 1978

from which new bearing trees

A fir, 11 ins. diam., bears N. 45° E., $68\frac{1}{2}$ lks. dist., mkd. T3S R31E S26 BT.

A fir, 14 ins. diam., bears S. $47\frac{1}{2}^{\circ}$ E., $30\frac{1}{2}$ lks. dist., mkd. T3S R31E S35 BT.

A fir, 17 ins. diam., bears N. 41° W., 35 lks. dist., mkd. T3S R31E S27 BT.

Deposit corner stone alongside iron post.

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 31 E., Willamette Meridian, Oregon

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, determined at record bearing and distance from the remaining original bearing tree:

A pine, 17 ins. diam., bears South, 14 lks. dist., with scribe marks BT visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 3 S R 31 E
 $\frac{1}{4}$ S 23
 S 26
1978

from which a new bearing tree

A white fir, 12 ins. diam., bears N. 3° W., 34 lks. dist., mkd. $\frac{1}{4}$ S23 BT.

The cor. of secs. 14, 15, 22, and 23, monumented with the original granite stone, 14 x 12 x 4 ins., firmly set 6 ins. in the ground, mkd. with 4 notches on S. and 3 notches on E. edges, from which the remains of the original bearing trees:

A root hole, bears N. 10° E., 25 lks. dist., with a down larch alongside, 16 ins. diam., with scribe marks R31E S14 visible on open blaze.

A larch stump, 14 ins. diam., bears S. 10° E., 21 lks. dist., with a down larch alongside, 14 ins. diam., with fragmentary scribe marks visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 3 S R 31 E
S 15 | S 14
S 22 | S 23
1978

from which new bearing trees

A fir, 15 ins. diam., bears N. 18° E., 27 lks. dist., mkd. T3S R31E S14 BT.

A fir, 12 ins. diam., bears S. 63° E., 33 lks. dist., mkd. T3S R31E S23 BT.

A larch, 16 ins. diam., bears S. 55° W., $56\frac{1}{2}$ lks. dist., mkd. T3S R31E S22 BT.

A fir, 15 ins. diam., bears N. 57° W., 82 lks. dist., mkd. T3S R31E S15 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 27, 28, 33, and 34, determined at record distance from the remains of the original bearing trees:

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 31 E., Willamette Meridian, Oregon

CHAINS

A sawed pine stump, 25 ins. diam., bears N. 44° E., 201 lks. dist., with scribe marks E S27 BT visible on open blaze.

A pine, 22 ins. diam., bears S. 14° W., 125 lks. dist., with scribe marks T3S R31E S33 visible on open blaze. (Record, S. 80° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

| |
|--------------|
| T 3 S R 31 E |
| S 28 S 27 |
| S 33 S 34 |
| 1978 |

from which new bearing trees

A ponderosa pine, 20 ins. diam., bears N. 46° E., 65 lks. dist., mkd. T3S R31E S27 BT.

A ponderosa pine, 14 ins. diam., bears S. 73° E., 74 lks. dist., mkd. T3S R31E S34 BT.

A ponderosa pine, 12 ins. diam., bears N. 54° W., 41 lks. dist., mkd. T3S R31E S28 BT.

The ¼ sec. cor. of secs. 27 and 34, monumented with the original unmarked basalt stone, 24 x 11 x 7 ins. (record, 17 x 11 x 7 ins.), firmly set 15 ins. in the ground, and in a mound of stone, 2 ft. base, 1 ft. high, from which the remains of the original bearing trees:

A pine, 22 ins. diam., bears N. 60° W., 115 lks. dist., with scribe marks BT visible on open blaze. (Record, 105 lks.)

A sawed and decayed pine stump, size indeterminate, bears S. 12° W., 114 lks. dist., no marks visible. (Record, 108 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

| |
|--------------|
| T 3 S R 31 E |
| ¼ S 27 |
| S 34 |
| 1978 |

from which a new bearing tree

A ponderosa pine, 12 ins. diam., bears S. 15° W., 262½ lks. dist., mkd. ¼ S34 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 21, 22, 27, and 28, monumented with the original granite stone, 20 x 14 x 5 ins., firmly set 10 ins. in the ground, mkd. with 4 notches on E. and 3 notches on S. edges, from which the remains of the original bearing trees:

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 31 E., Willamette Meridian, Oregon

CHAINS

A sawed pine stump, 18 ins. diam., bears N. 31° E., 24 lks. dist., with scribe marks R29E S22 visible on open blaze.

A root hole, bears N. 72° W., 52 lks. dist., with a down pine alongside, 14 ins. diam., with scribe marks T3S R31E S21 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

| |
|--------------|
| T 3 S R 31 E |
| S 21 S 22 |
| S 28 S 27 |
| 1978 |

from which new bearing trees

A ponderosa pine, 12 ins. diam., bears N. 32° E., 46½ lks. dist., mkd. T3S R31E S22 BT.

A white fir, 11 ins. diam., bears S. 13° E., 89 lks. dist., mkd. T3S R31E S27 BT.

A white fir, 12 ins. diam., bears S. 64° W., 90 lks. dist., mkd. T3S R31E S28 BT.

A ponderosa pine, 22 ins. diam., bears N. 56° W., 18½ lks. dist., mkd. T3S R31E S21 BT.

Deposit corner stone alongside iron post.

The ¼ sec. cor. of secs. 32 and 33, determined at record bearing and distance from the remains of the original bearing trees:

A larch snag, 13 ins. diam., bears N. 85° E., 17 lks. dist., with scribe marks 4 S visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

| |
|--------------|
| T 3 S R 31 E |
| ¼ |
| S 32 S 33 |
| 1978 |

from which new bearing trees

A white fir, 8 ins. diam., bears S. 22° E., 17 lks. dist., mkd. ¼ S33 BT.

A fir, 10 ins. diam., bears N. 44° W., 50½ lks. dist., mkd. ¼ S32 BT.

The cor. of secs. 28, 29, 32, and 33, monumented with the original granite stone, 16 x 10 x 6 ins., firmly set 4 ins. in the ground, mkd. with 5 notches on N. and E. edges, from which the remains of the original bearing trees:

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 31 E., Willamette Meridian, Oregon

CHAINS

A larch, 26 ins. diam., bears N. 58° E., 24 lks. dist., with scribe mark S visible on opened blaze.

A larch snag, 24 ins. diam., bears N. 48° W., 59 lks. dist., with scribe marks 31E S29 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

| | | |
|-----|------|------|
| T 3 | S R | 31 E |
| | S 29 | S 28 |
| | S 32 | S 33 |
| | 1978 | |

from which new bearing trees

A fir, 10 ins. diam., bears S. 42½° E., 42½ lks. dist., mkd. T3S R31E S33 BT.

A larch, 14 ins. diam., bears S. 26½° W., 66 lks. dist., mkd. T3S R31E S32 BT.

A ponderosa pine, 10 ins. diam., bears N. 11° W., 75 lks. dist., mkd. T3S R31E S29 BT.

Deposit corner stone alongside iron post.

The ¼ sec. cor. of secs. 28 and 33, monumented with the original basalt stone, 12 x 10 x 6 ins., firmly set 8 ins. in the ground, mkd. ¼ on N. face, from which the remains of the original bearing trees:

A pine snag, 10 ins. diam., bears N. 68° E., 15 lks. dist., with scribe marks ¼ S BT visible on open blaze. (Record, 28 lks.)

A root hole, bears S. 42° E., 28 lks. dist., with a down and decayed pine alongside, size indeterminate, with scribe marks ¼ S visible on decayed blaze. (Record, 15 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

| | | |
|-----|--------|------|
| T 3 | S R | 31 E |
| | ¼ S 28 | |
| | S 33 | |
| | 1978 | |

from which new bearing trees

A larch, 14 ins. diam., bears N. 7° W., 33½ lks. dist., mkd. ¼ S28 BT.

A white fir, 7 ins. diam., bears S. 42° E., 32 lks. dist., mkd. ¼ S33 BT.

Deposit corner stone alongside iron post.

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

| NAMES | CAPACITY |
|----------------|-----------------|
| Edward W. Moye | Engineering Aid |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

FEB 17 1969

(Date)

Chief, District Survey Examination and Approval Staff

CONTROL UNIT OF THE BUREAU

CLERK: THE FOLLOWING REPORT IS THE FIELD REPORT OF THE FIELD ASSISTANT...

Copy sent to...

CERTIFICATE OF SURVEY

(I) ~~(XX)~~, Craig L. Wanless, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May, 19 57, (I) ~~(XX)~~ have remonumented certain original corner points, township 3 south, range 31 east,

of the Willamette Meridian, in the State of Oregon, which are represented in the foregoing field notes as having been executed by (me), ~~(XX)~~ and under (my) ~~(XX)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 19, 1978
(Date)

Craig L. Wanless
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
~~Washington, D.C.~~
Denver, Colorado

The foregoing field notes of the remonumentation of certain original corner points, township 3 south, range 31 east, Willamette Meridian, Oregon,

executed by Craig L. Wanless, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

FEB 07 1980
(Date)

J. Voorhees
(Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-526