

FIELD NOTES

OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 3 SOUTH, RANGE 32 EAST,

Multiple horizontal lines for handwritten notes.

Of the WILLAMETTE Meridian,

In the State of OREGON

EXECUTED BY

Craig L. Wanless, Cadastral Surveyor

Under special instructions dated May 3, 19 57, approved May 6, 1957,

_____, which provided for the surveys included under U.S. Survey/Group
Number 350, and assignment instructions dated July 18, 19 77.

Survey commenced August 4, 19 77

Survey completed August 11, 19 77

INDEX DIAGRAM

Township 3 South, Range 32 East,

6	5	4	3	2	1	<u>3</u>
					<u>6</u>	<u>3</u>
7	8	9	10	<u>9</u> 11	12	<u>2</u>
18	17 <u>14</u>	16	15	14 <u>8</u> <u>9</u>	13 <u>5</u>	<u>2</u>
19	20	<u>13</u> 21	22 <u>11</u> <u>11</u>	23 <u>8</u>	<u>5</u> 24 <u>4</u>	
30	29	<u>13</u> 28 <u>12</u>	27 <u>10</u> <u>10</u>	<u>7</u> 26 <u>7</u>	25 <u>4</u>	<u>1</u>
31	32	<u>12</u> 33	34	<u>6</u> 35	36	

T. 3 S., R. 32 E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 3 south, range 32 east, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350 Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories when Needed".

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

East Boundary, T. 3 S., R. 32 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by George S. Pershin,
U. S. Deputy Surveyor, in 1882)

The cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., determined at record bearing and distance from the remains of the original bearing trees:

A pine, 25 ins. diam., bears N. 7° E., 234 lks. dist., with scribe marks T3S R33E S30 BT visible on open blaze.

A pine, 29 ins. diam., bears S. 16° W., 169 lks. dist., with healed blaze.

A sawed pine stump, 26 ins. diam., bears N. 8° W., 241 lks. dist., with scribe marks BT visible on open blaze.

At the corner point which falls in a gravelled road, 25 lks. wide, bears E. and W.

Drive an iron spike, 8 ins. long, ½ in. diam., the top 3 ins. below road surface.

from which a new bearing tree and reference monuments

An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 30° E., 60 lks. dist., with brass cap mkd. T3S R33E S31 RM 1977 and an arrow pointing to the corner.

An iron post, 28 ins. long, 2½ ins. diam., set 15 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears N. 30° W., 60 lks. dist., with brass cap mkd. T3S R32E S25 RM 1977 and an arrow pointing to the corner.

A lodgepole pine, 28 ins. diam., bears N. 23° W., 259½ lks. dist., mkd. T3S R32E S25 BT.

No other suitable trees available within limits.

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 32 E., Willamette Meridian, Oregon

CHAINS

The cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., monumented with the original basalt stone, 14 x 10 x 8 ins., firmly set 5 ins. in the ground, with 3 notches on N. and S. edges, from which the remains of the original bearing trees:

A pine, 20 ins. diam., bears N. 31° E., 60 lks. dist., with healed blaze. (Record, N. 38° E.)

A pine, 25 ins. diam., bears S. 77° E., 43 lks. dist., with healed blaze. (Record, S. 72° E.)

A decayed pine stump, size indeterminate, bears N. 45° W., 31 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 3 S	
R 32 E	R 33 E
S 13	S 18
S 24	S 19
1977	

from which new bearing trees

A fir, 8 ins. diam., bears S. 29½° W., 80 lks. dist., mkd. T3S R32E S24 BT.

A lodgepole pine, 21 ins. diam., bears N. 70½° W., 66½ lks. dist., mkd. T3S R32E S13 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., monumented with the original basalt stone, 14 x 8 x 7 ins., loosely set in a collar of stones, with 2 notches on N. and 4 notches on S. edges, from which the original bearing trees:

A fir, 24 ins. diam., bears N. 35° E., 37 lks. dist., with healed blaze. (Record, N. 28° E., 39 lks.)

A fir, 30 ins. diam., bears S. 66° E., 52 lks. dist., with healed blaze.

A pine, 20 ins. diam., bears S. 55° W., 129 lks. dist., with healed blaze.

A fir, 16 ins. diam., bears N. 34° W., 94 lks. dist., with scribe marks T3S R32E S12 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 3 S	
R 32 E	R 33 E
S 12	S 7
S 13	S 18
1977	

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 32 E., Willamette Meridian, Oregon

CHAINS

Deposit corner stone alongside iron post.

The cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., determined at record bearing and distance from the only remaining original bearing tree:

A ponderosa pine, 22 ins. diam., bears S. 78° E., 70 lks. dist., with scribe marks BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, to solid rock, and supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.

	T 3 S	
R 32 E		R 33 E
S 1		S 6
S 12		S 7
		1977

from which new bearing trees

A ponderosa pine, 12 ins. diam., bears N. 27° E., 131½ lks. dist., mkd. T3S R33E S6 BT.

A fir, 12 ins. diam., bears S. 67° W., 77½ lks. dist., mkd. T3S R32E S12 BT.

A fir, 15 ins. diam., bears N. 66° W., 99 lks. dist., mkd. T3S R32E S1 BT.

The SW. bearing tree is the corner of wire fences, extending N. and W.

The ¼ sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., determined at record bearing and distance from the remains of the original bearing trees:

A decayed fir stump, size indeterminate, bears S. 85° E., 22 lks. dist., with scribe marks ¼ S visible on overgrowth lying alongside.

A decayed fir stump, size indeterminate, bears S. 85° W., 12 lks. dist., with fragmentary scribe marks visible on overgrowth lying alongside.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

	T 3 S	
	¼	
R 32 E		R 33 E
S 1		S 6
		1977

from which new bearing trees

A fir, 20 ins. diam., bears S. 77° E., 54 lks. dist., mkd. ¼ S6 BT.

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 32 E., Willamette Meridian, Oregon

CHAINS

A fir, 15 ins. diam., bears S. 83° W., 21 lks.
dist., mkd. $\frac{1}{4}$ S1 BT.

Corner is located 5 lks. west of wire fence, extending
N. and S.

Subdivisions, T. 3 S., R. 32 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by George S. Pershin,
U. S. Deputy Surveyor, in 1882)

The cor. of secs. 25, 26, 35, and 36, monumented with the
original unmarked granite stone, 18 x 14 x 5 ins., firmly
set 2 ins. in the ground, from which the remains of the
original bearing trees:

A pine snag, 16 ins. diam., bears N. $76\frac{1}{2}^{\circ}$ W.,
71 lks. dist., with scribe marks T3S R32E S26 BT
visible on open and burned blaze. (Record,
N. 74° W.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T	3	S	R	32	E
	S	26		S	25
	S	35		S	36
					1977

from which a new bearing tree

A lodgepole pine, 8 ins. diam., bears S. 85° W.,
10 lks. dist., mkd. T3S R32E S35 BT.

No other suitable trees available within limits.

Deposit corner stone alongside iron post.

The cor. of secs. 23, 24, 25, and 26, monumented with
the original unmarked basalt stone, 15 x 8 x 7 ins.,
firmly set 4 ins. in the ground, from which the original
bearing trees:

A pine, 30 ins. diam., bears N. 81° E., 136 lks.
dist., with healed double blaze. (Record,
N. 64° E., 134 lks.)

A pine, 30 ins. diam., bears S. 57° E., 65 lks.
dist., with scribe marks S25 visible on
partially healed blaze. (Record, S. 38° E.,
61 lks.)

A pine, 35 ins. diam., bears N. 64° W., 195 lks.
dist., with scribe marks E S2 visible on
partially healed blaze. (Record, N. 42° W.,
193 lks.)

At the corner point

CERTIFICATE OF SURVEY

(I) ~~(WE)~~, Craig L. Wanless, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May, 19 57, (I) ~~(WE)~~ have remonumented certain original corner points, township 3 south, range 32 east,

of the Willamette Meridian, in the State of Oregon, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 16, 1978
(Date)

Craig L. Wanless
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
~~Washington, D.C.~~
Denver, Colorado

The foregoing field notes of the remonumentation of certain original corner points, township 3 south, range 32 east, Willamette Meridian, Oregon,

executed by Craig L. Wanless, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JAN 23 1980
(Date)

J. J. Voorhees
(Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 840 626