

INDEX DIAGRAM

Township 3 South, Range 33 East,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13 <u>2</u> <u>1</u>
19	20	21	22	23	24
30	29	28	27	26	25 <u>1</u>
31	32	33	34	35	36

T. 3 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 3 south, range 33 east, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories when Needed."

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

East Boundary, T. 3 S., R. 33 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by
Rufus S. Moore, Deputy Surveyor, in 1882)

The $\frac{1}{4}$ sec. cor. of sec. 25 only, on the E. bdy. of the Tp., monumented with the original basalt stone, 19 x 12 x 5 ins., firmly set 7 ins. in the ground, no marks visible, from which the original bearing trees:

A fir, 25 ins. diam., bears S. 82° E., 55 lks. dist., with healed blaze.

A pine, 28 ins. diam., bears N. 74° W., 29 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 3 S
R 33 E | R 33 $\frac{1}{2}$ E
 $\frac{1}{4}$ S 25 |
1975

from which a new bearing tree

A fir, 27 ins. diam., bears S. 34° W., 57 lks. dist., mkd. $\frac{1}{4}$ S25 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 13 and 24 only, on the E. bdy. of the Tp., monumented with the original basalt stone, 16 x 12 x 7 ins., firmly set 8 ins. in the ground, no marks visible, from which the remains of the original bearing trees:

A root hole, bears N. 19° E., 118 lks. dist., with a down and decayed pine snag alongside, 10 ins. diam., with scribe marks R34E S18 visible on decayed blaze.

A pine, 24 ins. diam., bears S. 13° E., 35 lks. dist., with healed blaze.

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

A pine snag, 22 ins. diam., bears S. 22° W., 68 lks. dist., with scribe marks T3S R33E S24 visible on partially healed blaze.

A root hole, bears N. 21° W., 99 lks. dist., with a down and decayed pine snag alongside, 16 ins. diam., with scribe marks BT visible on decayed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 3 S	T 3 S
S 13	R 33½ E
S 24	S 15
R 33 E	
	1975

from which new bearing trees

A fir, 5 ins. diam., bears S. 51½° W., 21 lks. dist., mkd. X BT.

A fir, 7 ins. diam., bears N. 78¾° W., 15 lks. dist., mkd. T3S R33E S13 BT.

Deposit corner stone alongside iron post.

The ¼ sec. cor. of sec. 13 only, on the E. bdy. of the Tp., monumented with the original basalt stone, 18 x 12 x 12 ins., firmly set 5 ins. in the ground, no marks visible, from which the remains of the original bearing trees:

A pine, 18 ins. diam., bears N. 57° E., 118 lks. dist., with healed blaze.

A pine stump, 8 ins. diam., bears N. 25½° W., 41 lks. dist., with scribe marks BT visible on decayed blaze. (Record, N. 23° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 2 ins. in the ground, to solid rock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.

T 3 S	
R 33 E	R 33½ E
¼ S 13	
	1975

from which new bearing trees

A juniper, 12 ins. diam., bears S. 28° W., 40 lks. dist., mkd. ¼ S13 BT.

A pine, 22 ins. diam., bears N. 58½° W., 115 lks. dist., mkd. ¼ S13 BT.

Deposit corner stone alongside iron post.

CERTIFICATE OF SURVEY

(I) ~~(WA)~~, A. Joseph Garrison, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May, 19 57, (I) ~~(WA)~~ have remonumented certain original corner points, township 3 south, range 33 east,

of the Willamette Meridian, in the State of Oregon, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

(Date) (Cadastral Surveyor)
July 31, 1975
(Date) *A. Joseph Garrison*
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the remonumentation of certain original corner points, township 3 south, range 33 east, Willamette Meridian, Oregon,

executed by A. Joseph Garrison, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUN 13 1977

(Date) *Roger T. Barron*
Acting (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date) _____ (Chief, Division of Cadastral Survey) GPO 849-626