

FIELD NOTES

Of the ~~survey of the~~ Examination of Corner & Termination
Lines of T. 1 N. R. 33 E., T. 3 & 4 N. R. 33-34 & 35 E.,
Willamette Meridian,

Oregon, as surveyed by James P. Currier & James E. Nolan,
U. S. Deputy Surveyor, under ^{Special} his Contract No.

dated May 4th 1887

Survey commenced, April 26th 1890

Survey completed, May 1st 1890

NAMES AND DUTIES OF ASSISTANTS.

-, Compassman.
- James J. Beck, Chainman.
- William Marberger, Chainman.
- Chainman.
- Chainman.
- Axeman.
- Axeman.
- Flagman.

PRELIMINARY OATHS OF ASSISTANTS.

We, *James J. Beck, and William Marburger,*

do solemnly swear that we will faithfully execute the duties of Chain Carriers; that we will level the chain over even and uneven ground, and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we will assist in measuring, to the best of our skill and ability, and in accordance with the instructions given us in

the ~~survey of the~~ *Examination of corners on Exterior* lines of *T. 1 N. R. 33 E. &*

T. 34 N. R. 33-34 & 35 E. Willamette Meridian, Oregon.

James J. Beck, Chainman.

William Marburger, Chainman.

....., Chainman.

....., Chainman.

Subscribed and sworn to before me, this *April 26th*

day of *April* 18. *90*

[SEAL]

W. Harrow
Notary Public for Or.

We, and

....., do solemnly swear that we will well and truly perform the duties of Axemen in the establishment of corners and other duties, according to instructions given us, and to the best of our

skill and ability, in the survey of the

..... Willamette Meridian, Oregon.

....., Axeman.

....., Axeman.

Subscribed and sworn to before me, this

day of 18.

[SEAL.]

FINAL OATHS FOR SURVEYS.

A list of the names of the individuals employed by James P. Currier
and James E. Poland, U. S. Deputy Surveyor, to assist in
 running, ~~measuring~~ and marking the lines and corners described in the foregoing
 field notes of the survey of the Examination of corners
on Exterior lines of T. N. R. 33 E. T. 34
N. R. 33. 34 + 35 - E. Williamette Meridian, Oregon,
 showing the respective capacities in which they acted:

-, Compassman.
- James T. Beck....., Chainman.
- William Marburger....., Chainman.
-, Chainman.
-, Chainman.
-, Axeman.
-, Axeman.
-, Flagman.

FINAL OATHS OF ASSISTANTS.

We hereby certify that we assisted James P. Currier &
James E. Poland, U. S. Deputy Surveyor, in surveying all
 those parts or portions of the Examination of corners
on Exterior Lines of T. N. R. 33 E. T. 34
N. R. 33 - 34 - 35 - E. Williamette Meridian, Oregon,

as are represented in the foregoing field notes as having been surveyed by him and
 under his direction; and that said survey has been in all respects, to the best of our
 knowledge and belief, well and faithfully surveyed, and the corner monuments es-
 tablished, according to the instructions furnished by the U. S. Surveyor General of
 Oregon.

-, Compassman.
- James T. Beck....., Chainman.
- William Marburger....., Chainman.
-, Chainman.
-, Chainman.
-, Axeman.
-, Axeman.
-, Flagman.

Subscribed and sworn to before me, this First day of

May 18 90

[SEAL.]

Harriet
Notary Public
for Oregon

FINAL OATH OF DEPUTY SURVEYOR.

We James J. Currier and James E. Holand
United States Deputy Surveyor, do solemnly swear that in pursuance of

instructions received from Douglas W. Taylor

U. S. Surveyor General for Oregon, bearing date of 15th

day of April 1890

fully and truly, in ^{our} own proper persons and in strict conformity with the instructions furnished by the U. S. Surveyor General for Oregon, the Surveying Manual, and the laws of the United States, ^{examined} surveying all those

parts or portions of T. 1 N. R. 33 E., T. 3 & 4 N. R. 33-

34 & 35 - E. 1

Willamette Meridian, in the State of Oregon, as are represented in the foregoing field notes as having been surveyed by ~~me~~ and under ^{our} directions; and ~~we~~ do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Surveying Manual, printed instructions, the special written instructions of the U. S. Surveyor General for Oregon, and in the specific manner described in the field notes, and that the foregoing are the true field notes of such survey, and should any fraud be detected ~~we~~ will suffer the penalty of perjury under the provisions of an Act of Congress approved August 8, 1846.

James J. Currier

James E. Holand

U. S. Deputy Surveyor.

Subscribed and sworn to before me, this 6th

day of May 1890

Herman Bammerges
Notary Public
for Oregon

Office U. S. Surveyor General,

Portland, Oregon, June - 4 1890.

The foregoing Field Notes of the ~~Survey of the~~
 Examination of Corners on Exterior lines
 of T. 1 N. R. 33 E - and T. 3 + 4 N. R. 34 -
 35 East - Will. Nev. Oregon
 executed by James P. Curran and James E. Holand
 under ^{Special} his contract No. _____, dated May
 4 - 1887, having been critically examined, the
 necessary corrections and explanations made, the said Field
 Notes and the survey they describe, are hereby approved.

Douglas W. Taylor.
 Surveyor General.

Exteriors of T. B. North R. 34 & 35 E.
Willamette Meridian, Oregon.

Examination of corners.

Find Township cor. T. 3 & 4
N. R. 34 & 35 E. To be a
Pine Post 48 x 6 x 8 ins 24 ins
in the ground. Marked S. 31
T. 4 N. R. 35 E on N. E. S. 6. T. 3 N. R.
35 E on S. E. S. 1 T. 3 N. R. 34 E
on S. N. S. 36 T. 4 N. R. 34 E.
on N. N. ^{face} with 6 notches on
N. E. S. & N. edges, with pits
6 ft dist in each line
& earth mound around Post.

South to cor sees. 1-6-7 & 12
a stone 12 x 10 x 8 ins ^{firmly set in ground} with 1 notch
on N. & S. on S. edges. Pits 5 1/2 ft
dist in each sec. Mud around
it. Pits partly filled. Mound scattered.
South bet. sees 7 & 12, I
find that cor sees. 7-12-13 & 18
is plowed up & gone.