

FIELD NOTES

Of the survey of the Exterior L

Lines of T₂ N. R₂ 32 & 33 E, T₄ N. R₂ 34 & 35

E & T₃ N. R₂ 33. 34. 35 & 36 E, Willamette Meridian, Oregon,

as surveyed by Jas. P. Currier & Jas. E. Nolan

U. S. Deputy Surveyors, under ^{their} his Contract No. Special

dated May 4th, 1887.

Survey commenced, July 27th, 1887.

Survey completed, Sept 10th, 1887.

NAMES AND DUTIES OF ASSISTANTS.

L. J. Wooley, Compassman.

Frank Belshaw, Chainman.

Guy Davis, Chainman.

W. H. Medley, Chainman.

J. S. Medley, Chainman.

Barney Coomer, Axman.

J. R. Gabley, Axman.

, Flagman.

PRELIMINARY OATHS OF ASSISTANTS.

We, *J. S. Medley, W. H. Medley, Frank Belshaw & Guy Davis*

do solemnly swear that we will faithfully execute the duties of Chain Carriers; that we will level the chain over even and uneven ground, and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we will assist in measuring, to the best of our skill and ability, and in accordance with the instructions given us in the survey

of the *Exterior Lines of T. 2 N. R. 32 & 33 E. T. 4 N. R. 34 & 35 E* lines of ~~*T. 3 N. R. 33. 34. 35 & 36 East.*~~ Willamette Meridian, Oregon.

J. S. Medley, Chainman.
W. H. Medley, Chainman.
Frank Belshaw, Chainman.
Guy Davis, Chainman.

Subscribed and sworn to before me this *14th* day of *June*, 188*7*



James P. Currier
U.S. Deputy Surveyor.


We, *B. B. Cronner* and *H. Beach*, do solemnly

swear that we will well and truly perform the duties of Axmen in the establishment of corners and other duties, according to instructions given us, and to the best of our skill and ability, in the survey of the

Exterior Lines of T. 2 N. R. 32 & 33 E. T. 4 N. R. 34 & 35 E
T. 3 N. R. 33. 34. 35 & 36 E. Willamette Meridian, Oregon.

B. B. Cronner, Axman.
H. Beach, Axman.

Subscribed and sworn to before me this *14th* day of *June*, 188*7*



James P. Currier
U.S. Deputy Surveyor.

Exteriors of T. 4 North R. 34 East

Willamette Meridian, Oregon.

I first took an observation in Polaris and tested my compass on line thus established and found it to be correct.

(8093-10 M.)

Commencing on line bet Tps -
4 N. R. 34 & 35 E, at Cor to Secs
13, 18, 19, & 24, which is a basalt stone
buried in the ground (Initial Point
to all surveys in vicinity)

Thence I run South on true line on
E bdy sec 24, Var 20° E

Across field

5550 To W. R. R. by set a basalt stone
12x6x4 ins - 8 ins in ground for man-
der Cor to sees 19 & 24, Dug a pit
3 ft square 1 ft deep. S. of stone
8 lbs dist raised mound of earth
2 ft high $4\frac{1}{2}$ ft base alongside
marked stone W. R. M. Co.

56.25 Wild Horse Creek 5 lbs wide Course W.

60.50 Kalla Kalla branch R. R. Course W.

61.75 Wagon Road Course W. & E.

62.25 Enter field

80 00 Found old pits & mound for C.

Extensions of T. 4 North R. 34 East

Willamette Meridian, Oregon.

(8093-10 M.)

From Con to Tps. 34 N. R. 34 & 35 E,
From W on random bet Tps. 34 & 35 N,
R 34 E. = Var. $19^{\circ} 45' E$

Set temporary half mile and
mile corners at each 40 & 80 Chs. at
3 miles I found the Cor to Decs
3, 4, 33 & 34 to be 40 less N of line

From this Cor which is a post in earth
'mound with pits, I run $S 89^{\circ} 54' E$
on true line bet Dec 3 & 34,

Var $21^{\circ} E$.

1350 Intersect W R. bdy at meander Cor
Set a basalt stone $9 \times 8 \times 7$ ins, 6 ins
in the ground for meander Cor to frac-
tional Decs. 3 & 34, marked W R. M.
C., Dug a pit 3 ft square and 1 ft deep
8000 E. of Cor and raised a mound
of earth 2 ft high $4\frac{1}{2}$ ft base alongside

4000 Set a post $36 \times 3 \times 3$ ins, 12 ins in
the ground for $1/4$ Dec Cor marked
 $1/4$ on N face. Dug pits $78 \times 18 \times 12$ ins

FINAL OATHS FOR SURVEYS.

A list of the names of the individuals employed by Gas. P. Currier & Gas. E. Poland, U. S. Deputy Surveyor, to assist in running, measuring, and marking the lines and corners described in the foregoing field notes of the survey of the Exterior lines of T. 2 N. R. 32 & 33 E. lines of T. 4 N. R. 34 & 35 E. & T. 3 N. R. 33, 34, 35 & 36 E. Willamette Meridian, Oregon, showing the respective capacities in which they acted:

- L. J. Woolley, Compassman.
- Frank Belshaw, Chainman.
- Guy Davis, Chainman.
- H. J. Medley, Chainman.
- J. S. Medley, Chainman.
- Barny Crommer, Axman.
- J. R. Hadley, Axman.
- _____, Flagman.

FINAL OATHS OF ASSISTANTS.

We hereby certify that we assisted Gas. P. Currier & Gas. E. Poland, U. S. Deputy Surveyor, in surveying all those parts or portions of the Exterior lines of T. 2 N. R. 32 & 33 E. T. 4 N. R. 34 & 35 E. & T. 3 N. R. 33, 34, 35 & 36 E. Willamette Meridian, Oregon, as represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the U. S. Surveyor General of Oregon.

- L. J. Woolley, Compassman.
- J. S. Medley, Chainman.
- H. J. Medley, Chainman.
- Frank Belshaw, Chainman.
- Guy Davis, Chainman.
- B. B. Crommer, Axman.
- J. R. Hadley, Axman.
- _____, Flagman.

Subscribed and sworn to before me this 30th day of Sept, 1887.

[SEAL.]

James P. Currier
U. S. Surveyor

FINAL OATH OF DEPUTY SURVEYOR.

I, James P. Leurrin & James E. Toland, United States
 Deputy Surveyor, do solemnly swear that in pursuance of instructions
 received from Douglas H. Taylor, U. S.
 Surveyor General for Oregon, bearing date of the 13th
 day of May, 1887^{vol}, I have well, faithfully,
 and truly, in my own proper person, and in strict conformity with the
 instructions furnished by the U. S. Surveyor General for Oregon, the
 Surveying Manual, and the laws of the United States, surveying all
 those parts or portions of the Exterior Lines of T. 2 N. R. 32 & 33

& T. 4 N. R. 34 & 35 E. & T. 3 N. R. 33. 34. 35 & 36 E.

Willamette Meridian, in the State of Oregon, as are represented in the
 foregoing field notes as having been surveyed by me and under my
 directions; and I do further solemnly swear that all the corners of said
 survey have been established and perpetuated in strict accordance with
 the Surveying Manual, printed instructions, the special written instruc-
 tions of the U. S. Surveyor General for Oregon, and in the specific man-
 ner described in the field notes, and that the foregoing are the *true* field
 notes of such survey, and should any fraud be detected I will suffer the
 penalty of perjury under the provisions of an act of Congress approved
 August 8, 1846.

James P. Leurrin James E. Toland
 U. S. Deputy Surveyor.

Subscribed and sworn to before me this Fifteenth
 day of February, 1888.

Alfred Woodcock
 Notary Public
 for Oregon

Office of U. S. Surveyor General,

Portland, Oregon, June 19th, 1888.

^{for copying}
The following Field Notes of the Survey of the

Interior lines of T. 2 N Rqs

32 + 33 E. T. 4 N Rqs 34 + 35. E

and T. 3 N. Rqs 33 34 35 + 36 East

Will May Or.

executed by James J. Currier and James E. Nolan

Special Joint U. S. Dept. Surveyors-
under his Contract No. _____, dated May

4th

_____, 1887, having been critically examined,
the necessary corrections and explanations made, the
said Field Notes and the survey they describe, are
hereby approved.

Douglas W. Taylor -

Surveyor General.