UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

	REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,
	TOWNSHIP 4 SOUTH, RANGE 30 EAST,
AND PROTECTION AND A PROCESS OF THE PROPERTY O	
Of the	heMeridian,
In the State of	OREGON
	EXECUTED BY
	Craig L. Wanless, Cadastral Surveyor
Under special ins	tructions dated May 3, 1957, approved May 6, 1957,
	, which provided for the surveys included under U.S. Survey/Group
Number 350	
	Survey commenced April 18 , 1978

Survey completed May 23

INDEX DIAGRAM

	Towns	hip 4 South	1.	, Range30	East	and the second s	
	6	5 15	4	3	11 2	7 1	3
4	7	14 8	9	10	11	12	
<u>4</u> <u>3</u>	18	17	16	15	10 14 9 10	13	2
	19	20	21	22	23 8 9	24	1
	30	29	28	27	26	25	1
	31	32	12 33	34	35	36	

CHAINS

- A sawed larch stump, 20 ins. diam., bears S. 60° W., 30 lks. dist., no marks visible.
- A pine, 28 ins. diam., bears N. 24° W., 37 1ks. dist., with scribe marks T4S R29E S12 visible on open blaze. (Record, N. 28° W., 43 1ks.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, inside pine stump, with brass cap mkd.

T 4 S
R 29 E R 30 E
S 12 S 7
S 13 S 18
1978

from which new bearing trees

- A fir, 15 ins. diam., bears N. $59\frac{1}{2}$ ° E., 52 1ks. dist., mkd. T4S R30E S7 BT.
- A fir, 14 ins. diam., bears S. 85° E., 41 1ks. dist., mkd. T4S R30E S18 BT.
- A fir, 18 ins. diam., bears S. $53\frac{1}{2}^{\circ}$ W., 68 1ks. dist., mkd. T4S R29E S13 BT.

Subdivisions, T. 4 S., R. 30 E., Willamette Meridian, Oregon

(Remonumenting corners established by George S. Pershin, U. S. Deputy Surveyor, in 1882)

The cor. of secs. 25, 26, 35, and 36, monumented with the original unmarked basalt stone, $15 \times 10 \times 5$ ins., firmly set 4 ins. in the ground, and in a mound of stone, 2 ft. base, 6 ins. high, from which the remains of the original bearing trees:

- A sawed pine stump, 20 ins. diam., bears N. 80° E., 96 lks. dist., with scribe marks BT visible on open blaze.
- A pine, 24 ins. diam., bears S. 57° E., 85 1ks. dist., with healed blaze. (Record, 75 1ks.)
- A pine, 30 ins. diam., bears S. 55° W., 43 1ks. dist., with scribe marks T4S R30E visible on open blaze. (Record, S. 48° W.)
- A sawed pine stump, 26 ins. diam., bears N. 77° W., 82 lks. dist., with scribe marks BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

CHAINS

F 4 S R 30 E S 26 S 25 S 35 S 36 1978

from which new bearing trees

- A ponderosa pine, 17 ins. diam., bears N. 30° E., $114\frac{1}{2}$ 1ks. dist., mkd. T4S R30E S25 BT.
- A ponderosa pine, 15 ins. diam., bears N. $8\frac{1}{2}^{\circ}$ W., 49 lks. dist., mkd. T4S R30E S26 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 13, 14, 23, and 24, monumented with the original basalt stone, $15 \times 10 \times 5$ ins., firmly set 6 ins. in the ground, and in a mound of stone, 3 ft. base, 6 ins. high, mkd. with 1 notch on E. and 3 notches on S. edges, from which the remains of the original bearing trees:

- A pine, 16 ins. diam., bears N. 20° E., 11 1ks. dist., with scribe marks T4S R30E BT visible on open blaze.
- A root hole, bears S. 85° E., 100 lks. dist., with a down and decayed pine alongside, size indeterminate, with scribe marks T4S R30E S24 BT visible on open blaze.
- A pine, 14 ins. diam., bears S. 68° W., 8 1ks. dist., with scribe marks T4S R30E S23 BT visible on open blaze. (Record, S. 58° W.)
- A pine snag, 15 ins. diam., bears N. 73° W., 14 lks. dist., with scribe marks T4S R30E S14 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 30 E S 14 S 13 S 23 S 24 1978

from which new bearing trees

- A fir, 15 ins. diam., bears S. $38\frac{1}{2}^{\circ}$ E., 75 1ks. dist., mkd. T4S R30E S24 BT.
- A ponderosa pine, 15 ins. diam., bears N. 79° W., 23 1ks. dist., mkd. T4S R30E S14 BT.

Deposit corner stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 13 and 24, monumented with the original basalt stone, 18 x 12 x 5 ins., firmly set 6 ins. in the ground, and in a mound of stone, 4 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on N. face, from which the original bearing tree:

CHAINS

A pine, 40 ins. diam., bears S. 23° E., 170 1ks. dist., with healed blaze. (Record, 157 1ks.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

from which a new bearing tree

A ponderosa pine, 17 ins. diam., bears N. 1° E., 116 1ks. dist., mkd. ½ S13 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 11, 12, 13, and 14, monumented with a mound of stone, 4 ft. base, 1 ft. high, from which the remains of the original bearing trees:

- A pine, 45 ins. diam., bears N. 28° E., 205 1ks. dist., with healed blaze.
- A pine stump, 24 ins. diam., bears S. 83° E., 113 lks. dist., with a down pine alongside, 24 ins. diam., with scribe marks T4S R30E S13 visible on open blaze. (Record, 76 lks.)
- A pine, 33 ins. diam., bears S. 78° W., 56 lks. dist., with healed blaze. (Record, 113 lks.)
- A pine, 25 ins. diam., bears N. 76° W., 81 1ks. dist., no marks visible on partially open blaze. (Record, 56 1ks.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 30 E S 11 S 12 S 14 S 13 1978

from which a new bearing tree

A ponderosa pine, 10 ins. diam., bears S. 46° E., $70\frac{1}{2}$ 1ks. dist., mkd. T4S R30E S13 BT.

The ½ sec. cor. of secs. 1 and 2, determined at record bearing and distance from the remains of an original bearing tree:

A sawed pine stump, 16 ins. diam., bears S. 84° W., 64 lks. dist., with scribe marks ¼ S visible on open blaze.

At the corner point

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4 S R 30 E

1/4

S 2 | S 1

1978

from which new bearing trees

- A ponderosa pine, 19 ins. diam., bears S. $32\frac{1}{2}$ ° E., 64 lks. dist., mkd. ½ S1 BT.
- A fir, 14 ins. diam., bears N. 47° W., 86 1ks. dist., mkd. ½ S2 BT.

The cor. of secs. 26, 27, 34, and 35, determined at record distance from the remains of the original bearing trees:

- A decayed fir stump, size indeterminate, bears N. 44° E., 38 lks. dist., no marks visible. (Record, N. 40° E.)
- A pine, 30 ins. diam., bears S. 5° E., 38 lks. dist., with fragmentary scribe marks visible on open blaze. (Record, S. 50° E.)
- A sawed fir stump, 32 ins. diam., bears S. 74° W., 54 lks. dist., with healed blaze. (Record, S. 66° W.)
- A pine, 17 ins. diam., bears N. 5° W., 41 1ks. dist., with scribe marks T4S R30E S27 visible on open blaze. (Record, N. 14° W.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

F 4 S R 30 E S 27 S 26 S 34 S 35 1978

from which new bearing trees

- A ponderosa pine, 7 ins. diam., bears N. $84\frac{1}{2}^{\circ}$ E., 11 lks. dist., mkd. T4S R30E S26 BT.
- A ponderosa pine, 24 ins. diam., bears S. 59° W., 144 lks. dist., mkd. T4S R30E S34 BT.

The cor. of secs. 22, 23, 26, and 27, determined at record bearing and distance from the original bearing trees:

- A pine, 40 ins. diam., bears S. 14° E., 34 1ks. dist., with fragmentary scribe marks visible on partially open blaze.
- A pine, 32 ins. diam., bears S. 65° W., 98 1ks. dist., with scribe marks T4S R30E S27 visible on open blaze.

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 4 S R 30 E S 22 S 23 S 27 S 26 1978

from which new bearing trees

A ponderosa pine, 9 ins. diam., bears N. $2\frac{1}{2}^{\circ}$ E., $127\frac{1}{2}$ 1ks. dist., mkd. T4S R30E S23 BT.

A ponderosa pine, 17 ins. diam., bears N. 42° W., 67 lks. dist., mkd. T4S R30E S22 BT.

The ½ sec. cor. of secs. 23 and 26, determined at record distance from the remains of the original bearing trees:

A pine, 28 ins. diam., bears N. 41° W., 21 1ks. dist., with scribe marks ¼ S visible on open blaze. (Record, N. 34° W.)

A root hole, bears S. 44° W., 29 lks. dist., with a down pine alongside, 21 ins. diam., with scribe marks ½ S visible on opened blaze.

Corner is located in center of creek, 15 lks. wide, course S. 70° E., where it is impracticable to establish a permanent monument.

from the corner point, a new bearing tree and reference monuments

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears N. 30° E., 25 lks. dist., with brass cap mkd. T4S R30E ½ S23 RM 1978 and an arrow pointing to the corner.

A fir, 11 ins. diam., bears S. 19° W., 30 1ks. dist., mkd. ½ S26 BT.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears S. 30° W., 30 lks. dist., with brass cap mkd. T4S R30E ½ S26 RM 1978 and an arrow pointing to the corner.

The cor. of secs. 14, 15, 22, and 23, monumented with the original basalt stone, 17 x 12 x 5 ins., firmly set 6 ins. in the ground, and in a mound of stone, 2 ft. base, 6 ins. high, mkd. with 3 notches on S. and 2 notches on E. edges, from which the remains of the original bearing trees:

A root hole, bears N. 55° E., 62 lks. dist., with a down and decayed larch alongside, size indeterminate, no marks visible.

A root hole, bears S. 48° E., 40 lks. dist., with a down fir alongside, 22 ins. diam., with fragmentary scribe marks visible on open blaze.

CHAINS

A larch, 14 ins. diam., bears S. 70° W., 14 1ks. dist., with scribe mark S visible on opened blaze. (Record, 11 1ks.)

CHE CALL TO THE STATE OF THE

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 4 S R 30 E
S 15 S 14
S 22 S 23
1978

from which new bearing trees

A white fir, 8 ins. diam., bears N. 28° E., 32 lks. dist., mkd. T4S R30E S14 BT.

A white fir, 30 ins. diam., bears S. 40° E., 75 lks. dist., mkd. T4S R30E S23 BT.

A white fir, 22 ins. diam., bears N. 44° W., 48 lks. dist., mkd. T4S R30E S15 BT.

Deposit corner stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 14 and 23, monumented with the original unmarked basalt stone, 12 x 8 x 4 ins. (record, 12 x 10 x 8 ins.), firmly set 4 ins. in the ground, and in a mound of stone, 2 ft. base, 6 ins. high, from which the original bearing tree:

A pine, 32 ins. diam., bears S. 48° E., 72 1ks. dist., with healed blaze. (Record, S. 40° E.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 30 E $\frac{1}{4} = \frac{\frac{14}{5}}{\frac{1978}{5}}$

from which a new bearing tree

A ponderosa pine, 17 ins. diam., bears N. 6° W., 45 lks. dist., mkd. ½ S14 BT.

Deposit corner stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, monumented with the original basalt stone, 12 x 10 x 8 ins., firmly set 4 ins. in the ground, and in a mound of stone, 3 ft. base, 6 ins. high, mkd. $\frac{1}{4}$ on W. face, from which the original bearing trees:

A pine, 24 ins. diam., bears N. 88° E., 86 1ks. dist., with scribe marks ¼ S visible on open blaze. (Record, 74 1ks.)

CHAINS

A pine, 40 ins. diam., bears S. 10° W., 98 1ks. dist., with scribe marks ¼ visible on open blaze. (Record, 73 1ks.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 30 E

S 15 | S 14

1978

Deposit corner stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented with the original unmarked basalt stone, 15 x 8 x 6 ins., firmly set 6 ins. in the ground, from which the remains of the original bearing trees:

- A sawed pine stump, 24 ins. diam., bears East, 65 lks. dist., with scribe marks BT visible on open blaze.
- A sawed pine stump, 22 ins. diam., bears N. 58° W., 46 lks. dist., with scribe marks BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4 S R 30 E

\$\frac{1}{4}\$
S 3 | S 2

1978

from which new bearing trees

- A white fir, 9 ins. diam., bears N. 56° E., 21 lks. dist., mkd. ¼ S2 BT.
- A ponderosa pine, 12 ins. diam., bears N. 53° W., 6 1ks. dist., mkd. ½ S3 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 15, 16, 21, and 22, determined at record bearing and distance from the remaining original bearing trees:

- A pine, 54 ins. diam., bears N. 24° E., 47 lks. dist., with scribe marks T4S R30E S15 visible on open blaze.
- A pine, 22 ins. diam., bears S. 46° W., 55 lks. dist., with scribe marks T4S R30E S21 visible on open blaze.
- A pine, 25 ins. diam., bears N. 45° W., 8 1ks. dist., with scribe marks T4S R30E S16 visible on open blaze.

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

e su sidialy a simple spicios diving . Defr-

T 4 S R 30 E

S 16 S 15

S 21 S 22

1978

from which a new bearing tree

A ponderosa pine, 15 ins. diam., bears S. 65° E., 105 lks. dist., mkd. T4S R30E S22 BT.

The original NW. bearing tree is a fence corner, fence extends N., E., and W.

The cor. of secs. 9, 10, 15, and 16, monumented with the original basalt stone, $20 \times 6 \times 5$ ins., firmly set 6 ins. in the ground, and in a mound of stone, 3 ft. base, 1 ft. high, mkd. with 4 notches on S. and 3 notches on E. edges, from which the remains of the original bearing trees:

- A sawed pine stump, 28 ins. diam., bears N. 45° E., 20 lks. dist., no marks visible. (Record, N. 55° E.)
- A pine, 22 ins. diam., bears S. 56° E., 58 1ks. dist., with healed blaze.
- A root hole, bears S. 67° W., 24 lks. dist., with a down pine alongside, 26 ins. diam., with scribe marks T4S R30E S16 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 30 E S 9 S 10 S 16 S 15 1978

from which new bearing trees

- A white fir, 10 ins. diam., bears N. $76\frac{1}{2}^{\circ}$ E., 13 lks. dist., mkd. T4S R30E S10 BT.
- A fir, 8 ins. diam., bears S. 53½° W., 47 1ks. dist., mkd. T4S R30E S16 BT.
- A larch, 8 ins. diam., bears N. $55\frac{1}{2}^{\circ}$ W., 38 1ks. dist., mkd. T4S R30E S9 BT.

Deposit corner stone and set a 5 ft. steel fence post alongside iron post.

The ½ sec. cor. of secs. 32 and 33, determined at record bearing and distance from the remains of the original bearing trees:

CHAINS

- A root hole, bears S. 84° E., 70 lks. dist., with a down and decayed pine alongside, size indeterminate, with scribe marks ½ S BT visible on open blaze.
- A pine, 30 ins. diam., bears N. 82° W., 73 lks. dist., with scribe marks ¼ S visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 30 E

S 32 | S 33

1978

from which a new bearing tree

A ponderosa pine, 14 ins. diam., bears S. 69° E., $75\frac{1}{2}$ 1ks. dist., mkd. $\frac{1}{4}$ S33 BT.

The cor. of secs. 16, 17, 20, and 21, monumented with the original basalt stone, $15 \times 8 \times 5$ ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. with 4 notches on E. and 3 notches on S. edges, from which the remains of the original bearing trees:

- A pine, 34 ins. diam., bears N. 18° E., 80 lks. dist., with scribe marks T4S R30E S16 visible on open blaze.
- A root hole, bears N. 18° W., 104 lks. dist., with a down and decayed pine alongside, size indeterminate, with scribe marks T4S R30E S17 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 30 E S 17 S 16 S 20 S 21 1978

from which new bearing trees

- A fir, 11 ins. diam., bears S. $78\frac{1}{2}$ ° E., 41 1ks. dist., mkd. T4S R30E S21 BT.
- A ponderosa pine, 9 ins. diam., bears S. 66° W., 15 1ks. dist., mkd. T4S R30E S20 BT.
- A fir, 11 ins. diam., bears N. 67° W., $60\frac{1}{2}$ 1ks. dist., mkd. T4S R30E S17 BT.

Deposit corner stone alongside iron post.

CHAINS

The cor. of secs. 19, 20, 29, and 30, monumented with the original unmarked basalt stone, $17 \times 8 \times 5$ ins., firmly set in a mound of stone, 2 ft. base, 6 ins. high, from which the original bearing tree:

A pine, 34 ins. diam., bears S. 85° W., 137 1ks. dist., with scribe marks R30E S30 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 30 E S 19 S 20 S 30 S 29 1978

from which a new bearing tree

A ponderosa pine, 18 ins. diam., bears S. 4½° E., 211 1ks. dist., mkd. T4S R30E S29 BT.

No other suitable trees available wtihin limits.

Deposit corner stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 17 and 20, monumented with the original basalt stone, 14 x 8 x 6 ins., firmly set 5 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, from which the original bearing trees:

A pine, 22 ins. diam., bears N. 26° E., 20 1ks. dist., with healed blaze. (Record, N. 22° E.)

A pine, 37 ins. diam., bears S. 88° W., 46 1ks. dist., with scribe marks ¼ S visible on open blaze. (Record, 43 1ks.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit corner stone alongside iron post.

The ½ sec. cor. of secs. 7 and 8, determined at record bearing and distance from the remains of an original bearing tree:

A sawed pine stump, 36 ins. diam., bears S. 36° E., 96 lks. dist., with scribe mark S visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 30 E

14

S 7 | S 8

1978

from which new bearing trees

A ponderosa pine, 12 ins. diam., bears S. 60° E., 88 lks. dist., mkd. ½ S8 BT.

A ponderosa pine, 10 ins. diam., bears S. 66° W., 88 lks. dist., mkd. ½ S7 BT.

The cor. of secs. 5, 6, 7, and 8, monumented with the original unmarked basalt stone, $14 \times 8 \times 6$ ins., firmly set 6 ins. in the ground, and in a mound of stone, 3 ft. base, 1 ft. high, from which the original bearing trees:

A pine, 29 ins. diam., bears S. 76° W., 125 lks. dist., with healed blaze.

A pine, 33 ins. diam., bears N. 64° W., 58 lks. dist., with scribe marks T4S R30 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 30 E S 6 S 5 S 7 S 8 1978

from which a new bearing tree

A fir, 11 ins. diam., bears N. 15½° E., 175 1ks. dist., mkd. T4S R30E S5 BT.

No suitable tree available in SW. quadrant.

Deposit corner stone alongside iron post.

Form 9180-8 (March 1969)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Edward W. Moye	Engineering Aid

The fill lavorage to the most sense will be read to the fill the control of the c

CERTIFICATE OF SURVEY

(I) (XVEX, Craig L. Wanless, Cadastral Surveyor , HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day

of May , 19 57, (I) (XVEX) have remonumented certain original corner

points, township 4 south, range 30 east,

Meridian, in the State of Oregon , which are represented in the foregoing field notes as having been executed by (me), (me) and under (my) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 19, 1978

(Date)

Cray L. Wanless
(Cadastral Surveyor)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

Bureau of Land Management Washington, D.C.
Denver Colorado

4 1

The foregoing field notes of the remonumentation of certain original corner points, township 4 south, range 30 east, Willamette Meridian, Oregon,

executed by Craig L. Wanless, Cadastral Surveyor,
having been critically examined and found correct, are hereby approved.

FEB 07 1980

(Date)

(Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in , is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) 6P0 849 62