

INDEX DIAGRAM

Township 4 South, Range 29 East,

6	5	4	3	2	1
7	8	9	10	<u>4</u> 11	12
	<u>8</u>	<u>6</u>	<u>5</u>	<u>4</u>	
18	17	16	15	14	13
<u>8</u>	<u>7</u> <u>7</u>	<u>5</u>		<u>3</u>	<u>3</u>
19	20	21	22	23	24
<u>6</u>					
30	29	28	27	26	25
31	32	33	34	35	36
	<u>1</u>				

2

1

T. 4 S., R. 29 E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 4 south, range 29 east, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories when Needed".

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

South Boundary, T. 4 S., R. 29 E.,
Willamette Meridian, Oregon

(Remonumenting a corner established by Edward W. Sanderson U. S. Deputy Surveyor, in 1882, and changed to a corner of minimum control by Frank W. Campbell, U. S. Deputy Surveyor, in 1883)

The $\frac{1}{4}$ sec. cor. of sec. 32 only, on the S. bdy. of the Tp., monumented with the original basalt stone, 15 x 8 x 4 ins., firmly set 6 ins. in the ground, in a collar of stone, mkd. $\frac{1}{4}$ on N. face, from which the remains of the original bearing trees:

A root hole, bears N. 70° W., 75 lks. dist., with a down pine alongside, 10 ins. diam., no marks visible on opened blaze. (Record, N. 60° W.)

A pine, 32 ins. diam., bears S. 15° E., 120 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4 S R 29 E
 $\frac{1}{4}$ S 32
1977

from which new bearing trees

A lodgepole pine, 15 ins. diam., bears N. 32° E., 61 lks. dist., mkd. $\frac{1}{4}$ S32 BT.

A lodgepole pine, 13 ins. diam., bears N. 62° W., 58 lks. dist., mkd. $\frac{1}{4}$ S32 BT.

Deposit corner stone alongside iron post.

East Boundary, T. 4 S., R. 29 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by Edward W. Sanderson, U. S. Deputy Surveyor, in 1882)

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 29 E., Willamette Meridian, Oregon

CHAINS

The cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., determined at record bearing and distance from the remains of the original bearing trees:

A pine snag, 11 ins. diam., bears S. 48° E., 44 lks. dist., with scribe marks T4S R30E S31 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4 S	
R 29 E	R 30 E
S 25	S 30
S 36	S 31
1977	

from which new bearing trees

A lodgepole pine, 6 ins. diam., bears N. 84° E., 44 lks. dist., mkd. T4S R30E S30 BT.

A lodgepole pine, 11 ins. diam., bears S. 10° E., 26 lks. dist., mkd. T4S R30E S31 BT.

A lodgepole pine, 13 ins. diam., bears S. 29° W., 36 lks. dist., mkd. T4S R29E S36 BT.

A larch, 12 ins. diam., bears N. 11° W., 8½ lks. dist., mkd. T4S R29E S25 BT.

The cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with the original unmarked basalt stone, 15 x 8 x 5 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, from which the remains of the original bearing trees:

A pine, 18 ins. diam., bears N. 20° E., 67 lks. dist., with healed blaze.

A sawed pine stump, 34 ins. diam., bears S. 38° E., 222 lks. dist., with scribe marks BT visible on open blaze. (Record, 168 lks.)

A pine, 24 ins. diam., bears N. 61° W., 84 lks. dist., with scribe marks R29 visible on open blaze. (Record, 72 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S	
R 29 E	R 30 E
S 24	S 19
S 25	S 30
1977	

from which new bearing trees

A grand fir, 13 ins. diam., bears S. 45° E., 53 lks. dist., mkd. T4S R30E S30 BT.

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 29 E., Willamette Meridian, Oregon

CHAINS

A lodgepole pine, 8 ins. diam., bears S. 52° W.,
47 lks. dist., mkd. T4S R29E S25 BT.

Deposit corner stone alongside iron post.

Subdivisions, T. 4 S., R. 29 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by Edward W. Sanderson,
U. S. Deputy Surveyor, in 1882)

The cor. of secs. 13, 14, 23, and 24, monumented with the
original unmarked basalt stone, 18 x 8 x 6 ins., firmly
set 6 ins. in the ground, in a collar of stone, from
which the remains of the original bearing trees:

A root hole, bears N. 30° E., 61 lks. dist., with
a down pine alongside, 38 ins. diam., with scribe
marks T4S R29E S13 BT visible on open blaze.

A fir, 25 ins. diam., bears S. 21° E., 45 lks.
dist., with fragmentary scribe marks visible
on open blaze. (Record, S. 32° E.)

A pine, 35 ins. diam., bears S. 25° W., 16 lks.
dist., with scribe marks T4S R29E S23 visible
on open blaze.

A pine, 24 ins. diam., bears N. 50° W., 71 lks.
dist., with scribe marks T4S R29E S14 visible
on open and burned blaze. (Record, 78 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, in a mound of stone, 2 ft. base, to top,
with brass cap mkd.

T 4 S R 29 E
S 14 S 13
S 23 S 24
1977

from which a new bearing tree

A grand fir, 16 ins. diam., bears N. 35° E., 18½
lks. dist., mkd. T4S R29E S13 BT.

Deposit corner stone alongside iron post.

Corner is located 95 lks. south of wire fence, extending
S. 80° E. and N. 80° W.

The cor. of secs. 14, 15, 22, and 23, monumented with the
original unmarked sandstone, 15 x 12 x 7 ins., firmly
set 5 ins. in the ground, from which the original bearing
trees:

A pine, 28 ins. diam., bears N. 40° E., 46 lks.
dist., with scribe marks T4S R29 S14 visible
on open and burned blaze.

CERTIFICATE OF SURVEY

(I) (~~WE~~), Craig L. Wanless, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May, 19 57, (I) (~~WE~~) have remonumented certain original corner points, township 4 south, range 29 east,

of the Willamette Meridian, in the State of Oregon, which are represented in the foregoing field notes as having been executed by (me), (~~US~~) and under (my) (~~own~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 16, 1978
(Date)

Craig L. Wanless
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the remonumentation of certain original corner points, township 4 south, range 29 east, Willamette Meridian, Oregon,

executed by Craig L. Wanless, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

AUG 17 1978
(Date)

J. Voorhees
Acting (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849 626