

INDEX DIAGRAM

Township 4 South, Range 31 East,

6	<u>4</u>	5	4	3	2	1
		<u>4</u>	<u>3</u>			<u>1</u>
7	8	<u>3</u>	9	10	11	12
		<u>2</u>				
18	17	16	15	14	13	
19	20	21	22	23	24	
				<u>2</u>		
30	29	28	27	26	25	
31	32	33	34	35	36	

T. 4 S., R. 31 E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 4 south, range 31 east, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories when Needed".

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° 30' E.

Subdivisions, T. 4 S., R. 31 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by George S. Pershin,
U. S. Deputy Surveyor, in 1880)

The cor. of secs. 1, 2, 11, and 12, monumented with the original unmarked basalt stone, 17 x 12 x 8 ins., firmly set 4 ins. in the ground, and in a mound of stone, 3 ft. base, 1 ft. high, from which the remains of the original bearing trees:

A pine, 22 ins. diam., bears N. 38° E., 125 lks. dist., with healed blaze.

A sawed and decayed pine stump, size indeterminate, bears S. 77° E., 118 lks. dist., no marks visible. (Record, 115 lks.)

A sawed pine stump, 34 ins. diam., bears N. 21° W., 164 lks. dist., with fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 31 E
S 2 S 1
S 11 S 12
1978

from which new bearing trees

A ponderosa pine, 11 ins. diam., bears S. 71° E., 41 lks. dist., mkd. T4S R31E S12 BT.

A ponderosa pine, 13 ins. diam., bears S. 17° W., 24½ lks. dist., mkd. T4S R31E S11 BT.

A ponderosa pine, 14 ins. diam., bears N. 39° W., 131 lks. dist., mkd. T4S R31E S2 BT.

Deposit corner stone alongside iron post.

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 31 E., Willamette Meridian, Oregon

CHAINS

The cor. of secs. 22, 23, 26, and 27, determined at record bearing and distance from the remains of an original bearing tree:

A sawed pine stump, 40 ins. diam., bears S. 15° W., 100 lks. dist., with scribe marks BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4 S R 31 E
S 22 S 23
S 27 S 26
1978

from which new bearing trees

A ponderosa pine, 7 ins. diam., bears N. 17° E., 46½ lks. dist., mkd. T4S R31E S23 BT.

A ponderosa pine, 12 ins. diam., bears S. 29½° E., 28 lks. dist., mkd. T4S R31E S26 BT.

A ponderosa pine, 13 ins. diam., bears S. 30° W., 65½ lks. dist., mkd. T4S R31E S27 BT.

A ponderosa pine, 7 ins. diam., bears N. 25° W., 14 lks. dist., mkd. T4S R31E S22 BT.

Corner is located at intersection of fence lines, fences extend N., W., and S. 45° W.

The cor. of secs. 8, 9, 16, and 17, monumented with the original basalt stone, 18 x 12 x 4 ins., firmly set 10 ins. in the ground, and in a mound of stone, 2 ft. base, 6 ins. high, mkd. with 4 notches on E. and S. edges, from which the remains of the original bearing trees:

A decayed fir stump, size indeterminate, bears N. 41° E., 60 lks. dist., no marks visible.

A pine, 28 ins. diam., bears S. 40° W., 50 lks. dist., with healed blaze.

A root hole, bears N. 36° W., 42 lks. dist., with scribe marks T4S R31E S8 visible on piece of fir wood lying alongside.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 31 E
S 8 S 9
S 17 S 16
1978

from which new bearing trees

A fir, 6 ins. diam., bears N. 46° E., 23 lks. dist., mkd. T4S R31E S9 BT.

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 31 E., Willamette Meridian, Oregon

CHAINS

A fir, 10 ins. diam., bears S. 39° E., $64\frac{1}{2}$ lks. dist., mkd. T4S R31E S16 BT.

A fir, 17 ins. diam., bears N. $50\frac{1}{2}^{\circ}$ W., 89 lks. dist., mkd. T4S R31E S8 BT.

Deposit corner stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, monumented with the original basalt stone, 15 x 12 x 4 ins., firmly set 6 ins. in the ground, and in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on N. face, from which the original bearing tree:

A pine, 30 ins. diam., bears N. 22° E., 225 lks. dist., with healed blaze. (Record, 230 lks.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 31 E
 $\frac{1}{4}$
S 8 | S 9
1978

from which a new bearing tree

A ponderosa pine, 25 ins. diam., bears N. 7° W., 400 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

Deposit corner stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented with the original basalt stone, 18 x 10 x 8 ins., firmly set 10 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, from which the remains of an original bearing tree:

A root hole, bears N. 42° E., 240 lks. dist., with scribe marks BT visible on piece of pine wood lying alongside.

and bearing trees of which I have no record

A ponderosa pine, 12 ins. diam., bears N. 39° W., $69\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S4 BT RS691 visible on open blaze.

A ponderosa pine, 12 ins. diam., bears S. $79\frac{1}{2}^{\circ}$ E., 117 lks. dist., with scribe marks $\frac{1}{4}$ S9 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 31 E
 $\frac{1}{4}$ S 4
S 9
1978

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 31 E., Willamette Meridian, Oregon

CHAINS

Deposit corner stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 5 and 8, monumented with the original unmarked basalt stone, 14 x 12 x 10 ins., firmly set 6 ins. in the ground, and in a mound of stone, 2 ft. base, 6 ins. high, from which the remains of the original bearing trees:

A fir, 18 ins. diam., bears N. 12° E., 11 lks. dist., with scribe marks 4S visible on open blaze.

A pine snag, 25 ins. diam., bears South, 72 lks. dist., with scribe mark 4 visible on partially open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 31 E
 $\frac{1}{4}$ S 5
 S 8
 1978

from which a new bearing tree

A fir, 12 ins. diam., bears S. 39° W., 63 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

Deposit corner stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, determined at record bearing and distance from the remains of the original bearing trees:

A fir snag, 16 ins. diam., bears S. 75° E., 5 lks. dist., with fragmentary scribe marks visible on open blaze.

A pine, 25 ins. diam., bears N. 52° W., 42 lks. dist., with scribe mark 1 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4 S R 31 E
 $\frac{1}{4}$
 S 6 | S 5
 1978

from which a new bearing tree

A fir, 10 ins. diam., bears S. 85° E., 68½ lks. dist., mkd. $\frac{1}{4}$ S5 BT.

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Craig L. Wanless, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May, 19 57, (I) ~~(We)~~ have remonumented certain original corner points, township 4 south, range 31 east,

of the Willamette Meridian, in the State of Oregon, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 17, 1978 (Date) Craig L. Wanless (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C. Denver, Colorado

The foregoing field notes of the remonumentation of certain original corner points, township 4 south, range 31 east, Willamette Meridian, Oregon,

executed by Craig L. Wanless, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

FEB 07 1980 (Date) J. V. Vothke (Chief, Division of Cadastral Survey) Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-526