





# INDEX DIAGRAM

Township 4 South, Range 30 East

	6	5	4	3	<u>11</u> 2	<u>7</u> 1	
		<u>15</u>					<u>3</u>
	7	<u>14</u> 8	9	10	11	12	
<u>4</u>				<u>12</u>		<u>7</u>	
<u>4</u>	18	17	16	15	<u>10</u> 14	13	
<u>3</u>		<u>14</u>	<u>13</u>	<u>11</u>	<u>9</u> <u>10</u>	<u>6</u> <u>6</u>	<u>2</u>
	19	20	21	22	23	24	
		<u>14</u>			<u>8</u> <u>9</u>		<u>1</u>
	30	29	28	27	26	25	
					<u>8</u>	<u>5</u>	<u>1</u>
	31	32	<u>12</u> 33	34	35	36	



## T. 4 S., R. 30 E., Willamette Meridian, Oregon

## CHAINS

The following field notes describe the remonumentation of certain original corner points, township 4 south, range 30 east, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories when Needed".

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

East Boundary, T. 4 S., R. 30 E.,  
Willamette Meridian, Oregon

(Remonumenting corners established by George S. Pershin,  
U. S. Deputy Surveyor, in 1880)

The cor. of secs. 25, 30, 31, and 36, monumented with the original unmarked basalt stone, 14 x 12 x 5 ins., firmly set in a mound of stone, 2 ft. base, 1 ft. high, from which the remains of an original bearing tree:

A sawed pine stump, 26 ins. diam., bears S. 72° W.,  
32 lks. dist., with scribe marks BT visible on  
open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.  
in the ground, and in a mound of stone, 3 ft. base, to  
top, with brass cap mkd.

T 4 S			
R 30 E	R 31 E		
S 25	S 30		
S 36	S 31		
1978			

from which new bearing trees

A fir, 10 ins. diam., bears N. 30° E., 20 lks.  
dist., mkd. T4S R31E S30 BT.

A fir, 12 ins. diam., bears S. 46½° E., 27 lks.  
dist., mkd. T4S R31E S31 BT.

A ponderosa pine, 8 ins. diam., bears S. 6° W., 51  
lks. dist., mkd. T4S R30E S36 BT.

A fir, 12 ins. diam., bears N. 79° W., 25 lks.  
dist., mkd. T4S R30E S25 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 19, 24, 25, and 30, monumented with the original unmarked basalt stone, 20 x 12 x 8 ins., firmly set 10 ins. in the ground, and in a mound of stone, 2 ft. base, 1 ft. high, from which the remains of the original bearing trees:



Remonumentation of Certain Original Corner Points,  
T. 4 S., R. 30 E., Willamette Meridian, Oregon

CHAINS

A root hole, bears N. 48° E., 182 lks. dist., with a down pine alongside, 38 ins. diam., no marks visible on open blaze.

A pine, 35 ins. diam., bears S. 38° E., 196 lks. dist., with scribe marks T4S R31E S30 visible on open blaze.

A pine, 27 ins. diam., bears N. 78° W., 84 lks. dist., with scribe marks T4S R30E S19 visible on open blaze. (Record, N. 90° W., 92 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S			
R 30 E	R 31 E		
S 24	S 19		
S 25	S 30		
1978			

from which a new bearing tree

A ponderosa pine, 11 ins. diam., bears N. 75° E., 87 lks. dist., mkd. T4S R31E S19 BT.

No suitable tree available in SW. quadrant.

Deposit corner stone alongside iron post.

The cor. of secs. 13, 18, 19, and 24, monumented with the original unmarked basalt stone, 16 x 12 x 8 ins., firmly set in a mound of stone, 4 ft. base, 6 ins. high, from which the remains of the original bearing trees:

A pine stump, 38 ins. diam., bears N. 59° E., 53 lks. dist., no marks visible.

A pine, 33 ins. diam., bears S. 52° E., 57 lks. dist., with scribe marks S R31E S19 visible on open blaze. (Record, 61 lks.)

A root hole, bears S. 46° W., 78 lks. dist., with a down and decayed pine alongside, size indeterminate, with scribe marks T4S R30E S24 visible on open blaze. (Record, S. 34° W.)

A pine, 22 ins. diam., bears N. 54½° W., 77 lks. dist., with scribe marks S13 visible on open blaze. (Record, N. 68° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S			
R 30 E	R 31 E		
S 13	S 18		
S 24	S 19		
1978			

from which new bearing trees



Remonumentation of Certain Original Corner Points,  
T. 4 S., R. 30 E., Willamette Meridian, Oregon

## CHAINS

A fir, 14 ins. diam., bears N. 63° E., 34 lks. dist., mkd. T4S R31E S18 BT.

A fir, 11 ins. diam., bears S. 82° W., 48 lks. dist., mkd. T4S R30E S24 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 1, 6, 7, and 12, determined at record bearing and distance from the remaining original bearing trees:

A pine, 17 ins. diam., bears N. 34° E., 30 lks. dist., with scribe marks R31E S6 BT visible on open blaze.

A pine, 17 ins. diam., bears N. 35° W., 45 lks. dist., with scribe marks T4S R visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S	
R 30 E	R 31 E
S 1	S 6
S 12	S 7
1978	

from which new bearing trees

A fir, 13 ins. diam., bears S. 66° E., 37½ lks. dist., mkd. T4S R31E S7 BT.

A ponderosa pine, 17 ins. diam., bears S. 67° W., 60½ lks. dist., mkd. T4S R30E S12 BT.

West Boundary, T. 4 S., R. 30 E.,  
Willamette Meridian, Oregon

(Remonumenting corners established by Edward W. Sanderson  
U. S. Deputy Surveyor, in 1882)

The cor. of secs. 13, 18, 19, and 24, monumented with the original basalt stone, 14 x 10 x 5 ins., firmly set 4 ins. in the ground, mkd. with 3 notches on N. and S. edges, from which the remains of the original bearing trees:

A root hole, bears N. 45° E., 47 lks. dist., with a down pine alongside, 35 ins. diam., no marks visible.

A decayed larch stump, size indeterminate, bears S. 12° E., 40 lks. dist., no marks visible.

A larch, 20 ins. diam., bears N. 10° W., 43 lks. dist., with scribe marks 4S R29E visible on partially open blaze. (Record, 38 lks.)







CERTIFICATE OF SURVEY

(I) ~~(We)~~, Craig L. Wanless, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May, 19 57, (I) ~~(We)~~ have remonumented certain original corner points, township 4 south, range 30 east,

of the Willamette Meridian, in the State of Oregon, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 19, 1978 (Date) Craig L. Wanless (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C. Denver, Colorado

The foregoing field notes of the remonumentation of certain original corner points, township 4 south, range 30 east, Willamette Meridian, Oregon,

executed by Craig L. Wanless, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

FEB 07 1980 (Date) [Signature] (Chief, Division of Cadastral Survey) Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-626