

INDEX DIAGRAM

Township 4 South, Range 33 East,

6	5	<u>14</u> 4	3	2	1
		<u>13</u> <u>14</u>	<u>11</u>		
7	8	<u>13</u> 9	10	11	12
	<u>15</u>		<u>10</u>	<u>7</u>	
18	17	<u>12</u> 16	<u>10</u> 15	<u>7</u> 14	13
		<u>12</u>		<u>6</u>	
19	20	21	22	23	24
			<u>9</u>		
30	29	28	27	26	25
			<u>8</u> <u>9</u>	<u>5</u>	<u>5</u>
31	32	33	<u>8</u> 34	35	<u>4</u> 36 <u>3</u>
<u>3</u>	<u>2</u>				<u>1</u> <u>1</u>

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

	T 4 S	
R 33 E		R 33½ E
¼ S 36		
	1977	

from which new bearing trees

A lodgepole pine, 7 ins. diam., bears S. 46° W., 59 lks. dist., mkd. ¼ S36 BT.

A lodgepole pine, 7 ins. diam., bears N. 11° W., 31 lks. dist., mkd. ¼ S36 BT.

Deposit corner stone and set a 5 ft. steel fence post alongside iron post.

Subdivisions, T. 4 S., R. 33 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by George S. Pershin,
U. S. Deputy Surveyor, in 1881)

The ¼ sec. cor. of secs. 35 and 36, monumented with the original unmarked basalt stone, 18 x 10 x 6 ins., firmly set 6 ins. in the ground, from which the remains of the original bearing trees:

A pine snag, 34 ins. diam., bears S. 80° E., 34 lks. dist., with scribe marks ¼ S BT visible on open blaze. (Record, East)

A root hole, bears N. 40° W., 15 lks. dist., with a down and decayed pine alongside, size indeterminate, no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

	T 4 S R 33 E	
	¼	
S 35		S 36
	1977	

from which new bearing trees

A lodgepole pine, 9 ins. diam., bears N. 72° E., 27 lks. dist., mkd. ¼ S36 BT.

A lodgepole pine, 11 ins. diam., bears N. 34° W., 59 lks. dist., mkd. ¼ S35 BT.

Deposit corner stone and set a 5 ft. steel fence post alongside iron post.

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

The cor. of secs. 25, 26, 35, and 36, monumented with the original basalt stone, 20 x 8 x 6 ins., loosely set in a mound of stone, 3 ft. base, 6 ins. high, with 1 notch on E. and S. edges, from which the remains of the original bearing trees:

A root hole, bears S. 34° W., 127 lks. dist., with a down pine alongside, 30 ins. diam., with scribe marks T4S R33E S35 BT visible on open blaze.

A decayed pine stump, size indeterminate, bears N. 83° W., 120 lks. dist., with scribe marks T4S R33E S26 visible on open blaze. (Record, N. 72° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 33 E
S 26 S 25
S 35 S 36
1977

from which new bearing trees

A ponderosa pine, 12 ins. diam., bears N. 66° E., 35½ lks. dist., mkd. T4S R33E S25 BT.

A ponderosa pine, 14 ins. diam., bears S. 23° E., 198 lks. dist., mkd. T4S R33E S36 BT.

A ponderosa pine, 10 ins. diam., bears S. 68° W., 45½ lks. dist., mkd. T4S R33E S35 BT.

A fir, 15 ins. diam., bears N. 70° W., 117 lks. dist., mkd. T4S R33E S26 BT.

Deposit corner stone and set a 5 ft. steel fence post alongside iron post.

The cor. of secs. 26, 27, 34, and 35, determined at record bearing and distance from the remains of the original bearing trees:

A pine snag, 28 ins. diam., bears S. 34° W., 18 lks. dist., with scribe marks T4S R33E S34 BT visible on open blaze.

At the corner point which falls in road, 10 lks. wide, bears N. and S.

Drive an iron spike, 8 ins. long, ¼ in. diam., the top 3 ins. below road surface.

from which new bearing trees and reference monuments

An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 30° E., 40 lks. dist., with brass cap mkd. T4S R33E S26 RM 1977 and an arrow pointing to the corner.

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

A pine, 10 ins. diam., bears N. $63\frac{1}{2}^{\circ}$ E., 67 lks. dist., mkd. T4S R33E S26 BT.

A fir, 16 ins. diam., bears S. 48° E., 76 lks. dist., mkd. T4S R33E S35 BT.

A fir, 13 ins. diam., bears S. 21° W., $83\frac{1}{2}$ lks. dist., mkd. T4S R33E S34 BT.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monuments, bears N. 60° W., 40 lks. dist., with brass cap mkd. T4S R33E S27 RM 1977 and an arrow pointing to the corner.

No other suitable trees available within limits.

The cor. of secs. 14, 15, 22, and 23, monumented with the original basalt stone, 18 x 8 x 5 ins., firmly set 10 ins. in the ground, in a collar of stones, with 2 notches on E. and 3 notches on S. edges, from which the remains of the original bearing trees:

A pine snag, 20 ins. diam., bears N. 72° E., 45 lks. dist., with scribe marks S R33E S14 visible on opened blaze.

A root hole, bears S. 58° E., 7 lks. dist., with a down and decayed pine alongside, size indeterminate, with scribe marks T4S R33E S23 visible on open blaze.

A decayed pine stump, size indeterminate, bears S. 66° W., 106 lks. dist., with a down and decayed pine alongside, with scribe marks R33E S22 visible on open blaze. (Record, S. 60° W.)

A root hole, bears N. 85° W., 58 lks. dist., with a down and decayed pine alongside, size indeterminate, no marks visible.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4 S R 33 E
S 15 S 14
S 22 S 23
1977

from which new bearing trees

A lodgepole pine, 7 ins. diam., bears N. 62° E., 41 lks. dist., mkd. T4S R33E S14 BT.

A grand fir, 11 ins. diam., bears S. 60° E., 53 lks. dist., mkd. T4S R33E S23 BT.

A lodgepole pine, 13 ins. diam., bears S. 10° W., 209 lks. dist., mkd. T4S R33E S22 BT.

A grand fir, 9 ins. diam., bears N. $70\frac{1}{2}^{\circ}$ W., 71 lks. dist., mkd. T4S R33E S15 BT.

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

Deposit corner stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, monumented with the original basalt stone, 18 x 14 x 8 ins., firmly set 10 ins. in the ground, in a collar of stones, mkd. $\frac{1}{4}$ on W. face, from which the remains of the original bearing trees:

A pine, 23 ins. diam., bears S. 52° E., 44 lks. dist., with healed blaze. (Record, S. 38° E.)

A root hole, bears S. 48° W., 49 lks. dist., with a down pine alongside, 30 ins. diam., with scribe marks $\frac{1}{4}$ S visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 33 E
 $\frac{1}{4}$
 S 15 | S 14
 1977

from which a new bearing tree

A ponderosa pine, 11 ins. diam., bears N. 50° W., 201 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S15 BT.

Deposit corner stone alongside iron post.

Corner is located 75 lks. south of dirt road, 10 lks. wide, bears E. and W.

The cor. of secs. 10, 11, 14, and 15, monumented with the original basalt stone, 16 x 8 x 7 ins., firmly set 10 ins. in the ground, with 2 notches on E. and 4 notches on S. edges, from which the remains of the original bearing trees:

A root hole, bears N. 46° E., 21 lks. dist., with a down and decayed pine alongside, size indeterminate, with scribe marks S11 visible on open blaze.

A decayed pine stump, size indeterminate, bears N. 45° W., 12 lks. dist., with a down and decayed pine alongside, size indeterminate, with scribe marks T4S R33E S10 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4 S R 33 E
 S 10 | S 11
 S 15 | S 14
 1977

from which new bearing trees

A larch, 14 ins. diam., bears N. 24 $\frac{1}{2}$ ° E., 27 $\frac{1}{2}$ lks. dist., mkd. T4S R33E S11 BT.

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

A lodgepole pine, 4 ins. diam., bears S. 54° E.,
12 lks. dist., mkd. T4S R33E S14 BT.

A larch, 18 ins. diam., bears S. 51° W., 33 lks.
dist., mkd. T4S R33E S15 BT.

A grand fir, 7 ins. diam., bears N. 58° W., 23
lks. dist., mkd. T4S R33E S10 BT.

Deposit corner stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, monumented with the
original basalt stone, 18 x 8 x 5 ins., firmly set 10
ins. in the ground, and in a mound of stone, 2 ft. base,
6 ins. high, mkd. $\frac{1}{4}$ on W. face, from which the remains
of the original bearing trees:

A pine, 20 ins. diam., bears N. 84° E., 53 lks.
dist., with scribe marks $\frac{1}{4}$ S BT visible on open
blaze. (Record, N. 9° E.)

A pine stump, size indeterminate, bears N. 72° W.,
47 lks. dist., with fragmentary scribe marks
visible on open blaze. (Record, N. 11° W.,
44 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins.
in the ground, in a mound of stone, 2 ft. base, to top,
with brass cap mkd.

T 4 S R 33 E
 $\frac{1}{4}$
S 33 | S 34
1977

from which a new bearing tree

A ponderosa pine, 9 ins. diam., bears S. 36° W.,
52 lks. dist., mkd. $\frac{1}{4}$ S33 BT.

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

The cor. of secs. 27, 28, 33, and 34, monumented with the
original basalt stone, 20 x 10 x 5 ins., firmly set 4
ins. in the ground, in a collar of stones, with 3 notches
on E. and 1 notch on S. edges, from which the remains of
the original bearing trees:

A burned larch stump, size indeterminate, bears
N. 46° E., 50 lks. dist., no marks visible.

A burned fir stump, size indeterminate, bears
S. 42° W., 87 lks. dist., no marks visible.

A fir snag, 26 ins. diam., bears N. 28° W., 48
lks. dist., with scribe marks T4S R3 visible
on open and burned blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, and in a mound of stone, 2 ft. base, to
top, with brass cap mkd.

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

T 4 S R 33 E
S 28 S 27
S 33 S 34
1977

from which new bearing trees

A grand fir, 10 ins. diam., bears N. 80° E., 11½ lks. dist., mkd. T4S R33E S27 BT.

A grand fir, 9 ins. diam., bears S. 57° E., 47½ lks. dist., mkd. T4S R33E S34 BT.

A grand fir, 6 ins. diam., bears S. 35° W., 23 lks. dist., mkd. T4S R33E S33 BT.

A grand fir, 8 ins. diam., bears N. 15° W., 19 lks. dist., mkd. T4S R33E S28 BT.

Deposit corner stone alongside iron post.

The ¼ sec. cor. of secs. 27 and 34, monumented with the original basalt stone, 14 x 10 x 10 ins., firmly set 4 ins. in the ground, mkd. ¼ on N. face, from which the remains of the original bearing trees:

A pine snag, 32 ins. diam., bears N. 8° E., 12 lks. dist., with fragmentary scribe marks visible on open blaze. (Record, North)

A pine, 30 ins. diam., bears S. 3° W., 78 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 4 S R 33 E
¼ S 27
¼ S 34
1977

from which a new bearing tree

A pine, 28 ins. diam., bears N. 27° W., 86½ lks. dist., mkd. ¼ S27 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 21, 22, 27, and 28, monumented with the original unmarked basalt stone, 16 x 10 x 8 ins., firmly set 4 ins. in the ground, and in a mound of stone, 2 ft. base, 6 ins. high, from which the remains of the original bearing trees:

A ponderosa pine, 21 ins. diam., bears N. 13° E., 37 lks. dist., with healed blaze.

A ponderosa pine snag, 31 ins. diam., bears S. 48° E., 42 lks. dist., with scribe marks T4S R33E S27 visible on open blaze. (Record, S. 38° E.)

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

A sawed pine stump, 17 ins. diam., bears S. 8° W.,
22 lks. dist., no marks visible.

A ponderosa pine, 19 ins. diam., bears N. 60° W.,
157 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins.
in the ground, to solid rock, and in a mound of stone,
3 ft. base, to top, with brass cap mkd.

T 4 S R 33 E
S 21 S 22
S 28 S 27
1977

from which new bearing trees

A ponderosa pine, 18 ins. diam., bears S. 2° E.,
107 lks. dist., mkd. T4S R33E S27 BT.

A ponderosa pine, 11 ins. diam., bears S. 80° W.,
83 lks. dist., mkd. T4S R33E S28 BT.

Deposit corner stone alongside iron post.

The ¼ sec. cor. of secs. 15 and 16, monumented with the
original basalt stone, 18 x 8 x 5 ins., firmly set 6
ins. in the ground, and in a mound of stone, 3 ft. base,
1 ft. high, mkd. ¼ on W. face, from which the original
bearing trees:

A ponderosa pine, 15 ins. diam., bears S. 61° E.,
18 lks. dist., with scribe marks ¼ S visible
on open blaze. (Record, S. 52° E.)

A ponderosa pine, 22 ins. diam., bears N. 83° W.,
20 lks. dist., with scribe marks ¼ S visible
on open blaze. (Record, West)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, and in a mound of stone, 2 ft. base, to
top, with brass cap mkd.

T 4 S R 33 E
¼
S 16 S 15
1977

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

The cor. of secs. 9, 10, 15, and 16, monumented with the
original basalt stone, 18 x 14 x 5 ins., firmly set 8
ins. in the ground, and in a mound of stone, 2 ft. base,
6 ins. high, with 3 notches on E. and 4 notches on S.
edges, from which the remains of the original bearing
trees:

A root hole, bears N. 44° W., 61 lks. dist., with
a down and decayed pine alongside, size indeter-
minate, with scribe marks T4S R33E S9 visible
on open blaze.

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 33 E
S 9 S 10
S 16 S 15
1977

from which new bearing trees

A grand fir, 14 ins. diam., bears N. 31° E., 68 lks. dist., mkd. T4S R33E S10 BT.

A grand fir, 10 ins. diam., bears S. 63° E., 49 lks. dist., mkd. T4S R33E S15 BT.

A lodgepole pine, 8 ins. diam., bears S. 43° W., 50 lks. dist., mkd. T4S R33E S16 BT.

A lodgepole pine, 8 ins. diam., bears N. 44° W., 72 lks. dist., mkd. T4S R33E S9 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 3, 4, 9, and 10, monumented with the original basalt stone, 17 x 8 x 7 ins., loosely set 1 in. in the ground, with 3 notches on E. and 5 notches on S. edges, from which the remains of the original bearing trees:

A root hole, bears N. 78° E., 18 lks. dist., with a down and decayed pine alongside, size indeterminate, no marks visible.

A pine snag, 10 ins. diam., bears S. 45° E., 30 lks. dist., with scribe marks T4S R visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4 S R 33 E
S 4 S 3
S 9 S 10
1977

from which new bearing trees

A grand fir, 11 ins. diam., bears N. 15° E., 46½ lks. dist., mkd. T4S R33E S3 BT.

A fir, 22 ins. diam., bears S. 73° E., 44 lks. dist., mkd. T4S R33E S10 BT.

A larch, 12 ins. diam., bears S. 30½° W., 52 lks. dist., mkd. T4S R33E S9 BT.

A fir, 13 ins. diam., bears N. 71° W., 51 lks. dist., mkd. T4S R33E S4 BT.

Deposit corner stone alongside iron post.

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

The cor. of secs. 16, 17, 20, and 21, monumented with the original basalt stone, 20 x 10 x 4 ins., firmly set 6 ins. in the ground, with 4 notches on E. and 3 notches on S. edges, from which the remains of the original bearing trees:

A root hole, bears N. 24° E., 40 lks. dist., with a down and decayed larch alongside, size indeterminate, with scribe marks BT visible on open blaze.

A ponderosa pine, 17 ins. diam., bears S. 70° E., 15 lks. dist., with scribe marks T4S R33E S21 BT visible on open blaze.

A root hole, bears N. 50° W., 60 lks. dist., with a down and decayed pine alongside, size indeterminate, with scribe marks T4S R33E S17 BT visible on open blaze. (Record, N. 70° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 4	S R	33	E
S 17		S 16	
S 20		S 21	
1977			

from which new bearing trees

A grand fir, 7 ins. diam., bears N. 27° E., 21 lks. dist., mkd. T4S R33E S16 BT.

A grand fir, 8 ins. diam., bears S. 18° W., 45½ lks. dist., mkd. T4S R33E S20 BT.

A grand fir, 8 ins. diam., bears N. 59° W., 27 lks. dist., mkd. T4S R33E S17 BT.

Deposit corner stone and set a 5 ft. steel fence post alongside iron post.

The ¼ sec. cor. of secs. 16 and 17, monumented with the original basalt stone, 20 x 10 x 4 ins., firmly set 6 ins. in the ground, and in a mound of stone, 4 ft. base, 1 ft. high, mkd. ¼ on W. face, from which the original bearing trees:

A ponderosa pine, 16 ins. diam., bears N. 74° E., 140 lks. dist., with healed blaze.

A ponderosa pine, 26 ins. diam., bears S. 70° W., 63 lks. dist., with scribe marks ¼ S visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

T 4 S R 33 E

$\frac{1}{4}$
S 17 | S 16
1977

Deposit corner stone and set a 5 ft. steel fence post alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, monumented with the original basalt stone, 18 x 10 x 5 ins., firmly set 8 ins. in the ground, and in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on W. face, from which the original bearing tree:

A ponderosa pine, 22 ins. diam., bears N. 18° W., 117 lks. dist., with fragmentary scribe marks visible on open blaze. (Record, 114 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 33 E

$\frac{1}{4}$
S 8 | S 9
1977

from which a new bearing tree

A lodgepole pine, 14 ins. diam., bears S. 77° E., 142 lks. dist., mkd. $\frac{1}{4}$ S9 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 4, 5, 8, and 9, monumented with the original basalt stone, 18 x 12 x 6 ins., firmly set 10 ins. in the ground, in a collar of stones, with 5 notches on S. and 4 notches on E. edges, from which the remains of the original bearing trees:

A root hole, bears N. 56° E., 30 lks. dist.

A ponderosa pine, 22 ins. diam., bears S. 40° E., 59 lks. dist., with scribe marks 4 S visible on opened blaze. (Record, S. 45° E.)

A root hole, bears S. 32° W., 49 lks. dist., with a down pine alongside, 36 ins. diam., with scribe marks T4S R33E S8 visible on open blaze.

A pine snag, 32 ins. diam., bears N. 20° W., 38 lks. dist., with scribe marks S R33E S5 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 4 S R 33 E

S 5 | S 4
S 8 | S 9
1977

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

from which new bearing trees

A ponderosa pine, 13 ins. diam., bears N. 50° E.,
98 lks. dist., mkd. T4S R33E S4 BT.

A grand fir, 9 ins. diam., bears S. 29° W., 70
lks. dist., mkd. T4S R33E S8 BT.

A larch, 15 ins. diam., bears N. 73° W., 91 lks.
dist., mkd. T4S R33E S5 BT.

Deposit corner stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented with the
remains of the original corner tree, a pine snag, 9 ins.
diam., with fragmentary scribe marks visible on open
blaze on N. face, from which the remains of the original
bearing trees:

A root hole, bears N. 50° W., 16 lks. dist., with
a down and decayed pine alongside, size indeter-
minate, with fragmentary scribe marks visible
on open blaze.

A root hole, bears S. 43° E., 12 lks. dist., with
a down and decayed pine alongside, size indeter-
minate, no marks visible.

and new bearing trees

A grand fir, 7 ins. diam., bears N. 41° E., 21
lks. dist., mkd. $\frac{1}{4}$ S4 BT.

A grand fir, 7 ins. diam., bears S. 9° W., 16
lks. dist., mkd. $\frac{1}{4}$ S9 BT.

The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, monumented with the
original basalt stone, 16 x 10 x 5 ins., firmly set 5
ins. in the ground, mkd. $\frac{1}{4}$ on W. face, from which the
remains of the original bearing trees:

A root hole, bears N. 70° E., 72 lks. dist., with
a down and decayed pine alongside, size indeter-
minate, with fragmentary scribe marks visible on
open blaze.

A root hole, bears West, 54 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins.
in the ground, to solid rock, and in a mound of stone,
3 ft. base, to top, with brass cap mkd.

T 4 S R 33 E

$\frac{1}{4}$
S 5 | S 4
1977

from which new bearing trees

A ponderosa pine, 18 ins. diam., bears N. 44° E.,
49 lks. dist., mkd. $\frac{1}{4}$ S4 BT.

A grand fir, 14 ins. diam., bears S. 75° W., 103
lks. dist., mkd. $\frac{1}{4}$ S5 BT.

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

Deposit corner stone alongside iron post.

The cor. of secs. 7, 8, 17, and 18, monumented with the original basalt stone, 16 x 10 x 5 ins., firmly set 3 ins. in the ground, in a collar of stones, with 5 notches on E. and 4 notches on S. edges, from which the remains of the original bearing trees:

A pine, 12 ins. diam., bears N. 62° E., 19 lks. dist., with scribe marks T4S R33E S8 BT visible on open blaze. (Record, N. 53° E.)

A pine, 25 ins. diam., bears S. 35° E., 86 lks. dist., with scribe marks 4S R33E S17 visible on open and burned blaze.

A sawed pine stump, 18 ins. diam., bears S. 58° W., 38 lks. dist., no marks visible.

A pine snag, 11 ins. diam., bears N. 85° W., 45 lks. dist., with scribe marks 4S R33E S7 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 4 S R 33 E
S 7 S 8
S 18 S 17
1977

from which new bearing trees

A grand fir, 9 ins. diam., bears S. 14° W., 18 lks. dist., mkd. T4S R33E S18 BT.

A grand fir, 10 ins. diam., bears N. 75° W., 40 lks. dist., mkd. T4S R33E S7 BT.

Deposit corner stone alongside iron post.

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
June Klein	Engineering Aid

(Faint, mostly illegible text from the reverse side of the page, including a date stamp "JAN 2 1969")

CERTIFICATE OF SURVEY

(I) (~~WA~~), Craig L. Wanless, Cadastral Surveyor, , HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May , 19 57, (I) (~~WA~~) have remonumented certain original corner points, township 4 south, range 33 east,

of the Willamette Meridian, in the State of Oregon , which are represented in the foregoing field notes as having been executed by (me), (~~WA~~) and under (my) (~~WA~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 16, 1978 (Date) Craig L. Wanless (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C. Denver, Colorado

The foregoing field notes of the remonumentation of certain original corner points, township 4 south, range 33 east, Willamette Meridian, Oregon, executed by Craig L. Wanless, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JAN 23 1980 (Date) J.D. Voorhes (Chief, Division of Cadastral Survey) Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in , is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849 626