



# INDEX DIAGRAM

Township 4 South, Range 32 East,

	6	5	4	3	2	1	
<u>5</u>	<u>25</u>	<u>24</u> <u>25</u>		<u>17</u> <u>18</u>	<u>13</u>		
<u>5</u>	7	<u>24</u> 8	9	<u>17</u> 10	11	12	
<u>4</u>	<u>23</u>	<u>22</u> <u>23</u>	<u>20</u> <u>21</u>	<u>16</u>	<u>12</u>	<u>9</u>	
	18	17	16	<u>15</u> 15	14	<u>9</u> 13	
		<u>21</u> <u>22</u>	<u>19</u> <u>20</u>	<u>14</u> <u>15</u>	<u>11</u> <u>12</u>	<u>8</u>	<u>3</u>
	19	20	<u>19</u> 21	22	23	<u>8</u> 24	
			<u>18</u>	<u>14</u>	<u>10</u> <u>11</u>	<u>7</u> <u>7</u>	<u>3</u>
	30	29	28	27	26	25	<u>2</u>
				<u>13</u>		<u>6</u> <u>6</u>	<u>2</u>
	31	32	33	34	35	36	

## T. 4 S., R. 32 E., Willamette Meridian, Oregon

## CHAINS

The following field notes describe the remonumentation of certain original corner points, township 4 south, range 32 east, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350 Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories when Needed".

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

South Boundary, T. 4 S., R. 32 E.,  
Willamette Meridian, Oregon

(Remonumenting a corner established by George S. Pershin,  
U. S. Deputy Surveyor, in 1881)

The cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the  
Tp., determined at record bearing and distance from the  
original bearing trees:

A ponderosa pine, 34 ins. diam., bears N. 88° E.,  
76 lks. dist., with scribe marks 32E S visible  
on open blaze.

A ponderosa pine, 30 ins. diam., bears S. 31° E.,  
165 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T 4 S R 32 E
S 34   S 35
S 3   S 2
T 5 S
1977

from which a new bearing tree

A ponderosa pine, 23 ins. diam., bears S. 87° W.,  
81 lks. dist., mkd. T5S R32E S3 BT.

No other suitable trees available within limits.

Corner is located 15 lks. west of dirt road, 12 lks.  
wide, bears N. 25° E. and S. 25° W., and 4 lks.  
N. 45° W. of wire fence corner, fences extend E., W.,  
and N.

East Boundary, T. 4 S., R. 32 E.,  
Willamette Meridian, Oregon

(Remonumenting corners established by George S. Pershin,  
U. S. Deputy Surveyor, in 1881)

Remonumentation of Certain Original Corner Points,  
T. 4 S., R. 32 E., Willamette Meridian, Oregon

CHAINS

The cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears S. 87° W., 60 lks. dist.

A pine, 22 ins. diam., bears N. 34° W., 58 lks. dist., with scribe marks T4S R32E S25 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S	
R 32 E	R 33 E
S 25	S 30
S 36	S 31
1977	

from which new bearing trees

A fir, 19 ins. diam., bears N. 38° E., 93 lks. dist., mkd. T4S R33E S30 BT.

A fir, 10 ins. diam., bears S. 67½° E., 60 lks. dist., mkd. T4S R33E S31 BT.

A ponderosa pine, 17 ins. diam., bears S. 73° W., 48 lks. dist., mkd. T4S R32E S36 BT.

Fences extend N. and S. 60° E. from the NW. bearing tree.

The ¼ sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., monumented with the original basalt stone, 14 x 12 x 5 ins., loosely set 1 in. in the ground, mkd. ¼ on N. face, from which the remains of an original bearing tree:

A larch stump, 22 ins. diam., bears S. 60° W., 3 lks. dist., with scribe marks ¼ S BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S	
¼	
R 32 E	R 33 E
S 25	S 30
1977	

from which new bearing trees

A grand fir, 10 ins. diam., bears N. 83° E., 21 lks. dist., mkd. ¼ S30 BT.

A lodgepole pine, 5 ins. diam., bears S. 20° W., 44½ lks. dist., mkd. X BT.

Deposit corner stone alongside iron post.

Remonumentation of Certain Original Corner Points,  
T. 4 S., R. 32 E., Willamette Meridian, Oregon

## CHAINS

The cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with the original unmarked basalt stone, 24 x 18 x 4 ins. (record, 18 x 10 x 4 ins.), firmly set 6 ins. in the ground, and in a mound of stone, 4 ft. base, 1 ft. high, from which the remains of the original bearing trees:

A root hole, bears N. 24° E., 155 lks. dist., with a down pine alongside, size indeterminate, no marks visible on open blaze.

A decayed pine stump, size indeterminate, bears S. 7° E., 112 lks. dist., no marks visible. (Record, 105 lks.)

A pine, 20 ins. diam., bears S. 32° W., 74 lks. dist., no marks visible on open blaze. (Record, S. 27° W.)

A pine, 24 ins. diam., bears N. 26° W., 87 lks. dist., with scribe marks T4S R visible on open blaze. (Record, N. 28° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S
R 32 E R 33 E
S 24   S 19
S 25   S 30
1977

from which new bearing trees

A lodgepole pine, 9 ins. diam., bears N. 49½° E., 35½ lks. dist., mkd. T4S R33E S19 BT.

A lodgepole pine, 8 ins. diam., bears S. 36° E., 82½ lks. dist., mkd. T4S R33E S30 BT.

A lodgepole pine, 8 ins. diam., bears N. 33½° W., 47 lks. dist., mkd. T4S R32E S24 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., monumented with the original unmarked basalt stone, 14 x 12 x 4 ins., firmly set in a mound of stone, 4 ft. base, 6 ins. high, from which the original bearing trees:

A lodgepole pine, 17 ins. diam., bears N. 24° E., 135 lks. dist., with healed blaze.

A lodgepole pine, 23 ins. diam., bears S. 12° E., 74 lks. dist., with healed blaze.

A lodgepole pine, 23 ins. diam., bears S. 53° W., 94 lks. dist., with healed blaze.

A lodgepole pine, 25 ins. diam., bears N. 21° W., 81 lks. dist., with scribe marks 32E S13 BT visible on open blaze. (Record, N. 23° W., 79 lks.)

Remonumentation of Certain Original Corner Points,  
T. 4 S., R. 32 E., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S			
R 32 E	R 33 E		
S 13	S 18		
S 24	S 19		
1977			

from which a new bearing tree

A fir, 10 ins. diam., bears N. 36° W., 96 lks. dist., mkd. T4S R32E S13 BT.

Deposit corner stone alongside iron post.

West Boundary, T. 4 S., R. 32 E.,  
Willamette Meridian, Oregon

(Remonumenting corners established by George S. Pershin,  
U. S. Deputy Surveyor, in 1880)

The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with the original unmarked basalt stone, 15 x 10 x 10 ins., firmly set 4 ins. in the ground, and in a mound of stone, 3 ft. base, 1 ft. high, from which the remains of the original bearing trees:

A pine, 20 ins. diam., bears N. 68° E., 162 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A pine, 38 ins. diam., bears S. 62° W., 121 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S			
R 31 E	R 32 E		
S 12	S 7		
S 13	S 18		
1977			

from which new bearing trees

A lodgepole pine, 9 ins. diam., bears S. 41° E., 26 lks. dist., mkd. T4S R32E S18 BT.

A lodgepole pine, 9 ins. diam., bears N. 38½° W., 24½ lks. dist., mkd. T4S R31E S12 BT.

Deposit corner stone alongside iron post.



CERTIFICATE OF SURVEY

(I) (~~XX~~), Craig L. Wanless, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May, 1957, (I) (~~XX~~) have remonumented certain original corner points, township 4 south, range 32 east,

of the Willamette Meridian, in the State of Oregon, which are represented in the foregoing field notes as having been executed by (me), (~~XX~~) and under (my) (~~XXX~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 16, 1978  
(Date)

*Craig L. Wanless*  
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
~~Washington, D.C.~~  
Denver, Colorado

The foregoing field notes of the remonumentation of certain original corner points, township 4 south, range 32 east, Willamette Meridian, Oregon,

executed by Craig L. Wanless, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JAN 23 1980  
(Date)

*J. D. [Signature]*  
(Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626