

See page 183
for title page

22.

FIELD NOTES.

On the survey of the Eastern
Lines of Tps 3-4-5 S. R. 34 E
Tps 3-4-5. S. R. 33 1/2 E Willamette Meridian,
Oregon, as surveyed by Rufus J. Moore
U. S. Deputy Surveyor, under his Contract No. 451.
dated June 12th 1882
Survey commenced Oct 13th 1882
Survey completed December 1st 1882

NAMES AND DUTIES OF ASSISTANTS.

....., Compassman.
James Guttridge, Chainman.
John Guttridge, Chainman.
....., Chainman.
....., Chainman.
Joe Parodi, Axeman.
....., Axeman.
....., Flagman.

Copy
23
See page 184 for
these oaths

PRELIMINARY OATHS OF ASSISTANTS.

We, James Guttridge &
John Guttridge

do solemnly swear that we will faithfully execute the duties of Chain Carriers, that we will level the chain over even and uneven ground, and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we will assist in measuring, to the best of our skill and ability, and in accordance with the instructions given us in

the survey of the Enterings

lines of Tps 3-4 & 5
S. R. 33 1/2 & 34 0 Willamette Meridian, Oregon.

James Guttridge, Chainman.
John Guttridge, Chainman.
_____, Chainman.
_____, Chainman.

Subscribed and sworn to before me, this 15th
day of August 1882

[SEAL.] Rufus S. Morro
Notary Public

We, Joe Parodi and

do solemnly swear that we will well and truly perform the duties of Axemen in the establishment of corners and other duties, according to instructions given us, and to the best of our skill and ability

in the survey of the Enterings of Townships
3-4-5 S R 33 1/2 & 34 0 Willamette Meridian, Oregon.

Joe Parodi, Axeman.
_____, Axeman.

Subscribed and sworn to before me, this 15th
day of August 1882

[SEAL.] Rufus S. Morro
Notary Public

West bdy

41 11
Ontario of T. 5 South R. 33 1/2 East

Willamette Meridian, Oregon.

North on West boundary
of Sec 3.

Var 19° 30' East
Gradual Descent

- 14.65 The corner to Secs. 1 & 12
which is a basalt stone
16 x 10 x 5 marked with
5 notches on S. and 1 notch
on N edge; from which
a pine 6 in diam bears N 9°
E 90 lks dist marked T. 5
S. R. 34 E S. 6 B.T.
- A pine 8 in diam bears S 68°
E 88 lks dist marked T. 5
S R 34 E S 7 B.T.
- A pine 8 in diam bears
S 75° W 138 lks dist marked
T. 5 S. R. 33 E S 12 B.T.
- a pine 8 in diam bears
N 48° W 139 lks dist marked
T. 5 S R 33 E S 1. B.T.
- Destroyed marks referring

12 West bdy

42 Center of T. 5 South R. 33 1/2 East

Willamette Meridian, Oregon.

to Trees 6 and 7

5300 Enter creek bottom bears
E & W 250 ft below corner

5450 The 1/4 Sec corner

5750 Cannon Creek 29 ft wide
runs W.

5900 Leave bottom and ascend
hill

7200 Top of hill bears E & W

8000 Set a post 5 ft long 5
in square in stony ground
and raised mound of
stone 3 ft high and 5
ft base around post per
corner to Townships 4 & 5
S. R. 33 1/2 E marked

T. 4 S R 33 1/2 E S 34 on N.E. &

T. 5 S R 33 1/2 E S 3 on S.E.

with 6 notches on N & S
edges and 3 notches on
E edges

West by

25

Enterings of T. 5 South R. 34 East

Willamette Meridian, Oregon.

North between Secs
1 and 6.

Var 20° East

4000 Set a post 3 ft long 3 in
square 24 in in the
ground for $\frac{1}{4}$ Sec corner
marked $\frac{1}{4}$ S or W from
from which

a pine 4 in diam bears
S 75° E 66 lks dist marked
 $\frac{1}{4}$ S. B. T.

a pine 12 in diam bears
S 84° W 300 lks dist
marked $\frac{1}{4}$ S. B. T.

Leave heavy timber

8000 Set a basalt stone 15
x 15 x 15 in 10 in in the
ground for corner to S $\frac{1}{2}$
4 and 5. S. Rqs. 33 $\frac{1}{2}$ E
and 34 E marked with
6 notches on each edge

26

West body

56

Enterings of T. 5 South. 34 East

Willamette Meridian, Oregon.

and raised a mound
of stone 3 ft high and
5 ft base along side

Land rolling

Soil 2d rate

Heavily timbered with
pine and fir 40 chs

Scattering timber

40 chs.

North body #1

73

43

Exteriors of T. 5 S R. 33 1/2 E

Willamette Meridian, Oregon.

From the cor. to Tps 4 and 5 S.
R. 33 1/2 & 34 E I run west on a
random line on the north
boundary of Secs 1, 2 & 3
Va. 18° 15' E

I set temporary half-mile and mile
corners at each 40 and 80 chs and at
2 miles, 23 chs and 38 lks I intersect
the West boundary of R 33 1/2 E.
5 lks South of the established cor.
to Tps. 4 and 5 S R 33 1/2 E.

The correction will therefore be 2 lks
North to the mile. and its course
will be $89^{\circ} 59' E$.

From the cor. to Tps 4 and 5 S. R. 33 1/2 E,
I run

$89^{\circ} 59' E$ on a true line bet- Secs. 3 & 34

Va 18° 15' E

23.38 Set a basalt-stone 14 x 13 x 5 ins 9 ins
in the ground for cor. to Secs 2, 3
34 & 35. marked with 2 notches sw.

79 Exterior of T. 5 S R. 33 1/2 E

Willamette Meridian, Oregon.

North boundary.

on the E and 1 notch on the N.
edges. and raised a mound
of Stone 2 ft high and 4 1/2 ft.
base alongside -
Land rolling 1
soil 2d rate
Timber scattering pine

S 89° 59' E on true line bet. Specs. 2 & 35

or 19° 40' E

7.00 Enter heavy timber
40.00 Set a basalt-stone 16x13x9 ins 11 ins
in the ground for 1/4 sec cor.
marked 1/4 on N. face.

from which

A pine 24 ins diam bears S 7° E 27 lbs dist.
marked 1/4 S B. J

A pine 30 ins. diam. bears N 44° W 94 lbs. dist.
marked 1/4 S B. J

63.00 Creek 10 lbs wide runs S. W.

74.00 Leave heavy timber. and
enter scattering timber

North bely

~~75~~

45-

Exteriors. of T. 5 S R. 33 1/2 E 75

Willamette Meridian, Oregon.

80.00 Set a basalt-stone 24x15x15 ins 18 ins
in the ground for cor to secs. 1, 2,
35 & 36, marked with 1 notch on E,
and 2 notches on N. edges. dug
pits 18x18x12 ins in each sec.
5 1/2 ft dist. and raised a mound
of earth 2 ft high and 4 1/2 ft
base alongside -
Land rolling - Soil 2d rate
Heavily timbered with pine & fir 67 chs.

S 89° 59' E on a true line bet. Secs. 1 & 36

or 19° 40' E

40.00 Set a basalt-stone 12x10x8 ins, 8 ins
in the ground for 1/4 Sec cor,
marked 1/4 on N. face dug pits,
18x18x12 ins E and N. of stone 5 1/2 ft
dist. and raised a mound of
earth 1 1/2 ft high, and 3 1/2 ft base
alongside -

46

76

~~44~~
Exteriors of T. 5 S R. 33½ E

Willamette Meridian, Oregon.

North boundary.

80.00 The Cor to T. 5 S R. 33½ and
34 E.

Land level

Soil 2 d sub-

Timber scattering pine

Oct-16th 1882.

General Description

The land in
this Township is high
& rolling heavily timbered
with pine fir & Tamarack
of good quality with
Dense undergrowth

Copy
180
see page 220
for these oaths

FINAL OATHS FOR SURVEYS.

A list of the names of the individuals employed by Rufus S. Moore, U. S. Deputy Surveyor, to assist in running, measuring and marking the lines and corners described in the foregoing field notes of the survey of the Enterum lines of Trs 3-4-5 S. R. 33 1/2 & 34 E. 2d Willamette Meridian, Oregon, showing the respective capacities in which they acted:

_____, Compassman.
James Gutteridge, Chainman.
John Gutteridge, Chainman.
_____, Chainman.
_____, Chainman.
Joe Parodi, Axeman.
_____, Axeman.
_____, Flagman.

FINAL OATHS OF ASSISTANTS.

We hereby certify that we assisted Rufus S. Moore, U. S. Deputy Surveyor, in surveying all those parts or portions of the Enterum lines of Trs 3-4-5 S. R. 33 1/2 & 34 E. 2d Willamette Meridian, Oregon, as are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been, in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the U. S. Surveyor General of Oregon.

_____, Compassman.
James Gutteridge, Chainman.
John Gutteridge, Chainman.
_____, Chainman.
_____, Chainman.
Joe Parodi, Axeman.
_____, Axeman.
_____, Flagman.

Subscribed and sworn to before me, this 21st day of November 1882

[SEAL] Rufus S. Moore
Notary Public

Copy
181

See page 22!
for this oath

FINAL OATH OF DEPUTY SURVEYOR.

I, Rufus S Moore

United States Deputy Surveyor, do solemnly swear that in pursuance of

instructions received from James C. Tolman

U. S. Surveyor General for Oregon, bearing date of the 28th

day of June, 1882, I have well, faith-

fully and truly, in my own proper person, and in strict conformity with
the instructions furnished by the U. S. Surveyor General for Oregon, the
Surveying Manual, and the Laws of the United States, surveying all those

parts or portions of the Centering lines of
Trs 3-4-5 S. R. 33 1/2 & 34 East

Willamette Meridian, in the State of Oregon, as are represented in the
foregoing Field Notes as having been surveyed by me and under my di-
rections; and I do further solemnly swear that all the corners of said sur-
vey have been established and perpetuated in strict accordance with the
Surveying Manual, Printed Instructions, the Special Written Instructions
of the U. S. Surveyor General for Oregon, and in the specific manner de-
scribed in the Field Notes, and that the foregoing are the *true* Field Notes
of such survey, and should any fraud be detected I will suffer the penalty
of perjury under the provisions of an Act of Congress approved August
8th, 1846.

Rufus S Moore
U. S. Deputy Surveyor.

Subscribed and sworn to before me, this 10th

day of July, 1883

Barnford Robb
Notary Public

(Seal)

182

OFFICE U. S. SURVEYOR GENERAL,

Portland, Oregon, *Feb 1,* 1884

The following Field Notes of the Survey of the

Outer line of Tps

3 - 4 - 5 South Range

33½ and 34 O Will Met

Oregon
executed by

Refus S. Moore

under his Contract No. *451*, dated *June*

12th 1882, having been critically examined,

the necessary corrections and explanations made, the said

Field Notes and the survey they describe are hereby approved.

James C. Tolson

Surveyor General.