

STATE OF OREGON,

County of Union.



we Jeff D Fenton, W. P. Slater, R. M. Morgan,
 C. D. Goodnough, do
 solemnly swear that we will well and faithfully
 execute the duties of Chain carriers that we will level
 the chain upon even and uneven ground and
 plumb the tally pins either by sticking or
 dropping the same that we will report the true
 distance to all notable objects and the true
 length of all lines that we assist in meas-
 uring to the best of our skill and ability
 and in accordance with instructions given
 us in the survey of the exterior lines of
 Townships 4th & 5th South Ranges 35, 36, & 37.
 East of Willamette Meridian Oregon

Jeff D. Fenton Jr. Chairman

W. P. Slater Chairman

R. M. Morgan Chairman

C. D. Goodnough Chairman

Subscribed and sworn to before me
 this 16th day of July 1881

Geo. M. King

Notary Public for Oregon.

STATE OF OREGON,

County of Union.

ss.

475

We R. M. Morgan^{2d} & C, D.
Goodrough do solemnly
swear, that we will well
and truly perform the duties
of assessors in the establish-
ment of corners and other du-
ties according to instructions
given us and to the best of
our skill and ability in
the survey of the Exterior lines
of Townships 4th & 5th South
Ranges ~~4th & 5th~~ 35, 36^{2d} & 37 East
of Willamette Meridian
Oregon.

R M Morgan Assessor
C D Goodrough Assessor

Subscribed and sworn to before me
this 16 day of July 1881

Geo. M. King
Notary Public for Oregon.

129

Extreme of T 48 R. 35 E 600

Willamette Meridian, Oregon.

Chain S 89° W. 14 lks dist marked.

T 48 R 34 E. S 12 B. T.

Land rolling and hilly.

Soil gravelly 2nd rate.

Timber pine.

N. bet. secs 1 and 6.

N 17° 50' E.

Descend.

19.00 Enter timber.

27.50 point of rocks

30.50 Bed of dry creek course N E

Ascend

36.00 Descend

40.00 Set post 3 1/2 ft long 3 in square
18 in in ground on N slope of
mountain, in open pine timber
for 1/4 sec cor marked 1/4 S on E and
W faces.

Spine 30 in diam bears

N 68° W. 17 lks dist marked 1/4 S B. T.

610

130

Exterior

of T.

48

R.

35 E

Willamette Meridian, Oregon.

- Chain
Apine 26 mi diam base
N 47° E. 102 lks dist marked 4 S. B. S.
Descend
- 49.00 Precipice 30 ft high.
Starkey Creek 20 lks wide course E.
Ascend, leave timber.
- 57.25 Point of rocks.
- 67.11 The line bet Tpe 3 and 48 18.90 ch
E of the S.W. cor of T 3 R 35 E.
Set post 4 ft long 5 in square
18 in in ground with mound
of stone 2 ft high and 3 ft diam
at base around post. for closing
cor. to Tpe. 4 S. R. 34 and 35 E.
marked.
C.C. T 48 on S.
R 35 E S 6 on E and
R 34 E S 1 on W. faces with 6
notches on S. E. and W faces
In prairie sloping gently S
100 ft above creek

FINAL OATHS FOR SURVEYS.

A list of the names of the individuals employed by.....

J. C. Cooper, U. S. Deputy Surveyor, to assist in running measuring and marking the lines and corners described in the foregoing field notes of the survey of the *Exteriors of Townships 4th and 5th South, Range 35th, 36th and 37th E* of *South*, Range *35th, 36th and 37th E* Willamette Meridian, Oregon, showing the respective capacities in which they acted :

-, Compassman.
- M. T. Slater*....., Chainman.
- J. O. Fenlon Jr.*....., Chainman.
-, Chainman.
-, Chainman.
- C. D. Goodnough*....., Axeman.
- R. M. Morgan*....., Axeman.
-, Flagman.

FINAL OATHS OF ASSISTANTS.

We hereby certify that we assisted *Jacob C. Cooper*....., U. S. Deputy Surveyor, in surveying all

those parts or portions of the *Exteriors lines of Townships 4th and 5th South Range 35th, 36th and 37th East of* Willamette Meidian, Oregon, are represented in the foregoing field notes as having been surveyed by him and under his direction ; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the U. S. Surveyor General of Oregon.

-, Compassman.
- M. T. Slater*....., Chainman.
- J. O. Fenlon Jr.*....., Chainman.
-, Chainman.
-, Chainman.
- R. M. Morgan*....., Axeman.
- C. D. Goodnough*....., Axeman.
-, Flagman.

Subscribed and sworn to before me, this *second*..... day of

September..... 188.....

[SEAL.]

Robert J. Slater
Notary Public

FINAL OATH OF DEPUTY SURVEYOR.

I, Jacob C. Cooper

United States Deputy Surveyor, do solemnly swear that in pursuance of instructions

received from James C. Tolman

U. S. Surveyor General for Oregon, bearing date of the 1st day of

July, 1881, I have well, faithfully, and truly, in my own proper person, and in strict conformity with the instructions furnished by the U. S. Surveyor General for Oregon, the Surveying Manual, and the laws of

the United States, surveyed all those parts or portions of the Exterior

lines of Tps 4 & 5 S. Rs 35, 36 & 37 E

Willamette Meridian, in the State of Oregon, as are represented in the foregoing Field Notes as having been surveyed by me and under my directions; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Surveying Manual, printed instructions, the special written instructions of the U. S. Surveyor General for Oregon, and in the specific manner described in the field notes, and that the foregoing are the true field notes of such survey, and should any fraud be detected I will suffer the penalty of perjury under the provisions of an Act of Congress approved August 8, 1846.

Jacob C. Cooper
U. S. Deputy Surveyor.

Subscribed and sworn to before me, this Sixth

day of February 1881

Henry Warren
Notary Public

620

Office U. S. Surveyor General,

Portland, Oregon, April 5, 1882

The following Field Notes of the Survey of
Exterior lines of
T. 4^{and} 5 S. R. 35. 36. 37 E.
Will. Mer. Or.

executed by Jacob C. Cooper
under his contract No. 397

dated July 1st 1881, having been
critically examined, the necessary corrections and ex-
planations made, the said field notes and the survey
they describe, are hereby approved.

James C. Tolman
Surveyor General.