

FIELD NOTES

OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,
TOWNSHIP 4 SOUTH, RANGE 34 EAST,

Of the WILLAMETTE Meridian,
In the State of OREGON

EXECUTED BY

Craig L. Wanless, Cadastral Surveyor

Under special instructions dated May 3, 19 57, approved May 6, 1957,

_____ , which provided for the surveys included under U.S. Survey/Group
Number 350 , and assignment instructions dated August 23 , 19 77 .

Survey commenced September 12 , 19 77

Survey completed September 13 , 19 77

INDEX DIAGRAM

Township 4 South, Range 34 East,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
<u>3</u>	<u>3</u>				
30	<u>2</u>	29	28	27	26
	<u>1</u>				
31	<u>1</u>	32	33	34	35
					36

T. 4 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 4 south, range 34 east, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories when Needed".

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

Subdivisions, T. 4 S., R. 34 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by Rufus S. Moore,
U. S. Deputy Surveyor, in 1882)

The $\frac{1}{4}$ sec. cor. of secs. 31 and 32, monumented with the original unmarked basalt stone, 15 x 12 x 4 ins., loosely set 1 in. in the ground, from which the original bearing trees:

A ponderosa pine, 30 ins. diam., bears S. 10° E.,
103 lks. dist., with healed blaze. (Record,
S. 16° E.)

A ponderosa pine, 36 ins. diam., bears N. 57° W.,
47 lks. dist., with scribe marks $\frac{1}{4}$ visible on
open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins.
in the ground, and in a mound of stone, 3 ft. base, to
top, with brass cap mkd.

T 4 S R 34 E
 $\frac{1}{4}$
S 31 | S 32
1977

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

The cor. of secs. 29, 30, 31, and 32, determined at
record bearing and distance from the remains of the
original bearing trees:

A root hole, bears N. 41° E., 108 lks. dist., with
a down and decayed pine alongside, size indeter-
minate, with scribe marks T4S R34E S visible
on open blaze.

A pine, 25 ins. diam., bears S. 27° E., 109 lks.
dist., with healed blaze.

A pine, 23 ins. diam., bears S. 41° W., 110 lks.
dist., with scribe marks T4S R34E S21 BT
visible on open blaze.

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

A root hole, bears N. 45° W., 112 lks. dist., with a down and decayed pine alongside, size indeterminate, with fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 34 E	
S 30	S 29
S 31	S 32
1977	

from which new bearing trees

A lodgepole pine, 11 ins. diam., bears N. 26° E., 78 lks. dist., mkd. T4S R34E S29 BT.

A lodgepole pine, 10 ins. diam., bears N. 75° W., 106 lks. dist., mkd. T4S R34E S30 BT.

Set a 5 ft. steel fence post alongside iron post.

Corner is located 15 lks. west of dirt road, 10 lks. wide, bears N. 10° W. and S. 10° E.

The ¼ sec. cor. of secs. 29 and 30, monumented with the original unmarked basalt stone, 16 x 7 x 7 ins., firmly set in a mound of stone, 2 ft. base, 6 ins. high, from which the remains of the original bearing trees:

A root hole, bears N. 32° E., 36 lks. dist., with a down and decayed pine alongside, size indeterminate, no marks visible. (Record, N. 52° E.)

A pine snag, 36 ins. diam., bears S. 85° W., 67 lks. dist., with scribe marks 4S visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 34 E	
¼	
S 30	S 29
1977	

from which new bearing trees

A grand fir, 9 ins. diam., bears S. 49° E., 139 lks. dist., mkd. ¼ S29 BT.

A grand fir, 10 ins. diam., bears S. 70½° W., 45 lks. dist., mkd. ¼ S30 BT.

Deposit corner stone and set a 5 ft. steel fence post alongside iron post.

Corner is located 50 lks. north of dirt road, 10 lks. wide, bears E. and SW.

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

The cor. of secs. 19, 20, 29, and 30, determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears N. 29° E., 208 lks. dist., with a down and decayed pine alongside, size indeterminate, with scribe marks T4S R34E visible on open blaze.

A pine snag, 38 ins. diam., bears S. 52° W., 144 lks. dist., with scribe marks T4S R34E S30 visible on open blaze.

A pine snag, 34 ins. diam., bears N. 61° W., 325 lks. dist., with scribe marks 4S R34E visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 34 E
S 19 S 20
S 30 S 29
1977

from which new bearing trees

A lodgepole pine, 9 ins. diam., bears N. 34° E., 27 lks. dist., mkd. T4S R34E S20 BT.

A grand fir, 8 ins. diam., bears S. 27° E., 106 lks. dist., mkd. T4S R34E S29 BT.

A grand fir, 7 ins. diam., bears S. 24° W., 47 lks. dist., mkd. T4S R34E S30 BT.

A lodgepole pine, 12 ins. diam., bears N. 66½° W., 31½ lks. dist., mkd. T4S R34E S19 BT.

Set a 5 ft. steel fence post alongside iron post.

The ¼ sec. cor. of secs. 19 and 30, monumented with the original basalt stone, 18 x 12 x 5 ins., loosely set in a mound of stone, 2 ft. base, 6 ins. high, mkd. ¼ on W. face, from which the original bearing trees:

A ponderosa pine, 35 ins. diam., bears N. 25° E., 226 lks. dist., with healed blaze.

A ponderosa pine, 25 ins. diam., bears S. 70° E., 84 lks. dist., with scribe marks ¼ S visible on open blaze. (Record, 81 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 34 E
¼ S 19
S 30
1977

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
June Klein	Engineering Aid

[Handwritten signature]
[Faint text and lines, possibly a stamp or additional form instructions]

CERTIFICATE OF SURVEY

(I) (~~WE~~), Craig L. Wanless, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May, 19 57, (I) (~~WE~~) have remonumented certain original corner points, township 4 south, range 34 east,

of the Willamette Meridian, in the State of Oregon, which are represented in the foregoing field notes as having been executed by (me), (~~US~~) and under (my) (~~own~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 16, 1978
(Date)

Craig L. Wanless
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the remonumentation of certain original corner points, township 4 south, range 34 east,

executed by Craig L. Wanless, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

AUG 17 1978
(Date)

[Signature]
Acting (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626