

Township No 5 N, Range 33 E, Will, Mer,  
4000 Set 1/4 Sec post cor in dup

Barine Course N 100

Dug pits Drove Charred  
Stake, and raised Mound  
as per instructions.

8000 Set post corner for sec,  
1. 12. 677. on Spur of hill  
Course North.

Drove Charred Stake, dug  
pits, and raised Mound  
as per instructions.

Land hilly good Grass Soil  
2<sup>nd</sup> Rate,

North on East boundary of sec  
1 T. 5 N, R. 33. E, Will, Mer,  
Bar 21° E.

4000 Set 1/4 Sec post on ridge.  
Course N, W,

Drove Charred Stake, dug  
pits and raised Mound  
as per instructions



2  
 Township No 33 N, Range 33 E, Will, Mex,  
 8000 Set post corner for Townships  
 546 N in Ranges 33 & 34 E,  
 and sec 1. 6. 31. & 36.

Drove churned stake, dug pits  
 and raised mound as per  
 instructions,  
 Found Broken good  
 Grass soil hardly 2<sup>nd</sup> Rate,

West on Random between  
 Townships 546 N, Range 33 E,  
 Bar, 21<sup>st</sup> E,

April 20<sup>th</sup> 1865,  
 Set Half Mile and Mile posts  
 at 4000 and 8000 ch and  
 found the Town line to  
 be 5 Miles 78.60 The  
 falling to be, 50 South  
 of Corner post,

The correction will be  
 S 89° 56' E, on true line the  
 west fraction 1.40 Short



Surveyor General's Office  
 Eugene City Aug 23 1865

The foregoing field notes of the Survey of the ~~the~~  
~~Standard Quarter North, through Ranges 31,~~  
~~32, 33, 34, 35, 36 & 37 East Will. River Oregon,~~  
~~and of the exterior lines of Tps. 5 North Ranges~~  
 33, 34, 35 East Willamette Meridian, Oregon,  
 executed by Odell & Lewis, Deputies, under con-  
 tract No. 110, bearing date February 7<sup>th</sup> 1865,  
 having been critically examined, the necessary ex-  
 planations and corrections made, the said field  
 notes and the surveys they describe, are hereby approved.

E. L. Applegate  
 Surveyor General of Oregon.