



# INDEX DIAGRAM

Township 5 South, Range 31 East,

6	5	4	3	2	1
	<u>10</u>				
7	8	9	10	11	12
<u>9</u>		<u>4</u> <u>4</u>			
18	17	16	15	14	13
	<u>9</u>	<u>3</u> <u>3</u>			
19	<u>8</u> 20	<u>2</u> 21	22	23	24
<u>8</u>	<u>7</u> <u>7</u>	<u>2</u>			
30	<u>6</u> 29	28	27	26	25
<u>6</u>	<u>5</u>				
31	<u>5</u> 32	33	34	35	36

1

## T. 5 S., R. 31 E., Willamette Meridian, Oregon

## CHAINS

The following field notes describe the remonumentation of certain original corner points, township 5 south, range 31 east, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories when Needed".

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

South Boundary, T. 5 S., R. 31 E.,  
(First Standard Parallel South)  
Willamette Meridian, Oregon

(Remonumenting a corner established by George S. Pershin,  
U. S. Deputy Surveyor, in 1880)

The standard cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented with the original basalt stone, 16 x 10 x 6 ins., firmly set 8 ins. in the ground, and in a mound of stone, 3 ft. base, 1 ft. high, mkd. with 2 notches on E. edge, from which the remains of the original bearing trees:

A pine, 26 ins. diam., bears N. 66° E., 125 lks. dist., with scribe marks T5S R31E S32 visible on open blaze.

A pine snag, 22 ins. diam., bears N. 50° W., 78 lks. dist., with scribe marks T5S R31E S31 SC BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

S C  
T 5 S R 31 E  
S 31 | S 32  
1978

from which a new bearing tree

A ponderosa pine, 13 ins. diam., bears N. 50½° W., 48 lks. dist., mkd. T5S R31E S31 SC BT.

Deposit corner stone alongside iron post.

Subdivisions, T. 5 S., R. 31 E.,  
Willamette Meridian, Oregon

(Remonumenting corners established by George S. Pershin,  
U. S. Deputy Surveyor, in 1880)

Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 31 E., Willamette Meridian, Oregon

## CHAINS

The cor. of secs. 20, 21, 28, and 29, perpetuated by person(s) unknown, monumented with an iron pipe,  $\frac{1}{2}$  in. diam., firmly set, projecting 18 ins. above ground, from which the original bearing trees:

A pine, 35 ins. diam., bears N.  $59^{\circ}$  E., 70 lks. dist., with scribe marks S21 BT visible on opened blaze. (Record, N.  $54^{\circ}$  E.)

A fir, 35 ins. diam., bears S.  $40^{\circ}$  E., 57 lks. dist., with fragmentary scribe marks visible on open blaze. (Record, S.  $46^{\circ}$  E.)

A fir, 38 ins. diam., bears S.  $56^{\circ}$  W., 104 lks. dist., with fragmentary scribe marks visible on partially open blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S R 31 E
S 20   S 21
S 29   S 28
1978

from which a new bearing tree

A fir, 23 ins. diam., bears N.  $72\frac{1}{2}^{\circ}$  W., 205 lks. dist., mkd. T5S R31E S20 BT.

Reset iron pipe alongside iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 20 and 21, monumented with the original unmarked basalt stone, 14 x 12 x 5 ins., firmly set 6 ins. in the ground, and in a mound of stone, 2 ft. base, 6 ins. high, from which the original bearing tree:

A pine, 35 ins. diam., bears S.  $46^{\circ}$  W., 260 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 15 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S R 31 E
$\frac{1}{4}$
S 20   S 21
1978

from which a new bearing tree

A ponderosa pine, 19 ins. diam., bears S.  $41^{\circ}$  E., 168 lks. dist., mkd.  $\frac{1}{4}$  S20 BT.

Deposit corner stone alongside iron post.

Remonumentation of Certain Original Corner Points,  
T 5 S., R. 31 E., Willamette Meridian, Oregon

## CHAINS

The cor. of secs. 16, 17, 20, and 21, monumented with the original basalt stone, 14 x 12 x 7 ins., firmly set 6 ins. in the ground, mkd. with 3 notches on S. and 4 notches on E. edges, from which the remains of the original bearing trees:

A pine, 15 ins. diam., bears N. 72° E., 107 lks. dist., with fragmentary scribe marks visible on open blaze.

A root hole, bears S. 67° E., 87 lks. dist., with a down pine alongside, 25 ins. diam., with scribe marks 31E visible on open blaze.

A pine, 28 ins. diam., bears S. 87° W., 101 lks. dist., with scribe marks T5S R31E S20 visible on open blaze. (Record, S. 77° W., 97 lks.)

and bearing trees of which I have no record

A ponderosa pine, 10 ins. diam., bears S. 36½° E., 62 lks. dist., with scribe marks T5S R31E S21 BT visible on open blaze.

A ponderosa pine, 15 ins. diam., bears N. 30° W., 120 lks. dist., with scribe marks T5S R31E S17 BT RS691 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S R 31 E
S 17   S 16
S 20   S 21
1978

Deposit corner stone alongside iron post.

---

The ¼ sec. cor. of secs. 16 and 21, monumented with the original basalt stone, 18 x 12 x 8 ins., firmly set in a mound of stone, 3 ft. base, 2 ft. high, mkd. ¼ on N. face, from which the original bearing trees:

A pine, 29 ins. diam., bears N. 67° W., 161 lks. dist., with scribe marks ¼ S BT visible on open blaze.

A pine, 32 ins. diam., bears S. 38° W., 227 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S R 31 E
¼ S 16
¼ S 21
1978

Deposit corner stone alongside iron post.

---

Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 31 E., Willamette Meridian, Oregon

## CHAINS

The cor. of secs. 8, 9, 16, and 17, determined at record bearing and distance from the remains of the original bearing trees:

A pine, 26 ins. diam., bears N. 22° E., 112 lks. dist., with healed blaze.

A sawed pine stump, 36 ins. diam., bears S. 64° W., 70 lks. dist., with scribe marks BT visible on open blaze.

A sawed pine stump, 30 ins. diam., bears N. 24° W., 90 lks. dist., with scribe mark T visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 5 S R 31 E	
S 8	S 9
S 17	S 16
1978	

from which new bearing trees

A ponderosa pine, 19 ins. diam., bears S. 63° E., 242 lks. dist., mkd. T5S R31E S16 BT.

A ponderosa pine, 14 ins. diam., bears S. 72° W., 15 lks. dist., mkd. T5S R31E S17 BT.

A ponderosa pine, 10 ins. diam., bears N. 63° W., 54½ lks. dist., mkd. T5S R31E S8 BT.

The ¼ sec. cor. of secs. 9 and 16, monumented with the original basalt stone, 18 x 10 x 5 ins., firmly set 6 ins. in the ground, and in a mound of stone, 3 ft. base, 1 ft. high, mkd. ¼ on N. face, from which the remains of the original bearing trees:

A sawed pine stump, 30 ins. diam., bears N. 28° E., 74 lks. dist., with scribe marks BT visible on open blaze.

A pine snag, 29 ins. diam., bears S. 73° E., 145 lks. dist., with scribe marks ¼ S visible on open blaze.

and bearing trees of which I have no record

A ponderosa pine, 17 ins. diam., bears N. 38° E., 47 lks. dist., with scribe marks ¼ S9 BT visible on open blaze.

A ponderosa pine, 15 ins. diam., bears S. 6° W., 41½ lks. dist., with scribe marks ¼ S16 BT RS691 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 31 E., Willamette Meridian, Oregon

CHAINS

T 5 S R 31 E

$$\frac{1}{4} \frac{S \ 9}{S \ 16}$$

1978

Deposit corner stone alongside iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 31 and 32, monumented with the original basalt stone, 18 x 8 x 5 ins., firmly set 4 ins. in the ground, mkd.  $\frac{1}{4}$  on W. face, from which the remains of the original bearing trees:

A decayed pine stump, size indeterminate, bears S.  $56^{\circ}$  E., 38 lks. dist., with a down pine alongside, 14 ins. diam., with scribe marks 4 S visible on opened blaze.

A root hole, bears S.  $85^{\circ}$  W., 53 lks. dist., with a down pine alongside, 24 ins. diam., with scribe mark S visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S R 31 E

$$\frac{1}{4} \frac{S \ 31 | S \ 32}{S \ 31 | S \ 32}$$

1978

from which new bearing trees

A fir, 10 ins. diam., bears S.  $58^{\circ}$  E., 62 lks. dist., mkd.  $\frac{1}{4}$  S32 BT.

A ponderosa pine, 8 ins. diam., bears N.  $31^{\circ}$  W., 29 lks. dist., mkd.  $\frac{1}{4}$  S31 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 29, 30, 31, and 32, monumented with the original basalt stone, 17 x 12 x 8 ins., firmly set 6 ins. in the ground, and in a mound of stone, 3 ft. base, 6 ins. high, mkd. with 5 notches on E. and 1 notch on S. edges, from which the remains of the original bearing trees:

A sawed pine stump, 40 ins. diam., bears N.  $45^{\circ}$  E., 119 lks. dist., no marks visible. (Record, N.  $40^{\circ}$  E.)

A pine, 27 ins. diam., bears S.  $5\frac{1}{2}^{\circ}$  E., 77 lks. dist., with scribe marks T5S R31E S32 visible on open blaze. (Record, S.  $9^{\circ}$  E.)

A root hole, bears N.  $85^{\circ}$  W., 80 lks. dist., with a down pine alongside, 20 ins. diam., with fragmentary scribe marks visible on open blaze. (Record, S.  $88^{\circ}$  W.)

A pine, 20 ins. diam., bears N.  $10^{\circ}$  W., 82 lks. dist., with scribe marks T5S R31E S30 visible on open blaze. (Record, N.  $15^{\circ}$  W.)

At the corner point

Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 31 E., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S R 31 E
S 30   S 29
S 31   S 32
1978

from which new bearing trees

A fir, 9 ins. diam., bears N. 51½° E., 138 lks. dist., mkd. T5S R31E S29 BT.

A ponderosa pine, 8 ins. diam., bears S. 75° W., 29½ lks. dist., mkd. T5S R31E S31 BT.

Deposit corner stone alongside iron post.

---

The ¼ sec. cor. of secs. 30 and 31, monumented with the original basalt stone, 17 x 12 x 7 ins., firmly set 6 ins. in the ground, and in a mound of stone, 3 ft. base, 6 ins. high, mkd. ¼ on N. face, from which the remains of the original bearing trees:

A sawed pine stump, 26 ins. diam., bears N. 24° E., 71 lks. dist., with scribe marks ¼ S visible on open blaze. (Record, N. 18° E.)

A pine, 25 ins. diam., bears S. 5° E., 82 lks. dist., with scribe marks ¼ S BT visible on open blaze. (Record, S. 50° E.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S R 31 E
¼ S 30
¼ S 31
1978

from which a new bearing tree

A ponderosa pine, 8 ins. diam., bears N. 19° E., 22½ lks. dist., mkd. ¼ S30 BT.

Deposit corner stone alongside iron post.

---

The ¼ sec. cor. of secs. 29 and 30, monumented with the original unmarked basalt stone, 16 x 12 x 10 ins., firmly set 8 ins. in the ground, from which the remains of the original bearing trees:

A pine, 25 ins. diam., bears S. 57° E., 24 lks. dist., with healed blaze. (Record, S. 72° E.)

A pine snag, 26 ins. diam., bears N. 36° W., 20 lks. dist., with scribe marks ¼ S BT visible on open blaze. (Record, N. 45° W.)

At the corner point



Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 31 E., Willamette Meridian, Oregon

## CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S R 31 E

    ¼  
S 30 | S 29  
1978

from which a new bearing tree

A fir, 16 ins. diam., bears N. 59° W., 68 lks. dist., mkd. ¼ S30 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 19, 20, 29, and 30, determined at record distance from the remains of the original bearing trees:

A pine, 25 ins. diam., bears N. 40° E., 138 lks. dist., with scribe marks S R31E S20 visible on open blaze. (Record, N. 33° E.)

A sawed and decayed pine stump, 20 ins. diam., bears S. 72° E., 62 lks. dist., no marks visible.

A root hole, bears S. 80° W., 90 lks. dist., with a sawed and decayed pine alongside, size indeterminate, no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S R 31 E

    S 19 | S 20  
    S 30 | S 29  
1978

from which new bearing trees

A fir, 10 ins. diam., bears S. 36° E., 81 lks. dist., mkd. T5S R31E S29 BT.

A ponderosa pine, 13 ins. diam., bears S. 36° W., 32½ lks. dist., mkd. T5S R31E S30 BT.

A ponderosa pine, 16 ins. diam., bears N. 30° W., 46 lks. dist., mkd. T5S R31E S19 BT.

The ¼ sec. cor. of secs. 20 and 29, monumented with the original basalt stone, 14 x 12 x 10 ins., firmly set 6 ins. in the ground, mkd. ¼ on N. face, from which the remains of the original bearing trees:

A root crown, bears S. 24° W., 68 lks. dist., with a down pine alongside, 8 ins. diam., with scribe marks ¼ S visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 31 E., Willamette Meridian, Oregon

CHAINS

T 5 S R 31 E

$$\frac{1}{4} \begin{array}{l} S 20 \\ S 29 \end{array}$$

1978

from which new bearing trees

A fir, 8 ins. diam., bears N. 4° E., 20 lks. dist.,  
mkd.  $\frac{1}{4}$  S20 BT.

A fir, 13 ins. diam., bears S. 19½° W., 112 lks.  
dist., mkd.  $\frac{1}{4}$  S29 BT.

Deposit corner stone alongside iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 30, monumented with the  
original unmarked basalt stone, 16 x 10 x 4 ins., firmly  
set 6 ins. in the ground, from which the remains of the  
original bearing trees:

A pine, 32 ins. diam., bears North, 12 lks. dist.,  
with healed blaze. (Record, N. 20° W.)

A pine snag, 30 ins. diam., bears S. 82° W., 55  
lks. dist., with scribe marks  $\frac{1}{4}$  S BT visible  
on open and burned blaze. (Record, S. 77° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.  
in the ground, and in a mound of stone, 3 ft. base, to  
top, with brass cap mkd.

T 5 S R 31 E

$$\frac{1}{4} \begin{array}{l} S 19 \\ S 30 \end{array}$$

1978

from which a new bearing tree

A ponderosa pine, 12 ins. diam., bears S. 18° E.,  
35½ lks. dist., mkd.  $\frac{1}{4}$  S30 BT.

Deposit corner stone alongside iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 20, monumented with the  
original unmarked basalt stone, 20 x 12 x 10 ins., firmly  
set in a mound of stone, 3 ft. base, 1 ft. high, from  
which the remains of the original bearing trees:

A pine, 21 ins. diam., bears S. 53° E., 97 lks.  
dist., with scribe marks  $\frac{1}{4}$  visible on open blaze.

A pine snag, 25 ins. diam., bears N. 72° W., 170  
lks. dist., with scribe marks  $\frac{1}{4}$  S BT visible  
on open blaze. (Record, 166 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins.  
in the ground, and in a mound of stone, 3 ft. base, to  
top, with brass cap mkd.

Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 31 E., Willamette Meridian, Oregon

CHAINS

T 5 S R 31 E

$$\begin{array}{c} \frac{1}{4} \\ \hline S 19 | S 20 \\ 1978 \end{array}$$

from which a new bearing tree

A ponderosa pine, 8 ins. diam., bears N.  $59\frac{1}{2}^{\circ}$  W.,  
32 lks. dist., mkd.  $\frac{1}{4}$  S19 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 17, 18, 19, and 20, monumented with the  
original unmarked basalt stone, 20 x 12 x 8 ins., firmly  
set 10 ins. in a mound of stone, 3 ft. base, 1 ft. high,  
from which the remains of the original bearing trees:

A decayed pine stump, size indeterminate, bears  
N.  $17^{\circ}$  E., 23 lks. dist., with a down and decayed  
pine alongside, with scribe marks T5S R31E  
visible on open blaze. (Record, N.  $28^{\circ}$  E.)

A decayed fir stump, size indeterminate, bears  
S.  $64^{\circ}$  E., 7 lks. dist., with a down and decayed  
fir alongside, with scribe marks T5S R31E S20  
visible on open blaze.

A sawed pine stump, 15 ins. diam., bears S.  $45^{\circ}$  W.,  
72 lks. dist., no marks visible. (Record, 75 lks.)

A fir snag, 24 ins. diam., bears N.  $76^{\circ}$  W., 67 lks.  
dist., with scribe marks T5S R31E S18 visible on  
open blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, and in a mound of stone, 3 ft. base, to  
top, with brass cap mkd.

$$\begin{array}{c} T 5 S R 31 E \\ \hline S 18 | S 17 \\ S 19 | S 20 \\ 1978 \end{array}$$

from which new bearing trees

A fir, 13 ins. diam., bears N.  $31^{\circ}$  E.,  $54\frac{1}{2}$  lks.  
dist., mkd. T5S R31E S17 BT.

A fir, 12 ins. diam., bears S.  $22^{\circ}$  E., 26 lks.  
dist., mkd. T5S R31E S20 BT.

A ponderosa pine, 14 ins. diam., bears S.  $10^{\circ}$  W.,  
 $38\frac{1}{2}$  lks. dist., mkd. T5S R31E S19 BT.

A fir, 12 ins. diam., bears N.  $74\frac{1}{2}^{\circ}$  W., 26 lks.  
dist., mkd. T5S R31E S18 BT.

Deposit corner stone alongside iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 7 and 18, determined at record  
bearing and distance from the remains of the original  
bearing trees:

Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 31 E., Willamette Meridian, Oregon

CHAINS

A pine stump, 16 ins. diam., bears N. 62° W., 141 lks. dist., with scribe marks  $\frac{1}{4}$  S visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S R 31 E  
 $\frac{1}{4}$   $\frac{S 7}{S 18}$   
 1978

from which new bearing trees

A ponderosa pine, 15 ins. diam., bears N. 45½° W., 78 lks. dist., mkd.  $\frac{1}{4}$  S7 BT.

A ponderosa pine, 10 ins. diam., bears S. 45° W., 345 lks. dist., mkd.  $\frac{1}{4}$  S18 BT.

The cor. of secs. 5, 6, 7, and 8, monumented with the original basalt stone, 14 x 10 x 8 ins., firmly set 6 ins. in the ground, and in a mound of stone, 2 ft. base, 1 ft. high, mkd. with 5 notches on E. and S. edges, from which the remains of the original bearing trees:

A sawed pine stump, 40 ins. diam., bears N. 40° E., 37 lks. dist., with scribe marks BT visible on open blaze.

A sawed pine stump, 26 ins. diam., bears S. 33° E., 44 lks. dist., with scribe marks BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S R 31 E  
 $\frac{S 6}{S 7} | \frac{S 5}{S 8}$   
 1978

from which new bearing trees

A ponderosa pine, 8 ins. diam., bears N. 50° E., 20 lks. dist., mkd. T5S R31E S5 BT.

A ponderosa pine, 17 ins. diam., bears S. 47° E., 17½ lks. dist., mkd. T5S R31E S8 BT.

A ponderosa pine, 8 ins. diam., bears S. 24° W., 86 lks. dist., mkd. T5S R31E S7 BT.

A ponderosa pine, 16 ins. diam., bears N. 56° W., 26½ lks. dist., mkd. T5S R31E S6 BT.

Deposit corner stone alongside iron post.



CERTIFICATE OF SURVEY

(I) (~~WX~~), Craig L. Wanless, Cadastral Surveyor, , HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May , 19 57, (I) (~~WX~~) have remonumented certain original corner points, township 5 south, range 31 east,

of the Willamette Meridian, in the State of Oregon , which are represented in the foregoing field notes as having been executed by (me), (~~WX~~) and under (my) (~~own~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 13, 1978  
(Date)

*Craig L. Wanless*  
(Cadastral Surveyor)

\_\_\_\_\_  
(Date)

\_\_\_\_\_  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
~~Washington, D.C.~~  
Denver,, Colorado

The foregoing field notes of the remonumentation of certain original corner points, township 5 south, range 31 east, Willamette Meridian, Oregon,

executed by Craig L. Wanless, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

FEB 07 1980  
(Date)

*J. Voorhees*  
(Chief, Division of Cadastral Survey)  
Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in , is a true copy of the original field notes.

\_\_\_\_\_  
(Date)

\_\_\_\_\_  
(Chief, Division of Cadastral Survey) GPO 849-626