

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 5 SOUTH, RANGE 30 EAST,

[Lined area for field notes]

Of the WILLAMETTE Meridian,

In the State of OREGON

EXECUTED BY

Craig L. Wanless, Cadastral Surveyor

[Lined area for signature]

Under special instructions dated May 3, 1957, approved May 6, 1957,

[Lined area for notes]

_____, which provided for the surveys included under U.S. Survey/Group
Number 350, and assignment instructions dated March 27, 1978.

[Lined area for notes]

Survey commenced April 5, 1978

Survey completed April 18, 1978

INDEX DIAGRAM

Township 5 South, Range 30 East,

					<u>7</u>	<u>3</u>
6	5	4	3	2	1	
	<u>17</u>	<u>14</u>	<u>11</u> <u>11</u>			
7	8	9	<u>10</u> 10	<u>9</u> 11	12	
<u>17</u>	<u>16</u>	<u>13</u>		<u>8</u>		
18	<u>16</u> 17	16	<u>10</u> 15	<u>8</u> 14	13	
<u>15</u>		<u>12</u> <u>13</u>			<u>7</u>	
19	20	21	22	23	<u>6</u> 24	<u>3</u>
	<u>15</u>		<u>9</u>		<u>6</u>	<u>2</u>
30	29	28	27	26	<u>5</u> 25	<u>2</u>
<u>14</u>		<u>12</u>			<u>5</u>	<u>1</u>
31	32	33	34	35	36	

4

T. 5 S., R. 30 E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 5 south, range 30 east, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories when Needed".

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is $20^{\circ} 30'$ E.

East Boundary, T. 5 S., R. 30 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by George S. Pershin,
U. S. Deputy Surveyor, in 1880)

The cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., monumented with the original unmarked basalt stone, 18 x 16 x 8 ins., firmly set 6 ins. in the ground, and in a mound of stone, 2 ft. base, 6 ins. high, from which the remains of the original bearing trees:

A sawed and decayed pine stump, size indeterminate, bears N. 77° E., 46 lks. dist., no marks visible.

A pine, 22 ins. diam., bears S. 60° E., 103 lks. dist., with scribe marks 5S R31E S31 visible on open blaze.

A pine, 22 ins. diam., bears N. 66° W., 37 lks. dist., with scribe marks T5S R30E S25 visible on open blaze. (Record, 34 lks.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S	
R 30 E	R 31 E
S 25	S 30
S 36	S 31
1978	

from which new bearing trees

A ponderosa pine, 11 ins. diam., bears N. $23\frac{1}{2}^{\circ}$ E., 98 lks. dist., mkd. T5S R31E S30 BT.

A ponderosa pine, 11 ins. diam., bears S. 60° W., 45 lks. dist., mkd. T5S R30E S36 BT.

Deposit corner stone alongside iron post.

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 30 E., Willamette Meridian, Oregon

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., monumented with the original unmarked basalt stone, 14 x 10 x 8 ins., firmly set 8 ins. in the ground, and in a mound of stone, 3 ft. base, 1 ft. high, from which the remains of the original bearing trees:

A pine, 25 ins. diam., bears S. 12° E., 94 lks. dist., with healed blaze.

A pine snag, 23 ins. diam., bears N. 80° W., 43 lks. dist., with scribe marks $\frac{1}{4}$ S visible on open blaze. (Record, N. 85° W.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S			
$\frac{1}{4}$			
R 30 E	R 31 E		
S 25	S 30		
1978			

from which a new bearing tree

A ponderosa pine, 9 ins. diam., bears N. 44° W., 46 lks. dist., mkd. $\frac{1}{4}$ S25 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with the original unmarked basalt stone, 17 x 10 x 7 ins., firmly set 8 ins. in the ground, and in a mound of stone, 2 ft. base, 6 ins. high, from which the remains of the original bearing trees:

A decayed fir stump, size indeterminate, bears N. 47° E., 31 lks. dist., with scribe marks T5S R31E S19 visible on piece of wood lying alongside.

A decayed fir stump, size indeterminate, bears S. 42° E., 38 lks. dist., no marks visible.

A decayed fir stump, size indeterminate, bears S. 40° W., 23 lks. dist., with scribe marks T5S R30E S2 visible on piece of wood lying alongside.

A pine stump, 22 ins. diam., bears N. 8° W., 88 lks. dist., with scribe mark T visible on open blaze. (Record, N. 13° W.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S			
R 30 E	R 31 E		
S 24	S 19		
S 25	S 30		
1978			

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 30 E., Willamette Meridian, Oregon

CHAINS

from which new bearing trees

A fir, 10 ins. diam., bears N. 31° E., 54 lks.
dist., mkd. T5S R31E S19 BT.

A fir, 8 ins. diam., bears S. 13½° E., 17 lks.
dist., mkd. T5S R31E S30 BT.

A ponderosa pine, 9 ins. diam., bears S. 71° W.,
58 lks. dist., mkd. T5S R30E S25 BT.

A fir, 8 ins. diam., bears N. 38½° W., 11 lks.
dist., mkd. T5S R30E S24 BT.

Deposit corner stone alongside iron post.

The ¼ sec. cor. of secs. 19 and 24, on the E. bdy. of the
Tp., monumented with the original unmarked basalt stone,
15 x 10 x 5 ins., firmly set 6 ins. in the ground, and
in a mound of stone, 2 ft. base, 6 ins. high, from which
the remains of the original bearing trees:

A pine, 27 ins. diam., bears N. 57° E., 38 lks.
dist., with healed blaze. (Record, 35 lks.)

A pine snag, 33 ins. diam., bears N. 35° W., 33
lks. dist., with scribe mark S visible on open
blaze. (Record, N. 42° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, and in a mound of stone, 3 ft. base, to
top, with brass cap mkd.

T 5 S
¼
R 30 E | R 31 E
S 24 | S 19
1978

from which a new bearing tree

A ponderosa pine, 8 ins. diam., bears S. 71° W.,
17 lks. dist., mkd. ¼ S24 BT.

Deposit corner stone alongside iron post.

The cor. of Tps. 4 and 5 S., Rs. 30 and 31 E., monumented
with the original unmarked basalt stone, 18 x 14 x 10
ins., firmly set 5 ins. in the ground, and in a mound of
stone, 4 ft. base, 1 ft. high, from which the remains of
the original bearing trees:

A sawed pine stump, 22 ins. diam., bears N. 50° E.,
54 lks. dist., with fragmentary scribe marks
visible on open blaze. (Record, N. 56° E.)

A sawed pine stump, 26 ins. diam., bears S. 33° E.,
118 lks. dist., with scribe marks BT visible
on open blaze.

A pine, 21 ins. diam., bears S. 70° W., 39 lks.
dist., with scribe marks T5S R30E S1 B visible
on open blaze. (Record, S. 62° W.)

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 30 E., Willamette Meridian, Oregon

CHAINS

A pine, 29 ins. diam., bears N. 80° W., 80 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S			
R 30 E		R 31 E	
S 36		S 31	
S 1		S 6	
T 5 S			
1978			

from which new bearing trees

A ponderosa pine, 9 ins. diam., bears N. 34° E., 27½ lks. dist., mkd. T4S R31E S31 BT.

A ponderosa pine, 11 ins. diam., bears S. 52½° E., 31 lks. dist., mkd. T5S R31E S6 BT.

Deposit corner stone alongside iron post.

West Boundary, T. 5 S., R. 30 E.,
Willamette Meridian, Oregon

(Remonumenting a corner established by Edward W. Sanderson
U. S. Deputy Surveyor, in 1882)

The ¼ sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp., monumented with the original basalt stone, 20 x 10 x 8 ins. (record, 18 x 8 x 7 ins.), firmly set 6 ins. in the ground, and in a mound of stone, 2 ft. base, 6 ins. high, mkd. ¼ on W. face, from which the remains of an original bearing tree:

A root hole, bears S. 50° E., 52 lks. dist., with a sawed pine alongside, 36 ins. diam., with scribe marks BT visible on open blaze. (Record, S. 52° E.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S			
¼			
R 29 E		R 30 E	
S 25		S 30	
1978			

from which new bearing trees

A lodgepole pine, 6 ins. diam., bears N. 75° E., 66½ lks. dist., mkd. ¼ S30 BT.

A fir, 8 ins. diam., bears N. 45° W., 65½ lks. dist., mkd. ¼ S25 BT.

Deposit corner stone alongside iron post.

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
William R. Moore	Engineering Aid

FEB 07 1980

CERTIFICATE OF SURVEY

(I) (~~XX~~), Craig L. Wanless, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May, 1957, (I) (~~XX~~) have remonumented certain original corner points, township 5 south, range 30 east,

of the Willamette Meridian, in the State of Oregon, which are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 17, 1978 (Date) Craig L. Wanless (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C. Denver, Colorado

The foregoing field notes of the remonumentation of certain original corner points, township 5 south, range 30 east, Willamette Meridian, Oregon,

executed by Craig L. Wanless, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

FEB 07 1980 (Date) J.D. Voorhes (Chief, Division of Cadastral Survey) Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-526