

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

R621

01

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY

(FIRST STANDARD PARALLEL SOUTH),

A PORTION OF THE SUBDIVISIONAL LINES,

SUBDIVISION OF SECTIONS 32, 33, 34, AND 35,

and

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 5 SOUTH, RANGE 32 EAST,

Of the WILLAMETTE Meridian,

In the State of OREGON

EXECUTED BY

James E. Jelley, Cadastral Surveyor

Harvey E. Wofford, Cadastral Surveyor

William D. Kimmel, Cadastral Surveyor

Rick E. Tawney, Cadastral Surveyor

Under special instructions dated May 3, 19 57, approved May 6, 1957,

special instructions dated June 16, 1967, approved August 24, 1967, and
supplemental special instructions dated July 25, 1978, approved July 31, 1978,

_____, which provided for the surveys included under U.S. Survey/Group
Number s 643 and 350, and assignment instructions dated August 21, 19 67,

June 2, 1975; May 30, 1979; March 26, 1980; and April 4, 1980

Survey commenced August 24, 19 67

Survey completed June 9, 19 80

ORIGINAL

FIELD NOTES

OF THE

01

02

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY

(FIRST STANDARD PARALLEL SOUTH)

A PORTION OF THE SUBDIVISIONAL LINES

SUBDIVISION OF SECTIONS 32, 33, 34, AND 35

and

INDEX DIAGRAM

Township 5 South, Range 32 East

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	21	32	17	33	14

- Subdivision of Section 32 -- Pages 24-27
- Subdivision of Section 33 -- Pages 27-30
- Subdivision of Section 34 -- Pages 30-33
- Subdivision of Section 35 -- Pages 33-36

T. 5 S., R. 32 E., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary (First Standard Parallel South), a portion of the subdivisional lines, the subdivision of sections 32, 33, 34, and 35, and the remonumentation of certain original corner points, township 5 south, range 32 east, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey, is as follows:

The south boundary of the township (First Standard Parallel South) was surveyed by George S. Pershin, in 1880.

The east boundary of the township and subdivisional lines were surveyed by George S. Pershin, in 1881.

The area covered by this resurvey was dependently resurveyed by Jerome C. Ives, Cadastral Surveyor, in 1967-68, utilizing photogrammetric methods. Prior to submission of the final field returns to the Director for final review and acceptance, a field investigation disclosed sufficient variances from acceptable Manual standards to warrant retracements and corrections. This dependent resurvey and survey by conventional methods is to resolve and correct the discrepancies. Due to the length of time in executing the survey, the field notes indicate the year new accessories were marked at each corner.

The survey was executed in accordance with the specifications as set forth in the Manuals of Surveying Instructions, 1947 and 1973, Special Instructions dated May 3, 1957, Special Instructions dated June 16, 1967, and Supplemental Special Instructions dated July 25, 1978, under Group Numbers 350 and 643, Oregon.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed. Those lines not forming a closure were measured twice.

The directions of the lines were determined by deflections from azimuths obtained by direct solar observations.

The geographic position of the standard corner of sections 35 and 36, on the south boundary of the township, as scaled from the Ukiah SE. quadrangle map, published by the United States Geological Survey, in 1967, is as follows:

Latitude $45^{\circ} 05.0' N.$ Longitude $118^{\circ} 47.8' W.$

The mean magnetic declination is $20^{\circ} E.$

Dependent Resurvey of a Portion of the South Boundary
(First Standard Parallel South)

T. 5 S., R. 32 E., Willamette Meridian, Oregon

Dependent Resurvey of a Portion of the South Boundary
(First Standard Parallel South)

T. 5 S., R. 32 E., Willamette Meridian, Oregon

CHAINS

A pine, 28 ins. diam., bears N. 22° W., 478 lks.
dist., mkd. T5S R31E S36 SC BT. (1968)

Deposit corner stone alongside iron post.

Land, rolling hills.

Soil, rocky.

Timber, pine, fir, juniper, and larch; undergrowth,
sagebrush.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 32 E., Willamette Meridian, Oregon

(Restoring the survey by George S. Pershin,
U. S. Deputy Surveyor, in 1881)

From the standard cor. of secs. 34 and 35, on the S. bdy.
of the Tp.

N. 0° 03' E., bet. secs. 34 and 35, marking and blazing
the true line.

Descend 165 ft. over NE. slope, through light timber and
undergrowth.

19.94 Point for the S 1/16 sec. cor. of secs. 34 and 35.

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins.
in the ground, in a mound of stone, 3 ft. base, to top,
with brass cap mkd.

S 1/16
S 34 | S 35
1980

from which

A pine, 16 ins. diam., bears N. 84° E., 23 lks.
dist., mkd. S 1/16 S35 BT. (1980)

A pine, 14 ins. diam., bears S. 22° W., 131½ lks.
dist., mkd. S 1/16 S34 BT. (1980)

Descend 275 ft. over NE. slope.

28.80 Abandoned dirt road, 20 lks. wide, bears NW. and SE.

37.30 Abandoned dirt road, 20 lks. wide, bears NW. and SE.

38.95 Abandoned dirt road, 20 lks. wide, bears NW. and SE.

39.88 The ¼ sec. cor. of secs. 34 and 35, determined from the
remaining original bearing tree:

A larch, 16 ins. diam., bears S. 45° W., 10 lks.
dist., with scribe marks ¼ S visible on partially
opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

14

Dependent Resurvey, Portion of Subdivisional Lines,
T. 5 S., R. 32 E., Willamette Meridian, Oregon

CHAINS

T 5 S R 32 E

$$\begin{array}{c} \frac{1}{4} \\ \hline S 34 | S 35 \\ 1968 \end{array}$$

from which new bearing trees

A fir, 12 ins. diam., bears S. $35\frac{1}{2}^{\circ}$ E., 18 $\frac{1}{2}$ lks.
dist., mkd. $\frac{1}{4}$ S35 BT. (1968)

A fir, 8 ins. diam., bears N. 20° W., 59 $\frac{1}{2}$ lks.
dist., mkd. $\frac{1}{4}$ S34 BT. (1968)

N. $0^{\circ} 11'$ W., beginning new measurement.

Descend 90 ft. over NE. slope.

17.85 Creek, 2 lks. wide, course N. 25° E.; asc. 1 ft. over
nearly level land.

20.06 Point for the N 1/16 sec. cor. of secs. 34 and 35.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins.
in the ground, in a mound of stone, 2 $\frac{1}{2}$ ft. base, to top,
with brass cap mkd.

$$\begin{array}{c} N 1/16 \\ \hline S 34 | S 35 \\ 1968 \end{array}$$

from which

A fir, 15 ins. diam., bears N. $85\frac{1}{2}^{\circ}$ E., 122 lks.
dist., mkd. N 1/16 S35 BT. (1968)

A fir, 10 ins. diam., bears N. 85° W., 18 lks.
dist., mkd. N 1/16 S34 BT. (1968)

From this point, a corner of fences extending N., S.,
and W., bears N. 20° W., 0.64 chs. dist.

Descend 15 ft. over nearly level land.

25.25 Creek, 2 lks. wide, course N. 10° W.; desc. 25 ft. over
nearly level land.

31.40 Leave timber and undergrowth, enter open grassland, edge
bears E. and W.

40.12 Point for the cor. of secs. 26, 27, 34, and 35, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins.
in the ground, in a mound of stone, 3 ft. base, to top,
with brass cap mkd.

$$\begin{array}{c} T 5 S R 32 E \\ \hline S 27 | S 26 \\ \hline S 34 | S 35 \\ 1968 \end{array}$$

from which

A pine, 36 ins. diam., bears N. 32° E., 454 lks.
dist., mkd. T5S R32E S26 BT. (1968)

Dependent Resurvey, Portion of Subdivisional Lines,
T. 5 S., R. 32 E., Willamette Meridian, Oregon

CHAINS

No other suitable trees available within limits.

From this point, the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, bears N. $0^{\circ} 11'$ E., 40.12 chs. dist., determined from the remains of the original bearing tree:

A burned pine snag, 20 ins. diam., bears S. 10° W., 74 lks. dist., with scribe marks BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

$\frac{1}{4}$
S 27 | S 26
T 5 S R 32 E
1968

from which new bearing trees

A birch, 10 ins. diam., bears S. 45° E., $216\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S26 BT. (1980)

A pine, 15 ins. diam., bears N. 14° W., 58 lks. dist., mkd. $\frac{1}{4}$ S27 BT. (1980)

Land, rolling hills.

Soil, rocky.

Timber, pine, fir, larch, and spruce; undergrowth, young timber, arrowwood, and hazel.

From the cor. of secs. 25, 26, 35, and 36, determined at the intersection of an abandoned dirt road, 20 lks. wide, bears N. and S., and the remains of fence line extending E. and W. This point is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, to solid rock, in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap mkd.

T 5 S R 32 E
S 26 | S 25
S 35 | S 36
1968

Raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, W. of corner.

No suitable trees available within limits.

S. $89^{\circ} 34'$ W., bet. secs. 26 and 35.

Descend 95 ft. over W. slope, across open rocky grassland.

40.03

Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, to solid rock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.

Dependent Resurvey, Portion of Subdivisional Lines,
T. 5 S., R. 32 E., Willamette Meridian, Oregon

CHAINS		
	<p>T 5 S R 32 E</p> <p>$\frac{1}{4}$ $\frac{S 26}{S 35}$</p> <p>1968</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, N. of corner.</p> <p>No suitable trees available within limits.</p> <p>Descend 85 ft. over W. slope.</p>	
47.70	Dirt road, 20 lks. wide, bears N. 30° W. and S. 30° E.	
55.55	Pine Creek, 4 lks. wide, course N. 10° W.; asc. 60 ft. over NE. slope.	
67.65	Dirt road, 20 lks. wide, bears N. 25° W. and S. 25° E.	
67.75	Barbed wire fence, bears N. 25° W. and S. 25° E.	
68.85	Barbed wire fence, bears N. 50° E. and S. 50° W.	
74.70	Top of ascent, slopes N.; desc. 5 ft. over nearly level land.	
80.06	The cor. of secs. 26, 27, 34, and 35.	
	<p>Land, rolling hills.</p> <p>Soil, rocky loam.</p> <p>Timber, none; vegetation, arrowwood, hazel, and grasses.</p>	
	<p>From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp.</p> <p>N. 0° 02' E., bet. secs. 33 and 34.</p> <p>Descend 120 ft. over NE. slope, through moderate timber and light undergrowth.</p>	
19.90	Bottom of descent, slopes E.; asc. 35 ft. over SE. slope.	
30.15	Spur, slopes E.; desc. 140 ft. over NE. slope.	
35.40	Abandoned dirt road, 20 lks. wide, bears NW. and SE.	
37.30	Dry Creek, 5 lks. wide, course N. 20° E.; asc. 5 ft. over SW. slope.	
40.05	<p>The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, determined from the remains of the original bearing trees:</p> <p>A fir snag, 22 ins. diam., bears S. 61° E., 41 lks. dist., with scribe marks $\frac{1}{4}$ S visible on partially opened blaze. (Record, S. 54° E.)</p> <p>A sawed larch stump, 35 ins. diam., bears S. 12° W., 41 lks. dist., with healed blaze. (Record, S. 18° W.)</p> <p>At the cornerpoint</p> <p>Seat a brass tablet, 3$\frac{1}{4}$ ins. diam., 3$\frac{1}{2}$ ins. stem, in drill hole in exposed bedrock, with top mkd.</p>	

Dependent Resurvey, Portion of Subdivisional Lines,
T. 5 S., R. 32 E., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">T 5 S R 32 E $\frac{1}{4}$ S 33 S 34 1980</p> <p>from which new bearing trees</p> <p>A fir, 12 ins. diam., bears N. 44° E., 76 lks., dist., mkd. $\frac{1}{4}$ S34 BT. (1968)</p> <p>A spruce, 10 ins. diam., bears S. 71° W., 66½ lks., dist., mkd. $\frac{1}{4}$ S33 BT. (1968)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 33' W., beginning new measurement.</p> <p>Descend 20 ft. over NW. slope.</p>
1.70	Dry Creek, 5 lks. wide, course N. 5° E.; asc. 15 ft. over SE. slope.
7.35	Abandoned dirt road, 20 lks. wide, bears N. 15° E. and S. 15° W.
18.35	Spur, slopes S. 70° E.; desc. 90 ft. over NE. slope.
25.75	Dry Creek, 5 lks. wide, course N. 10° W.; asc. 50 ft. over SW. slope.
29.85	Abandoned dirt road, 20 lks. wide, bears N. 20° W. and S. 20° E.
34.80	Top of ascent, slopes W.; desc. 35 ft. over NW. slope.
39.98	<p>The cor. of secs. 27, 28, 33, and 34, determined from the remains of the original bearing trees:</p> <p>A burned larch stump, 18 ins. diam., bears N. 70° E., 36 lks. dist., with scribe marks T5S R32E S27 BT visible on open blaze. (Record, N. 68° E.)</p> <p>A larch snag, 18 ins. diam., bears S. 28° E., 77 lks. dist., with scribe marks T5S R32E S34 BT visible on opened blaze. (Record, S. 26° E.)</p> <p>A pine snag, 25 ins. diam., bears S. 22° W., 73 lks. dist., with scribe marks R32E S33 visible on open blaze. (Record, S. 26° W.)</p> <p>A burned and decayed fir stump, size indeterminate, bears N. 20° W., 34 lks. dist., no marks visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 32 E S 28 S 27 S 33 S 34 1968</p> <p>from which new bearing trees</p> <p>A larch, 9 ins. diam., bears N. 52° E., 91 lks. dist., mkd. T5S R32E S27 BT. (1968)</p>

18

Dependent Resurvey, Portion of Subdivisional Lines,
T. 5 S., R. 32 E., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 8 ins. diam., bears S. 28½° E., 70½ lks. dist., mkd. T5S R32E S34 BT. (1968)</p> <p>A fir, 6 ins. diam., bears S. 28° W., 11½ lks. dist., mkd. T5S R32E S33 BT. (1968)</p> <p>A fir, 9 ins. diam., bears N. 44° W., 40½ lks. dist., mkd. T5S R32E S28 BT. (1968)</p> <p>Corner is located in ravine, drains S. 25° W.</p> <p>Land, mountainous. Soil, rocky loam. Timber, pine, fir, and larch; undergrowth, young timber, arrowwood, and hazel.</p>
	<p>From the cor. of secs. 26, 27, 34, and 35. S. 89° 57' W., bet. secs. 27 and 34.</p> <p>Descend 2 ft. over nearly level open grassland.</p>
5.20	Creek, 2 lks. wide, course N. 15° W.; asc. 1 ft. over nearly level land.
7.00	Top of ascent, slopes N.; desc. 2 ft. over nearly level land.
8.00	Creek, 2 lks. wide, course N. 10° E.; asc. 40 ft. over NE. slope.
16.50	Leave grassland, enter light timber and undergrowth, edge bears N. and S.
19.95	Point for the E 1/16 sec. cor. of secs. 27 and 34.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 $\frac{S\ 27}{S\ 34}$ 1968</p> <p>from which</p> <p>A larch, 12 ins. diam., bears N. 36° E., 90 lks. dist., mkd. E 1/16 S27 BT. (1968)</p> <p>A pine, 17 ins. diam., bears S. 2° E., 58 lks. dist., mkd. E 1/16 S34 BT. (1968)</p> <p>From this point, a rock crib, 4 x 4 x 4 ft., bears S. 10° E., 8½ lks. dist., with fences extending S. and W.</p> <p>Ascend 55 ft. over NE. slope, along fence line.</p>
25.90	Top of ascent, slopes N.; desc. 40 ft. over NW. slope.
39.90	<p>The ¼ sec. cor. of secs. 27 and 34, determined from the remains of the original bearing trees:</p> <p>A pine, 36 ins. diam., bears S. 23° W., 44 lks. dist., with scribe marks ¼ S visible on partially healed blaze. (Record, S. 26° W.)</p>

Dependent Resurvey, Portion of Subdivisional Lines,
T. 5 S., R. 32 E., Willamette Meridian, Oregon

CHAINS	
	<p>A sawed pine stump, 34 ins. diam., bears N. 40° W., 6 lks. dist., with scribe marks BT visible on open blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ $\frac{S\ 27}{S\ 34}$ T 5 S R 32 E 1967 </p> <p>from which new bearing trees</p> <p>A fir, 9 ins. diam., bears S. 22° E., 44½ lks. dist., mkd. $\frac{1}{4}$ S34 BT. (1967)</p> <p>A fir, 6 ins. diam., bears N. 56° W., 35 lks. dist., mkd. $\frac{1}{4}$ S27 BT. (1967)</p> <hr/> <p>S. 89° 55' W., beginning new measurement.</p> <p>Descend 10 ft. over NW. slope.</p> <p>1.05 Ravine, drains NW.; asc. 225 ft. over NE. slope.</p> <p>18.10 Abandoned dirt road, 20 lks. wide, bears N. 70° W. and S. 70° E.</p> <p>33.80 Spur, slopes NW.; desc. 130 ft. over NW. slope.</p> <p>39.74 The cor. of secs. 27, 28, 33, and 34.</p> <p>Land, rolling hills. Soil, rocky loam. Timber, pine, fir, larch, and spruce; undergrowth, young timber and arrowwood.</p> <hr/> <p>From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp.</p> <p>N. 0° 07' W., bet. secs. 32 and 33.</p> <p>Descend 45 ft. over N. slope, through light timber and undergrowth.</p> <p>0.75 Dirt road, 20 lks. wide, bears N. 80° W. and S. 80° E.</p> <p>9.55 Ravine, drains N. 75° W.; asc. 20 ft. over SW. slope.</p> <p>16.05 Top of ascent, slopes N. 60° W.; desc. 35 ft. over NW. slope.</p> <p>25.35 Ravine, drains W.; asc. 25 ft. over SW. slope.</p> <p>30.05 Leave timber, enter open rocky grassland, edge bears E. and W.</p> <p>35.70 Top of ascent, slopes NW.; desc. 15 ft. over NE. slope.</p> <p>35.80 Dirt road, 20 lks. wide, bears N. 30° W. and S. 30° E.</p> <p>38.10 Leave grassland, enter moderate timber and light undergrowth, edge bears E. and W.</p>

Dependent Resurvey, Portion of Subdivisional Lines,
T. 5 S., R. 32 E., Willamette Meridian, Oregon

<p>CHAINS 40.09</p>	<p>The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, monumented with the original basalt stone, 16 x 12 x 4 ins., firmly set, projecting 8 ins. above ground, mkd. $\frac{1}{4}$ on W. face, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A fir stump, size indeterminate, bears N. 66° E., 14 lks. dist., with scribe marks BT visible on opened blaze. (Record, N. 68° E.)</p> <p style="padding-left: 40px;">A root hole, bears S. 47° W., 18 lks. dist.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 5 S R 32 E</p> <p style="margin-left: 40px;">$\frac{1}{4}$</p> <p style="margin-left: 40px;">S 32 S 33</p> <p style="margin-left: 40px;">1968</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 88½° E., 229 lks. dist., mkd. $\frac{1}{4}$ S33 BT. (1968)</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 81° W., 36 lks. dist., mkd. $\frac{1}{4}$ S32 BT. (1968)</p> <p style="padding-left: 40px;">Deposit corner stone alongside iron post.</p> <hr style="width: 20%; margin-left: 40px;"/> <p style="padding-left: 40px;">N. 0° 09' W., beginning new measurement.</p> <p style="padding-left: 40px;">Descend 330 ft. over NE. slope.</p>
<p>19.975</p>	<p>Point for the N 1/16 sec. cor. of secs. 32 and 33.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16</p> <p style="margin-left: 40px;">S 32 S 33</p> <p style="margin-left: 40px;">1968</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 33½° E., 49½ lks. dist., mkd. N 1/16 S33 BT. (1968)</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 22° W., 11½ lks. dist., mkd. N 1/16 S32 BT. (1968)</p> <p style="padding-left: 40px;">Descend 90 ft. over NE. slope.</p>
<p>20.35</p>	<p>Barbed wire fence, bears E. and W.</p>
<p>27.50</p>	<p>Creek, 3 lks. wide, course N. 10° W.; asc. 5 ft. over nearly level land.</p>
<p>32.60</p>	<p>Top of ascent, slopes N. 10° W.; desc. 90 ft. over NE. slope.</p>
<p>39.95</p>	<p>The cor. of secs. 28, 29, 32, and 33, monumented with the original unmarked basalt stone, 18 x 12 x 5 ins., firmly set 6 ins. in the ground, from which the remains of the original bearing trees:</p>

Dependent Resurvey, Portion of Subdivisional Lines,
T. 5 S., R. 32 E., Willamette Meridian, Oregon

CHAINS							
	<p>A fir stump, 16 ins. diam., bears N. 62° E., 59 lks. dist., with scribe marks 5S R32E S28 BT visible on opened blaze.</p> <p>A root hole, bears S. 66° E., 92 lks. dist.</p> <p>A fir stump, 18 ins. diam., bears N. 24° W., 84 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 5 S R 32 E</td> </tr> <tr> <td>S 29 S 28</td> </tr> <tr> <td>S 32 S 33</td> </tr> <tr> <td>1968</td> </tr> </table> </div> <p>from which new bearing trees</p> <p>A larch, 9 ins. diam., bears N. 48° E., 40 lks. dist., mkd. T5S R32E S28 BT. (1968)</p> <p>A larch, 8 ins. diam., bears S. 25° E., 46 lks. dist., mkd. T5S R32E S33 BT. (1968)</p> <p>A larch, 20 ins. diam., bears S. 24° W., 54 lks. dist., mkd. T5S R32E S32 BT. (1968)</p> <p>A larch, 12 ins. diam., bears N. 79° W., 43 lks. dist., mkd. T5S R32E S29 BT. (1968)</p> <p>Deposit corner stone alongside iron post.</p> <p>Land, rolling hills. Soil, rocky loam. Timber, pine, fir, and larch; undergrowth, young timber, arrowwood, and hazel.</p>	T 5 S R 32 E	S 29 S 28	S 32 S 33	1968		
T 5 S R 32 E							
S 29 S 28							
S 32 S 33							
1968							
	<p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>S. 89° 54' W., bet. secs. 28 and 33.</p> <p>Ascend 40 ft. over SE. slope, through moderate timber and light undergrowth.</p>						
1.40	Spur, slopes S.; desc. 45 ft. over W. slope.						
2.80	Abandoned dirt road, 20 lks. wide, bears N. 10° W. and S. 10° E.						
5.70	Dry Creek, 5 lks. wide, course N. 30° W.; asc. 220 ft. over NE. slope.						
19.965	Point for the E 1/16 sec. cor. of secs. 28 and 33.						
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, to solid rock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>E 1/16</td> <td>S 28</td> </tr> <tr> <td></td> <td>S 33</td> </tr> <tr> <td>1968</td> <td></td> </tr> </table> </div> <p>from which</p>	E 1/16	S 28		S 33	1968	
E 1/16	S 28						
	S 33						
1968							

22

Dependent Resurvey, Portion of Subdivisional Lines,
T. 5 S., R. 32 E., Willamette Meridian, Oregon

CHAINS	
	<p>A pine, 14 ins. diam., bears N. 64° E., 206 lks. dist., mkd. E 1/16 S28 BT. (1968)</p> <p>A pine, 13 ins. diam., bears S. 28° E., 143 lks. dist., mkd. E 1/16 S33 BT. (1968)</p> <p>Ascend 1 ft. over nearly level land.</p>
20.10	Top of ascent, slopes N.; desc. 80 ft. over NW. slope.
33.35	Dirt road, 20 lks. wide, bears N. 35° E. and S. 35° W.
39.93	<p>The ¼ sec. cor. of secs. 28 and 33, monumented with the original basalt stone, 18 x 10 x 5 ins., firmly set 10 ins. in the ground, mkd. ¼ on N. face, from which the remains of the original bearing trees:</p> <p>A sawed pine stump, 30 ins. diam., bears N. 36° E., 50 lks. dist., with scribe marks BT visible on opened blaze.</p> <p>A sawed pine stump, 38 ins. diam., bears S. 38° W., 74 lks. dist., no marks visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 32 E ¼ $\frac{S 28}{S 33}$ 1968</p> <p>from which new bearing trees</p> <p>A fir, 11 ins. diam., bears S. 53° W., 33 lks. dist., mkd. ¼ S33 BT. (1968)</p> <p>A pine, 13 ins. diam., bears N. 43° W., 96½ lks. dist., mkd. ¼ S28 BT. (1968)</p> <p>Deposit corner stone alongside iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89° 49' W., beginning new measurement.</p> <p>Descend 2 ft. over nearly level land.</p>
0.10	Ravine, drains N.; asc. 50 ft. over NE. slope.
11.10	Top of ascent, slopes N.; desc. 65 ft. over NW. slope.
20.05	<p>Point for the W 1/16 sec. cor. of secs. 28 and 33.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 $\frac{S 28}{S 33}$ 1980</p> <p>from which</p> <p>A fir, 6 ins. diam., bears N. 89° E., 121½ lks. dist., mkd. W 1/16 S28 BT. (1980)</p>

Dependent Resurvey, Portion of Subdivisional Lines,
T. 5 S., R. 32 E., Willamette Meridian, Oregon

CHAINS	
	<p>A pine, 15 ins. diam., bears S. $60\frac{1}{2}^{\circ}$ E., 70$\frac{1}{2}$ lks. dist., mkd. W 1/16 S33 BT. (1980)</p> <p>Descend 100 ft. over NW. slope.</p>
25.15	Abandoned dirt road, 20 lks. wide, bears NW. and SE.
40.10	<p>The cor. of secs. 28, 29, 32, and 33.</p> <p>Land, rolling hills. Soil, rocky loam. Timber, pine, fir, larch, and spruce; undergrowth, young timber, arrowwood, and hazel.</p> <hr/> <p>From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp.</p> <p>N. $0^{\circ} 08'$ E., bet. secs. 31 and 32.</p> <p>Descend 105 ft. over NE. slope, through light timber and undergrowth.</p>
7.20	Dirt road, 20 lks. wide, bears N. 5° W. and S. 5° E.
14.50	Randall Canyon, 4 lks. wide, course N. 15° W.; asc. 60 ft. over SW. slope.
24.25	Dirt road, 20 lks. wide, bears N. 15° W. and S. 15° E.
32.30	Top of ascent, slopes W.; desc. 50 ft. over NW. slope.
35.40	Ravine, drains S. 65° W.; asc. 120 ft. over SW. slope.
39.99	<p>The $\frac{1}{4}$ sec. cor. of secs. 31 and 32, monumented with the original basalt stone, 17 x 8 x 5 ins., loosely set 6 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A sawed pine stump, 24 ins. diam., bears S. 68° E., 53 lks. dist., with scribe marks BT visible on opened blaze.</p> <p style="padding-left: 40px;">A root hole, bears S. 52° W., 42 lks. dist.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a mound of stone, 2$\frac{1}{2}$ ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 5 S R 32 E</p> <p>$\frac{1}{4}$</p> <p>S 31 S 32</p> <p>1968</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. $41\frac{1}{2}^{\circ}$ E., 44 lks. dist., mkd. T5S R32E $\frac{1}{4}$ S32 BT. (1975)</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears N. 38° W., 36 lks. dist., mkd. T5S R32E $\frac{1}{4}$ S31 BT. (1975)</p> <p>Deposit corner stone alongside iron post.</p> <hr/>

24

Dependent Resurvey, Portion of Subdivisional Lines,
T. 5 S., R. 32 E., Willamette Meridian, Oregon

CHAINS	
	<p>N. 0° 09' E., beginning new measurement.</p> <p>Ascend 60 ft. over SW. slope.</p>
2.20	<p>Leave timber, enter open rocky grassland, edge bears E. and W.</p>
10.15	<p>Top of ascent, slopes NW.; desc. 25 ft. over NW. slope.</p>
20.02	<p>Point for the N 1/16 sec. cor. of secs. 31 and 32.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 31 S 32 1968</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.</p> <p>No suitable trees available within limits.</p> <p>Descend 120 ft. over NE. slope.</p>
40.04	<p>The cor. of secs. 29, 30, 31, and 32, monumented with the original unmarked basalt stone, 20 x 10 x 8 ins., firmly set in a mound of stone, 3 ft. base, 1½ ft. high, from which the remains of the original bearing trees:</p> <p>A root hole, bears N. 69° E., 250 lks. dist., with a down and decayed pine alongside, size indeterminate, with scribe marks T5 R visible on open and burned blaze. (Record, N. 58° E.)</p> <p>A sawed pine stump, 30 ins. diam., bears S. 88° E., 321 lks. dist., with scribe marks 32 visible on opened blaze. (Record, 290 lks.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, to solid rock, in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 32 E S 30 S 29 S 31 S 32 1968</p> <p>from which new bearing trees</p> <p>A fir, 15 ins. diam., bears N. 74° E., 235 lks. dist., mkd. T5S R32E S29 BT. (1968)</p> <p>A pine, 10 ins. diam., bears S. 56½° E., 383 lks. dist., mkd. T5S R32E S32 BT. (1968)</p> <p>No other suitable trees available within limits.</p> <p>Deposit corner stone alongside iron post.</p> <p>Land, rolling hills. Soil, rocky loam. Timber, pine, fir, and larch; undergrowth, young timber, arrowwood, and hazel.</p>

Dependent Resurvey, Portion of Subdivisional Lines,
T. 5 S., R. 32 E., Willamette Meridian, Oregon

CHAINS	
	From the cor. of secs. 28, 29, 32, and 33.
	S. 89° 41' W., bet. secs. 29 and 32.
	Descend 1 ft. over nearly level land, through light timber and undergrowth.
0.15	Ravine, drains N.; asc. 15 ft. over NE. slope.
0.70	Spur, slopes N. 10° W.; desc. 25 ft. over NW. slope.
2.05	Creek, 3 lks. wide, course N. 25° W.; asc. 160 ft. over NE. slope.
18.80	Top of ascent, slopes N.; desc. 80 ft. over NW. slope.
34.10	Bottom of descent, slopes N. 30° W.; asc. 120 ft. over NE. slope.
39.85	The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented with the original basalt stone, 16 x 10 x 5 ins., firmly set 10 ins. in the ground, mkd. 4 on N. face, from which the remains of the original bearing trees: <p style="margin-left: 40px;">A decayed fir stump, 24 ins. diam., bears N. 42° E., 50 lks. dist., no marks visible.</p> <p style="margin-left: 40px;">A pine, 20 ins. diam., bears S. 31° W., 115 lks. dist., with healed blaze. (Record, 119 lks.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> T 5 S R 32 E $\frac{1}{4}$ S 29 S 32 1968 </div> <p>from which a new bearing tree</p> <p style="margin-left: 40px;">A larch, 20 ins. diam., bears N. 83° E., 138 lks. dist., mkd. $\frac{1}{4}$ S29 BT. (1968)</p> <p style="margin-left: 40px;">Deposit corner stone alongside iron post.</p> <hr style="width: 20%; margin-left: 40px;"/> <p>S. 89° 25' W., beginning new measurement.</p> <p>Ascend 85 ft. over NE. slope.</p>
17.75	Spur, slopes NW.; desc. 15 ft. over NW. slope.
19.895	Point for the W 1/16 sec. cor. of secs. 29 and 32. <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> W 1/16 S 29 S 32 1980 </div> <p>from which</p> <p style="margin-left: 40px;">A pine, 12 ins. diam., bears S. 36° E., 139 lks. dist., mkd. W 1/16 S32 BT. (1980)</p>

26

Dependent Resurvey, Portion of Subdivisional Lines,
T. 5 S., R. 32 E., Willamette Meridian, Oregon

CHAINS	
	<p>A pine, 10 ins. diam., bears N. 72° W., 243 lks. dist., mkd. W 1/16 S29 BT. (1980)</p> <p>Descend 230 ft. over NW. slope.</p>
31.45	Creek, 2 lks. wide, course N. 25° W.; asc. 175 ft. over NE. slope.
39.79	<p>The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, mountainous. Soil, rocky loam. Timber, pine, fir, larch, and spruce; undergrowth, young timber, arrowwood, and hazel.</p>
<p>Subdivision of Section 32, T. 5 S., R. 32 E., Willamette Meridian, Oregon</p>	
	<p>From the standard ¼ sec. cor. of sec. 32.</p> <p>N. 0° 08' E., on the N. and S. center line of sec. 32.</p> <p>Ascend 5 ft. over nearly level land, through light timber and undergrowth.</p>
1.50	Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W.
2.85	Top of ascent, slopes NW.; desc. 40 ft. over NW. slope.
8.60	Ravine, drains N. 55° W.; asc. 5 ft. over nearly level land.
12.70	Top of ascent, slopes NW.; desc. 25 ft. over NW. slope.
17.40	Ravine, drains N. 75° W.; asc. 20 ft. over SW. slope.
25.50	Top of ascent, slopes W.; desc. 75 ft. over NW. slope.
34.75	Ravine, drains NW.; asc. 15 ft. over SW. slope.
39.97	<p>Point for the center ¼ sec. cor. of sec. 32, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, to solid rock, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 32 E C ¼ S 32 1968</p> <p>from which</p> <p>A pine, 10 ins. diam., bears S. 28° E., 45 lks. dist., mkd. C ¼ S32 BT. (1968)</p> <p>A pine, 7 ins. diam., bears N. 50° W., 78 lks. dist., mkd. C ¼ S32 BT. (1968)</p> <p>Ascend 1 ft. over nearly level land.</p>
40.10	Top of ascent, slopes N. 30° W.; desc. 90 ft. over N. slope.
47.15	Creek, 3 lks. wide, course N. 60° W.; asc. 110 ft. over SW. slope.

Subdivision of Section 32, T. 5 S., R. 32 E.,
Willamette Meridian, Oregon

CHAINS	
51.60	Leave timber, enter open rocky grassland, edge bears E. and W.
55.55	Dirt road, 20 lks. wide, bears N. 20° E. and S. 20° W.
57.40	Top of ascent, slopes NW.; desc. 1 ft. over nearly level land.
60.025	Point for the center N 1/16 sec. cor. of sec. 32. Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, to solid rock, in a mound of stone, 2½ ft. base, to top, with brass cap mkd. C N 1/16 S 32 C 1968 No suitable trees available within limits. Descend 230 ft. over N. slope.
60.30	Barbed wire fence, bears E. and W.
63.80	Leave grassland, enter light timber and undergrowth, edge bears E. and W.
80.08	The ¼ sec. cor. of secs. 29 and 32. From the ¼ sec. cor. of secs. 32 and 33. S. 89° 32' W., on the E. and W. center line of sec. 32. Ascend 2 ft. over nearly level land, through light timber and undergrowth.
4.00	Top of ascent, slopes NW.; desc. 125 ft. over NW. slope.
4.25	Dirt road, 20 lks. wide, bears NW. and SE.
17.60	Creek, 2 lks. wide, course N. 65° W.; asc. 5 ft. over broken NE. slope.
39.80	Top of ascent, slopes NW.; desc. 1 ft. over nearly level land.
40.05	The center ¼ sec. cor. of sec. 32. Descend 40 ft. over NW. slope.
43.35	Ravine, drains N. 10° W.; asc. 30 ft. over NE. slope.
51.65	Top of ascent, slopes NW.; desc. 30 ft. over NW. slope.
58.60	Dirt road, 20 lks. wide, bears N. and S.
59.85	Barbed wire fence, bears N. and S.
59.945	Point for the center W 1/16 sec. cor. of sec. 32. Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

Subdivision of Section 32, T. 5 S., R. 32 E.,
Willamette Meridian, Oregon

CHAINS		
	<p style="text-align: center;">C $\frac{W 1/16}{S 32}$ C 1980</p> <p>from which</p> <p>A pine, 13 ins. diam., bears S. 47° E., 136½ lks. dist., mkd. CW 1/16 S32 BT. (1980)</p> <p>No other suitable trees available within limits.</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of corner.</p> <p>Descend 115 ft. over NW. slope.</p>	
68.55	Creek, 3 lks. wide, course NW.; asc. 5 ft. over nearly level land.	
69.60	Top of ascent, slopes N.; desc. 5 ft. over nearly level land.	
71.15	Creek, 3 lks. wide, course S. 70° W.; asc. 25 ft. over SE. slope.	
79.84	The ¼ sec. cor. of secs. 31 and 32.	
	From the N 1/16 sec. cor. of secs. 32 and 33.	
	S. 89° 36' W., on the E. and W. center line of the NE¼ of sec. 32.	
	Ascend 180 ft. over NE. slope, through moderate timber and light undergrowth, along fence line.	
10.25	Top of ascent, slopes N.; desc. 75 ft. over NW. slope.	
20.55	Bottom of descent, slopes N.; asc. 110 ft. over NE. slope.	
33.00	Top of ascent, slopes NW.; desc. 15 ft. over NW. slope.	
39.95	The center N 1/16 sec. cor. of sec. 32.	
	From the standard W 1/16 sec. cor. of sec. 32.	
	N. 0° 09' E., on the N. and S. center line of the SW¼ of sec. 32.	
	Descend 130 ft. over N. slope, through light timber and undergrowth, along fence line.	
28.20	Ravine, drains S. 70° E.; asc. 50 ft. over SW. slope.	
39.99	The center W 1/16 sec. cor. of sec. 32.	
	From the center W 1/16 sec. cor. of sec. 32.	
	N. 0° 09' E., on the N. and S. center line of the NW¼ of sec. 32.	
	Ascend 2 ft. over nearly level ground, through scattering timber and light undergrowth, along fence line.	

Subdivision of Section 32, T. 5 S., R. 32 E.,
Willamette Meridian, Oregon

CHAINS 3.90	Top of ascent, slopes NW.; desc. 215 ft. over N. slope.
19.35	Creek, 3 lks. wide, course N. 55° W.; asc. 15 ft. over SW. slope.
20.02	Point for the NW 1/16 sec. cor. of sec. 32, at intersection with the E. and W. center line of the NW¼. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd. NW 1/16 S 32 1980 from which A fir, 14 ins. diam., bears S. 75° E., 83 lks. dist., mkd. NW 1/16 S32 BT. (1980) A fir, 12 ins. diam., bears S. 80° W., 53 lks. dist., mkd. NW 1/16 S32 BT. (1980) Ascend 50 ft. over SW. slope.
40.06	The W 1/16 sec. cor. of secs. 29 and 32. From the center N 1/16 sec. cor. of sec. 32. S. 89° 27' W., on the E. and W. center line of the NW¼ of sec. 32. Descend 215 ft. over SW. slope, through scattering timber and light undergrowth.
19.89	The NW 1/16 sec. cor. of sec. 32. Descend 15 ft. over SW. slope.
20.95	Creek, 3 lks. wide, course N. 55° W.; asc. 125 ft. over NE. slope.
30.75	Leave timber and undergrowth, enter open rocky grassland, edge bears N. and S.
39.78	The N 1/16 sec. cor. of secs. 31 and 32.
Subdivision of Section 33, T. 5 S., R. 32 E., Willamette Meridian, Oregon	
17.00	Ravine, drains N. 70° W.; asc. 105 ft. over SW. slope.
29.40	Top of ascent, slopes W.; desc. 15 ft. over NW. slope.
34.10	Bottom of descent, slopes W.; asc. 5 ft. over SW. slope.
39.20	Barbed wire fence, bears irregularly E. and W.

30

Subdivision of Section 33, T. 5 S., R. 32 E.,
Willamette Meridian, Oregon

<p>CHAINS 40.09</p>	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 33, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 32 E C $\frac{1}{4}$ S 33 1968</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 75° E., 227 lks. dist., mkd. C $\frac{1}{4}$ S33 BT. (1968)</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears S. 70° W., 50 lks. dist., mkd. C $\frac{1}{4}$ S33 BT. (1968)</p> <p style="padding-left: 40px;">Raise a mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, W. of corner.</p> <p>Ascend 2 ft. over nearly level land.</p>
<p>41.80</p>	<p>Top of ascent, slopes NW.; desc. 215 ft. over N. slope.</p>
<p>60.085</p>	<p>Point for the center N $\frac{1}{16}$ sec. cor. of sec. 33.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N $\frac{1}{16}$ S 33 C 1980</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. $7\frac{1}{2}^\circ$ E., 46 lks. dist., mkd. CN $\frac{1}{16}$ S33 BT. (1980)</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. $76\frac{1}{2}^\circ$ W., $62\frac{1}{2}$ lks. dist., mkd. CN $\frac{1}{16}$ S33 BT. (1980)</p> <p>Descend 250 ft. over N. slope.</p>
<p>73.65</p>	<p>Abandoned dirt road, 20 lks. wide, bears N. 65° E. and S. 65° W.</p>
<p>80.08</p>	<p>The $\frac{1}{4}$ sec. cor. of secs. 28 and 33.</p>
<p>1.60</p>	<p>From the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.</p> <p>S. $89^\circ 52'$ W., on the E. and W. center line of sec. 33.</p> <p>Descend 15 ft. over W. slope, through light timber and undergrowth.</p>
<p>20.095</p>	<p>Dry Creek, 5 lks. wide, course N. 20° E.; asc. 390 ft. over E. slope.</p>
<p>20.095</p>	<p>Point for the center E $\frac{1}{16}$ sec. cor. of sec. 33.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

Subdivision of Section 33, T. 5 S., R. 32 E.,
Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">C $\frac{E\ 1/16}{S\ 33}$ C 1968</p> <p>from which</p> <p>A fir, 7 ins. diam., bears N. 20° E., 18 lks. dist., mkd. CE 1/16 S33 BT. (1980)</p> <p>A fir, 10 ins. diam., bears S. 3° W., 14 lks. dist., mkd. CE 1/16 S33 BT. (1980)</p> <p>Ascend 60 ft. over NE. slope.</p>
29.25	Top of ascent, slopes N.; desc. 40 ft. over NW. slope.
39.30	Dirt road, 20 lks. wide, bears N. 10° W. and S. 10° E.
40.19	The center $\frac{1}{4}$ sec. cor. of sec. 33.
	Descend 250 ft. over NW. slope.
57.35	Barbed wire fence, bears N. and S.
59.10	Creek, 3 lks. wide, course N. 25° W.; asc. 15 ft. over NE. slope.
60.265	Point for the center W 1/16 sec. cor. of sec. 33.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">C $\frac{W\ 1/16}{S\ 33}$ C 1968</p> <p>from which</p> <p>A fir, 14 ins. diam., bears N. 72$\frac{1}{2}$° E., 12 lks. dist., mkd. CW 1/16 S33 BT. (1980)</p> <p>A fir, 13 ins. diam., bears S. 3° W., 10$\frac{1}{2}$ lks. dist., mkd. CW 1/16 S33 BT. (1980)</p> <p>Ascend 190 ft. over NE. slope.</p>
80.34	The $\frac{1}{4}$ sec. cor. of secs. 32 and 33.
	From the center E 1/16 sec. cor. of sec. 33.
	N. 0° 21' W., on the N. and S. center line of the NE $\frac{1}{4}$ of sec. 33.
	Descend 385 ft. over N. slope, through light timber and undergrowth.
39.97	The E 1/16 sec. cor. of secs. 28 and 33.
	From the center W 1/16 sec. cor. of sec. 33.
	N. 0° 09' W., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 33.
	Descend 30 ft. over NE. slope, through light timber and undergrowth.
1.90	Creek, 3 lks. wide, course N. 35° W.; asc. 175 ft. over SW. slope.

32

Subdivision of Section 33, T. 5 S., R. 32 E.,
Willamette Meridian, Oregon

CHAINS 15.45	Spur, slopes NW.; desc. 75 ft. over N. slope.
19.98	Point for the NW 1/16 sec. cor. of sec. 33, at inter- section with the E. and W. center line of the NW $\frac{1}{4}$. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. NW 1/16 S 33 1968 from which A fir, 12 ins. diam., bears S. 84° E., 94 lks. dist., mkd. NW 1/16 S33 BT. (1968) A pine, 17 ins. diam., bears N. 83° W., 103 lks. dist., mkd. NW 1/16 S33 BT. (1968) From this point, a fence corner, bears S. 52° W., 93 lks. dist., with fences extending S. and W. Descend 315 ft. over NW. slope.
39.96	The W 1/16 sec. cor. of secs. 28 and 33.
	From the center N 1/16 sec. cor. of sec. 33. S. 89° 49' W., on the E. and W. center line of the NW $\frac{1}{4}$ of sec. 33. Descend 25 ft. over NW. slope, through light timber and undergrowth.
3.65	Bottom of descent, slopes N.; asc. 75 ft. over NE. slope.
16.60	Top of ascent, slopes N.; desc. 10 ft. over nearly level land.
20.065	The NW 1/16 sec. cor. of sec. 33. Descend 270 ft. over NW. slope.
35.70	Creek, 3 lks. wide, course NW.; asc. 35 ft. over NE. slope.
40.13	The N 1/16 sec. cor. of secs. 32 and 33.
	Subdivision of Section 34, T. 5 S., R. 32 E., Willamette Meridian, Oregon
	From the standard $\frac{1}{4}$ sec. cor. of sec. 34. N. 0° 07' W., on the N. and S. center line of sec. 34. Descend 195 ft. over NE. slope, through light timber and undergrowth.
21.65	Abandoned dirt road, 20 lks. wide, bears N. 65° W. and S. 65° E.
39.92	Point for the center $\frac{1}{4}$ sec. cor. of sec. 34, at inter- section with the E. and W. center line.

Subdivision of Section 34, T. 5 S., R. 32 E.,
Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.

T 5 S R 32 E
C ¼ S 34
1968

from which

A fir, 17 ins. diam., bears S. 1° E., 161½ lks. dist., mkd. C ¼ S34 BT. (1968)

A fir, 10 ins. diam., bears N. 58° W., 54 lks. dist., mkd. C ¼ S34 BT. (1968)

Descend 270 ft. over NE. slope.

59.955 Point for the center N 1/16 sec. cor. of sec. 34.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

C
N 1/16 | S 34
C
1980

from which

A fir, 10 ins. diam., bears N. 81° E., 54 lks. dist., mkd. CN 1/16 S34 BT. (1980)

A fir, 8 ins. diam., bears N. 15° W., 36 lks. dist., mkd. CN 1/16 S34 BT. (1980)

Descend 2 ft. over nearly level land.

60.45 Bottom of descent, slopes NE.; asc. 20 ft. over SE. slope.

62.05 Abandoned dirt road, 20 lks. wide, bears E. and W.

64.35 Top of ascent, slopes E.; desc. 115 ft. over N. slope.

68.45 Abandoned dirt road, 20 lks. wide, bears NW. and SE.

75.85 Abandoned dirt road, 20 lks. wide, bears N. 70° W. and S. 70° E.

79.95 Barbed wire fence, bears E. and W.

79.99 The ¼ sec. cor. of secs. 27 and 34.

From the ¼ sec. cor. of secs. 34 and 35.

N. 89° 58' W., on the E. and W. center line of sec. 34.

Ascend 20 ft. over NE. slope, through light timber and undergrowth.

0.85 Abandoned dirt road, 20 lks. wide, bears N. 30° W. and S. 30° E.

4.20 Top of ascent, slopes N.; desc. 15 ft. over NW. slope.

7.70 Creek, 3 lks. wide, course N. 10° W.; asc. 95 ft. over broken NE. slope.

88

34

Subdivision of Section 34, T. 5 S., R. 32 E.,
Willamette Meridian, Oregon

<p>CHAINS 19.97</p>	<p>Point for the center E 1/16 sec. cor. of sec. 34.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \quad \text{---} \quad \text{C} \\ \text{S } 34 \\ 1980 \end{array}$ </p> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 36° E., 6 lks. dist., mkd. CE 1/16 S34 BT. (1980)</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 44° W., 28 lks. dist., mkd. CE 1/16 S34 BT. (1980)</p> <p>Ascend 10 ft. over broken NE. slope.</p>
<p>21.45</p>	<p>Spur, slopes N.; desc. 2 ft. over nearly level land.</p>
<p>26.25</p>	<p>Creek, 3 lks. wide, course N. 55° E.; asc. 165 ft. over NE. slope.</p>
<p>39.94</p>	<p>The center ¼ sec. cor. of sec. 34.</p> <p>Ascend 70 ft. over NE. slope.</p>
<p>52.60</p>	<p>Abandoned dirt road, 20 lks. wide, bears N. and S.</p>
<p>58.00</p>	<p>Top of ascent, slopes N.; desc. 270 ft. over NW. slope.</p>
<p>79.41</p>	<p>The ¼ sec. cor. of secs. 33 and 34.</p> <hr/> <p>From the center E 1/16 sec. cor. of sec. 34.</p> <p>N. 0° 08' W., on the N. and S. center line of the NE¼ of sec. 34.</p> <p>Descend 70 ft. over NW. slope, through light timber and undergrowth.</p>
<p>6.45</p>	<p>Creek, 3 lks. wide, course N. 30° E.; desc. 90 ft. over broken NE. slope.</p>
<p>16.25</p>	<p>Abandoned dirt road, 20 lks. wide, bears N. 80° W. and S. 80° E.</p>
<p>19.00</p>	<p>Barbed wire fence, bears E. and W.</p>
<p>20.07</p>	<p>Point for the NE 1/16 sec. cor. of sec. 34, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} \text{NE } 1/16 \text{ S } 34 \\ 1968 \end{array}$ </p> <p>from which</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears S. 11½° E., 22 lks. dist., mkd. NE 1/16 S34 BT. (1980)</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 74° W., 46 lks. dist., mkd. NE 1/16 S34 BT. (1980)</p>

Subdivision of Section 34, T. 5 S., R. 32 E.,
Willamette Meridian, Oregon

CHAINS	<p>Descend 55 ft. over broken NE. slope.</p> <p>40.12 The E 1/16 sec. cor. of secs. 27 and 34.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 34 and 35.</p> <p>S. 89° 59' W., on the E. and W. center line of the NE¼ of sec. 34.</p> <p>Ascend 20 ft. over broken NE. slope, through light timber and undergrowth.</p> <p>15.60 Top of ascent, slopes NE.; desc. 2 ft. over nearly level land.</p> <p>17.20 Creek, 3 lks. wide, course N. 25° W.; asc. 5 ft. over NE. slope.</p> <p>19.96 The NE 1/16 sec. cor. of sec. 34.</p> <p>Ascend 75 ft. over NE. slope.</p> <p>20.65 Barbed wire fence, bears N. and S.</p> <p>23.85 Abandoned dirt road, 20 lks. wide, bears N. 25° W. and S. 25° E.</p> <p>26.70 Spur, slopes N. 20° E.; desc. 10 ft. over NW. slope.</p> <p>35.70 Creek, 2 lks. wide, course N. 10° W.; asc. 5 ft. over NE. slope.</p> <p>39.90 The center N 1/16 sec. cor. of sec. 34.</p> <hr/> <p style="text-align: center;">Subdivision of Section 35, T. 5 S., R. 32 E., Willamette Meridian, Oregon</p> <hr/> <p>From the standard ¼ sec. cor. of sec. 35.</p> <p>N. 0° 04' W., on the N. and S. center line of sec. 35.</p> <p>Descend 170 ft. over N. slope, through light timber and undergrowth.</p> <p>0.10 Barbed wire fence, bears E. and W.</p> <p>20.11 Point for the center S 1/16 sec. cor. of secs. 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p>S 1/16 S 35</p> <p>C</p> <p>1968</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears N. 88½° E., 30½ lks. dist., mkd. CS 1/16 S35 BT. (1968)</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears N. 55° W., 16 lks. dist., mkd. CS 1/16 S35 BT. (1968)</p>
--------	--

36

Subdivision of Section 35, T. 5 S., R. 32 E.,
Willamette Meridian, Oregon

CHAINS	
	Descend 120 ft. over N. slope.
40.22	Point for the center $\frac{1}{4}$ sec. cor. of sec. 35, at intersection with the E. and W. center line.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass mkd.
	<p style="text-align: center;">T 5 S R 32 E C $\frac{1}{4}$ S 35 1968</p>
	from which
	A fir, 12 ins. diam., bears S. 49° E., $61\frac{1}{2}$ lks. dist., mkd. C $\frac{1}{4}$ S35 BT. (1968)
	A larch, 4 ins. diam., bears N. 89° W., $108\frac{1}{2}$ lks. dist., mkd. X BT. (1968)
	Corner is located on N. edge of timber, bears E. and W.
	Descend 35 ft. over N. slope, across open grassland.
52.50	Creek, 3 lks. wide, course NW.; asc. 20 ft. over SW. slope.
55.85	Barbed wire fence, bears N. 60° W. and S. 60° E.
59.30	Gravelled road, 25 lks. wide, bears N. 70° W. and S. 70° E.
62.30	Gravelled road, 25 lks. wide, bears NW. and SE.
63.00	Top of ascent, slopes NW.; desc. 25 ft. over N. slope.
70.35	Pine Creek, 4 lks. wide, course N. 60° W.; asc. 45 ft. over SW. slope.
73.25	Dirt road, 20 lks. wide, bears N. 60° W. and S. 60° E.
80.32	The $\frac{1}{4}$ sec. cor. of secs. 26 and 35.
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented with the original basalt stone, 17 x 12 x 5 ins., firmly set, projecting 8 ins. above ground, mkd. $\frac{1}{4}$ on W. face, from which the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A sawed pine stump, 30 ins. diam., bears N. 85° E., 28 lks. dist., with scribe marks BT visible on opened blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 32 E $\frac{1}{4}$ S 35 S 36 1968</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A pine, 25 ins. diam., bears N. $54\frac{1}{2}^\circ$ E., 166 lks. dist., mkd. $\frac{1}{4}$ S36 BT. (1968)</p>

Subdivision of Section 35, T. 5 S., R. 32 E.,
Willamette Meridian, Oregon

CHAINS	
	<p>A pine, 45 ins. diam., bears N. 28° W., 131 lks. dist., mkd. ¼ S35 BT. (1968)</p> <p>Deposit corner stone alongside iron post.</p> <p>S. 89° 35' W., on the E. and W. center line of sec. 35.</p> <p>Descend 75 ft. over broken NW. slope, across open grassland.</p>
23.40	Creek, 2 lks. wide, course N. 35° W.; asc. 10 ft. over broken NE. slope.
34.70	Top of ascent, slopes NW.; desc. 1 ft. over nearly level land.
39.96	The center ¼ sec. cor. of sec. 35.
	Descend 10 ft. over broken NW. slope.
56.70	Ravine, drains N. 10° E.; asc. 20 ft. over NE. slope.
59.00	Top of ascent, slopes NE.; desc. 5 ft. over NW. slope.
59.50	Ravine, drains N. 25° W.; asc. 5 ft. over NE. slope, also enter light timber and undergrowth, edge bears NW. and SE.
59.935	Point for the center W 1/16 sec. cor. of sec. 35.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> $\begin{array}{c} \text{C} \frac{\text{W } 1/16}{\text{S } 35} \text{C} \\ 1968 \end{array}$ <p>from which</p> <p>A fir, 12 ins. diam., bears S. 46° E., 38 lks. dist., mkd. CW 1/16 S35 BT. (1968)</p> <p>No other suitable trees available within limits.</p> <p>Ascend 70 ft. over NE. slope.</p>
79.91	The ¼ sec. cor. of secs. 34 and 35.
	<p>From the standard W 1/16 sec. cor. of sec. 35.</p> <p>N. 0° 01' W., on the N. and S. center line of the SW¼ of sec. 35.</p> <p>Descend 370 ft. over N. slope, through moderate timber and light undergrowth.</p>
0.65	Abandoned dirt road, 20 lks. wide, bears E. and W.
11.45	Abandoned dirt road, 20 lks. wide, bears NW. and SE.
17.40	Barbed wire fence, bears N. 70° W. and S. 70° E.
20.03	Point for the SW 1/16 sec. cor. of sec. 35, at intersection with the E. and W. center line of the SW¼.

38

Subdivision of Section 35, T. 5 S., R. 32 E.,
Willamette Meridian, Oregon

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 35 1968</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 46° E., 27½ lks. dist., mkd. SW 1/16 S35 BT. (1968)</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 80½° W., 56½ lks. dist., mkd. SW 1/16 S35 BT. (1968)</p> <p>Descend 90 ft. over NE. slope.</p>
30.20	Creek, 2 lks. wide, course NE.; desc. 50 ft. over broken NE. slope.
40.05	The center W 1/16 sec. cor. of sec. 35.
	<p>From the center S 1/16 sec. cor. of sec. 35.</p> <p>S. 89° 50' W., on the E. and W. center line of the SW¼ of sec. 35.</p> <p>Descend 20 ft. over NW. slope, through light timber and undergrowth.</p>
6.60	Ravine, drains N. 20° W.; asc. 70 ft. over NE. slope.
15.75	Spur, slopes N.; desc. 15 ft. over NW. slope.
19.15	Creek, 2 lks. wide, course N.; asc. 5 ft. over NE. slope.
19.995	The SW 1/16 sec. cor. of sec. 35.
	Ascend 35 ft. over NE. slope.
21.30	Barbed wire fence, bears N. and S.
26.30	Spur, slopes N. 20° E.; desc. 5 ft. over NW. slope.
27.70	Creek, 2 lks. wide, course N. 10° E.; asc. 170 ft. over NE. slope.
30.55	Abandoned dirt road, 20 lks. wide, bears N. and S.
39.98	The S 1/16 sec. cor. of secs. 34 and 35.
	<p>Remonumentation of Certain Original Corner Points, T. 5 S., R. 32 E., Willamette Meridian, Oregon</p>
	<p>The following field notes describe the remonumentation of certain original corner points, township 5 south, range 32 east, Willamette Meridian, Oregon, as provided for under the General Special Instructions, Group Number 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories when Needed."</p>

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 32 E., Willamette Meridian, Oregon

CHAINS

The remonumentation of certain original corner points was made at the request of the United States Forest Service.

East Boundary, T. 5 S., R. 32 E.,
Willamette Meridian, Oregon

(Remonumenting a corner established by George S. Pershin,
U. S. Deputy Surveyor, in 1881)

The cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., monumented with a mound of stone, 3 ft. base, 1 ft. high, from which the remains of the original bearing trees:

A larch, 21 ins. diam., bears N. 48° E., 10½ lks. dist., with healed blaze. (Record, N. 30° E., 10 lks.)

A larch, 16 ins. diam., bears S. 22° W., 73½ lks. dist., with healed blaze. (Record, S. 32° W., 72 lks.)

A larch snag, 22 ins. diam., bears N. 18° W., 80 lks. dist., with illegible scribe marks visible on partially open blaze. (Record, N. 25° W., 43 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 5 S	
R 32 E	R 33 E
S 25	S 30
S 36	S 31
1967	

from which new bearing trees

A fir, 8 ins. diam., bears S. 46½° E., 43½ lks. dist., mkd. T5S R33E S31 BT. (1967)

A fir, 6 ins. diam., bears N. 37° W., 36 lks. dist., mkd. T5S R32E S25 BT. (1967)

Subdivisions, T. 5 S., R. 32 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by George S. Pershin,
U. S. Deputy Surveyor, in 1881)

The ¼ sec. cor. of secs. 23 and 24, monumented with the original basalt stone, 18 x 16 x 7 ins., firmly set 10 ins. in the ground, mkd. ¼ on W. face, from which the remains of an original bearing tree:

A root hole, bears S. 48° E., 37 lks. dist., with a down larch alongside, 14 ins. diam., with scribe marks ¼ S BT visible on partially healed blaze.

40

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 32 E., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

$\frac{1}{4}$
S 23 | S 24
T 5 S R 32 E
1967

from which new bearing trees

A fir, 9 ins. diam., bears S. $79\frac{1}{2}^\circ$ E., $27\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S24 BT. (1967)

A fir, 9 ins. diam., bears S. 85° W., 29 lks. dist., mkd. $\frac{1}{4}$ S23 BT. (1967)

Deposit corner stone alongside iron post.

The cor. of secs. 14, 15, 22, and 23, monumented with the original basalt stone, 20 x 10 x 5 ins., loosely set 6 ins. in the ground, with fragmentary grooves on E. face, from which the remains of the original bearing trees:

A pine, 30 ins. diam., bears N. 55° E., $110\frac{1}{2}$ lks. dist., with healed blaze. (Record, N. 56° E., 109 lks.)

A sawed pine stump, 22 ins. diam., bears S. $46\frac{1}{2}^\circ$ E., 112 lks. dist., with scribe marks BT visible on opened blaze. (Record, S. 48° E., 111 lks.)

A sawed pine stump, 22 ins. diam., bears S. 68° W., 166 lks. dist., with decayed blaze, no marks visible. (Record, S. 66° W., 165 lks.)

A pine, 32 ins. diam., bears N. 77° W., $76\frac{1}{2}$ lks. dist., with illegible scribe marks visible on partially opened blaze. (Record, N. 76° W., 75 lks.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S R 32 E
S 15 | S 14
S 22 | S 23
1967

from which new bearing trees

A pine, 23 ins. diam., bears S. 24° E., $178\frac{1}{2}$ lks. dist., mkd. T5S R32E S23 BT. (1967)

A pine, 32 ins. diam., bears S. $56\frac{1}{2}^\circ$ W., $202\frac{1}{2}$ lks. dist., mkd. T5S R32E S22 BT. (1967)

Deposit corner stone alongside iron post.

T. 5 S., R. 32 E., Willamette Meridian, Oregon

CHAINS

GENERAL DESCRIPTION

The lands covered by this resurvey are located in Umatilla County, about 3 miles southeast of the town of Ukiah, Oregon. The main drainages in the area are Randall Canyon, Dry Creek, and Pine Creek. The area is situated in the Umatilla National Forest in a portion of the Blue Mountains.

Access is gained by way of numerous dirt and gravelled roads leading from State Highway Number 244, to the north.

The elevation ranges from about 4000 feet above sea level at the corner of sections 26, 27, 34, and 35, to about 4700 feet above sea level on the south boundary of section 33.

Timber is light to moderate and consists of pine, fir, and larch. The undergrowth is also light and consists mainly of young timber, with some arrowwood and hazel near the drainages.

The soil is rocky loam. There was no indication of mineral activity.

The average of a number of readings along the lines surveyed gives a value of 20° E. for the mean magnetic declination. There is a range of 1° in local attraction.

CHAINS	GENERAL DESCRIPTION	CHAINS
	<p>The lands covered by this resurvey are located in Umatilla County, about 3 miles southeast of the town of Ukiah, Oregon. The main drainages in the area are Randall Canyon, Dry Creek, and Pine Creek. The area is situated in the Umatilla National Forest in a portion of the Blue Mountains.</p> <p>Access is gained by way of numerous dirt and gravel roads leading from State Highway Number 344, to the north.</p> <p>The elevation ranges from about 4000 feet above sea level at the corner of sections 26, 27, 34, and 35, to about 4700 feet above sea level on the south boundary of section 33.</p> <p>Timber is light to moderate and consists of pine, fir, and larch. The undergrowth is also light and consists mainly of young timber, with some arrowwood and hazel near the drainages.</p> <p>The soil is rocky loam. There was no indication of mineral activity.</p> <p>The average of a number of readings along the lines surveyed gives a value of 30° E. for the mean magnetic declination. There is a range of 1° in local declination.</p>	

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Lester E. Fischer	Cadastral Surveyor (Assisting)
Wayne L. Rogers	Cadastral Surveyor (Assisting)
James J. Carlson	Surveying Technician
Robert A. Brown	Surveying Technician
Louis A. Kautz	Surveying Technician
Max E. Farron	Surveying Technician
Robert B. Fink	Surveying Technician
Martin L. Epperly	Surveying Technician
Jay L. Mehr	Surveying Aid
Kurt A. Wycaver	Surveying Aid
Robert R. Thornton	Surveying Aid
Richard T. Helms III	Surveying Aid
Michael R. Druckrey	Surveying Aid
James R. VonGrabow	Surveying Aid
Robert L. Nelson	Surveying Aid
Jerome C. Ives	Cadastral Surveyor
Delbert E. Baldwin	Cadastral Surveyor
Thomas D. Brown	Cadastral Surveyor
Donevan C. Harris	Cadastral Surveyor
James A. Rhea, Jr.	Surveying Technician

(Chief Cadastral Surveyor of Oregon)

June 30, 1983

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
is a true copy of the original field notes

43

CERTIFICATE OF SURVEY

(X) (We), James E. Jelley, Harvey E. Wofford, William D. Kimmel, and Rick E. Tawney, Cadastral Surveyors,

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day

of May 19 57, ~~(XXXXXX)~~ special instructions bearing date of the 16th day of June, 1967, and supplemental special instructions bearing date of the 25th day of July, 1978, we have dependently resurveyed a portion of the south boundary (First Standard Parallel South), a portion of the subdivisional lines, subdivided sections 32, 33, 34, and 35, and remonumented certain original corner points, township 5 south, range 32 east,

of the Willamette Meridian, in the State of Oregon, which are represented in the foregoing field notes as having been executed by ~~(XXX)~~ (us) and under ~~(XXX)~~ (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 9, 1982 (Date)	<u>James E. Jelley</u> (Cadastral Surveyor)
August 11, 1982 (Date)	<u>Harvey E. Wofford</u> (Cadastral Surveyor)
August 25, 1982 (Date)	<u>William D. Kimmel</u> (Cadastral Surveyor)
August 23, 1982 (Date)	<u>Rick E. Tawney</u> (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Portland, Oregon

The foregoing field notes of the dependent resurvey of a portion of the south boundary (First Standard Parallel South), a portion of the subdivisional lines, subdivision of sections 32, 33, 34, and 35, and remonumentation of certain original corner points, township 5 south, range 32 east, Willamette Meridian, Oregon,

executed by James E. Jelley, Harvey E. Wofford, William D. Kimmel, and Rick E. Tawney, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

<u>June 30, 1983</u> (Date)	<u>William W. Glenn</u> (Chief Cadastral Surveyor of Oregon)
--------------------------------	---

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

_____ (Date)	_____ (Chief, Cadastral Survey Examination and Approval Staff)
-----------------	---