



# INDEX DIAGRAM

Township 5 South, Range 33 East,

6	<u>19</u> 5 <u>18</u> <u>19</u>	4 <u>14</u>	3	2	1 <u>5</u> <u>6</u>
7	8 <u>18</u>	9 <u>13</u>	<u>10</u> 10 <u>9</u> <u>10</u>	11 <u>8</u>	12 <u>3</u> <u>5</u> <u>3</u>
18	<u>17</u> 17	16 <u>13</u>	15 <u>9</u>	<u>7</u> 14 <u>7</u>	13 <u>4</u> <u>2</u>
19	20 <u>17</u>	21 <u>12</u>	<u>8</u> 22	<u>6</u> 23	<u>4</u> 24
30	<u>16</u> 29 <u>15</u> <u>16</u>	<u>12</u> 28 <u>11</u>	27	26	25
31	<u>14</u> 32 <u>1</u>	<u>11</u> 33 <u>1</u>	34	35	36

## T. 5 S., R. 33 E., Willamette Meridian, Oregon

## CHAINS

The following field notes describe the remonumentation of certain original corner points, township 5 south, range 33 east, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories when Needed".

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

First Standard Parallel South,  
(South Boundary, T. 5 S., R. 33 E.)  
Willamette Meridian, Oregon

(Remonumenting corners established by George S. Pershin,  
U. S. Deputy Surveyor, in 1880)

The standard cor. of secs. 32 and 33, on the S. bdy. of the Tp., determined at record bearing and distance from the remains of the original bearing trees:

A pine snag, 15 ins. diam., bears N. 70° E., 32 lks. dist., with fragmentary scribe marks visible on open blaze.

A pine, 25 ins. diam., bears N. 17° W., 70 lks. dist., with fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

S C  
T 5 S R 33 E  
S 32 | S 33  
1977

from which a new bearing tree

A ponderosa pine, 28 ins. diam., bears N. 47° E., 105 lks. dist., mkd. T5S R33E S33 SC BT.

Set a 5 ft. steel fence post alongside iron post.

Corner is located 5 lks. south of wire fence, extending E. and W.

The standard ¼ sec. cor. of sec. 32, on the S. bdy. of the Tp., determined at record bearing and distance from the original bearing tree:

A pine, 36 ins. diam., bears N. 72° W., 92 lks. dist., with scribe marks ¼ S visible on open blaze.

At the corner point

Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

S C  
T 5 S R 33 E  
 $\frac{1}{4}$  S 32  
1977

from which a new bearing tree

A lodgepole pine, 7 ins. diam., bears N.  $16^\circ$  E., 16 lks. dist., mkd.  $\frac{1}{4}$  S32 SC BT.

Set a 5 ft. steel fence post alongside iron post.

East Boundary, T. 5 S., R. 33 E.,  
Willamette Meridian, Oregon

(Remonumenting corners established by George S. Pershin, U. S. Deputy Surveyor, in 1881, and changed to corners of minimum control by Rufus S. Moore, U. S. Deputy Surveyor, in 1882)

The cor. of secs. 13 and 24 only, on the E. bdy. of the Tp., monumented with the original basalt stone, 17 x 10 x 8 ins., firmly set 6 ins. in the ground, with 3 notches on N. and S. edges, from which the remains of the original bearing trees:

A larch snag, 18 ins. diam., bears N.  $34^\circ$  E., 36 lks. dist., with scribe marks T5S R34E S18 visible on open blaze.

A root hole, bears S.  $58^\circ$  E., 33 lks. dist., with a down larch alongside, 7 ins. diam., with scribe marks T5S R34E S19 BT visible on open blaze.

A larch snag, 13 ins. diam., bears S.  $42^\circ$  W., 75 lks. dist., with fragmentary scribe marks visible on decayed blaze.

A larch, 22 ins. diam., bears N.  $37^\circ$  W., 96 lks. dist., with scribe marks 13 visible on open blaze. (Record, N.  $41^\circ$  W.)

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S | T 5 S  
S 13 | R 33 $\frac{1}{2}$  E  
S 24 |  
R 33 E | S 15  
1977

from which a new bearing tree

A lodgepole pine, 7 ins. diam., bears S.  $73^\circ$  W., 22 lks. dist., mkd. T5S R33E S24 BT.

Deposit corner stone alongside iron post.



CERTIFICATE OF SURVEY

(I) (~~W~~), Craig L. Wanless, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May, 19 57, (I) (~~W~~) have remonumented certain original corner points, township 5 south, range 33 east,

of the Willamette Meridian, in the State of Oregon, which are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 16, 1978  
(Date)

*Craig L. Wanless*  
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
~~Washington, D.C.~~  
Denver, Colorado

The foregoing field notes of the remonumentation of certain original corner points, township 5 south, range 33 east, Willamette Meridian, Oregon,

executed by Craig L. Wanless, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JAN 23 1980  
(Date)

*J. D. Voorhees*  
(Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) CPO 840 626