

INDEX DIAGRAM

Township 5 South, Range 33 East,

6	<u>19</u> 5 <u>18</u> <u>19</u>	4 <u>14</u>	3	2	1 <u>5</u> <u>6</u>
7	8 <u>18</u>	9 <u>13</u>	<u>10</u> 10 <u>9</u> <u>10</u>	11 <u>8</u>	12 <u>3</u> <u>5</u> <u>3</u>
18	<u>17</u> 17	16 <u>13</u>	15 <u>9</u>	<u>7</u> 14 <u>7</u>	13 <u>4</u> <u>2</u>
19	20 <u>17</u>	21 <u>12</u>	<u>8</u> 22	<u>6</u> 23	<u>4</u> 24
30	<u>16</u> 29 <u>15</u> <u>16</u>	<u>12</u> 28 <u>11</u>	27	26	25
31	<u>14</u> 32 <u>1</u>	<u>11</u> 33 <u>1</u>	34	35	36

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

Deposit corner stone alongside iron post.

Corner is located 10 lks. west of wire fence, extending
N. and S.

Subdivisions, T. 5 S., R. 33 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by George S. Pershin,
U. S. Deputy Surveyor, in 1882)

The $\frac{1}{4}$ sec. cor. of secs. 23 and 24, monumented with the
original basalt stone, 14 x 12 x 5 ins., firmly set 4
ins. in the ground, mkd. $\frac{1}{4}$ on W. face, from which the
remains of the original bearing trees:

A sawed pine stump, 18 ins. diam., bears S. 55° W.,
55 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 5 S R 33 E

$\frac{1}{4}$
S 23 | S 24
1977

from which new bearing trees

A grand fir, 9 ins. diam., bears S. $85\frac{1}{2}^{\circ}$ E., 90
lks. dist., mkd. $\frac{1}{4}$ S24 BT.

A grand fir, 13 ins. diam., bears N. 86° W., 53
lks. dist., mkd. $\frac{1}{4}$ S23 BT.

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 13 and 24, monumented with the
original basalt stone, 18 x 14 x 10 ins. firmly set 8
ins. in the ground, and in a collar of stones, mkd. $\frac{1}{4}$ on
N. face, from which the original bearing trees:

A pine, 27 ins. diam., bears N. 7° W., 106 lks.
dist., with scribe marks 4 S visible on open
blaze. (Record, N. 12° W.)

A pine, 17 ins. diam., bears S. 62° E., 104 lks.
dist., with scribe marks $\frac{1}{4}$ S visible on open
blaze. (Record, S. 67° E.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, and in a mound of stone, 2 ft. base, to
top, with brass cap mkd.

T 5 S R 33 E

$\frac{1}{4}$ S 13
 S 24
1977

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

Deposit corner stone and set a 5 ft. steel fence post alongside iron post.

The cor. of secs. 11, 12, 13, and 14, determined at record bearing and distance from the remains of the original bearing trees:

A pine snag, 19 ins. diam., bears N. 28° E., 62 lks. dist., with healed blaze.

A pine, 20 ins. diam., bears S. 47° E., 137 lks. dist., with healed blaze.

A pine, 25 ins. diam., bears N. 70° W., 141 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12-ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S R 33 E
S 11 S 12
S 14 S 13
1977

from which new bearing trees

A lodgepole pine, 11 ins. diam., bears N. 12° E., 12½ lks. dist., mkd. T5S R33E S12 BT.

A grand fir, 12 ins. diam., bears S. 28° W., 141 lks. dist., mkd. T5S R33E S14 BT.

Set a 5 ft. steel fence post alongside iron post.

The cor. of secs. 1, 2, 11, and 12, monumented with the original basalt stone, 18 x 8 x 5 ins., firmly set 4 ins. in the ground, with 1 notch on E. and 5 notches on S. edges, from which the remains of the original bearing trees:

A larch, 25 ins. diam., bears N. 78° E., 54 lks. dist., with scribe marks 3E S1 visible on opened blaze.

A pine snag, 12 ins. diam., bears S. 36° E., 42 lks. dist., with fragmentary scribe marks visible on open blaze.

A root hole, bears S. 10° W., 20 lks. dist., with a down and decayed pine alongside, size indeterminate, no marks visible.

A sawed larch stump, 17 ins. diam., bears N. 70° W., 52 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

T 5 S R 33 E
S 2 | S 1
S 11 | S 12
1977

from which new bearing trees

A grand fir, 12 ins. diam., bears S. $55\frac{1}{2}^\circ$ E., 50 lks. dist., mkd. T5S R33E S12 BT.

A grand fir, 10 ins. diam., bears S. 19° W., $54\frac{1}{2}$ lks. dist., mkd. T5S R33E S11 BT.

A grand fir, 9 ins. diam., bears N. 10° W., 5 lks. dist., mkd. T5S R33E S2 BT.

Deposit corner stone and set a 5 ft. steel fence post alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 1 and 12, monumented with the original basalt stone, 20 x 10 x 3 ins., loosely set 1 in. in the ground, mkd. $\frac{1}{4}$ on N. face, from which the remains of the original bearing trees:

A root hole, bears N. 36° W., 30 lks. dist., with a down and decayed pine alongside, size indeterminate, with scribe marks $\frac{1}{4}$ visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S R 33 E
 $\frac{1}{4}$ S 1
S 12
1977

from which new bearing trees

A lodgepole pine, 6 ins. diam., bears N. 54° E., 59 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

A lodgepole pine, 12 ins. diam., bears S. 1° W., 50 lks. dist., mkd. $\frac{1}{4}$ S12 BT.

Deposit corner stone and set a 5 ft. steel fence post alongside iron post.

Corner is located 11 lks. east of wire fence, extending N. and S.

The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, determined at record bearing and distance from the remains of the original bearing trees:

A sawed pine stump, 26 ins. diam., bears S. 3° E., 21 lks. dist., with scribe mark S visible on open blaze. (Record, larch)

At the corner point

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S R 33 E
 $\frac{1}{4}$
 S 22 | S 23
 1977

from which new bearing trees

A grand fir, 12 ins. diam., bears N. 74° E., 54 lks. dist., mkd. $\frac{1}{4}$ S23 BT.

A grand fir, 10 ins. diam., bears N. 82° W., 50½ lks. dist., mkd. $\frac{1}{4}$ S22 BT.

Set a 5 ft. steel fence post alongside iron post.

The cor. of secs. 14, 15, 22, and 23, monumented with the original basalt stone, 12 x 10 x 5 ins., loosely set 1 in. in the ground, with 2 notches on E. and 3 notches on S. edges, from which the remains of the original bearing trees:

A pine, 35 ins. diam., bears N. 3° E., 58 lks. dist., with scribe marks T5S R33E S14 BT visible on open blaze.

A pine, 38 ins. diam., bears S. 69° E., 14 lks. dist., with scribe marks T5S R33E S visible on open and burned blaze. (Record, S. 87° E.)

A pine snag, size indeterminate, bears N. 54° W., 24 lks. dist., with scribe marks S15 visible on open and burned blaze. (Record, N. 43° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S R 33 E
 S 15 | S 14
 S 22 | S 23
 1977

from which new bearing trees

A lodgepole pine, 12 ins. diam., bears S. 64° W., 37 lks. dist., mkd. T5S R33E S22 BT.

A lodgepole pine, 8 ins. diam., bears N. 40° W., 73 lks. dist., mkd. T5S R33E S15 BT.

Deposit corner stone and set a 5 ft. steel fence post alongside iron post.

Corner is located 40 lks. S. 40° E. of fence corner, fences extend N., S., and E.

The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, determined at record bearing and distance from the original bearing trees:

A fir, 23 ins. diam., bears S. 65° E., 24 lks. dist., with healed blaze.

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

A fir, 17 ins. diam., bears N. 70° W., 47 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 5 S R 33 E

 ¼
S 15 | S 14
 1977

Set a 5 ft. steel fence post alongside iron post.

The cor. of secs. 10, 11, 14, and 15, monumented with the
original basalt stone, 16 x 8 x 7 ins., firmly set 4 ins.
in the ground, in a collar of stones, with 2 notches on
E. and 4 notches on S. edges, from which the remains of
the original bearing trees:

A fir, 27 ins. diam., bears N. 23° E., 70 lks.
dist., with scribe marks T5S R33E S11 visible
on open blaze.

A larch snag, 25 ins. diam., bears S. 28° E., 62
lks. dist., with healed blaze.

A root hole, bears S. 64° W., 14 lks. dist., with
a down and decayed pine alongside, size indeter-
minate, with scribe marks T5S R33E S15 visible
on open blaze.

A decayed pine stump, size indeterminate, bears
N. 21° W., 93 lks. dist., with scribe marks
R33E S10 BT visible on decayed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 5 S R 33 E

 S 10 | S 11
 S 15 | S 14
 1977

from which new bearing trees

A grand fir, 9 ins. diam., bears S. 20° E., 37½
lks. dist., mkd. T5S R33E S14 BT.

A grand fir, 8 ins. diam., bears S. 77° W., 26
lks. dist., mkd. T5S R33E S15 BT.

A grand fir, 22 ins. diam., bears N. 17° W., 18
lks. dist., mkd. T5S R33E S10 BT.

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

The ¼ sec. cor. of secs. 21 and 22, determined at record
bearing and distance from the remains of the original
bearing trees:

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

A larch snag, 12 ins. diam., bears N. 34° W., 35 lks. dist., with scribe mark S visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S R 33 E
S 21 | S 22
1977

from which new bearing trees

A lodgepole pine, 6 ins. diam., bears S. 80° E., 35 lks. dist., mkd. ¼ S22 BT.

A lodgepole pine, 7 ins. diam., bears N. 39° W., 51 lks. dist., mkd. ¼ S21 BT.

Set a 5 ft. steel fence post alongside iron post.

The cor. of secs. 15, 16, 21, and 22, determined at record distance from the remains of the original bearing trees:

A pine, 20 ins. diam., bears N. 36° E., 140 lks. dist., with scribe marks T5S R33E B visible on open blaze.

A pine, 22 ins. diam., bears S. 45° E., 185 lks. dist., with fragmentary scribe marks visible on open blaze.

A pine, 20 ins. diam., bears S. 10° W., 40 lks. dist., with healed blaze. (Record, S. 5° W.)

A pine snag, size indeterminate, bears N. 32° W., 83 lks. dist., with scribe marks T5S R33E S16 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S R 33 E
S 16 | S 15
S 21 | S 22
1977

from which a new bearing tree

A grand fir, 6 ins. diam., bears N. 29° W., 85 lks. dist., mkd. T5S R33E S16 BT.

Set a 5 ft. steel fence post alongside iron post.

The cor. of secs. 9, 10, 15, and 16, determined at record distance from the remains of the original bearing trees:

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

A pine, 21 ins. diam., bears N. 51° E., 149 lks. dist., with scribe marks S R33 visible on open blaze.

A pine, 26 ins. diam., bears S. 33° E., 170 lks. dist., with scribe marks R33E S1 visible on open blaze. (Record, S. 40° E.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S R 33 E
S 9 S 10
S 16 S 15
1977

from which new bearing trees

A lodgepole pine, 7 ins. diam., bears S. 56° W., 103 lks. dist., mkd. T5S R33E S16 BT.

A lodgepole pine, 15 ins. diam., bears N. 36° W., 123 lks. dist., mkd. T5S R33E S9 BT.

The ¼ sec. cor. of secs. 10 and 15, monumented with the original basalt stone, 14 x 12 x 8 ins., firmly set 3 ins. in the ground, mkd. ¼ on N. face, from which the original bearing trees:

A pine, 20 ins. diam., bears N. 54° W., 40 lks. dist., with scribe mark S visible on partially opened blaze. (Record, larch)

A pine, 23 ins. diam., bears S. 54° E., 47 lks. dist., with scribe mark 4 visible on partially opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S R 33 E
¼ S 10
S 15
1977

Deposit corner stone and set a 5 ft. steel fence post alongside iron post.

The ¼ sec. cor. of secs. 9 and 10, monumented with the remains of the original corner tree, a pine snag, 15 ins. diam., with scribe mark S visible on partially opened blaze on W. face, from which the remains of the original bearing trees:

A pine, 12 ins. diam., bears N. 71° E., 77 lks. dist., with healed blaze. (Record, 74 lks.)

A pine snag, 17 ins. diam., bears N. 86° W., 36 lks. dist., with scribe marks BT visible on open blaze.

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

and a new bearing tree

A lodgepole pine, 6 ins. diam., bears S. 44° W.,
21 lks. dist., mkd. $\frac{1}{4}$ S9 BT.

The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, monumented with the
original basalt stone, 15 x 8 x 7 ins., firmly set 10
ins. in the ground, mkd. $\frac{1}{4}$ on W. face, from which the
original bearing trees:

A pine, 18 ins. diam., bears N. 76° E., 61 lks.
dist., with healed blaze.

A pine, 19 ins. diam., bears S. 84° W., 61 lks.
dist., with healed blaze. (Record, S. 78° W.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 5 S R 33 E
 $\frac{1}{4}$
S 32 | S 33
1977

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

The cor. of secs. 28, 29, 32, and 33, monumented with the
original basalt stone, 12 x 6 x 5 ins. (record, 15 x 9 x
7 ins.), firmly set 3 ins. in the ground, in a collar of
stones, with 4 notches on E. and 1 notch on S. edges,
from which the remains of the original bearing trees:

A pine, 18 ins. diam., bears S. 34° W., 53 lks.
dist., with scribe marks S2 visible on partially
healed blaze.

A pine, 37 ins. diam., bears N. 67° W., 106 lks.
dist., with scribe marks S R33E S29 visible on
partially opened blaze. (Record, 103 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins.
in the ground, to solid rock, and in a mound of stone,
3 ft. base, to top, with brass cap mkd.

T 5 S R 33 E
S 29 | S 28
S 32 | S 33
1977

from which new bearing trees

A lodgepole pine, 6 ins. diam., bears N. 38° E.,
31 $\frac{1}{2}$ lks. dist., mkd. T5S R33E S28 BT.

A lodgepole pine, 6 ins. diam., bears S. 45 $\frac{1}{2}$ ° E.,
90 lks. dist., mkd. T5S R33E S33 BT.

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 28 and 29, monumented with the original basalt stone, 12 x 10 x 8 ins., firmly set 4 ins. in the ground, in a collar of stones, mkd. $\frac{1}{4}$ on W. face, from which the remains of the original bearing trees:

A decayed pine stump, size indeterminate, bears N. 74° E., 60 lks. dist., with a down and decayed pine alongside with scribe marks $\frac{1}{4}$ visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S R 33 E

$\frac{1}{4}$
S 29 | S 28
1977

from which new bearing trees

A lodgepole pine, 7 ins. diam., bears N. 78° E., 26 lks. dist., mkd. $\frac{1}{4}$ S28 BT.

A lodgepole pine, 7 ins. diam., bears S. 82° W., 90 lks. dist., mkd. $\frac{1}{4}$ S29 BT.

Deposit corner stone and set a 5 ft. steel fence post alongside iron post.

The cor. of secs. 20, 21, 28, and 29, monumented with the original basalt stone, 14 x 12 x 4 ins., firmly set 3 ins. in the ground, and in a mound of stone, 3 ft. base, 6 ins. high, with 4 notches on E. and 2 notches on S. edges, from which the remains of the original bearing trees:

A pine snag, 43 ins. diam., bears N. 76° E., 118 lks. dist., with scribe marks S R33E S21 visible on open blaze. (Record, N. 69° E.)

A pine, 26 ins. diam., bears S. 44° E., 56 lks. dist., with fragmentary scribe marks visible on open blaze.

A pine, 22 ins. diam., bears S. 57° W., 86 lks. dist., with scribe marks 33E visible on open blaze. (Record, S. 45° W.)

A pine, 40 ins. diam., bears N. 40° W., 141 lks. dist., with scribe marks 20 visible on open blaze. (Record, 136 lks.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 5 S R 33 E

S 20 | S 21
S 29 | S 28
1977

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

from which a new bearing tree

A lodgepole pine, 17 ins. diam., bears N. 45° E.,
34 lks. dist., mkd. T5S R33E S21 BT.

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

The cor. of secs. 16, 17, 20, and 21, determined at
record bearing and distance from the remains of the
original bearing trees:

A grand fir, 17 ins. diam., bears N. 72° E., 44
lks. dist., with fragmentary scribe marks
visible on open and burned blaze.

A decayed larch stump, size indeterminate, bears
S. 53° E., 53 lks. dist., with fragmentary scribe
marks visible on open and burned blaze.

A fir stump, size indeterminate, bears S. 64° W.,
26 lks. dist., with fragmentary scribe marks
visible on open and burned blaze.

A fir snag, 30 ins. diam., bears N. 40° W., 9 lks.
dist., with fragmentary scribe marks visible on
open and burned blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 5 S R 33 E
S 17 S 16
S 20 S 21
1977

from which new bearing trees

A grand fir, 6 ins. diam., bears S. 43° E., 27
lks. dist., mkd. T5S R33E S21 BT.

A grand fir, 4 ins. diam., bears S. 53° W., 87
lks. dist., mkd. T5S R33E S20 BT.

A grand fir, 10 ins. diam., bears N. 72° W., 94
lks. dist., mkd. T5S R33E S17 BT.

Set a 5 ft. steel fence post alongside iron post.

The ¼ sec. cor. of secs. 9 and 16, monumented with the
original basalt stone, 12 x 10 x 5 ins., loosely set 1
in. in the ground, mkd. ¼ on N. face, from which the
remains of the original bearing trees:

A decayed pine stump, size indeterminate, bears
N. 52° E., 48 lks. dist., with scribe marks
¼ S BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

T 5 S R 33 E

$$\frac{1}{4} \frac{S 9}{S 16}$$

1977

from which new bearing trees

A lodgepole pine, 10 ins. diam., bears N. 60° E.,
28 lks. dist., mkd. $\frac{1}{4}$ S9 BT.

A lodgepole pine, 10 ins. diam., bears S. 16° W.,
53 lks. dist., mkd. $\frac{1}{4}$ S16 BT.

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

Corner is located 26 lks. north of fence corner, fences
extend E., W., and S.

The cor. of secs. 4, 5, 8, and 9, monumented with the
original basalt stone, 16 x 8 x 6 ins., loosely set 1 in.
in the ground, in a collar of stones, with 4 notches on
E. and 5 notches on S. edges, from which the remains of
the original bearing trees:

A larch, 19 ins. diam., bears N. 55° E., 23 lks.
dist., with healed blaze. (Record, N. 43° E.,
20 lks.)

A larch, 9 ins. diam., bears S. 15° E., 60 lks.
dist., with healed blaze.

A root hole, bears S. 30° W., 28 lks. dist., with
a down larch alongside, 16 ins. diam., no marks
visible.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, and in a mound of stone, 2 ft. base, to
top, with brass cap mkd.

T 5 S R 33 E

$$\frac{S 5}{S 8} \frac{S 4}{S 9}$$

1977

from which new bearing trees

A lodgepole pine, 10 ins. diam., bears S. 68° W.,
84 lks. dist., mkd. T5S R33E S8 BT.

A fir, 18 ins. diam., bears N. 11° W., 137 lks.
dist., mkd. T5S R33E S5 BT.

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 31 and 32, monumented with the
original basalt stone, 14 x 10 x 6 ins., loosely set in
a mound of stone, 4 ft. base, 2 ft. high, mkd. $\frac{1}{4}$ on W.
face, from which the remains of the original bearing
trees:

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

A pine, 29 ins. diam., bears N. 66° E., 28 lks. dist., with fragmentary scribe marks visible on opened blaze. (Record, N. 48° E.)

A sawed pine stump, 26 ins. diam., bears N. 46° W., 92 lks. dist., with fragmentary scribe marks visible on decayed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S R 33 E
S 31^¼ | S 32
1977

from which a new bearing tree

A lodgepole pine, 12 ins. diam., bears N. 10° W., 149 lks. dist., mkd. ¼ S31 BT.

Deposit corner stone and set a 5 ft. steel fence post alongside iron post.

Corner is located 87 lks. west of wire fence, extending N. and S.

The cor. of secs. 29, 30, 31, and 32, monumented with the original basalt stone, 18 x 12 x 7 ins., loosely set 1 in. in the ground, with 5 notches on E. and 1 notch on S. edges, from which the remains of the original bearing trees:

A larch, 25 ins. diam., bears N. 64° E., 15 lks. dist., with healed blaze.

A larch snag, 18 ins. diam., bears S. 82° E., 45 lks. dist., with fragmentary scribe marks visible on open blaze.

A root hole, bears N. 17° W., 57 lks. dist., with a down larch alongside, 14 ins. diam., with scribe marks T5S R33E S30 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 5 S R 33 E
S 30 | S 29
S 31 | S 32
1977

from which new bearing trees

A grand fir, 10 ins. diam., bears S. 49° E., 50 lks. dist., mkd. T5S R33E S32 BT.

A grand fir, 25 ins. diam., bears S. 50° W., 79 lks. dist., mkd. T5S R33E S31 BT.

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

A grand fir, 13 ins. diam., bears N. 10° W., 49 lks. dist., mkd. T5S R33E S30 BT.

Deposit corner stone and set a 5 ft. steel fence post alongside iron post.

Corner is located 2 lks. west of wire fence, extending N. and S.

The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented with a mound of stone, 2 ft. base, 6 ins. high, from which the original bearing trees:

A pine, 18 ins. diam., bears N. 46° E., 42 lks. dist., with healed blaze. (Record, N. 42° E., 48 lks.)

A pine, 23 ins. diam., bears S. 30° W., 77 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S R 33 E
 $\frac{1}{4}$ S 29
S 32
1977

Set a 5 ft. steel fence post alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 29 and 30, monumented with the original basalt stone, 16 x 10 x 7 ins., firmly set 8 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, from which the remains of the original bearing trees:

A larch, 40 ins. diam., bears N. 70° E., 14 lks. dist., with scribe marks $\frac{1}{4}$ visible on open blaze. (Record, N. 58° E.)

A root hole, bears N. 70° W., 33 lks. dist., with a down and decayed fir alongside, size indeterminate, with scribe marks BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S R 33 E
 $\frac{1}{4}$
S 30 | S 29
1977

from which a new bearing tree

A grand fir, 10 ins. diam., bears N. 51° W., 19 lks. dist., mkd. $\frac{1}{4}$ S30 BT.

Deposit corner stone and set a 5 ft. steel fence post alongside iron post.

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

Corner is located 1 lk. west of wire fence, extending N. and S.

The cor. of secs. 19, 20, 29, and 30, monumented with the original basalt stone, 18 x 8 x 6 ins., loosely set 1 in. in the ground, with 5 notches on E. and 2 notches on S. edges, from which the remains of the original bearing trees:

A root hole, bears N. 69° E., 239 lks. dist., with a down and decayed pine alongside, size indeterminate, no marks visible.

A pine, 38 ins. diam., bears S. 64° E., 279 lks. dist., with fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S R 33 E
S 19 S 20
S 30 S 29
1977

from which a new bearing tree

A lodgepole pine, 18 ins. diam., bears N. 59½° E., 308 lks. dist., mkd. T5S R33E S20 BT.

No other suitable trees available within limits.

Deposit corner stone and set a 5 ft. steel fence post alongside iron post.

Corner is located 3 lks. east of wire fence, extending N. and S.

The ¼ sec. cor. of secs. 17 and 18, determined at record bearing and distance from the remains of an original bearing tree:

A sawed and decayed pine stump, size indeterminate, bears S. 30° E., 16 lks. dist., with scribe marks 4 S visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S R 33 E
¼
S 18 S 17
1977

from which new bearing trees

A larch, 13 ins. diam., bears S. 76° E., 27 lks. dist., mkd. ¼ S17 BT.

A lodgepole pine, 13 ins. diam., bears N. 29° W., 157 lks. dist., mkd. ¼ S18 BT.

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 8 and 17, determined at record bearing and distance from the remains of the original bearing trees:

A pine snag, 28 ins. diam., bears N. 62° E., 86 lks. dist., with scribe marks $\frac{1}{4}$ S visible on open and burned blaze.

A sawed pine stump, 28 ins. diam., bears S. 38° E., 40 lks. dist., with scribe marks BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 5 S R 33 E
 $\frac{1}{4}$ $\frac{S 8}{S 17}$
1977

from which new bearing trees

A lodgepole pine, 15 ins. diam., bears N. 16° E., 47 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

A fir, 13 ins. diam., bears S. 43° W., $37\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S17 BT.

Corner is located 25 lks. S. 70° E. of fence corner, fences extend S. and W.

The cor. of secs. 5, 6, 7, and 8, monumented with the original basalt stone, 18 x 8 x 6 ins., firmly set 6 ins. in the ground, and in a mound of stone, 2 ft. base, 6 ins. high, with 5 notches on E. edge, from which the remains of the original bearing trees:

A root hole, bears N. 20° E., 33 lks. dist., with a down and decayed larch alongside, size indeterminate, no marks visible.

A decayed larch stump, size indeterminate, bears S. 47° W., 63 lks. dist., with fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 5 S R 33 E
 $\frac{S 6}{S 7} \mid \frac{S 5}{S 8}$
1977

from which new bearing trees

A lodgepole pine, 11 ins. diam., bears N. 57° E., $37\frac{1}{2}$ lks. dist., mkd. T5S R33E S5 BT.

A lodgepole pine, 15 ins. diam., bears S. 56° E., 45 lks. dist., mkd. T5S R33E S8 BT.

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

A lodgepole pine, 10 ins. diam., bears S. 50° W.,
63 lks. dist., mkd. T5S R33E S7 BT.

A larch, 10 ins. diam., bears N. 31° W.,
33 lks. dist., mkd. T5S R33E S6 BT.

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 5 and 8, monumented with the
original basalt stone, 12 x 10 x 8 ins., firmly set 6
ins. in the ground, mkd. $\frac{1}{4}$ on N. face, from which the
remains of the original bearing trees:

A fir snag, 29 ins. diam., bears N. 18° E., 20
lks. dist., with healed blaze. (Record,
N. 40° E.)

A root hole, bears S. 57° E., 22 lks. dist., with a
down larch alongside, 15 ins. diam., no marks
visible.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 5 S R 33 E

$\frac{1}{4}$ $\frac{S 5}{S 8}$

1977

from which new bearing trees

A grand fir, 8 ins. diam., bears N. 40° E., $2\frac{1}{2}$
lks. dist., mkd. $\frac{1}{4}$ S5 BT.

A grand fir, 10 ins. diam., bears S. 63° E., $43\frac{1}{2}$
lks. dist., mkd. $\frac{1}{4}$ S8 BT.

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, monumented with the
original unmarked basalt stone, 12 x 10 x 8 ins., firmly
set 2 ins. in the ground, from which the remains of the
original bearing trees:

A root hole, bears N. 45° E., 33 lks. dist., with
a down and decayed pine alongside, size indeter-
minate, with scribe marks $\frac{1}{4}$ S BT visible on
open blaze.

A sawed pine stump, 14 ins. diam., bears West, 38
lks. dist., with scribe marks BT visible on
open blaze. (Record, 33 lks.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, and in a mound of stone, 2 ft. base, to
top, with brass cap mkd.

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

T 5 S R 33 E

 $\frac{1}{4}$

S 6 | S 5

1977

from which new bearing trees

A fir, 11 ins. diam., bears N. 62° E., 53 lks.
dist., mkd. $\frac{1}{4}$ S5 BT.

A fir, 10 ins. diam., bears N. 43° W., 51 $\frac{1}{2}$ lks.
dist., mkd. $\frac{1}{4}$ S6 BT.

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

Corner is located 10 lks. east of wire fence, extending
N. and S.

CERTIFICATE OF SURVEY

(I) (~~XX~~), Craig L. Wanless, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May, 19 57, (I) (~~XX~~) have remonumented certain original corner points, township 5 south, range 33 east,

of the Willamette Meridian, in the State of Oregon, which are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 16, 1978
(Date)

Craig L. Wanless
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
~~Washington, D.C.~~
Denver, Colorado

The foregoing field notes of the remonumentation of certain original corner points, township 5 south, range 33 east, Willamette Meridian, Oregon,

executed by Craig L. Wanless, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JAN 23 1980
(Date)

J. D. Voorhees
(Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) CPO 340 626