

## FIELD NOTES.

On the survey of the Subdivisional  
 Lines of T. 6 S.  
R. 34 E. Willamette Meridian,  
 Oregon, as surveyed by F. W. Campbell  
 U. S. Deputy Surveyor, under his Contract No. 468  
 dated April 12<sup>th</sup> 1883  
 Survey commenced July 20<sup>th</sup> 1883  
 Survey completed August 5<sup>th</sup> 1883

## NAMES AND DUTIES OF ASSISTANTS.

....., Compassman.  
John S. Guttridge, Chainman.  
 ..... , Chainman.  
Frank Ellis, Chainman.  
 ..... , Chainman.  
Cory A. Matlock, Axeman.  
 ..... , Axeman.  
 ..... , Flagman.

740

PRELIMINARY OATHS OF ASSISTANTS.

We, John S. Guttridge &  
Frank Ellis

do solemnly swear that we will faithfully execute the duties of Chain Carriers, that we will level the chain over even and uneven ground, and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we will assist in measuring, to the best of our skill and ability, and in accordance with the instructions given us in

the survey of the Subdivisional  
lines of T. 6 S.  
R. 34 E. Willamette Meridian, Oregon.

John S. Guttridge, Chainman.  
Frank Ellis, Chainman.  
\_\_\_\_\_, Chainman.  
\_\_\_\_\_, Chainman.

Subscribed and sworn to before me, this Eighteenth  
day of April 1883

[SEAL.] Frank W. Campbell  
U.S. Deputy Surveyor

We, J. Cary K. Matlock and

do solemnly swear that we will well and truly perform the duties of Axemen in the establishment of corners and other duties, according to instructions given us, and to the best of our skill and ability

in the survey of the Subdivisions of T. 6 S.  
R. 34 E. Willamette Meridian, Oregon.

Cary K. Matlock, Axeman.  
\_\_\_\_\_, Axeman.

Subscribed and sworn to before me, this Eighteenth  
day of April 1883

[SEAL.] Frank W. Campbell  
U.S. Deputy Surveyor

# INDEX.

Referring the Lines to the Pages of the Field Notes.

T. 6 S R. 34 E Will. Mer.

6	111	5	81	4	61	3	42	2	22	1
<del>108</del>		<del>107</del>		<del>80</del>		<del>60</del>		<del>41</del>		<del>20</del>
7	105	8	78	9	58	10	39	11	18	12
<del>102</del>		<del>101</del>		<del>77</del>		<del>56</del>		<del>37</del>		<del>16</del>
18	99	17	75	16	54	15	35	14	14	13
<del>97</del>		<del>96</del>		<del>73</del>		<del>53</del>		<del>34</del>		<del>12</del>
19	94	20	71	21	57	22	32	23	10	24
<del>92</del>		<del>91</del>		<del>69</del>		<del>50</del>		<del>30</del>		<del>8</del>
30	89	29	67	28	48	27	28	26	6	25
<del>87</del>		<del>86</del>		<del>66</del>		<del>47</del>		<del>26</del>		<del>4</del>
31	83	32	64	33	45	34	24	35	2	36

Meanders of ..... Page ..... to .....

Meanders of ..... Page ..... to .....

Subdivisions of T. 6 S. R. 34 E. 801

Willamette Meridian, Oregon.

lks. dist. marked 1/4 S. B. T.  
A pine 10 ins. dia. brs. N. 40° E. 18 lks.  
dist. marked 1/4 S. B. T.

79.95 The cor. to secs. 3, 4, 9 & 10

Land rolling & hilly.

Soil 2<sup>nd</sup> rate.

Densely covered with forests of  
pine & fir 79.95 chs.

Thick undergrowth of balm,  
huckleberry and small pine 79.95 chs.

North bet. secs. 3 & 4

Var. 19° 40' E.

Over rolling ground.

18.00 Ravine course W. -100

40.00 Set a pine post 3 ft. long 3 ins. +100

square 24 ins. in ground for  
1/4 sec. cor. marked 1/4 S. on W. face;  
from which

A fir 12 ins. dia. brs. N. 61° W. 33 lks. dist.  
marked 1/4 S. B. T.

## Subdivisions of T. 6 S. R. 34 E.

802

Willamette Meridian, Oregon.

Afir 24 ins. dia. brs. S. 80° E. 105 lbs.  
 dist. marked 1/4 S. B.T.  
 Ascend

~~54.00 Lumber course E. & W.~~

61.30 Intersect the 1<sup>st</sup> Standard  
 Parallel S. at a point 27.47 chs.  
 W. of cor. to T. 5 S. R. 33 1/2 & 34 E.  
 at which point I set a pine  
 post 4 ft. long 4 ins. square  
 24 ins. in ground for closing  
 cor. to sect. 3 & 4 marked  
 S. E. T. 6 S. R. 34 E. on S.  
 S. 3 on E. & S. 4 on W. faces,  
 with 3 notches on E. & W. edges;  
 from which

Afir 10 ins. dia. brs. S. 80° E. 5 lbs.  
 dist. marked T. 6 S. R. 34 E. S. 3 B.T.  
 Afir 8 ins. dia. brs. S. 8° W. 45 lbs.  
 dist. marked T. 6 S. R. 34 E. S. 4 B.T.

Land rolling. Soil 2<sup>nd</sup> rate.

81

Subdivisions of T. 6 S. R. 34 E 821  
Willamette Meridian, Oregon.

dist. marked  $\frac{1}{4}$  S. B. T.

80.00 The cor. to secs. 4, 5, 8 & 9  
Land rolling. Soil, 2<sup>nd</sup> rate.  
Densely covered with forests of  
pine, fir & tamarack 80. chs.  
July, 30 - 1883

North bet. secs. 4 & 5

Var. 20° E.

Descending.

40.00 Set a pine post 3 ft. long 3 ins. - 200  
square 2 1/2 ins. in ground for  
 $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  S. on W. face;  
from which

A pine 8 ins. dia. br. S. 73° E. 29 lks.  
dist. marked  $\frac{1}{4}$  S. B. T.

A tamarack 10 ins. dia. br. N. 80° W. 24 lks.  
dist. marked  $\frac{1}{4}$  S. B. T.

52.00 Enter flat at foot of hill - 200

60.70 Intersect the 1<sup>st</sup> Standard  
Parallel S. at a point 27.78 chs.

82 822

Subdivisions of T. 6 S. R. 34 E.

Willamette Meridian, Oregon.

W. of cor. to secs. 35 & 36 - T. 5 S.  
R. 33½ E. - at which point I  
set a pine post 4 ft. long 4 ins.  
square 24 ins. in ground  
for closing cor. to secs. 4 & 5,  
marked E. 6. T. 6 S. R. 34 E. on S.  
S. 4 on E. and

S. 5. W. faces, with 4 notches  
on E. & 2 notches on W. edges;  
from which

A pine 9 ins. dia. brs. S. 71° W.  
dist. marked T. 6 S. R. 34 E. S. 5 B. T.

A pine 9 ins. dia. brs. S. 41° E. -  
dist. marked T. 6 S. R. 34 E. S. 4 B. T.

Land hillside facing N.  
Soil 2<sup>nd</sup> rate.

Densely covered with forests of  
pine, tamarack & spruce 60, 70 chs.  
Thick undergrowth of small  
pine 60, 70 chs.

111

Subdivisions of T. 6 S. R. 34 E. 851

Willamette Meridian, Oregon.

North bet. secs. 5 and 6

Var.  $19^{\circ}50'$  E.

Descending to

17.50 Ravine course N. at foot of hill, -250

thence ascend to

38.00 Top of hill course E. & N. +250

40.00 Set a pine post 3 ft. long 3 ins.

square 24 ins. in ground for

$\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  S. on N.

face; from which

Atamarack 12 ins. dia. br. S.  $89^{\circ}$  E.

42 lbs. dist. marked  $\frac{1}{4}$  S. B.T.

Atamarack 12 ins. dia. br. N.  $78^{\circ}$  N.

51 lbs. dist. marked  $\frac{1}{4}$  S. B.T.

42.00 Descend.

60.00 Ravine course N. N.

77.20 Intersect the 1<sup>st</sup> Standard

Parallel S. at a point 4.18 chs. N.

of cor. to Tps. 5 S. R. 33 &  $33\frac{1}{2}$  E.

at which point I set a

pine post 4 ft. long 4 ins.

square, 24 ins. in ground

852

Subdivisions of T. 6 S. R. 34 E.

Willamette Meridian, Oregon.

for closing cor. to secs. 5 & 6  
 marked N. E. T. 6 S. R. 34 E. on S.  
 S. 5 on E. & S. 6 on W. faces,  
 with 5 notches on E. & 1 notch  
 on W. edges; from which  
 A pine 6 ins. dia. br. S. 28° E. 20 lks.  
 dist. marked T. 6 S. R. 34 E. S. 5 B. T.  
 A fir 8 ins. dia. br. S. 8° W. 5 lks.  
 dist. marked T. 6 S. R. 34 E. S. 6 B. T.  
 Land mountainous.

Soil 2<sup>nd</sup> rate.

Densely covered with forests of  
 pine, fir & tamarack 77.20 chs.  
 Thick undergrowth of small  
 pine, & fir 77.20 chs.

Aug. 5, 1883

FINAL OATHS FOR SURVEYS.

A list of the names of the individuals employed by Frank W. Campbell, U. S. Deputy Surveyor, to assist in running, measuring and marking the lines and corners described in the foregoing field notes of the survey of the Subdivisional lines of T. 6 S. R. 34 E. Willamette Meridian, Oregon, showing the respective capacities in which they acted:

- John S. Guttridge, Compassman.
- John S. Guttridge, Chainman.
- Frank Ellis, Chainman.
- Frank Ellis, Chainman.
- Lacey A. Matlock, Chainman.
- Lacey A. Matlock, Axeman.
- Lacey A. Matlock, Axeman.
- Lacey A. Matlock, Flagman.

FINAL OATHS OF ASSISTANTS.

We hereby certify that we assisted Frank W. Campbell, U. S. Deputy Surveyor, in surveying all those parts or portions of the Subdivisional lines of T. 6 S. R. 34 E. Willamette Meridian, Oregon, as are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been, in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the U. S. Surveyor General of Oregon.

- John S. Guttridge, Compassman.
- John S. Guttridge, Chainman.
- Frank Ellis, Chainman.
- Frank Ellis, Chainman.
- Frank Ellis, Chainman.
- Frank Ellis, Chainman.
- Lacey A. Matlock, Axeman.
- Lacey A. Matlock, Axeman.
- Lacey A. Matlock, Flagman.

Subscribed and sworn to before me, this The twenty fifth day of August 1883

[SEAL] Frank W. Campbell  
U. S. Deputy Surveyor

FINAL OATH OF DEPUTY SURVEYOR.

857

I, Frank W. Campbell

United States Deputy Surveyor, do solemnly swear that in pursuance of

instructions received from

James C. Tolman

U. S. Surveyor General for Oregon, bearing date of the

12<sup>th</sup>

day of

April

, 1883, I have well, faith-

fully and truly, in my own proper person, and in strict conformity with the instructions furnished by the U. S. Surveyor General for Oregon, the Surveying Manual, and the Laws of the United States, surveying all those

parts, or portions of

the Subdivisions of

T. 6 S. R. 34 E.

Willamette Meridian, in the State of Oregon, as are represented in the foregoing Field Notes as having been surveyed by me and under my directions; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Surveying Manual, Printed Instructions, the Special Written Instructions of the U. S. Surveyor General for Oregon, and in the specific manner described in the Field Notes, and that the foregoing are the *true* Field Notes of such survey, and should any fraud be detected I will suffer the penalty of perjury under the provisions of an Act of Congress approved August 8th, 1846.

Frank W. Campbell

U. S. Deputy Surveyor.

Subscribed and sworn to before me, this

18<sup>th</sup>

day of

October

1883

W. P. Burling

Notary Public for Oregon