

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

# FIELD NOTES

OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 5 SOUTH, RANGE 33½ EAST,

---



---



---



---



---



---



---



---



---



---



---



---



---



---



---



---



---



---



---



---



---



---



---



---

Of the WILLAMETTE Meridian,  
 In the State of OREGON

### EXECUTED BY

Craig L. Wanless, Cadastral Surveyor

---



---



---

Under special instructions dated May 3, 19 57, approved May 6, 1957,

which provided for the surveys included under U.S. Survey/Group  
 Number 350, and assignment instructions dated September 21, 19 77.

Survey commenced October 3, 19 77  
 Survey completed October 5, 19 77

# INDEX DIAGRAM

Township 5 South, Range 33½ East

6	5	4	3	<u>6</u> 2	<u>4</u> 1	<u>2</u>	
				<u>5</u> <u>5</u>	<u>3</u> <u>3</u>		
7	8	9	10		11	12	<u>1</u>
				<u>4</u>			
18	17	16	15		14	13	<u>1</u>
						<u>2</u>	
19	20	21	22		23	24	
30	29	28	27		26	25	
31	32	33	34		35	36	

Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 33½ E., Willamette Meridian, Oregon

CHAINS

T 5 S	
¼	
R 33½ E	R 34 E
S 12	S 7
1977	

from which a new bearing tree

A pine, 17 ins. diam., bears S. 39° E., 31 lks.  
dist., mkd. ¼ S7 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the  
Tp., determined at record distance from the remains of  
the original bearing trees:

A larch, 17 ins. diam., bears N. 26° E., 58 lks.  
dist., with healed blaze. (Record, N. 20° E.)

A decayed pine stump, size indeterminate, bears  
S. 25° E., 17 lks. dist., with scribe marks S7  
visible on open blaze. (Record, S. 20° E.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 5 S	
R 33½ E	R 34 E
S 1	S 6
S 12	S 7
1977	

from which new bearing trees

A lodgepole pine, 18 ins. diam., bears S. 54½° E.,  
72 lks. dist., mkd. T5S R34E S7 BT.

A larch, 8 ins. diam., bears S. 84° W., 27 lks.  
dist., mkd. T5S R33½E S12 BT.

A lodgepole pine, 15 ins. diam., bears N. 45° W.,  
91 lks. dist., mkd. T5S R33½E S1 BT.

Subdivisions, T. 5 S., R. 33½ E.,  
Willamette Meridian, Oregon

(Remonumenting corners established by Rufus S. Moore,  
U. S. Deputy Surveyor, in 1882)

The cor. of secs. 13, 14, 23, and 24, monumented with the  
original basalt stone, 13 x 8 x 7 ins., firmly set 6 ins.  
in the ground, in a collar of stone, mkd. with 1 notch on  
E. and 3 notches on S. edges, from which the original  
bearing trees:

A fir, 29 ins. diam., bears N. 74° E., 85 lks.  
dist., with scribe mark 1 visible on open  
blaze.

A mahogany, 11 ins. diam., bears S. 47° E., 22 lks.  
dist., with healed blaze.

Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 33½ E., Willamette Meridian, Oregon

## CHAINS

A juniper, 31 ins. diam., bears S. 45° W., 21 lks. dist., with scribe marks T5S R33½E S23 BT visible on open blaze.

A juniper, 26 ins. diam., bears N. 49° W., 58 lks. dist., with scribe marks T5S R33½E S14 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground, to solid rock, and supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T 5 S R 33½ E			
S 14	S 13		
S 23	S 24		
1977			

Deposit corner stone alongside iron post.

The cor. of secs. 1, 2, 11, and 12, determined at record bearing and distance from the original bearing tree:

A pine, 41 ins. diam., bears S. 54° E., 240 lks. dist., with scribe marks BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 5 S R 33½ E			
S 2	S 1		
S 11	S 12		
1977			

No suitable trees available within limits.

Set a 5 ft. steel fence post alongside iron post.

Corner is located 37 lks. south of wire fence extending E. and W., and 60 lks. south of gravelled road, 12 lks. wide, bears E. and W.

The ¼ sec. cor. of secs. 1 and 12, monumented with the original basalt stone, 12 x 10 x 4 ins., firmly set 4 ins. in the ground, in a collar of stone, mkd. ¼ on N. face, from which the remains of the original bearing trees:

A sawed pine stump, 14 ins. diam., bears S. 30° E., 31 lks. dist., with fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 33½ E., Willamette Meridian, Oregon

CHAINS

T 5 S R 33½ E

$$\frac{1}{4} \begin{array}{l} S 1 \\ S 12 \end{array}$$

1977

from which new bearing trees

A fir, 28 ins. diam., bears N. 37½° W., 59 lks.  
dist., mkd. ¼ S1 BT.

A fir, 14 ins. diam., bears S. 5° W., 62 lks.  
dist., mkd. ¼ S12 BT.

Deposit corner stone alongside iron post.

Corner is located in wire fence, extending E. and W., and  
25 lks. south of dirt road, 12 lks. wide, bears E. and W.

The ¼ sec. cor. of secs. 1 and 2, determined at record  
bearing and distance from the remains of the original  
bearing trees:

A sawed pine stump, 13 ins. diam., bears N. 58° W.,  
46 lks. dist., with scribe marks ¼ S visible  
on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 5 S R 33½ E

$$\frac{1}{4} \begin{array}{l} S 2 \\ S 1 \end{array}$$

1977

from which new bearing trees

A pine, 5 ins. diam., bears S. 73° E., 60 lks.  
dist., mkd. ¼ S1 BT.

A larch, 28 ins. diam., bears N. 76½° W., 378  
lks. dist., mkd. ¼ S2 BT.

The cor. of secs. 10, 11, 14, and 15, determined at  
record bearing and distance from the remains of the  
original bearing trees:

A sawed pine stump, 15 ins. diam., bears N. 11° E.,  
109 lks. dist., no marks visible on open blaze.

A juniper, 28 ins. diam., bears S. 59° E., 112 lks.  
dist., with scribe marks S14 BT visible on open  
blaze.

A pine, 23 ins. diam., bears N. 31° W., 114 lks.  
dist., with fragmentary scribe marks visible  
on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins.  
in the ground, to solid rock, and in a mound of stone,  
3 ft. base, to top, with brass cap mkd.

Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 33 $\frac{1}{2}$  E., Willamette Meridian, Oregon

CHAINS

T 5 S R 33 $\frac{1}{2}$  E  
 S 10 | S 11  
 S 15 | S 14  
 1977

from which new bearing trees

A pine, 10 ins. diam., bears N. 5° E., 69 lks.  
 dist., mkd. T5S R33 $\frac{1}{2}$ E S11 BT.

A pine, 15 ins. diam., bears S. 50° W., 51 lks.  
 dist., mkd. T5S R33 $\frac{1}{2}$ E S15 BT.

The cor. of secs. 2, 3, 10, and 11, monumented with the  
 original sandstone, 16 x 12 x 4 ins., firmly set 12 ins.  
 in the ground, mkd. with 2 notches on E. and 5 notches  
 on S. edges, from which the remains of the original  
 bearing trees:

A pine, 25 ins. diam., bears S. 67° E., 26 lks.  
 dist., with scribe marks 33 $\frac{1}{2}$ E S11 BT visible  
 on open blaze.

A fir, 25 ins. diam., bears S. 70° W., 40 lks.  
 dist., with scribe marks 33 $\frac{1}{2}$ E visible on  
 open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins.  
 in the ground, with brass cap mkd.

T 5 S R 33 $\frac{1}{2}$  E  
 S 3 | S 2  
 S 10 | S 11  
 1977

from which new bearing trees

A grand fir, 10 ins. diam., bears N. 31° E., 64  
 lks. dist., mkd. T5S R33 $\frac{1}{2}$ E S2 BT.

A grand fir, 10 ins. diam., bears N. 29° W., 40  
 lks. dist., mkd. T5S R33 $\frac{1}{2}$ E S3 BT.

Deposit corner stone alongside iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 2 and 11, determined at record  
 bearing and distance from the only remaining original  
 bearing tree:

A pine, 20 ins. diam., bears N. 35° E., 52 lks.  
 dist., with scribe marks  $\frac{1}{4}$  S visible on open  
 blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins.  
 in the ground, with brass cap mkd.

T 5 S R 33 $\frac{1}{2}$  E  
 $\frac{1}{4}$  S 2  
 S 11  
 1977

Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 33 $\frac{1}{2}$  E., Willamette Meridian, Oregon

CHAINS

from which a new bearing tree

A larch, 15 ins. diam., bears S. 75° W., 59 lks.  
dist., mkd.  $\frac{1}{4}$  S11 BT.

The  $\frac{1}{4}$  sec. cor. of secs. 2 and 3, monumented with the  
original basalt stone, 13 x 12 x 12 ins., firmly set 4  
ins. in the ground, mkd.  $\frac{1}{4}$  on W. face, from which the  
remains of the original bearing trees:

A pine stump, 7 ins. diam., bears S. 37° E., 23  
lks. dist., with healed blaze. (Record,  
S. 41° E., 17 lks.)

A pine snag, 32 ins. diam., bears N. 42° W., 122  
lks. dist., with scribe marks  $\frac{1}{4}$  S visible on  
open blaze. (Record, N. 47° W.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T 5 S R 33 $\frac{1}{2}$  E  
 $\frac{1}{4}$   
S 3 | S 2  
1977

from which new bearing trees

A pine, 13 ins. diam., bears N. 48° E., 94 $\frac{1}{2}$  lks.  
dist., mkd.  $\frac{1}{4}$  S2 BT.

A pine, 10 ins. diam., bears N. 82° W., 38 lks.  
dist., mkd.  $\frac{1}{4}$  S3 BT.

Deposit corner stone alongside iron post.

Corner is located 88 lks. south of wire fence, extending  
E. and W.

Form 9180-8  
(March 1969)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
June Klein	Engineering Aid

*[Faint handwritten signature and text, likely a stamp area]*



CERTIFICATE OF SURVEY

(I) (~~W~~), Craig L. Wanless, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May, 19 57, (I) (~~W~~) have remonumented certain original corner points, township 5 south, range 33½ east,

of the Willamette Meridian, in the State of Oregon, which are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 16, 1978  
(Date)

*Craig L. Wanless*  
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Washington, D.C.

The foregoing field notes of the remonumentation of certain original corner points, township 5 south, range 33½ east, Willamette Meridian, Oregon,

executed by Craig L. Wanless, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

AUG 17 1978  
(Date)

*J. Voorhees*  
Acting (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey)