

INDEX DIAGRAM

Township 5 South, Range 33 East,

6	<u>19</u> 5 <u>18</u> <u>19</u>	4 <u>14</u>	3	2	1 <u>5</u> <u>6</u>
7	8 <u>18</u>	9 <u>13</u>	<u>10</u> 10 <u>9</u> <u>10</u>	11 <u>8</u>	12 <u>3</u> <u>5</u> <u>3</u>
18	<u>17</u> 17	16 <u>13</u>	15 <u>9</u>	<u>7</u> 14 <u>7</u>	13 <u>4</u> <u>2</u>
19	20 <u>17</u>	21 <u>12</u>	<u>8</u> 22	<u>6</u> 23	<u>4</u> 24
30	<u>16</u> 29 <u>15</u> <u>16</u>	<u>12</u> 28 <u>11</u>	27	26	25
31	<u>14</u> 32 <u>1</u>	<u>11</u> 33 <u>1</u>	34	35	36

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

S C
T 5 S R 33 E
 $\frac{1}{4}$ S 32
1977

from which a new bearing tree

A lodgepole pine, 7 ins. diam., bears N. 16° E., 16 lks. dist., mkd. $\frac{1}{4}$ S32 SC BT.

Set a 5 ft. steel fence post alongside iron post.

East Boundary, T. 5 S., R. 33 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by George S. Pershin, U. S. Deputy Surveyor, in 1881, and changed to corners of minimum control by Rufus S. Moore, U. S. Deputy Surveyor, in 1882)

The cor. of secs. 13 and 24 only, on the E. bdy. of the Tp., monumented with the original basalt stone, 17 x 10 x 8 ins., firmly set 6 ins. in the ground, with 3 notches on N. and S. edges, from which the remains of the original bearing trees:

A larch snag, 18 ins. diam., bears N. 34° E., 36 lks. dist., with scribe marks T5S R34E S18 visible on open blaze.

A root hole, bears S. 58° E., 33 lks. dist., with a down larch alongside, 7 ins. diam., with scribe marks T5S R34E S19 BT visible on open blaze.

A larch snag, 13 ins. diam., bears S. 42° W., 75 lks. dist., with fragmentary scribe marks visible on decayed blaze.

A larch, 22 ins. diam., bears N. 37° W., 96 lks. dist., with scribe marks 13 visible on open blaze. (Record, N. 41° W.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S | T 5 S
S 13 | R 33 $\frac{1}{2}$ E
S 24 |
R 33 E | S 15
1977

from which a new bearing tree

A lodgepole pine, 7 ins. diam., bears S. 73° W., 22 lks. dist., mkd. T5S R33E S24 BT.

Deposit corner stone alongside iron post.

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

The cor. of secs. 12 and 13 only, on the E. bdy. of the Tp., monumented with the original basalt stone, 18 x 12 x 5 ins., loosely set 1 in. in the ground, with 2 grooves on N. and 4 grooves on S. faces, from which the remains of the original bearing trees:

A root hole, bears N. 28° E., 24 lks. dist., with a down and decayed pine alongside, size indeterminate, with fragmentary scribe marks visible on open blaze. (Record, 21 lks.)

A sawed pine stump, 17 ins. diam., bears S. 38° E., 55 lks. dist., with scribe marks BT visible on open blaze.

A pine, 26 ins. diam., bears S. 40° W., 93 lks. dist., with healed blaze.

A pine, 30 ins. diam., bears N. 66° W., 46 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S	T 5 S
S 12	R 33½ E
S 13	S 10
R 33 E	1977

Deposit corner stone alongside iron post.

Corner is located 3 lks. east of wire fence, extending N. and S.

The ¼ sec. cor. of sec. 12 only, on the E. bdy. of the Tp., monumented with the original basalt stone, 14 x 10 x 8 ins., firmly set 12 ins. in the ground, in a collar of stones, mkd. ¼ on W. face, from which the remains of the original bearing trees:

A root hole, bears East, 70 lks. dist., with a down fir alongside, 18 ins. diam., with healed blaze.

A pine, 13 ins. diam., bears S. 18° W., 55 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 5 S	R 33½ E
R 33 E	¼ S 12
¼ S 12	1977

from which a new bearing tree

A grand fir, 8 ins. diam., bears N. 83° W., 66 lks. dist., mkd. ¼ S12 BT.

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

Deposit corner stone alongside iron post.

Corner is located 10 lks. west of wire fence, extending
N. and S.

Subdivisions, T. 5 S., R. 33 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by George S. Pershin,
U. S. Deputy Surveyor, in 1882)

The $\frac{1}{4}$ sec. cor. of secs. 23 and 24, monumented with the
original basalt stone, 14 x 12 x 5 ins., firmly set 4
ins. in the ground, mkd. $\frac{1}{4}$ on W. face, from which the
remains of the original bearing trees:

A sawed pine stump, 18 ins. diam., bears S. 55° W.,
55 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 5 S R 33 E

$\frac{1}{4}$
S 23 | S 24
1977

from which new bearing trees

A grand fir, 9 ins. diam., bears S. $85\frac{1}{2}^{\circ}$ E., 90
lks. dist., mkd. $\frac{1}{4}$ S24 BT.

A grand fir, 13 ins. diam., bears N. 86° W., 53
lks. dist., mkd. $\frac{1}{4}$ S23 BT.

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 13 and 24, monumented with the
original basalt stone, 18 x 14 x 10 ins. firmly set 8
ins. in the ground, and in a collar of stones, mkd. $\frac{1}{4}$ on
N. face, from which the original bearing trees:

A pine, 27 ins. diam., bears N. 7° W., 106 lks.
dist., with scribe marks 4 S visible on open
blaze. (Record, N. 12° W.)

A pine, 17 ins. diam., bears S. 62° E., 104 lks.
dist., with scribe marks $\frac{1}{4}$ S visible on open
blaze. (Record, S. 67° E.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, and in a mound of stone, 2 ft. base, to
top, with brass cap mkd.

T 5 S R 33 E

$\frac{1}{4}$ S 13
 S 24
1977

CERTIFICATE OF SURVEY

(I) (~~we~~), Craig L. Wanless, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May, 19 57, (I) (~~we~~) have remonumented certain original corner points, township 5 south, range 33 east,

of the Willamette Meridian, in the State of Oregon, which are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 16, 1978
(Date)

Craig L. Wanless
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
~~Washington, D.C.~~
Denver, Colorado

The foregoing field notes of the remonumentation of certain original corner points, township 5 south, range 33 east, Willamette Meridian, Oregon,

executed by Craig L. Wanless, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JAN 23 1980
(Date)

J. D. Voorhees
(Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) CPO 340 626